


ELSD (Ellipse and Line Segment Detector)

by Viorica Pătrăucean, Pierre Gurdjos, and Rafael Grompone von Gioi

About

This is the homepage of ELSD (Ellipse and Line Segment Detector). ELSD is a parameterless detector, that can be applied on any grey-scale image without prior edge detection or parameter tuning.

Example:



The preprint of the article published at ECCV2012 [A parameterless line segment and elliptical arc detector with enhanced ellipse fitting](#). The source code of ELSD can be found [here](#). Note that a newer improved version of the algorithm is available [here](#).

It might be useful to test online our detector, before downloading and compiling it. A demo where users can upload their images and test ELSD is available here [demo](#) (user: demo, pass: demo). Check out the [result of ELSD](#) applied on a real video (frame size: 638x360, average execution time 0.7s/frame).

For any questions or remarks, please contact the corresponding author at [vpatrauc at gmail dot com](mailto:vpatrauc@gmail.com).

Here follows a summary description of ELSD.

Abstract

Geometric shape detection (line segment, ellipse) is often a prerequisite for high level tasks; hence we need automatic detectors, i.e. no parameter tuning.

ELSD

- parameterless Ellipse and Line Segment Detector;
- works with grey-scale images (no edge detector needed);
- grounded on the a contrario theory [1], it controls statistically the number of false positives; extends LSD [2];
- it offers a better precision due to enhanced ellipse fitting.

ELSD Overview

We pose the geometric shape detection in the statistical framework of multiple hypothesis testing, in order to focus on reducing/controlling false detections. The main steps of ELSD are:


1. Hypothesis selection:
 - **heuristic**, but free of critical parameters in order to **avoid false negatives**.
2. Validation:
 - parameterless, grounded on a contrario theory; **controls the number of false positives**.
3. Model selection:
 - parameterless; follows Ockham' s razor principle.

1. Hypothesis Selection

This step must produce line segment and elliptical candidates.


A. Region grow

- starting from a seed pixel, gather recursively neighbour pixels with similar gradient orientation.



B. Curve grow


- gather recursively neighbour regions that follow a convex, roughly smooth contour.



C. Fitting:

- pixels gathered in steps A and B respectively, are used to estimate the line segment and the elliptical hypotheses

- region => rectangle fit => line segment hypothesis;
- curve => circular/elliptical ring fit => circle/ellipse hypothesis.




- The tangent to the conic in a point p_i is also the polar of the point p_i w.r.t. the conic [4].
- The algebraic distance error and the gradient orientation error can be simultaneously minimised through a non-iterative procedure. This improves the accuracy, especially when pixels are sampled along incomplete circles/ellipses.

2. A Contrario Validation

The a contrario theory uses the non-accidentalness principle; informally, it says that "we see nothing in noise". Thus, hypotheses that are likely to be observed in noise should be automatically discarded. To this end we need to define two elements: a model of "noise" (unstructured data) and a function to measure the quality (degree of structuredness) of a hypothesis.


Model of unstructured data:

- field of gradients whose orientations can be considered i.i.d. random variables => Gaussian white noise image;



Degree of structuredness:

- the number of σ -aligned pixels contained in a hypothesis. For a line segment, a pixel is said to be σ -aligned if its gradient orientation is orthogonal to the line segment, up to a precision σ (see left figure below). Similarly, for circle/ellipse case, a pixel is σ -aligned if its gradient orientation is orthogonal to the tangent to the circle/ellipse in that point (see middle and right figures below).



Validation test:

- accept as meaningful hypotheses only those too structured to appear by chance in unstructured data. If a hypothesis contains too many aligned points, it is not likely for it to be observed in noise; thus it is meaningful.

The Number of False Alarms (NFA) is the essential quantity used to assess the validity of a hypothesis, and is given by:

$NFA = N \cdot B(l, k, \sigma)$, where

N - number of hypotheses (n^5 line segments, n^6 circular arcs, n^8 elliptical arcs, for an $n \times n$ image);

l - number of pixels in hypothesis;

k - number of aligned pixels in hypothesis;

$B(l, k, \sigma)$ - binomial tail = $\sum_{i=k}^l C_l^i \sigma^i (1-\sigma)^{l-i}$.

A hypothesis is considered meaningful iff it satisfies the validation test $NFA \leq \varepsilon$.

Control of false positives: If a hypothesis is accepted as meaningful only when the above validation test stands, then the number of meaningful hypotheses observed by chance in unstructured data is less than ε (see the paper for a proof of this proposition).

3. Model Selection

When more than one hypothesis passes the validation test, a model selection needs to be performed to choose the most suitable geometric interpretation for the given data.

Ockham's razor principle recommends to

- choose the best geometric interpretation for the data,
- but penalize complexity.

We use NFA as model selection criterion [3] and keep as valid hypothesis the one with the lowest NFA.

Results

Here are some results of ELSD applied on real images. For each row: original image, ELSD result, Etemadi result [5], Hough-based circle detector result. For more examples, see the archive of the [online demo](http://ubee.enseeiht.fr/vision/ELSD/) (user: demo, pass: demo).



Image size: 445 x 304 pixels, ELSD execution time: 1s






Image size: 640 x 480 pixels, ELSD execution time: 0.4s







Image size: 442 x 450 pixels, ELSD execution time: 0.6s







Image size: 1600 x 1200 pixels, ELSD execution time: 1.3s






Image size: 1600 x 1200 pixels, ELSD execution time: 3.1s






Image size: 612 x 563 pixels, ELSD execution time: 0.1s

Conclusion

Efficient (multiple) geometric shape detectors can be obtained using the scheme: [hypothesis selection, validation \(and model selection\)](#).

Ellipse fitting: more accurate using simultaneously positional and tangential constraints.

Model selection: needs improvement to handle correctly polygonal shapes.

References

- [1] Desolneux, A., Moisan, L., Morel, J.M.: From Gestalt Theory to Image Analysis: A Probabilistic Approach. Springer-Verlag (2008)
- [2] Grompone von Gioi, R., Jakubowicz, J., Morel, J.M., Randall, G.: LSD: A fast line segment detector with a false detection control. PAMI 32, 722-732 (2010)
- [3] Pătrăucean, V.: Detection and identification of elliptical structure arrangements in images: Theory and algorithms. PhD thesis. University of Toulouse, France, <http://ethesis.inp-toulouse.fr/archive/00001847/>
- [4] Hartley, R.I., Zisserman, A.: Multiple View Geometry in Computer Vision, 2nd edn. Cambridge University Press (2004)

[5] Etemadi, A. : Robust segmentation of edge data. In: Int. Conf. on Image Processing and its Applications. 311-314 (1992)

0010738

This Website Visits