

Energy-efficient execution of Federated learning tasks on mobile phones: An exploratory study.

Presented by Patrick Wapet, Post Doc at LIRIS Laboratory, INSA Lyon
In collaboration with Dr. Tran Giang Son, University of Science and
Technology of Hanoi
and Dr. Boris Teabe, INP Toulouse
Supervised by By Vlad Nitu,


Summary

1. **Context:** Federated Learning and mobile phones.
2. **Problem definition:** Global scheme
3. **Challenges:** Parameters, metrics, approach and measurement tools.
4. **Experiments and observations:** reported according to the parameters, graphs and partial conclusions.
5. **Next steps:** next experiments, possibly implementations and submissions.


1. Context: Federated Learning

- Artificial Intelligence is more and more used in everyday life.
- By default it is a system that centralizes data.
- Posing the problem of privacy.
- A solution: keep the data with the users.
- On their devices : **Mobile phones**
- Do the processing on these phones: **Federated Learning**


2. Let state the problem: general scheme




2. Let state the problem: general scheme



2. Let state the problem: general scheme



2. Let state the problem: general scheme



3.a. Let us define the **metric** to optimize

- The metric should reflect both:
 - **Computing power** of the FL task execution
 - **Electrical power absorption** of the phone.
- To compute this metric we have:
 - The **workload** of the FL task: number of CPU operations.
 - The **energy** consumed by the system: obtained by measurements.
- Metric adopted for the project: **energy efficiency**

$$energy_{eff} = \frac{Energy\ consumed}{workload\ computed} = \frac{Power\ absorbed}{Computing\ power}$$

3.b. What influences the energy efficiency

- The type of cores executing the task
 - Intuitively Big cores consumed high amount of Energy
 - Some research experiments prove that it can be a factor. [1]
- The task already present of the cores.
 - Energy discounted approach [2].
- The core frequency.

[1] Full-System Simulation of big.LITTLE Multicore Architecture for Performance and Energy Exploration. *Anastasiia Butko et al*


[2] Energy Discounted Computing on Multicore Smartphones, *Meng Zhu Kai Shen University of Rochester*

[3] Machine Learning-Based Approaches for Energy-Efficiency Prediction and Scheduling in Composite Cores Architectures
Hossein Sayadi et al.

[4] Temperature-Aware Scheduler Based on Thermal Behavior Grouping in Multicore Systems Inchoon Yeo and Eun Jung Kim

3.b. What influences the energy efficiency

- The type of cores executing the task
 - Intuitively Big cores consumed high amount of Energy
 - Some research experiments prove that it can be a factor. [1]
- The task already present of the cores.
 - Energy discounted approach [2].
- The core frequency.



We wanted to limit ourselves to the previous parameters, but it was with no real basis.

[1] Full-System Simulation of big.LITTLE Multicore Architecture for Performance and Energy Exploration. *Anastasiia Butko et al*


[2] Energy Discounted Computing on Multicore Smartphones, *Meng Zhu Kai Shen University of Rochester*

[3] Machine Learning-Based Approaches for Energy-Efficiency Prediction and Scheduling in Composite Cores Architectures
Hossein Sayadi et al.

[4] Temperature-Aware Scheduler Based on Thermal Behavior Grouping in Multicore Systems *Inchoon Yeo and Eun Jung Kim*

3.b. What influences the energy efficiency

- The type of cores executing the task
 - Intuitively Big cores consumed high amount of Energy
 - Some research experiments prove that it can be a factor. [1]
- The task already present of the cores.
 - Energy discounted approach [2].
- The core frequency.
- The Number of threads of the best effort task [3].
- Core temperature [4].



We wanted to limit ourselves to the previous parameters, but it was with no real basis.


[1] Full-System Simulation of big.LITTLE Multicore Architecture for Performance and Energy Exploration. *Anastasiia Butko et al*

[2] Energy Discounted Computing on Multicore Smartphones, *Meng Zhu Kai Shen University of Rochester*


[3] Machine Learning-Based Approaches for Energy-Efficiency Prediction and Scheduling in Composite Cores Architectures
Hossein Sayadi et al.

[4] Temperature-Aware Scheduler Based on Thermal Behavior Grouping in Multicore Systems *Inchoon Yeo and Eun Jung Kim*


2. Let state the problem: general scheme




3.a. Let us define the **metric** to optimize on our problem scheme




3.a. Let us define the **metric** to optimize on our problem scheme




3.a. Let us define the **metric** to optimize on our problem scheme




3.b. What **influences** the energy efficiency on our problem scheme




3.b. What **influences** the energy efficiency on our problem scheme




3.b. What **influences** the energy efficiency on our problem scheme




3.b. What **influences** the energy efficiency on our problem scheme



3.b. What **influences** the energy efficiency on our problem scheme



3.b. What **influences** the energy efficiency on our problem scheme



3.d Approach to resolve the problem

I. Make in-lab experiments by varying scenarios parameters:

- Number of interactive task present on phones
- Number of threads of the FL task
- Type of cores
- Core frequencies
- Temperature

II. Bringing out the lessons learned **about HOW those parameters influence energy efficiency.**

III. Apply these lessons learned in the FL task scheduling decision:

- At user space Level
- At kernel Level (Scheduler, governor).

3.e Workload measurement

- Benchmarks (Newly added FL task)
 - **Prime number computation** (to quickly get an overview of cores energy efficiency) [1]
 - Tensor Flow Lite model on Mobile Device [2] (to have ML-like task behavior)
 - Federated Learning Tool from FLEET (for FL-like experiments) [3]
- Interactive apps (Other apps)
 - **Interactive app simulation** (with interruptions to quickly get an overview) [1]
 - Widely used mobile apps (YouTube, Instagram ...)
- Phone 1: Google Pixel 4A 5G:
 - 3 sockets: CPUs 0-5: 1.8048 GHz; CPU 6: 2.208 GHz; CPU 7: 2.4 GHz
 - Memory: 6GB RAM
- Phone 2: Samsung galaxy S8
 - 2 sockets CPUs 0-3 : 1.69 GHz , CPUs 4-7: 2.314 GHz
 - Memory: 4GB RAM

[1] Prime number computation source code

https://gitlab.liris.cnrs.fr/plwapet/benchmarking_app_to_test_big_cores/-/blob/main/app/src/main/java/com/opportunistask/scheduling/benchmarking_app_to_test_big_cores/PrimeNumberThread.java

[2] On-Device Training with TensorFlow Lite https://www.tensorflow.org/lite/examples/on_device_training/overview

[3] FLEET: Online Federated Learning via Staleness Awareness and Performance Prediction, Georgios Damaskinos, Rachid Guerraoui, Vlad Nitu et al. Source code <https://github.com/gdamaskinos/fleet/>

3.f Energy consumption measurement:

Power-meter tool

system API “*dumpsys batterystats*” from Android OS

- Widely used in research [1]
- We have used it for more than 7 months.
- Confirms the influence of the above-mentioned parameters on the energy efficiency
- But some results incompatible with reality

- Also widely used in research [2][3]
- The common installation required is **expensive**
 - Its makes phone battery no longer usable.
- **Alternative 1:** Software simulation of battery shutdown (Google Pixel 4A, 5G).
 - Modifying internal system file : “*charge_stop_level*”, “*charge_limit*”
 - USB mode power supply
 - Retrieving data from power-meter
- **Alternative 2 :** Full battery charging (Samsung)
 - Retriving data from system file “*cc_info*”
 - Retrieving data form power-meter

[1] Resource utilization and per formance, A comparative study on mobile crossplatform tools, Lucas Arvidsson, Max Bekkhus

[2]"Energy Consumption and Conservation in WiFi Based Phones: A Measurement-Based Study By Ashima Gupta and Prasant Mohapatra"

[3] Energy-Efficient Collaborative Sensing with Mobile Phones Xiang Sheng

4. Experiments and observations (made using APIs)



Phone: Samsung S8

Impact of: **Type or Core**

Experiments duration: 10 min

Legend: Configuration 0-1 means

- 0 thread on Little sockets
- 1 Thread on Big Socket



4. Experiments and observations (made using APIs)

Phone: Samsung S8



Impact of: **Type or Core**

Experiments duration: 10 min

Legend: Configuration 0-1 means

- 0 thread on Little sockets
- 1 Thread on Big Socket

Big Cores consume
a lot of energy
compared to little
cores



4. Experiments and observations (made using APIs)

Phone: Samsung S8

Impact of: **Type or Core**



Experiments duration: 10 min

Legend: Configuration 0-1 means

- 0 thread on Little sockets
- 1 Thread on Big Socket

Big Cores consume a lot of energy compared to little cores

Big cores are very fast in computation



4. Experiments and observations (made using APIs)


Phone: Samsung S8

Impact of: **Number of Threads**

Experiments duration: 10 min

Legend: Configuration 0-1 means

- 0 thread on Little sockets
- 1 Thread on Big Socket



4. Experiments and observations (made using APIs)

Phone: Samsung S8

Impact of: **Number of Threads**


Experiments duration: 10 min

Legend: Configuration 0-1 means

- 0 thread on Little sockets
- 1 Thread on Big Socket

On the same socket the number of threads slightly increases with the efficiency

Energy efficiency (Energy/Workload) according number of threads
(lower is better)



4. Experiments and observations (made using APIs)

Phone: Samsung S8


Impact of: **Frequency**

Experiments duration: 5 min

Legend: Configuration 0-1_mid means

- 0 thread on Little sockets
- 1 Thread on Big Socket
- Big socket runs with frequency at middle level.
- Mid = middle level, min = minimum level
 - Max = maximum frequency

Energy efficiency (Energy/Workload) according to configuration and frequency (lower is better)



4. Experiments and observations (made using APIs)

Phone: Samsung S8

Impact of: **Frequency**


Experiments duration: 5 min

Legend: Configuration 0-1_mid means

- 0 thread on Little sockets
- 1 Thread on Big Socket
- Big socket runs with frequency at middle level.
- Mid = middle level, min = minimum level
 - Max = maximum frequency

At slightly reduced frequency the Little cores are efficient

Energy efficiency (Energy/Workload) according to configuration and frequency (lower is better)



4. Experiments and observations (made using APIs)

Phone: Samsung S8

Impact of: **Frequency**

Experiments duration: 5 min


Legend: Configuration 0-1_mid means

- 0 thread on Little sockets
- 1 Thread on Big Socket
- Big socket runs with frequency at middle level.
- Mid = middle level, min = minimum level
 - Max = maximum frequency

At slightly reduced frequency the Little cores are efficient

It is more efficient to reduced frequency on the Big cores as much as possible for one task.

Energy efficiency (Energy/Workload) according to configuration and frequency (lower is better)



4. Experiments and observations (made using the power-meter)

Phone: Google Pixel

Impact of: **Number of threads**


Experiments duration: 10 min

Battery level: 50

No charging: Yes by the file
charge_stop_level

Legend: Configuration 0-1 means:

- 0 thread on Little core
- 1 thread on Big core



4. Experiments and observations (made using the power-meter)

Phone: Google Pixel

Impact of: **Number of threads**

Experiments duration: 10 min

Battery level: 50


No charging: Yes by the file
charge_stop_level

Legend: Configuration 0-1 means:

- 0 thread on Little core
- 1 thread on Big core

On the same socket the number of threads slightly increases with the efficiency

Energy efficiency (Energy/Workload) according to the configuration (lower is better)



4. Experiments and observations (made using the power-meter)

Phone: Google Pixel

Impact of: **Type of Cores**

Experiments duration: 10 min


Battery level: 50

No charging: Yes by the file
charge_stop_level

Legend: Configuration 0-1 means:

- 0 thread on Little core
- 1 thread on Big core

Energy efficiency (Energy/Workload) according to the configuration (lower is better)



4. Experiments and observations (made using the power-meter)

Phone: Google Pixel

Impact of: **Type of Cores**

Experiments duration: 10 min

Battery level: 50


No charging: Yes by the file
charge_stop_level

Legend: Configuration 0-1 means:

- 0 thread on Little core
- 1 thread on Big core

Big cores are much more efficient
than little cores

Energy efficiency (Energy/Workload) according to
the configuration (lower is better)



4. Experiments and observations (made using the power-meter)

Phone: Google Pixel

Impact of: **Type of Cores**

Experiments duration: 10 min

Battery level: 50

No charging: Yes by the file
charge_stop_level


Legend: Configuration 0-1 means:

- 0 thread on Little core
- 1 thread on Big core

Big cores are much more efficient than little cores

The efficiency of the big cores influences the overall efficiency of the configuration

Energy efficiency (Energy/Workload) according to the configuration (lower is better)



4. Experiments and observations (made using the power-meter)

Phone: Google Pixel

Impact of: **Frequency**

Experiments duration: 10 min


Battery level: 50

No charging: Yes by the file
charge_stop_level

Legend: Configuration 0-1m means:

- 0 thread on Little core
- 1 thread on Big core
- The Big core has the min frequency
- H = half frequency, nothing = max frequency

Energy/ Workload according to the number of CPUs
m = idle (minimum) frequency, h = half frequency



4. Experiments and observations (made using the power-meter)

Phone: Google Pixel

Impact of: **Frequency**

Experiments duration: 10 min

Battery level: 50


No charging: Yes by the file
charge_stop_level

Legend: Configuration 0-1m means:

- 0 thread on Little core
- 1 thread on Big core
- The Big core has the min frequency
- H = half frequency, nothing = max frequency

On the Little cores we are much more efficient with the maximum frequency

Energy/ Workload according to the number of CPUs
m = idle (minimum) frequency, h = half frequency



4. Experiments and observations (made using the power-meter)

Phone: Google Pixel

Impact of: **Frequency**

Experiments duration: 10 min

Battery level: 50

No charging: Yes by the file
charge_stop_level


Legend: Configuration 0-1m means:

- 0 thread on Little core
- 1 thread on Big core
- The Big core has the min frequency
- H = half frequency, nothing = max frequency

On the Little cores we are much more efficient with the maximum frequency

On the Big cores we are much more efficient with the mid frequency

Energy/ Workload according to the number of CPUs
m = idle (minimum) frequency, h = half frequency



4. Experiments and observations (made using the power-meter)

Phone: Google Pixel

Impact of: **Frequency and number of Threads**

Experiments duration: 10 min

Battery level: 50


No charging: Yes by the file
charge_stop_level

Legend: Configuration 0-1m means:

- 0 thread on Little core
- 1 thread on Big core
- The Big core has the min frequency
- H = half frequency, nothing = max frequency



Fixing the frequency at mid level and increasing the number of threads increases the efficiency drastically

Energy/ Workload according to the number of CPUs
m = idle (minimum) frequency, h = half frequency





4. Next steps

- Same experiments on Samsung
 - Good news: No limitations on the number of configurations as with APIs.
We use *cc_info* file and the *power-meter*
 - We suspect that APIs on samsung was not far from reality in term of energy ratio.



4. Next steps



- Made same experiments on Samsung
 - Good news: No limitations on the number of configurations as with APIs.
We use *cc_info* file and the *power-meter*
 - We suspect that APIs on samsung was not far from reality in term of energy ratio.



- **Validate observations made with other Benchmarks**

4. Next steps

- Made same experiments on Samsung
 - Good news: No limitations on the number of configurations as with APIs.
We use *cc_info* file and the *power-meter*
 - We suspect that APIs on samsung was not far from reality in term of energy ratio.



- **Validate observations made with other Benchmarks.**
- **Valorise lessons learned and observations (publication, solution..).**

Tank you for your attention.

General Problem Scheme

