

CS 170 Project Algorithm

Smeet Patel

December 8, 2020

1 QP

Algorithm 1: Quadratic program for Graph Partitioning with Dynamic Constraints

Input: $i, j, h_{i,j}, s_{i,j} \forall i, j, R, S_{max}$

Output: $\{\text{room}_r: [\text{people} \in \text{room}_r]\}$

Initialization:

$e_{i,j_k} \leftarrow \{0, 1\}, \forall i, j \ \& \ k = \{1, \dots K\}$

$v_{i_k} \leftarrow \{0, 1\}, \forall i \ \& \ k = \{1, \dots K\}$

Objective:

$\max\{e_{i,j_k} * h_{i,j}, \forall i, j \ \& \ k = \{1, \dots K\}\}$

Constraints:

$\sum_{k=1}^K e_{i,j_k} = 1, \forall i, j$

$\sum_{(i,j)} e_{i,j_k} \leq \frac{S_{max}}{K}, k = \{1, \dots K\}$

$e_{i,j_k} = v_i v_j, \forall i, j \ \& \ k = \{1, \dots K\}$

2 LP

Algorithm 2: Linear program for Graph Partitioning with Dynamic Constraints

Input: $i, j, h_{i,j}, s_{i,j} \forall i, j, K, S_{max}$

Output: $\{\text{room}_r: [\text{people} \in \text{room}_r]\}$

Initialization:

$e_{i,j_k} \leftarrow \{0, 1\}, \forall i, j \ \& \ k = \{1, \dots K\}$

$v_{i_k} \leftarrow \{0, 1\}, \forall i \ \& \ k = \{1, \dots K\}$

Objective:

$\max\{e_{i,j_k} * h_{i,j}, \forall i, j \ \& \ k = \{1, \dots K\}\}$

Constraints:

$\sum_{k=1}^K e_{i,j_k} = 1, \forall i, j$

$\sum_{(i,j)} e_{i,j_k} \leq \frac{S_{max}}{K}, k = \{1, \dots K\}$

$e_{i,j_k} \leq v_{i_k} \forall i \ \& \ k = \{1, \dots K\}$

$e_{i,j_k} \leq v_{j_k} \forall i \ \& \ k = \{1, \dots K\}$

$e_{i,j_k} \geq v_{i_k} + v_{j_k} - 1 \forall i, j \ \& \ k = \{1, \dots K\}$
