

Neural Network Loss + Activation Cheat Sheet

Problem Type	Output Meaning	Activation Function	Loss Function	When to Use	Key Caveats
Binary Classification	Single probability (0–1)	Sigmoid	Binary Cross-Entropy (BCE)	Spam detection, yes/no tasks	Avoid MSE → poor gradients near 0/1
Multi-Class (Exclusive)	Probability distribution (sum = 1)	Softmax	Categorical Cross-Entropy (CCE)	Digit classification, image labels	Classes must be mutually exclusive
Multi-Class (Sparse Labels)	Same as above (integer labels)	Softmax	Sparse Categorical Cross-Entropy	Same as above, memory-efficient	Same caveat as CCE
Multi-Label Classification	Independent probabilities per class	Sigmoid (per output)	Binary Cross-Entropy (BCE)	Tags, object detection labels	Do NOT use softmax
Regression (Standard)	Continuous value	Linear (no activation)	Mean Squared Error (MSE)	Predicting prices, demand	Sensitive to outliers
Regression (Robust)	Continuous value	Linear	Mean Absolute Error (MAE)	Noisy data, outliers present	Less smooth gradients
Regression (Hybrid)	Continuous value	Linear	Huber Loss	Balance of MSE + MAE	Requires tuning delta
Imbalanced Classification	Probability	Sigmoid / Softmax	Focal Loss	Rare events (fraud, defects)	Extra hyperparameter (gamma)
Distribution Prediction	Full probability distribution	Softmax	KL Divergence	Forecasting distributions, generative models	Asymmetric (direction matters)
Margin-Based Classification	Distance from decision boundary	Linear / None	Hinge Loss	SVM-style classifiers	Not probabilistic

🔥 The Pairing Patterns (Memorize This)

1. Probabilities → Cross-Entropy Family

- Sigmoid → BCE
- Softmax → CCE

👉 Why:

- These losses are derived from log-likelihood
- They match probability theory → better gradients

2. Continuous Values → Distance-Based Loss

- Linear → MSE / MAE / Huber

👉 Why:

- You're measuring distance between numbers

3. Independent vs Competing Outputs

Case	Activation	Loss
Independent labels	Sigmoid	BCE
Competing classes	Softmax	CCE

👉 This is one of the most important distinctions in ML

⚠️ Common Mistakes (High-Value)

❌ Mistake 1: Softmax for multi-label

- Forces probabilities to sum to 1
- Breaks independent predictions

- ✗ Mistake 2: MSE for classification
 - Leads to slow / unstable training
 - Especially bad with sigmoid
 - ✗ Mistake 3: Ignoring outliers with MSE
 - Large errors dominate loss
 - Model overfits rare extreme cases
 - ✗ Mistake 4: Using BCE with Softmax
 - Assumes independence when outputs are dependent
-

🧠 Mental Shortcut (What you should think in practice)

When designing a model, ask:

1. What is my output?
 - Probability? → Cross-entropy
 - Number? → MSE/MAE
 2. Are outputs independent or competing?
 - Independent → Sigmoid
 - Competing → Softmax
 3. Do I have outliers or imbalance?
 - Yes → MAE / Huber / Focal
-

💡 Key Insight

If you want a one-liner for students:

Activation defines the output space.

Loss defines how mistakes are measured in that space.