

SITEPULSE

Technical Specifications / Hybrid Battery / Starlink / Generator

BATTERY	30 Ah / 48 V LFP (1.54 kWh) / 22 lb / active BMS / cell-level protection
INVERTER	2,000 W continuous / 4,000 W peak / hybrid w/ generator input / 120 V pure sine / 60 Hz
ENGINE	79cc single-cylinder gas / propane-ready / vibration-isolated mounts
STARTER GENERATOR	BLDC starter/alternator / 600-800 W sustained charging / VESC controller
CONNECTIVITY	Starlink Mini integrated (3.5 lb kit) / cellular failover / OTA firmware
FUEL	External quick-disconnect tank / gasoline w/ auto-stabilizer dosing on shutdown
SENSORS	Ultrasonic fuel level / SOC/V//temp / CO / enclosure temp / GPS
CHASSIS	SendcutSend sheet metal enclosure / IP65 / 8 lb / integrated carry handles
ENVIRONMENT	-20 C to +50 C (heaters optional) / <60 dB(A) enclosed / vibration-isolated
SAFETY	CO shutdown / fuel cutoff / BMS protect / GFCI / surge / local + remote E-stop
TOTAL WEIGHT	~90 lb dry (no fuel) / 85-95 lb range

Made in Yakima, Washington / Patents pending / V1 prototype / Generated 2026-07-14