

A statistical framework of watermarks for large language models:

Pivot, detection efficiency and optimal rules

Xiang Li

Joint work with Feng Ruan, Huiyuan Wang, Qi Long, and Weijie Su

University of Pennsylvania

May 29, 2024

Outline

Introduction

A statistical framework for watermark detection

Efficiency measure and optimal detection rule

Application to Gumbel-max watermark

Application to inverse transform watermark

Summary

Outline

Introduction

A statistical framework for watermark detection

Efficiency measure and optimal detection rule

Application to Gumbel-max watermark

Application to inverse transform watermark

Summary

Large language models (LLMs)


- ▶ LLMs is advanced AI systems trained to understand and generate human-like text.
- ▶ Many applications: content creation, customer service, education, code generation, healthcare, business intelligence,



Intelligent research assistant



Automated document generation and editing



Creative content creation

Large language models (LLMs)


- ▶ LLMs is advanced AI systems trained to understand and generate human-like text.
- ▶ Many applications: content creation, customer service, education, code generation, healthcare, business intelligence,



Intelligent research assistant



Automated document generation and editing



Creative content creation

- ▶ However, there are some issues.....

Academic integrity

- ▶ Did the student write this homework/paper by himself, or did an LLM lend a hand?



Peer review or LLM review?

- ▶ Liang et al. [2024] finds that between 6.5% and 16.9% reviews of some ML conferences were substantially modified by LLMs.
- ▶ Is your paper review really your own, or did an LLM lend a hand?



Document authenticity

- Is an impressively detailed patient report written by the patient or an LLM?



Central problem

Central problem

Given a text, how to determine whether it is generated by an LLM.

Central problem

Central problem

Given a text, how to determine whether it is generated by an LLM.

- ▶ Importance: misinformation, academic integrity, fair use and copyright.....

Central problem

Central problem

Given a text, how to determine whether it is generated by an LLM.

- ▶ Importance: misinformation, academic integrity, fair use and copyright.....
- ▶ Directly comparing the distribution of LLM outputs and human-written texts are neither accurate nor reliable [Weber-Wulff et al., 2023] and often biased [Krishna et al., 2024, Sadasivan et al., 2023, Liang et al., 2023].

Central problem

Central problem

Given a text, how to determine whether it is generated by an LLM.

- ▶ Importance: misinformation, academic integrity, fair use and copyright.....
- ▶ Directly comparing the distribution of LLM outputs and human-written texts are neither accurate nor reliable [Weber-Wulff et al., 2023] and often biased [Krishna et al., 2024, Sadasivan et al., 2023, Liang et al., 2023].
- ▶ More accurate detection requires us to have inner access of LLMs and thereby transition from a black-box to a white-box approach.
- ▶ Watermark is such an elegant and powerful method.

Watermark

- ▶ Watermarking enables more accurate detection of LLM-generated text by injecting subtle statistical patterns during text generation.
- ▶ Those patterns are unlikely to be replicated by a human but are constantly repeated by the watermarked LLM.
- ▶ Detecting the patterns help us detect the watermarks or equivalently the LLM-generated texts.

Preliminaries about LLM watermarks

Tokenization

- ▶ The tokenization process breaks down the text into smaller units called "tokens."
- ▶ Tokens can be words, parts of words, or even punctuation marks.¹

GPT-3.5 & GPT-4 GPT-3 (Legacy)

OpenAI's large language models (sometimes referred to as GPTs) process text using tokens, which are common sequences of characters found in a set of text. The models learn to understand the statistical relationships between these tokens and excel at producing the next token in a sequence of tokens.

OpenAI's large language models (sometimes referred to as GPTs) process text using tokens, which are common sequences of characters found in a set of text. The models learn to understand the statistical relationships between these tokens and excel at producing the next token in a sequence of tokens.

Tokens	Characters
57	299

[5109, 15836, 596, 3544, 4221, 4211, 320, 57753, 14183, 311, 439, 480, 2898, 82, 8, 1920, 1495, 1701, 11460, 11, 902, 527, 4279, 24630, 315, 5885, 1766, 304, 264, 743, 315, 1495, 13, 578, 4211, 4048, 311, 3619, 279, 29564, 12135, 1990, 1521, 11460, 323, 25555, 520, 17843, 279, 1828, 4037, 304, 264, 8668, 315, 11460, 13]

¹Refer to the website <https://platform.openai.com/tokenizer> for more examples of tokenization.

Autoregressive generation

- ▶ Let $\mathcal{W} = \{1, 2, \dots, K\}$ be the vocabulary and w a token therein.

Autoregressive generation

- ▶ Let $\mathcal{W} = \{1, 2, \dots, K\}$ be the vocabulary and w a token therein.
- ▶ The vocabulary size $K = |\mathcal{W}|$ is large and varies for different models.
- ▶ $K = 50272$ for the OPT-1.3B model; $= 32000$ for the LLaMA-7B model.


Autoregressive generation

- ▶ Let $\mathcal{W} = \{1, 2, \dots, K\}$ be the vocabulary and w a token therein.
- ▶ The vocabulary size $K = |\mathcal{W}|$ is large and varies for different models.
- ▶ $K = 50272$ for the OPT-1.3B model; $= 32000$ for the LLaMA-7B model.
- ▶ An LLM \mathcal{M} generates each token sequentially by sampling from a probability distribution conditioned on previous tokens:


$$w_t \sim \mathbf{P}_t \text{ where } \mathbf{P}_t = \mathcal{M}(w_{1:(t-1)}) \text{ is a distribution on } \mathcal{W}.$$

- ▶ The categorical distribution \mathbf{P}_t is referred to next-token prediction (NTP) distribution.

Autoregressive generation




Autoregressive generation




- ▶ Watermarks are embedded in each next-token sampling.

Watermarked generation



Watermarked generation



- ▶ \mathcal{S} is referred to as decoder.
- ▶ The watermark signal is the dependence of w_7 on ζ_7 .

A baby watermark

- ▶ Let $\mathcal{W} = \{0, 1\}$, $\mathbf{P}_t = (P_{t,0}, P_{t,1})$, ζ_t be i.i.d. copies of $\mathcal{U}(0, 1)$.
- ▶ The decoder is

$$w_t = \mathcal{S}(\mathbf{P}_t, \zeta_t) = \begin{cases} 0 & \text{if } \zeta_t \leq P_{t,0} \\ 1 & \text{otherwise.} \end{cases}$$

A baby watermark

- ▶ Let $\mathcal{W} = \{0, 1\}$, $\mathbf{P}_t = (P_{t,0}, P_{t,1})$, ζ_t be i.i.d. copies of $\mathcal{U}(0, 1)$.
- ▶ The decoder is

$$w_t = \mathcal{S}(\mathbf{P}_t, \zeta_t) = \begin{cases} 0 & \text{if } \zeta_t \leq P_{t,0} \\ 1 & \text{otherwise.} \end{cases}$$

- ▶ This watermark is unbiased in the following sense:

Definition (Unbiased)

For any $\mathbf{P} = (P_{t,0}, P_{t,1})$ and $w \in \{0, 1\}$,

$$\mathbb{P}_{\zeta_t \sim \mathcal{U}(0,1)}(\mathcal{S}(\mathbf{P}_t, \zeta_t) = w_t) = P_{t,w}.$$

A baby watermark

- ▶ Let $\mathcal{W} = \{0, 1\}$, $\mathbf{P}_t = (P_{t,0}, P_{t,1})$, ζ_t be i.i.d. copies of $\mathcal{U}(0, 1)$.
- ▶ The decoder is

$$w_t = \mathcal{S}(\mathbf{P}_t, \zeta_t) = \begin{cases} 0 & \text{if } \zeta_t \leq P_{t,0} \\ 1 & \text{otherwise.} \end{cases}$$

- ▶ This watermark is unbiased in the following sense:

Definition (Unbiased)

For any $\mathbf{P} = (P_{t,0}, P_{t,1})$ and $w \in \{0, 1\}$,

$$\mathbb{P}_{\zeta_t \sim \mathcal{U}(0,1)}(\mathcal{S}(\mathbf{P}_t, \zeta_t) = w_t) = P_{t,w}.$$

- ▶ If ζ_t is large, then w_t is more likely to be 1 instead of 0, and vice versa.
- ▶ Using the following statistic for detecting the watermark:

$$\sum_{t=1}^n (2w_t - 1)(2\xi_t - 1).$$


Watermarks are embedded in each next-token sampling: $w_t = \mathcal{S}(\mathbf{P}_t, \zeta_t)$

- Q1 How to make these $\zeta_{1:n}$ recoverable?
- Q2 Any examples of other unbiased decoder \mathcal{S} ?
- Q3 How to detect the dependence of w_t on ζ_t ?

Watermarks are embedded in each next-token sampling: $w_t = \mathcal{S}(\mathbf{P}_t, \zeta_t)$

- Q1** How to make these $\zeta_{1:n}$ recoverable?
- Q2** Any examples of other unbiased decoder \mathcal{S} ?
- Q3** How to detect the dependence of w_t on ζ_t ?

Q1. Use pseudorandom variables



Hash function \mathcal{A}

- ▶ In general, $\zeta_t = \mathcal{A}(w_{1:(t-1)}, \text{Key})$ is deterministic function.
- ▶ The deterministic nature makes $\zeta_{1:n}$ **recoverable** so they're termed as pseudorandom.

Hash function \mathcal{A}

- ▶ In general, $\zeta_t = \mathcal{A}(w_{1:(t-1)}, \text{Key})$ is deterministic function.
- ▶ The deterministic nature makes $\zeta_{1:n}$ **recoverable** so they're termed as pseudorandom.
- ▶ In analysis, we assume perfect randomness: $\zeta_t = \mathcal{A}(w_{1:(t-1)}, \text{Key}) \overset{i.i.d.}{\sim} \mathcal{U}(\Xi)$.
- ▶ The distribution of ζ_t in the watermarked model is **computationally indistinguishable** to the unwatermarked distribution.

Hash function \mathcal{A}

- ▶ In general, $\zeta_t = \mathcal{A}(w_{1:(t-1)}, \text{Key})$ is deterministic function.
- ▶ The deterministic nature makes $\zeta_{1:n}$ **recoverable** so they're termed as pseudorandom.
- ▶ In analysis, we assume perfect randomness: $\zeta_t = \mathcal{A}(w_{1:(t-1)}, \text{Key}) \overset{i.i.d.}{\sim} \mathcal{U}(\Xi)$.
- ▶ The distribution of ζ_t in the watermarked model is **computationally indistinguishable** to the unwatermarked distribution.
- ▶ Finding a feasible \mathcal{A} is a cryptography problem.

*Watermarks are embedded in each
next-token sampling: $w_t = \mathcal{S}(\mathbf{P}_t, \zeta_t)$*

Q1 How to make these $\zeta_{1:n}$ recoverable?

Use pseudorandom variables.

Q2 Any examples of other unbiased decoder \mathcal{S} ?

Q3 How to detect the dependence of w_t on ζ_t ?

Watermarks are embedded in each next-token sampling: $w_t = \mathcal{S}(\mathbf{P}_t, \zeta_t)$

Q1 How to make these $\zeta_{1:n}$ recoverable?

Use pseudorandom variables.

Q2 Any examples of other unbiased decoder \mathcal{S} ?

Q3 How to detect the dependence of w_t on ζ_t ?

Q1. Decoder \mathcal{S}^{gum} from Gumbel-max trick

Definition (Unbiased)

We say the decoder \mathcal{S} is unbiased if for any \mathbf{P} and $w \in \mathcal{W}$,

$$\mathbb{P}_{\zeta \sim \mathcal{U}(\Xi)}(\mathcal{S}(\mathbf{P}, \zeta) = w) = P_w.$$

Q1. Decoder \mathcal{S}^{gum} from Gumbel-max trick

Definition (Unbiased)

We say the decoder \mathcal{S} is unbiased if for any \mathbf{P} and $w \in \mathcal{W}$,

$$\mathbb{P}_{\zeta \sim \mathcal{U}(\Xi)}(\mathcal{S}(\mathbf{P}, \zeta) = w) = P_w.$$

Gumbel-max trick [Gumbel, 1948]

Let $\Xi = [0, 1]^K$ and $\zeta = (U_1, U_2, \dots, U_K) \in \Xi$ with U_k 's i.i.d. copies of $\mathcal{U}(0, 1)$. The Gumbel-max trick asserts that

$$\arg \max_{w \in \mathcal{W}} \frac{\log U_w}{P_w} \sim \mathbf{P} \equiv (P_w)_{w \in \mathcal{W}}.$$

Q1. Decoder \mathcal{S}^{gum} from Gumbel-max trick

Definition (Unbiased)

We say the decoder \mathcal{S} is unbiased if for any \mathbf{P} and $w \in \mathcal{W}$,

$$\mathbb{P}_{\zeta \sim \mathcal{U}(\Xi)}(\mathcal{S}(\mathbf{P}, \zeta) = w) = P_w.$$

Gumbel-max trick [Gumbel, 1948]

Let $\Xi = [0, 1]^K$ and $\zeta = (U_1, U_2, \dots, U_K) \in \Xi$ with U_k 's i.i.d. copies of $\mathcal{U}(0, 1)$. The Gumbel-max trick asserts that

$$\arg \max_{w \in \mathcal{W}} \frac{\log U_w}{P_w} \sim \mathbf{P} \equiv (P_w)_{w \in \mathcal{W}}.$$

Gumbel-max watermark [Aaronson, 2023]

$$\mathcal{S}^{\text{gum}}(\mathbf{P}, \zeta) = \arg \max_{k \in [K]} \left\{ \frac{1}{P_k} \cdot \log U_k \right\} \quad \text{where } \zeta = (U_1, \dots, U_K).$$

Q1. Decoder \mathcal{S}^{inv} from inverse transform sampling

Inverse transform sampling

The CDF of \mathbf{P} on \mathcal{W} is

$$F_{\mathbf{P}}(x) = \sum_{w' \in \mathcal{W}} P_{w'} \cdot \mathbf{1}_{\{w' \leq x\}}.$$

Taking as input $U \sim U(0, 1)$, the generalized inverse of this CDF is defined as

$$F_{\mathbf{P}}^{-1}(U) = \min \left\{ x : F_{\mathbf{P}}(x) \geq U \right\}.$$

The inverse transform sampling asserts that $F_{\mathbf{P}}^{-1}(U) \sim \mathbf{P} \equiv (P_w)_{w \in \mathcal{W}}$.

Q1. Decoder \mathcal{S}^{inv} from inverse transform sampling

Inverse transform sampling

The CDF of \mathbf{P} on \mathcal{W} is

$$F_{\mathbf{P}}(x) = \sum_{w' \in \mathcal{W}} P_{w'} \cdot \mathbf{1}_{\{w' \leq x\}}.$$

Taking as input $U \sim U(0, 1)$, the generalized inverse of this CDF is defined as

$$F_{\mathbf{P}}^{-1}(U) = \min \left\{ x : F_{\mathbf{P}}(x) \geq U \right\}.$$

The inverse transform sampling asserts that $F_{\mathbf{P}}^{-1}(U) \sim \mathbf{P} \equiv (P_w)_{w \in \mathcal{W}}$.

Inverse transform watermark [Kuditipudi et al., 2023]

$$\mathcal{S}_{\text{inv}}(\mathbf{P}, \zeta) := \pi \circ (F_{\pi(\mathbf{P})}^{-1}(U)) \quad \text{where} \quad \zeta = (U, \pi), \quad U \sim \mathcal{U}(\Pi), \quad U \perp \pi.$$

Watermarks are embedded in each next-token sampling: $w_t = \mathcal{S}(\mathbf{P}_t, \zeta_t)$

Q1 How to make these $\zeta_{1:n}$ recoverable?

Use pseudorandom variables.

Q2 Any examples of other unbiased decoder \mathcal{S} ?

$\mathcal{S}^{\text{gum}}, \mathcal{S}^{\text{inv}} \dots$

Q3 How to detect the dependence of w_t on ζ_t ?

Watermarks are embedded in each next-token sampling: $w_t = \mathcal{S}(\mathbf{P}_t, \zeta_t)$

Q1 How to make these $\zeta_{1:n}$ recoverable?

Use pseudorandom variables.

Q2 Any examples of other unbiased decoder \mathcal{S} ?

$\mathcal{S}^{\text{gum}}, \mathcal{S}^{\text{inv}} \dots$

Q3 How to detect the dependence of w_t on ζ_t ?

Watermarks are embedded in each next-token sampling: $w_t = \mathcal{S}(\mathbf{P}_t, \zeta_t)$

Q1 How to make these $\zeta_{1:n}$ recoverable?

Use pseudorandom variables.

Q2 Any examples of other unbiased decoder \mathcal{S} ?

$\mathcal{S}^{\text{gum}}, \mathcal{S}^{\text{inv}} \dots$

Q3 How to detect the dependence of w_t on ζ_t ?

A statistical framework is needed.

Outline

Introduction

A statistical framework for watermark detection

Efficiency measure and optimal detection rule

Application to Gumbel-max watermark

Application to inverse transform watermark

Summary

Review

Two-step watermarked generation

1. Generate a pseudorandom number: $\zeta_t = \mathcal{A}(w_{1:(t-1)}, \text{Key}) \sim \mathcal{U}(\Xi)$.
2. Compute the next token: $w_t = \mathcal{S}(\mathbf{P}_t, \zeta_t)$.

Definition (Watermark)

A watermark is defined by a tuple $(\mathcal{S}, \mathcal{A}, \text{Key})$.

The watermark signal is the dependence of each w_t on ζ_t .

Definition (Unbiased)

We say the decoder \mathcal{S} is unbiased if for any \mathbf{P} and $w \in \mathcal{W}$,

$$\mathbb{P}_{\zeta \sim \mathcal{U}(\Xi)}(\mathcal{S}(\mathbf{P}, \zeta) = w) = P_w.$$

Detection: The difficulty

Given data $(w_{1:n}, \zeta_{1:n})$,

$H_0 : w_{1:n}$ is written by human, *versus* $H_1 : w_{1:n}$ is watermarked by $(\mathcal{S}, \mathcal{A}, \text{Key})$.

Detection: The difficulty

Given data $(w_{1:n}, \zeta_{1:n})$,

$H_0 : w_{1:n}$ is written by human, *versus* $H_1 : w_{1:n}$ is watermarked by $(\mathcal{S}, \mathcal{A}, \text{Key})$.

Working Hypothesis

- ▶ Under H_0 , $(w_t, \zeta_t) \mid (w_{1:(t-1)}, \zeta_{1:(t-1)}) \stackrel{d}{=} \mathbf{P}_{\text{human},t} \times \mathcal{U}(\Xi)$.
- ▶ Under H_1 , $(w_t, \zeta_t) \mid (w_{1:(t-1)}, \zeta_{1:(t-1)}) \stackrel{d}{=} (\mathcal{S}(\zeta_t, \mathbf{P}_t), \zeta_t)$ and $\zeta_t \sim \mathcal{U}(\Xi)$.

Detection: The difficulty

Given data $(w_{1:n}, \zeta_{1:n})$,

$H_0 : w_{1:n}$ is written by human, *versus* $H_1 : w_{1:n}$ is watermarked by $(\mathcal{S}, \mathcal{A}, \text{Key})$.

Working Hypothesis

- ▶ Under H_0 , $(w_t, \zeta_t) \mid (w_{1:(t-1)}, \zeta_{1:(t-1)}) \stackrel{d}{=} \mathbf{P}_{\text{human},t} \times \mathcal{U}(\Xi)$.
- ▶ Under H_1 , $(w_t, \zeta_t) \mid (w_{1:(t-1)}, \zeta_{1:(t-1)}) \stackrel{d}{=} (\mathcal{S}(\zeta_t, \mathbf{P}_t), \zeta_t)$ and $\zeta_t \sim \mathcal{U}(\Xi)$.

But, we don't know $\mathbf{P}_{\text{human},1}, \dots, \mathbf{P}_{\text{human},n}$ and other $\mathbf{P}_1, \dots, \mathbf{P}_n$.

Detection: The difficulty

Given data $(w_{1:n}, \zeta_{1:n})$,

$H_0 : w_{1:n}$ is written by human, *versus* $H_1 : w_{1:n}$ is watermarked by $(\mathcal{S}, \mathcal{A}, \text{Key})$.

Working Hypothesis

- ▶ Under H_0 , $(w_t, \zeta_t) \mid (w_{1:(t-1)}, \zeta_{1:(t-1)}) \stackrel{d}{=} \mathbf{P}_{\text{human},t} \times \mathcal{U}(\Xi)$.
- ▶ Under H_1 , $(w_t, \zeta_t) \mid (w_{1:(t-1)}, \zeta_{1:(t-1)}) \stackrel{d}{=} (\mathcal{S}(\zeta_t, \mathbf{P}_t), \zeta_t)$ and $\zeta_t \sim \mathcal{U}(\Xi)$.

*But, we don't know $\mathbf{P}_{\text{human},1}, \dots, \mathbf{P}_{\text{human},n}$ and other $\mathbf{P}_1, \dots, \mathbf{P}_n$.
Impossible to estimate these unknown \mathbf{P}_t 's.*

Detection: The solution

Find a pivotal statistic $Y_t = Y(w_t, \zeta_t)$ such that

- ▶ Under H_0 , $Y_t \sim \mu_0$ regardless of $\mathbf{P}_{\text{human},t}$.
- ▶ Under H_1 , $Y_t \sim Y(\mathcal{S}(\zeta_t, \mathbf{P}_t), \zeta_t)$. Hence, $Y_t | \mathbf{P}_t \sim \mu_{1, \mathbf{P}_t}$.

Detection: The solution

Find a pivotal statistic $Y_t = Y(w_t, \zeta_t)$ such that

- ▶ Under H_0 , $Y_t \sim \mu_0$ regardless of $\mathbf{P}_{\text{human},t}$.
- ▶ Under H_1 , $Y_t \sim Y(\mathcal{S}(\zeta_t, \mathbf{P}_t), \zeta_t)$. Hence, $Y_t | \mathbf{P}_t \sim \mu_{1, \mathbf{P}_t}$.

Final formulation

$$H_0 : Y_t \stackrel{i.i.d.}{\sim} \mu_0 \quad \forall t \in [n] \quad \text{versus} \quad H_1 : Y_t | \mathbf{P}_t \sim \mu_{1, \mathbf{P}_t} \quad \forall t \in [n].$$

Good Detect distributional difference rather than independence.

Bad Use less information and sacrifice some power.

Detection: The solution

Find a pivotal statistic $Y_t = Y(w_t, \zeta_t)$ such that

- ▶ Under H_0 , $Y_t \sim \mu_0$ regardless of $\mathbf{P}_{\text{human},t}$.
- ▶ Under H_1 , $Y_t \sim Y(\mathcal{S}(\zeta_t, \mathbf{P}_t), \zeta_t)$. Hence, $Y_t | \mathbf{P}_t \sim \mu_{1, \mathbf{P}_t}$.

Final formulation

$$H_0 : Y_t \stackrel{i.i.d.}{\sim} \mu_0 \quad \forall t \in [n] \quad \text{versus} \quad H_1 : Y_t | \mathbf{P}_t \sim \mu_{1, \mathbf{P}_t} \quad \forall t \in [n].$$

Good Detect distributional difference rather than independence.

Bad Use less information and sacrifice some power.

- ▶ A score function $h : \mathbb{R} \rightarrow \mathbb{R}$ introduces a detection rule $T_h = \sum_{t=1}^n h(Y_t)$ which reject H_0 if T_h is larger than a threshold.

$$H_0 : Y_t \stackrel{i.i.d.}{\sim} \mu_0 \quad \forall t \in [n] \quad \text{versus} \quad H_1 : Y_t | \mathbf{P}_t \sim \mu_{1, \mathbf{P}_t} \quad \forall t \in [n]$$

Let's see some detection examples.

Detection for Gumbel-max watermark



- ▶ Recall $\mathcal{S}^{\text{gum}}(\mathbf{P}, \zeta) = \arg \max_{k \in [K]} \frac{\log U_k}{P_k}$ and $\zeta_t = (U_{t,1}, \dots, U_{t,K}) \in [0, 1]^K$.
- ▶ The pivotal statistic is $Y_t^{\text{ars}} = U_{t,w_t}$.

Detection for Gumbel-max watermark

- ▶ Recall $\mathcal{S}^{\text{gum}}(\mathbf{P}, \zeta) = \arg \max_{k \in [K]} \frac{\log U_k}{P_k}$ and $\zeta_t = (U_{t,1}, \dots, U_{t,K}) \in [0, 1]^K$.
- ▶ The pivotal statistic is $Y_t^{\text{ars}} = U_{t,w_t}$.
- ▶ Under H_0 , $Y_t^{\text{ars}} \stackrel{i.i.d.}{\sim} \mu_0 = \mathcal{U}(0, 1)$.
- ▶ Under H_1 , the CDF of μ_{1,\mathbf{P}_t} is $\mathbb{P}_1(Y_t^{\text{ars}} \leq y | \mathbf{P}_t) = \sum_{k \in [K]} P_{t,k} y^{1/P_{t,k}}$.

Detection for Gumbel-max watermark

- ▶ Recall $\mathcal{S}^{\text{gum}}(\mathbf{P}, \zeta) = \arg \max_{k \in [K]} \frac{\log U_k}{P_k}$ and $\zeta_t = (U_{t,1}, \dots, U_{t,K}) \in [0, 1]^K$.
- ▶ The pivotal statistic is $Y_t^{\text{ars}} = U_{t,w_t}$.
- ▶ Under H_0 , $Y_t^{\text{ars}} \stackrel{i.i.d.}{\sim} \mu_0 = \mathcal{U}(0, 1)$.
- ▶ Under H_1 , the CDF of μ_{1,\mathbf{P}_t} is $\mathbb{P}_1(Y_t^{\text{ars}} \leq y | \mathbf{P}_t) = \sum_{k \in [K]} P_{t,k} y^{1/P_{t,k}}$.



--- $\text{Pow}(2, 1)$
--- $\text{Pow}(1, 1)$
--- $\text{Pow}(0.5, 1)$
--- Uniform

Detection for Gumbel-max watermark

Default detection for Gumbel-max watermark [Aaronson, 2023]

Aaronson proposes to reject H_0 if the following quantity is larger than a given threshold:

$$T_{h_{\text{ars}}} = \sum_{t=1}^n h_{\text{ars}}(Y_t^{\text{ars}}) \quad \text{where} \quad h_{\text{ars}}(y) = -\log(1 - y).$$

Detection for Gumbel-max watermark

Default detection for Gumbel-max watermark [Aaronson, 2023]

Aaronson proposes to reject H_0 if the following quantity is larger than a given threshold:

$$T_{h_{\text{ars}}} = \sum_{t=1}^n h_{\text{ars}}(Y_t^{\text{ars}}) \text{ where } h_{\text{ars}}(y) = -\log(1 - y).$$

- ▶ Under H_0 , $h_{\text{ars}}(Y_t^{\text{ars}}) \stackrel{i.i.d.}{\sim} \text{Exp}(1)$ so that $\mathbb{E}_0 T_{\text{ars}} = n$.
- ▶ Under H_1 , $\mathbb{E}_1 T_{\text{ars}} \geq n + \left(\frac{\pi^2}{6} - 1\right) \sum_{t=1}^n \mathbb{E}_1 \text{Ent}(\mathbf{P}_t)$ where $\text{Ent}(\mathbf{P}_t)$ is Shannon entropy defined by $\sum_{k=1}^K P_{t,k} \log \frac{1}{P_{t,k}}$.

Detection for Gumbel-max watermark

Default detection for Gumbel-max watermark [Aaronson, 2023]

Aaronson proposes to reject H_0 if the following quantity is larger than a given threshold:

$$T_{h_{\text{ars}}} = \sum_{t=1}^n h_{\text{ars}}(Y_t^{\text{ars}}) \text{ where } h_{\text{ars}}(y) = -\log(1 - y).$$

- ▶ Under H_0 , $h_{\text{ars}}(Y_t^{\text{ars}}) \stackrel{i.i.d.}{\sim} \text{Exp}(1)$ so that $\mathbb{E}_0 T_{\text{ars}} = n$.
- ▶ Under H_1 , $\mathbb{E}_1 T_{\text{ars}} \geq n + \left(\frac{\pi^2}{6} - 1\right) \sum_{t=1}^n \mathbb{E}_1 \text{Ent}(\mathbf{P}_t)$ where $\text{Ent}(\mathbf{P}_t)$ is Shannon entropy defined by $\sum_{k=1}^K P_{t,k} \log \frac{1}{P_{t,k}}$.
- ▶ **Other h ?** Using the same Y_t^{ars} , Fernandez et al. [2023] finds that $-\log(1 - y)$ works better than the variant $\log y$.

Detection for inverse transform watermark

- ▶ Recall that $\zeta_t = (\pi_t, U_t) \in \Pi \times [0, 1]$. Define $\eta(k) = (k - 1)/(K - 1)$.
- ▶ The pivotal statistic used by Kuditipudi et al. [2023] is $Y_t^{\text{dif}} = |U_t - \eta(\pi_t(w_t))|$.

Detection for inverse transform watermark

- ▶ Recall that $\zeta_t = (\pi_t, U_t) \in \Pi \times [0, 1]$. Define $\eta(k) = (k - 1)/(K - 1)$.
- ▶ The pivotal statistic used by Kuditipudi et al. [2023] is $Y_t^{\text{dif}} = |U_t - \eta(\pi_t(w_t))|$.

Default detection for inverse transform watermark [Kuditipudi et al., 2023]

Kuditipudi proposes to reject H_0 if the following quantity is larger than a given threshold:

$$T_{h_{\text{neg}}} = \sum_{t=1}^n h_{\text{neg}}(Y_t^{\text{dif}}) \quad \text{where} \quad h_{\text{neg}}(y) = -y.$$

- ▶ Y_t^{dif} should be smaller under H_1 than under H_0 due to the correlation between U_t and $\eta(\pi_t(w_t))$.
- ▶ No analysis for μ_0 and μ_{1, \mathbf{p}_t} as well as the detection rationale.

Questions studied

- ▶ Multiple detection rules for Gumbel-max watermark. No theoretical justification.
- ▶ No theoretical analysis for the inverse transform watermark.
- ▶ What is the “optimal” score function h ?

Questions studied

- ▶ Multiple detection rules for Gumbel-max watermark. No theoretical justification.
- ▶ No theoretical analysis for the inverse transform watermark.
- ▶ What is the “optimal” score function h ?

Main questions

- ▶ Could we propose an **efficiency measure** to rank different detection rule?
- ▶ Could we find **the optimal detection rule** according to the efficiency measure?

Outline

Introduction

A statistical framework for watermark detection

Efficiency measure and optimal detection rule

Application to Gumbel-max watermark

Application to inverse transform watermark

Summary

Efficiency measure

$$H_0 : Y_t \overset{i.i.d.}{\sim} \mu_0 \quad \forall t \in [n] \quad \text{versus} \quad H_1 : Y_t | \mathbf{P}_t \sim \mu_{1, \mathbf{P}_t} \quad \forall t \in [n]$$

Efficiency measure

$$H_0 : Y_t \overset{i.i.d.}{\sim} \mu_0 \quad \forall t \in [n] \quad \text{versus} \quad H_1 : Y_t | \mathbf{P}_t \sim \mu_{1, \mathbf{P}_t} \quad \forall t \in [n]$$

- ▶ Under H_0 , $Y_t \overset{i.i.d.}{\sim} \mu_0$ so that Type I error can be controlled.
- ▶ Under H_1 , $Y_t | \mathbf{P}_t \sim \mu_{1, \mathbf{P}_t}$. Unknown and varies \mathbf{P}_t 's make analysis hard.

Efficiency measure

$$H_0 : Y_t \stackrel{i.i.d.}{\sim} \mu_0 \quad \forall t \in [n] \quad \text{versus} \quad H_1 : Y_t | \mathbf{P}_t \sim \mu_{1, \mathbf{P}_t} \quad \forall t \in [n]$$

- ▶ Under H_0 , $Y_t \stackrel{i.i.d.}{\sim} \mu_0$ so that Type I error can be controlled.
- ▶ Under H_1 , $Y_t | \mathbf{P}_t \sim \mu_{1, \mathbf{P}_t}$. Unknown and varies \mathbf{P}_t 's make analysis hard.

Key idea

Given a prior set \mathcal{P} , we consider the least-favorable type II error over \mathcal{P} .

- ▶ We then believe all the LLM-generated \mathbf{P}_t 's fall into \mathcal{P} .

Efficiency measure

Theorem

Fix a pivot scalar Y and a score function h . Let the Type I error of T_h be α . Then

$$\limsup_{n \rightarrow \infty} \sup_{\forall \mathbf{P}_t \in \mathcal{P}} [1 - \mathbb{E}_1 T_h(Y_{1:n})]^{1/n} \leq \exp(-R_{\mathcal{P}}(h)),$$

where $R_{\mathcal{P}}(h)$ is \mathcal{P} -dependent efficiency rate defined by

$$R_{\mathcal{P}}(h) = - \inf_{\theta \geq 0} \{ \theta \mathbb{E}_0 h(Y) + \log \phi_{\mathcal{P},h}(\theta) \} \quad \text{with} \quad \phi_{\mathcal{P},h}(\theta) = \sup_{\mathbf{P} \in \mathcal{P}} \mathbb{E}_1 [e^{-\theta h(Y)} | \mathbf{P}].$$

Efficiency measure

Theorem

Fix a pivot scalar Y and a score function h . Let the Type I error of T_h be α . Then

$$\limsup_{n \rightarrow \infty} \sup_{\forall \mathbf{P}_t \in \mathcal{P}} [1 - \mathbb{E}_1 T_h(Y_{1:n})]^{1/n} \leq \exp(-R_{\mathcal{P}}(h)),$$

where $R_{\mathcal{P}}(h)$ is \mathcal{P} -dependent efficiency rate defined by

$$R_{\mathcal{P}}(h) = - \inf_{\theta \geq 0} \{ \theta \mathbb{E}_0 h(Y) + \log \phi_{\mathcal{P},h}(\theta) \} \quad \text{with} \quad \phi_{\mathcal{P},h}(\theta) = \sup_{\mathbf{P} \in \mathcal{P}} \mathbb{E}_1 [e^{-\theta h(Y)} | \mathbf{P}].$$

- ▶ Motivated by large deviation theory.
- ▶ $R_{\mathcal{P}}(h) \geq 0$ by definition.
- ▶ The upper bound is tight under some regularities.

Optimal detection rule

- Maximize to find the optimal score function h^* :

$$h^* = \arg \max_h R_{\mathcal{P}}(h)$$

where we need to solve the following minimax problem:

$$\inf_h \left\{ \mathbb{E}_0 h(Y) + \sup_{P \in \mathcal{P}} \log \left(\mathbb{E}_1 [e^{-h(Y)} | P] \right) \right\}.$$

Optimal detection rule

- Maximize to find the optimal score function h^* :

$$h^* = \arg \max_h R_{\mathcal{P}}(h)$$

where we need to solve the following minimax problem:

$$\inf_h \left\{ \mathbb{E}_0 h(Y) + \sup_{P \in \mathcal{P}} \log \left(\mathbb{E}_1 [e^{-h(Y)} | P] \right) \right\}.$$

- It is generally not jointly convex-concave.

How to maximize $R_{\mathcal{P}}(h)$

$$\inf_h \left\{ \mathbb{E}_0 h(Y) + \sup_{P \in \mathcal{P}} \log \left(\mathbb{E}_1 [e^{-h(Y)} | P] \right) \right\}$$

Theorem

If there exists an $P^* \in \mathcal{P}$ and a score function class \mathcal{H} such that for all $h \in \mathcal{H}$,

$$\sup_{P \in \mathcal{P}} \mathbb{E}_1 [e^{-h(Y)} | P] = \mathbb{E}_1 [e^{-h(Y)} | P^*], \quad (P^*)$$

$$h^* := \log \frac{d\mu_{1,P^*}}{d\mu_0} \in \mathcal{H}, \quad (h^*)$$

we then have

$$\max_h R_{\mathcal{P}}(h) = D_{\text{KL}}(\mu_0, \mu_{1,P^*}),$$

where the maximum is obtained at h^* .

Our choice of the prior set \mathcal{P}

$$H_0 : Y_t \stackrel{i.i.d.}{\sim} \mu_0 \quad \forall t \in [n] \quad \text{versus} \quad H_1 : Y_t | \mathbf{P}_t \sim \mu_{1, \mathbf{P}_t} \quad \forall t \in [n], \mathbf{P}_t \in \mathcal{P}$$

Our choice of the prior set \mathcal{P}

$$H_0 : Y_t \stackrel{i.i.d.}{\sim} \mu_0 \quad \forall t \in [n] \quad \text{versus} \quad H_1 : Y_t | \mathbf{P}_t \sim \mu_{1, \mathbf{P}_t} \quad \forall t \in [n], \mathbf{P}_t \in \mathcal{P}$$

- ▶ Singleton: $\mathcal{P} = \{\mathbf{P}\}$. Classic focus [Chernoff, 1952, 1956, Bahadur, 1960].

Our choice of the prior set \mathcal{P}

$$H_0 : Y_t \stackrel{i.i.d.}{\sim} \mu_0 \quad \forall t \in [n] \quad \text{versus} \quad H_1 : Y_t | \mathbf{P}_t \sim \mu_{1, \mathbf{P}_t} \quad \forall t \in [n], \mathbf{P}_t \in \mathcal{P}$$

- ▶ Singleton: $\mathcal{P} = \{\mathbf{P}\}$. Classic focus [Chernoff, 1952, 1956, Bahadur, 1960].
- ▶ Our focus: Δ -regular set, i.e.,

$$\mathcal{P}_\Delta := \{\mathbf{P} = (P_1, \dots, P_K) : \max_k P_k \leq 1 - \Delta\}.$$

Our choice of the prior set \mathcal{P}

$$H_0 : Y_t \stackrel{i.i.d.}{\sim} \mu_0 \quad \forall t \in [n] \quad \text{versus} \quad H_1 : Y_t | \mathbf{P}_t \sim \mu_{1, \mathbf{P}_t} \quad \forall t \in [n], \mathbf{P}_t \in \mathcal{P}$$

- ▶ Singleton: $\mathcal{P} = \{\mathbf{P}\}$. Classic focus [Chernoff, 1952, 1956, Bahadur, 1960].
- ▶ Our focus: Δ -regular set, i.e.,

$$\mathcal{P}_\Delta := \{\mathbf{P} = (P_1, \dots, P_K) : \max_k P_k \leq 1 - \Delta\}.$$

- ▶ Why called regular? $\mu_0 \in \mathcal{P}_\Delta|_{\Delta=0}$ so $R_{\mathcal{P}}(h) = 0$ for any h .

Outline

Introduction

A statistical framework for watermark detection

Efficiency measure and optimal detection rule

Application to Gumbel-max watermark

Application to inverse transform watermark

Summary

Application to Gumbel-max watermark

$$\sup_{\mathbf{P} \in \mathcal{P}_\Delta} \phi_h(\mathbf{P}) := \mathbb{E}_1[e^{-h(Y)} | \mathbf{P}] \quad \text{where} \quad \mathcal{P}_\Delta = \{\mathbf{P} = (P_1, \dots, P_K) : \max_k P_k \leq 1 - \Delta\}.$$

To verify the (\mathbf{P}^\star) condition, we show that

Application to Gumbel-max watermark

$$\sup_{\mathbf{P} \in \mathcal{P}_\Delta} \phi_h(\mathbf{P}) := \mathbb{E}_1[e^{-h(Y)} | \mathbf{P}] \quad \text{where} \quad \mathcal{P}_\Delta = \{\mathbf{P} = (P_1, \dots, P_K) : \max_k P_k \leq 1 - \Delta\}.$$

To verify the (\mathbf{P}^*) condition, we show that

- For any non-decreasing h , $\mathbf{P} \mapsto \phi_h(\mathbf{P})$ is convex in \mathbf{P} .

Application to Gumbel-max watermark

$$\sup_{\mathbf{P} \in \mathcal{P}_\Delta} \phi_h(\mathbf{P}) := \mathbb{E}_1[e^{-h(Y)} | \mathbf{P}] \quad \text{where} \quad \mathcal{P}_\Delta = \{\mathbf{P} = (P_1, \dots, P_K) : \max_k P_k \leq 1 - \Delta\}.$$

To verify the (\mathbf{P}^*) condition, we show that

- ▶ For **any non-decreasing** h , $\mathbf{P} \mapsto \phi_h(\mathbf{P})$ is convex in \mathbf{P} .
- ▶ Let $\pi(\mathbf{P})$ denote the distribution whose k th coordinate is $P_{\pi(k)}$.

Extreme points of $\mathcal{P}_\Delta = \{\pi(\mathbf{P}_\Delta^*) : \pi \text{ is a permutation on } \{1, 2, \dots, |\mathcal{W}|\}\}$,

where

$$\mathbf{P}_\Delta^* = \left(\underbrace{1 - \Delta, \dots, 1 - \Delta}_{\lfloor \frac{1}{1-\Delta} \rfloor \text{ times}}, \tilde{\Delta}, 0, \dots \right) \quad \text{and} \quad \tilde{\Delta} = 1 - (1 - \Delta) \cdot \left\lfloor \frac{1}{1 - \Delta} \right\rfloor.$$

Application to Gumbel-max watermark

$$\sup_{\mathbf{P} \in \mathcal{P}_\Delta} \phi_h(\mathbf{P}) := \mathbb{E}_1[e^{-h(Y)} | \mathbf{P}] \quad \text{where} \quad \mathcal{P}_\Delta = \{\mathbf{P} = (P_1, \dots, P_K) : \max_k P_k \leq 1 - \Delta\}.$$

To verify the (\mathbf{P}^*) condition, we show that

- ▶ For any non-decreasing h , $\mathbf{P} \mapsto \phi_h(\mathbf{P})$ is convex in \mathbf{P} .
- ▶ Let $\pi(\mathbf{P})$ denote the distribution whose k th coordinate is $P_{\pi(k)}$.

Extreme points of $\mathcal{P}_\Delta = \{\pi(\mathbf{P}_\Delta^*) : \pi \text{ is a permutation on } \{1, 2, \dots, |\mathcal{W}|\}\}$,

where

$$\mathbf{P}_\Delta^* = \left(\underbrace{1 - \Delta, \dots, 1 - \Delta}_{\lfloor \frac{1}{1-\Delta} \rfloor \text{ times}}, \tilde{\Delta}, 0, \dots \right) \quad \text{and} \quad \tilde{\Delta} = 1 - (1 - \Delta) \cdot \left\lfloor \frac{1}{1 - \Delta} \right\rfloor.$$

$$\Rightarrow \sup_{\mathbf{P} \in \mathcal{P}_\Delta} \phi_h(\mathbf{P}) := \mathbb{E}_1[e^{-h(Y)} | \mathbf{P}_\Delta^*] \quad \text{for all any non-decreasing } h.$$

Efficiency comparison for Gumbel watermark

To verify the (h^*) condition, we find that

Efficiency comparison for Gumbel watermark

To verify the (h^*) condition, we find that

- The score function $h_{\text{gum},\Delta}^*$ is increasing:

$$h_{\text{gum},\Delta}^*(y) = \log \frac{d\mu_{1,\mathbf{P}_{\Delta}^*}}{d\mu_0}(y) = \log \left(\left\lfloor \frac{1}{1-\Delta} \right\rfloor y^{\frac{\Delta}{1-\Delta}} + y^{\frac{\tilde{\Delta}}{1-\tilde{\Delta}}} \right).$$

where

$$\tilde{\Delta} = 1 - (1 - \Delta) \cdot \left\lfloor \frac{1}{1-\Delta} \right\rfloor.$$

Efficiency comparison for Gumbel watermark

To verify the (h^*) condition, we find that

- ▶ The score function $h_{\text{gum},\Delta}^*$ is increasing:



$$h_{\text{gum},\Delta}^*(y) = \log \frac{d\mu_{1,\mathbf{P}_{\Delta}^*}}{d\mu_0}(y) = \log \left(\left\lfloor \frac{1}{1-\Delta} \right\rfloor y^{\frac{\Delta}{1-\Delta}} + y^{\frac{\tilde{\Delta}}{1-\tilde{\Delta}}} \right).$$

where



$$\tilde{\Delta} = 1 - (1 - \Delta) \cdot \left\lfloor \frac{1}{1-\Delta} \right\rfloor.$$

\Rightarrow The optimal score function is $h_{\text{gum},\Delta}^*$.

Efficiency comparison for Gumbel watermark



Simulation results



Outline

Introduction

A statistical framework for watermark detection

Efficiency measure and optimal detection rule

Application to Gumbel-max watermark

Application to inverse transform watermark

Summary

Analysis of μ_0 and $\mu_{1,\mathbf{P}}$ for inverse transform watermark

Lemma

- Recall $\eta(i) := \frac{i-1}{|\mathcal{W}|-1}$. Under H_0 , the CDF of Y_t^{dif} is

$$\mathbb{P}_0(Y_t^{\text{dif}} \leq r) = \frac{1}{|\mathcal{W}|} \sum_{i=1}^{|\mathcal{W}|} [\min\{\eta(i) + r, 1\} - \max\{\eta(i) - r, 0\}]. \quad (\mu_0)$$

- Under H_1 , the conditional CDF of Y_t^{dif} is

$$\mathbb{P}_1(Y_t^{\text{dif}} \leq r | \mathbf{P}_t) = \frac{1}{|\mathcal{W}|!} \sum_{\pi} \sum_{i=1}^{|\mathcal{W}|} |(a_{\pi,i-1}, a_{\pi,i}] \cap B(\eta(i), r)|, \quad (\mu_{1,\mathbf{P}_t})$$

where $a_{\pi,i} = \sum_{j=1}^i P_{t,\pi(j)}$, $B(v, r) = \{x \in [0, 1] : |x - v| \leq r\}$ and $|\cdot|$ represents the length of an interval.

Analysis of μ_0 and $\mu_{1,\mathbf{P}}$ for inverse transform watermark

Lemma

- Recall $\eta(i) := \frac{i-1}{|\mathcal{W}|-1}$. Under H_0 , the CDF of Y_t^{dif} is

$$\mathbb{P}_0(Y_t^{\text{dif}} \leq r) = \frac{1}{|\mathcal{W}|} \sum_{i=1}^{|\mathcal{W}|} [\min\{\eta(i) + r, 1\} - \max\{\eta(i) - r, 0\}]. \quad (\mu_0)$$

- Under H_1 , the conditional CDF of Y_t^{dif} is

$$\mathbb{P}_1(Y_t^{\text{dif}} \leq r | \mathbf{P}_t) = \frac{1}{|\mathcal{W}|!} \sum_{\pi} \sum_{i=1}^{|\mathcal{W}|} |(a_{\pi,i-1}, a_{\pi,i}] \cap B(\eta(i), r)|, \quad (\mu_{1,\mathbf{P}_t})$$

where $a_{\pi,i} = \sum_{j=1}^i P_{t,\pi(j)}$, $B(v, r) = \{x \in [0, 1] : |x - v| \leq r\}$ and $|\cdot|$ represents the length of an interval.

- A complicated combinatorial structure due to the permutation.

Weak convergence of CDFs

Key observation

Only dominant probabilities in \mathbf{P} matters. Simplify formulation by asymptotic analysis.

Weak convergence of CDFs

Key observation

Only dominant probabilities in \mathbf{P} matters. Simplify formulation by asymptotic analysis.

Theorem

Under H_0 ,

$$\lim_{|\mathcal{W}| \rightarrow \infty} \mathbb{P}_0(Y_t^{\text{dif}} \leq y) = 1 - (1 - y)^2 \quad \text{for any } y \in [0, 1]. \quad (\mu_0)$$

Under H_1 , assuming that $\lim_{|\mathcal{W}| \rightarrow \infty} P_{t,(1)} = 1 - \Delta$ and $\lim_{|\mathcal{W}| \rightarrow \infty} \log |\mathcal{W}| \cdot P_{t,(2)} = 0$ hold,

$$\lim_{|\mathcal{W}| \rightarrow \infty} \mathbb{P}_1(Y_t^{\text{dif}} \leq y \mid \mathbf{P}_t) = 1 - \left(1 - \frac{y}{1 - \Delta}\right)^2 \quad \text{for any } y \in [0, 1 - \Delta]. \quad (\mu_{1,\Delta})$$

Limit efficiency measure

- ▶ Let $K = |\mathcal{W}|$. For any $\log K \cdot \varepsilon_K \rightarrow 0$, we define

$$\overline{\mathcal{P}}_{\Delta} = \left\{ \mathbf{P} : P_{(1)} \leq 1 - \Delta, P_{(2)} \leq \varepsilon_K \right\}.$$

- ▶ The asymptotic perspective leads to the following limit efficiency measure:

$$\overline{R}_{\Delta}(h) = \liminf_{K \rightarrow \infty} R_{\overline{\mathcal{P}}_{\Delta}}(h).$$

Limit efficiency measure

- ▶ Let $K = |\mathcal{W}|$. For any $\log K \cdot \varepsilon_K \rightarrow 0$, we define

$$\overline{\mathcal{P}}_{\Delta} = \left\{ \mathbf{P} : P_{(1)} \leq 1 - \Delta, P_{(2)} \leq \varepsilon_K \right\}.$$

- ▶ The asymptotic perspective leads to the following limit efficiency measure:

$$\overline{R}_{\Delta}(h) = \liminf_{K \rightarrow \infty} R_{\overline{\mathcal{P}}_{\Delta}}(h).$$

- ▶ Under some technical conditions, we can exchange the order of \liminf , \sup , \inf , so

$$\overline{R}_{\Delta}(h) = - \inf_{\theta \geq 0} \left\{ \theta \mathbb{E}_{\mu_0} h(Y^{\text{dif}}) + \sup_{\Delta_0 \geq \Delta} \log \mathbb{E}_{\mu_{1, \Delta_0}} [e^{-\theta h(Y^{\text{dif}})}] \right\}.$$

Optimal detection rule

Finding optimal detection rule is reduced to solve the minimax optimization problem:

$$\sup_h \bar{R}_\Delta(h) = -\inf_h \left\{ \mathbb{E}_{\mu_0} h(Y^{\text{dif}}) + \sup_{\Delta_0 \geq \Delta} \log \phi_h(\Delta_0) \right\} \quad \text{where } \phi_h(\Delta_0) := \mathbb{E}_{\mu_1, \Delta_0} [e^{-h(Y^{\text{dif}})}].$$

Optimal detection rule

Finding optimal detection rule is reduced to solve the minimax optimization problem:

$$\sup_h \bar{R}_\Delta(h) = -\inf_h \left\{ \mathbb{E}_{\mu_0} h(Y^{\text{dif}}) + \sup_{\Delta_0 \geq \Delta} \log \phi_h(\Delta_0) \right\} \quad \text{where } \phi_h(\Delta_0) := \mathbb{E}_{\mu_1, \Delta_0} [e^{-h(Y^{\text{dif}})}].$$

- ▶ For (\mathbf{P}^*) , $\sup_{\Delta_0 \geq \Delta} \phi_h(\Delta_0) := \phi_h(\Delta)$ for all any non-increasing and Lipschitz h .
- ▶ For (h^*) , the score function $h_{\text{dif}, \Delta}^*$ is decreasing and local Lipschitz:

$$h_{\text{dif}, \Delta}^*(y) = \log \frac{f_{\text{dif}, \Delta}(y)}{f_{\text{dif}, 0}(y)} \quad \text{where} \quad f_{\text{dif}, \Delta}(y) = \frac{2}{1 - \Delta} \cdot \max \left\{ 1 - \frac{y}{1 - \Delta}, 0 \right\}.$$

Optimal detection rule

Finding optimal detection rule is reduced to solve the minimax optimization problem:

$$\sup_h \bar{R}_\Delta(h) = -\inf_h \left\{ \mathbb{E}_{\mu_0} h(Y^{\text{dif}}) + \sup_{\Delta_0 \geq \Delta} \log \phi_h(\Delta_0) \right\} \quad \text{where } \phi_h(\Delta_0) := \mathbb{E}_{\mu_1, \Delta_0} [e^{-h(Y^{\text{dif}})}].$$

- ▶ For (\mathbf{P}^*) , $\sup_{\Delta_0 \geq \Delta} \phi_h(\Delta_0) := \phi_h(\Delta)$ for all any non-increasing and Lipschitz h .
- ▶ For (h^*) , the score function $h_{\text{dif}, \Delta}^*$ is decreasing and local Lipschitz:

$$h_{\text{dif}, \Delta}^*(y) = \log \frac{f_{\text{dif}, \Delta}(y)}{f_{\text{dif}, 0}(y)} \quad \text{where} \quad f_{\text{dif}, \Delta}(y) = \frac{2}{1 - \Delta} \cdot \max \left\{ 1 - \frac{y}{1 - \Delta}, 0 \right\}.$$

\Rightarrow The optimal score function is $h_{\text{dif}, \Delta}^*$.

Optimal detection rule

Finding optimal detection rule is reduced to solve the minimax optimization problem:

$$\sup_h \bar{R}_\Delta(h) = -\inf_h \left\{ \mathbb{E}_{\mu_0} h(Y^{\text{dif}}) + \sup_{\Delta_0 \geq \Delta} \log \phi_h(\Delta_0) \right\} \quad \text{where } \phi_h(\Delta_0) := \mathbb{E}_{\mu_1, \Delta_0} [e^{-h(Y^{\text{dif}})}].$$



- ▶ For (\mathbf{P}^*) , $\sup_{\Delta_0 \geq \Delta} \phi_h(\Delta_0) := \phi_h(\Delta)$ for all any non-increasing and Lipschitz h .
- ▶ For (h^*) , the score function $h_{\text{dif}, \Delta}^*$ is decreasing and local Lipschitz:

$$h_{\text{dif}, \Delta}^*(y) = \log \frac{f_{\text{dif}, \Delta}(y)}{f_{\text{dif}, 0}(y)} \quad \text{where } f_{\text{dif}, \Delta}(y) = \frac{2}{1 - \Delta} \cdot \max \left\{ 1 - \frac{y}{1 - \Delta}, 0 \right\}.$$

\Rightarrow The optimal score function is $h_{\text{dif}, \Delta}^*$.

!! $\sup_h \bar{R}_\Delta(h) = \infty$. Be cautious to interpret this result.

Simulation results



Efficiency comparison on C4 newlike dataset and OPT-1.3B




Figure: Left: Type I. Right: Type II. Top: Gumbel-max. Bottom: Inverse transform.

Outline

Introduction

A statistical framework for watermark detection

Efficiency measure and optimal detection rule

Application to Gumbel-max watermark

Application to inverse transform watermark

Summary

Summary

- ▶ A statistical framework for detecting unbiased watermarks.
- ▶ Define the least-favorable efficiency measure to compare different detection rules.
- ▶ Identify the optimal detection rule according to the efficiency measure.

Future work

- ▶ Robust detection methods.
- ▶ Compare different watermarks or pivots.
- ▶ Analysis for biased watermarks.
- ▶ Failure of working hypothesis.

References I

- Scott Aaronson. Watermarking of large language models, August 2023. URL <https://simons.berkeley.edu/talks/scott-aaronson-ut-austin-openai-2023-08-17>.
- Raghu R Bahadur. On the asymptotic efficiency of tests and estimates. *Sankhyā: The Indian Journal of Statistics*, pages 229–252, 1960.
- Herman Chernoff. A measure of asymptotic efficiency for tests of a hypothesis based on the sum of observations. *The Annals of Mathematical Statistics*, pages 493–507, 1952.
- Herman Chernoff. Large-sample theory: Parametric case. *The Annals of Mathematical Statistics*, 27(1):1–22, 1956.
- Pierre Fernandez, Antoine Chaffin, Karim Tit, Vivien Chappelier, and Teddy Furon. Three bricks to consolidate watermarks for large language models. *arXiv preprint arXiv:2308.00113*, 2023.
- Emil Julius Gumbel. *Statistical theory of extreme values and some practical applications: A series of lectures*, volume 33. US Government Printing Office, 1948.
- Kalpesh Krishna, Yixiao Song, Marzena Karpinska, John Wieting, and Mohit Iyer. Paraphrasing evades detectors of AI-generated text, but retrieval is an effective defense. In *Advances in Neural Information Processing Systems*, volume 36, 2024.
- Rohith Kuditipudi, John Thickstun, Tatsunori Hashimoto, and Percy Liang. Robust distortion-free watermarks for language models. *arXiv preprint arXiv:2307.15593*, 2023.
- Weixin Liang, Mert Yuksekgonul, Yining Mao, Eric Wu, and James Zou. GPT detectors are biased against non-native english writers. In *ICLR 2023 Workshop on Trustworthy and Reliable Large-Scale Machine Learning Models*, 2023.
- Weixin Liang, Zachary Izzo, Yaohui Zhang, Haley Lepp, Hancheng Cao, Xuandong Zhao, Lingjiao Chen, Haotian Ye, Sheng Liu, Zhi Huang, et al. Monitoring AI-modified content at scale: A case study on the impact of chatgpt on ai conference peer reviews. *arXiv preprint arXiv:2403.07183*, 2024.
- Vinu Sankar Sadasivan, Aounon Kumar, Sriram Balasubramanian, Wenxiao Wang, and Soheil Feizi. Can AI-generated text be reliably detected? *arXiv preprint arXiv:2303.11156*, 2023.
- Debora Weber-Wulff, Alla Anohina-Naumeca, Sonja Bjelobaba, Tomávs Foltýnek, Jean Guerrero-Dib, Olumide Popoola, Petr vSigt, and Lorna Waddington. Testing of detection tools for AI-generated text. *International Journal for Educational Integrity*, 19(1):26, 2023.