

Standing All-In-One ESS

AIO Series

- LiFePO4 Battery + Inverter
- Integrated PV and AC charging
- High integration and easy installation
- Integrated UPS function

Model	AIO-2K607R-01-TVN		AIO-04K05R-01-TVN
Battery			
Battery Type	LiFePO4 Battery		
Battery Energy	2.6kWh		4kWh
Nominal Voltage	12.8V		12.8V
Rated Capacity	206Ah		314Ah
Voltage Range	10.0-14.6V		
PV			
Max.Power	3kW		
Max.PV Voltage	450Vdc		
MPPT Voltage Range	30-400Vdc		
Max.PV Input Current	18A		
AC Output			
Rated Power	2kW		
AC Voltage	230Vac±5%		
AC Frequency	50Hz/60Hz		
Efficiency	≤93%		
Transfer Time	<20ms		
Waveform	Pure sine wave		
AC Input			
Rated AC Voltage	230Vac		
AC Voltage Range	170-280Vac(for PC)90-280Vac(for Applis)		
Frequency Range	50Hz/60Hz		
General Parameters			
Altitude	≤2000m		
Humidity	5%-95%		
Work Temperature	-10℃-50℃		
IP Grade	IP20&IP54		
Communication	RS485/WiFi		
Size(mm)	610*390*230mm		610*390*230mm
Weight(kg)	20kg(about)		30kg(about)

