



IP65
Ingress Protection

10ms
Switching Time

2
MPPT

97%
Efficiency

Key Advantages

- Smart Energy Control**
Integrated 7 kW AC charger(supports plug to charge), smart port and remote O&M.
- Easy Installation**
Compact structure for convenient installation and maintenance.
- Safe, Reliable and Outdoor-Ready**
Advanced BMS, active fuse protection and IP65 enclosure.
- Powerful Backup for Heavy Loads**
200% peak output and up to 180 A charge/discharge current.
- ≤10 ms Ultra-Fast Switching**
Seamless Power During Outages
- Dual MPPT for Higher PV Yield**
Maximize solar generation with dual-channel tracking. Supports 2x PV power input capacity to cut electricity expenses further.

EcoLink Series

Single-phase Hybrid Inverter with optional EV Charger

Model	HYB-3K6LSG-01-TVN	HYB-4K6LSG-01-TVN	HYB-05KLSG-01-TVN	HYB-06KLSG-01-TVN	HYB-08KLSG-01-TVN
Input Data(PV)Power Supply					
Max. PV input power	7200W	9200W	10000W	12000W	12000W
Start-up voltage	90V				
Max. PV open-circuit voltage	550V				
MPPT voltage range	90V-530V				
Rated MPPT voltage	380V				
Max. PV short-circuit current	2*23A				
Max. PV input current	20A/20A				
MPP tracker/No. of Strings per MPP Tracker	2/1				
Battery					
Battery type	Lead-acid or Li-ion				
Battery voltage range	42-59V				
Nominal voltage	51.2V				
Max. charging/discharging current	83A/83A	104A/104A	112A/112A	130A/130A	180A/180A
Max. battery charging/discharging power	4000W/4000W	5000W/5000W	5400W/5400W	6500W/6500W	8800W/8800W
Battery communication	RS485/CAN				
Output Data (AC, On-grid)					
Rated AC output power	3600W	4600W	5000W	6000W	8000W
Rated output/Max. input current	16/50Aa.c.	20/50Aa.c.	21.7/50Aa.c.	26.1/50Aa.c.	34.8/50Aa.c.
Nominal grid voltage/range	230V/180-270V				
Nominal frequency/range	50 /60Hz; ±5Hz				
Power factor(@full load)	>0.99				
Power factor range	0.8lagging-0.8leading				
THDI (@rated power)	<3%				
Output data (AC, backup)					
Nominal EPS output Power	3600W	4600W	5000W	6000W	8000W
EPS Peak Power(10s)	10s @ 2 times of rated power				
AC nominal voltage	230Va.c.				
Rated/Max. output current	16Aa.c.	20Aa.c.	21.7Aa.c.	26Aa.c.	34Aa.c.
Pass through current (from grid to off grid)	50Aa.c.				
Nominal frequency	50 Hz/60Hz				
Automatic switch time	≤10ms				
THDV(Linear load)	<3%				
General data					
Battery Max. charging/discharging efficiency	94%/94%				
PV to AC max. efficiency	97.00%				
Euro efficiency	96.50%				
MPPT efficiency	99.90%				
Ingress Protection	IP65				
Protective Class	I				
Overvoltage category	PV: II, Battery: II, AC: III				
Topology	PV: Transformer-less; Battery: Isolated				
Cooling	Forced air cooling				
Noise emission (typical)	<58dB				
Operating temperature range	-25~+60 °C				
Full load operation temperature	-25~+45 °C				
Relative humidity	0-100%, non-condensing				
Max. altitude	4000m(Derating above 2000 m)				
Self-consumption	10W				
Display	LCD/LED				
Interface	Communication with Meter--Pluggable connector Communicaiton with Portal--Wi-Fi(USB)				
Certificates	CE, IEC61851, IEC62955, IEC62109-1, IEC 62109-2, EN IEC61000-6-1, EN IEC61000-6-2, EN IEC61000-6-3, EN IEC61000-6-4, IEC 61727, IEC 62116, IEC 61683				