



Rack Mount LiFePO4 Battery

LST Series

- BMS self-developed
- Communication protocol customization
- Max. 15 units in parallel
- 15 layers of protection

Model	BAT-5KLSK-00-TVN	BAT-7K5LSK-00-TVN	BAT-10KLSK-00-TVN	BAT-16KLSK-00-TVN
Battery Type	LiFePO4 Battery			
Battery Style	51.2V100Ah	51.2V150Ah	51.2V206Ah	51.2V314Ah
Battery Energy	5.12kWh	7.5kWh	10.5kWh	16kWh
Nominal Voltage	48V/51.2V			
Rated Capacity	100Ah	150Ah	206Ah	280/314Ah
End-of-Charge Voltage	54.0V/58.0V			
End-of-Discharge Voltage	39.0V/42.0V			
Standard Charge Current	50A	75A	100A	200A
Max.Charge Current	100A	150A	200A	200A
Standard Discharge Current	100A	100A	200A	200A
Max.Discharge Current	100A	150A	200A	200A
Max.Peak Current	150A	200A	300A	400A
Charge/Discharge Interface	2P/M8 Terminal(optional)			
Communication Interface	RS485/CAN			
Shell Material/Color	Metal/White(color optional)			
Work Temperature Range	Charge: 0°C~50°C Discharge: -15°C~60°C			
Size(mm)	442*420*133mm	442*450*168mm	442*420*266mm	442*715*233mm
Weight(kg)	43/45kg(about)	63/66kg(about)	85/88kg(about)	100/104kg(about)

