JC1503: Object-Oriented Programming
Group Project: Personal Finance Tracker

Group [AI Group 20]

May 2, 2026

Individual Contributions

Member	Responsibilities	Technical Implementation
Xinyuan Lin	System architecture, main program logic, data persistence, undo system, participated in the development of account.py	`main.py`, `linked_list.py`, `transaction.py`, account.py `exceptions.py`; HashMap/BST index integration, bug fixing
Zidan Ye	Account hierarchy design, OOP modelling (inheritance and polymorphism)	`account.py` (Account ABC, SavingsAccount, CreditAccount); code debugging
Yu Chen	Core data structure implementations	`bst.py`, `hashmap.py`, `tree.py`, `set.py`, `stack.py`, `queue.py`
Erhao Yao	Category management, notification system, testing and QA	`category.py`, `notification.py`; data generation, manual testing , report writing

Table 1: Summary of individual member responsibilities.

1 Problem and System Design

1.1 Application Domain

Our system is a **Personal Finance Tracker** that helps individuals manage their daily income and expenditure records. In everyday life, people need to track where their money goes, categorise spending habits, monitor large or unusual transactions, and manage bank account balances—tasks that are tedious and error-prone when done manually. Our application addresses this by providing a structured, persistent tool for recording, searching, and analysing personal financial data.

The system models three core real-world entities and their relationships:

- **Transaction** — an individual income or expense record, linked to a category and optionally to an account.
- **Category** — a hierarchical classification (e.g. *Expense* > *Food* > *Takeaway*), organised as a tree.
- **Account** — a bank account (savings or credit) whose balance is automatically updated when transactions are linked.

These entities are not independent: a transaction belongs to a category and may belong to an account; an account's balance evolves as transactions are added or removed. This interdependency makes the system a coherent whole rather than a loose collection of features.

1.2 System Architecture

The system is organised into three layers, as shown in Figure 1.

User Interface Layer (`main.py` — menu-driven CLI)
Business Logic Layer
Transaction CRUD | Category Management | Account Management
Undo (Stack) | Notification (Queue)
Data and Index Layer
DoublyLinkedList | HashMap (tid index) | BST (date/amount index)
Tree + Set (categories) | JSON Persistence

Figure 1: System architecture overview.

Why a system, not a script? The application maintains persistent state across sessions (JSON files), evolves its data as the user interacts, and its modules interact through shared indices and data structures. A script would simply re-compute results from static inputs; our system loads previous state, allows incremental modification, and saves the updated state—behaving like a real application.

2 Technical Design

2.1 Object-Oriented Modelling

Our design applies all core OOP principles:

Abstraction. `Account` is an abstract base class (inheriting from `ABC`) with two abstract methods—`get_account_type()` and `calculate_interest()`—that every concrete account type must implement. This enforces a consistent interface while allowing type-specific behaviour.

```python
class Account(ABC):
    @abstractmethod
    def get_account_type(self): pass
    @abstractmethod
```

```
    def calculate_interest(self): pass
```

Inheritance. `SavingsAccount` and `CreditAccount` both extend `Account`, inheriting common fields (`account_id`, `owner`, `_balance`) and methods (`deposit`, `get_balance`, `to_dict`). Each subclass adds its own attributes: `interest_rate` for savings and `credit_limit` for credit.

Polymorphism. `calculate_interest()` behaves differently in each subclass: savings accounts return `balance` $\times$ `rate`, while credit accounts return `|overdraft|` $\times$ `0.20` (or 0 if no overdraft). Similarly, `CreditAccount.withdraw()` overrides the base method to allow negative balances up to the credit limit. The call site in `main.py` uses the base-class interface without knowing the concrete type.

Encapsulation. Internal state is hidden using Python's convention: `_balance` is a private attribute accessed only through `get_balance()` and modified only through `deposit()`/`withdraw()`, which validate inputs and raise custom exceptions on errors. Similarly, `Stack._items` and `Queue._items` are not exposed externally.

Composition. `CategoryManager` composes a `Tree` (for hierarchical structure) and a `Set` (for name uniqueness). `NotificationManager` composes a `Queue` (for FIFO message consumption). These has-a relationships are preferred over inheritance because manager classes delegate to their component structures rather than specialising them.

2.2 Data Structures and Algorithms

All six required data structures are **implemented from scratch** (no Python built-in `dict` or `list` used for core logic) and are integrated into the system's behaviour:

Structure	File	Role in System	Complexity
Doubly Linked List	`linked_list.py`	Primary storage for transactions; O(1) head insert/delete	O(1)
HashMap	`hashmap.py`	tid $\rightarrow$ Node index for O(1) lookup	O(1) avg
BST	`bst.py`	Date and amount indices for range queries	O($\log n$) avg
Stack	`stack.py`	Undo operation history (LIFO)	O(1) push/pop
Queue	`queue.py`	Notification FIFO consumption	O(1) enq/deq
Tree (multi-way)	`tree.py`	Hierarchical category structure	—
Set (on HashMap)	`set.py`	Category name uniqueness check	O(1) avg

Table 2: Data structure usage summary.

Recursive algorithms. The BST implements recursive insert, search, delete, in-order traversal, and range query. The Tree implements recursive DFS traversal, height computation, and the CategoryManager uses recursive serialisation. A representative example is the BST range query:

```
def _range_query_recursive(self, node, low, high, result):
    if node is None: return
    if low < node.key:
        self._range_query_recursive(node.left, low, high, result)
    if low <= node.key <= high:
        result.append(node.value)
    if node.key < high:
        self._range_query_recursive(node.right, low, high, result)
```

2.3 Efficiency and Complexity

A key design decision was building auxiliary indices on top of the linked list to avoid $O(n)$ linear scans:

- **HashMap index** (`tid_index`): Finding a transaction by ID is $O(1)$ on average instead of $O(n)$ list traversal. This is critical for update and delete operations.
- **BST indices** (`date_index`, `amount_index`): Range queries run in $O(\log n + k)$ where k is the number of matching records, compared to $O(n)$ for a full scan.
- **Trade-off**: Building indices takes $O(n \log n)$ at startup, but this is a one-time cost that pays off across all subsequent queries.
- **Limitation**: The BST is not self-balancing; in the worst case it degrades to a linked list with $O(n)$ search time. An AVL or red-black tree would guarantee $O(\log n)$ worst-case performance.

3 Development and Testing

3.1 Iterative Development

The system was built in four stages:

1. **Foundation**: Doubly linked list plus Transaction model plus basic CRUD (add/delete/view). Data persisted via JSON with `to_dict()`/`from_dict()` class methods.
2. **Indexing**: Added HashMap (tid index) and BST (date/amount indices) to optimise lookup and range queries from $O(n)$ to $O(1)$ and $O(\log n)$.
3. **Support features**: Added Stack-based undo system, Queue-based notification system, Tree plus Set category management with recursive serialisation.
4. **Account system**: Introduced `Account` abstract class with `SavingsAccount` and `CreditAccount` subclasses, demonstrating inheritance, polymorphism, and custom exceptions.

Each stage added functionality that was tested manually and then integrated into the growing system.

3.2 Problem Solving

Problem 1: JSON-to-Object Conversion. When loading data from JSON, we needed to convert plain dictionaries back into `Transaction` and `Account` objects. Initially we used standalone functions, but this scattered creation logic away from the class definition. The solution was to use `@classmethod` factory methods:

```
@classmethod
def from_dict(cls, data: dict) -> 'Transaction':
    return cls(tid=data["tid"], type=data["type"],
               amount=data["amount"], ...)
```

This keeps serialisation and deserialisation logic paired with the class, improving cohesion and maintainability.

Problem 2: Transaction ID Uniqueness. Allowing duplicate tids would corrupt the HashMap index. We solved this with a validation loop in `main.py` that uses `check_tid_exists()` ($O(1)$ via HashMap) before accepting a new transaction, prompting the user to re-enter if a duplicate is detected.

Problem 3: Undo State Management. Recording enough information to reverse any operation was non-trivial. The Stack stores operation descriptors (`action`, `tid`, `old_data`) that allow the reverse operation to be computed: undoing an add means deleting; undoing a delete means re-adding with saved data; undoing an update means restoring original field values.

3.3 Testing Strategy

Unit Testing. Each module file includes an `if __name__ == "__main__"` block at the bottom that exercises the module's key operations. For example, `account.py` tests deposit, withdraw (including overdraft), interest calculation, and custom exception handling; `bst.py` tests insert, search, range query, and delete; `hashmap.py` tests put, get, update, and remove.

System Testing. We performed end-to-end manual testing by running the full application and verifying:

- Creating, updating, and deleting transactions with valid and invalid inputs.
- Range queries by date and amount returning correct results.
- Undo operations correctly restoring previous state.
- Account balance updating correctly when transactions are linked.
- The program not crashing on malformed input (negative amounts, non-numeric IDs).

4 Reflection

4.1 Critical Assessment

What works well. The choice of data structures maps naturally to the domain: a linked list for sequential transaction storage, a HashMap for instant ID lookup, BSTs for range queries, a Tree for hierarchical categories, a Stack for undo, and a Queue for notifications. The OOP design cleanly separates concerns. Moreover, the abstract `Account` class with polymorphic `calculate_interest()` makes it straightforward to add new account types in the future.

Current limitations.

- The BST is not self-balancing; sorted insertions degrade it to $O(n)$ search time.
- Interest calculation does not consider the time period (days/months); it always computes annual interest.
- Data is stored in plain JSON with no encryption or access control.
- The CLI interface, while functional, is not intuitive for non-technical users.

4.2 Future Improvements

If development continued, we would:

- Replace the plain BST with an AVL tree or red-black tree for guaranteed $O(\log n)$ worst-case performance.(P2)
- Add a `days` parameter to `calculate_interest()` so that users can compute interest for arbitrary periods.(P3)
- Implement a GUI (e.g. using Tkinter or a web framework) for better usability.(P1)
- Add password protection and data encryption for stored files.(P1)
- Implement budget tracking and spending trend visualisation.(P2)

4.3 Learning Outcomes

Through this project, we gained practical understanding of several key principles:

- **Composition over inheritance**: `CategoryManager` composes a `Tree` and a `Set` rather than inheriting from either, because it needs both behaviours simultaneously. This is cleaner than multiple inheritance.
- **Data structure choice matters**: Building HashMap and BST indices transformed $O(n)$ operations into $O(1)$ and $O(\log n)$, making the system responsive even with many records.

- **Recursion is natural for trees**: Traversal, serialisation, and height computation all follow the recursive structure of the tree itself, producing concise and readable code.
- **Iterative refinement**: The system grew through four stages, with each stage adding and testing functionality before proceeding. Problems discovered during testing led to further design improvements.
- **Object-oriented data handling**: When reading transaction records from JSON files, we mapped dictionary data to object instances. We discovered that encapsulating this logic within class methods significantly streamlined the process, reducing boilerplate code and improving maintainability