

```
===== FILE: src/app/(auth)/login/page.tsx =====
"use client";
import { useState } from "react";
import { useRouter } from "next/navigation";
import Link from "next/link";
import { Topbar } from "@components/dashboard/Topbar";
import { Button } from "@components/ui/Button";
import { Input } from "@components/ui/Input";
import { useToast } from "@hooks/useToast";
import { createClient } from "@lib/supabase/client";
import { Tabs, TabsList, TabsTrigger, TabsContent } from "@components/ui/Tabs";

export default function LoginPage() {
  const [loading, setLoading] = useState(false);
  const [identifier, setIdentifier] = useState("");
  const [password, setPassword] = useState("");
  const [phone, setPhone] = useState("");
  const [otpToken, setOtpToken] = useState("");
  const [otpSent, setOtpSent] = useState(false);
  const router = useRouter();
  const { showToast } = useToast();

  // 0^0^0-Û\212Û\204 0$Û\2040^-0@Û\210Û\204 0^-0$Û\2040^-0±Û\2120^- 0£Û\210 Û\203Û\204Û\2050
  © 0$Û\204Û\2050±Û\2100±
  const handlePasswordLogin = async (e: React.FormEvent) => {
    e.preventDefault();
    setLoading(true);
    try {
      const res = await fetch("/api/auth/login", {
        method: "POST",
        headers: { "Content-Type": "application/json" },
        body: JSON.stringify({ identifier, password }),
      });
      const data = await res.json();
      if (!res.ok) throw new Error(data.error);

      // 0-Û\2040^- 0$Û\204Û\2050^0^0@0^-Û\205 Û\205Û\206 0$Û\2040^-Û\2040^0^0
      const supabase = createClient();
      const { data: { user } } = await supabase.auth.getUser();
      const role = user?.user_metadata?.role || "retailer";

      let dashboardPath = "/dashboard/retailer/overview";
      if (role === "admin") dashboardPath = "/dashboard/admin/overview";
      else if (role === "wholesaler") dashboardPath = "/dashboard/wholesale/overview";
      else if (role === "delivery") dashboardPath = "/dashboard/delivery/overview";

      showToast("0^Û\205 0^0^0-Û\212Û\204 0$Û\2040^-0@Û\210Û\204 0^-Û\2060^-0$0-!", "success");

      router.push(dashboardPath);
    } catch (error: any) {
      showToast(error.message, "error");
    } finally {
      setLoading(false);
    }
  };

  // 0¥0±0^30$Û\204 0±Û\2050^2 OTP Û\204Û\204Û\2070$0^Û\201
  const handleSendOtp = async () => {
    if (!phone) return showToast("0£0^-0@Û\204 0±Û\202Û\205 0$Û\204Û\2070$0^Û\201", "error");
    setLoading(true);
    try {
      const res = await fetch("/api/auth/phone", {
        method: "POST",
        headers: { "Content-Type": "application/json" },
        body: JSON.stringify({ action: "send", phone }),
      });
      const data = await res.json();
      if (!res.ok) throw new Error(data.error);
      showToast("0^Û\205 0¥0±0^30$Û\204 0±Û\2050^2 0$Û\2040^0-Û\202Û\202 0¥Û\204Û\211 Û\207
```

```
ø$øªù\201ù\203", "success");
    setOtpSent(true);
  } catch (error: any) {
    showToast(error.message, "error");
  } finally {
    setLoading(false);
  }
};

// ø$ù\204øªø-ù\202ù\202 ù\205ù\206 ø$ù\204ø±ù\205ø² ù\210øªø³ø¬ù\212ù\204 ø$ù\204ø¬øøù\210ù\204
const handleVerifyOtp = async () => {
  if (!otpToken) return showToast("ø£ø¬øøù\204 ø±ù\205ø² ø$ù\204øªø-ù\202ù\202", "error");
  setLoading(true);
  try {
    const res = await fetch("/api/auth/phone", {
      method: "POST",
      headers: { "Content-Type": "application/json" },
      body: JSON.stringify({ action: "verify", phone, token: otpToken }),
    });
    const data = await res.json();
    if (!res.ok) throw new Error(data.error);

    const role = data.user?.user_metadata?.role || "retailer";
    let dashboardPath = "/dashboard/retailer/overview";
    if (role === "admin") dashboardPath = "/dashboard/admin/overview";
    else if (role === "wholesaler") dashboardPath = "/dashboard/wholesale/overview";
    else if (role === "delivery") dashboardPath = "/dashboard/delivery/overview";

    showToast("øªù\205 øªø³ø¬ù\212ù\204 ø$ù\204ø¬øøù\210ù\204 ø¬ù\206ø¬ø$ø¬!", "success");
    router.push(dashboardPath);
  } catch (error: any) {
    showToast(error.message, "error");
  } finally {
    setLoading(false);
  }
};

return (
  <div className="min-h-screen bg-gray-50">
    <Topbar />
    <div className="flex items-center justify-center p-4 pt-20">
      <div className="w-full max-w-md bg-white rounded-2xl shadow-xl p-8">
        <h1 className="text-3xl font-extrabold text-center mb-6">ù\205ø±ø-ø¬ø$ù\213 ø¬ø¹ù\210ø¬øªù\203 ø\237\221\213</h1>

        <Tabs defaultValue="email">
          <TabsList className="w-full mb-6">
            <TabsTrigger value="email" className="flex-1">ø$ù\204ø¬ø±ù\212ø¬ ø$ù\204ø¥ù\204ù\203øªø±ù\210ù\206ù\212</TabsTrigger>
            <TabsTrigger value="phone" className="flex-1">ø±ù\202ù\205 ø$ù\204ù\207ø$øªù\201</TabsTrigger>
          </TabsList>

          {/* øªø³ø¬ù\212ù\204 ø$ù\204ø¬øøù\210ù\204 ø¬ø$ù\204ø¬ø±ù\212ø¬ */}
          <TabsContent value="email">
            <form onSubmit={handlePasswordLogin} className="space-y-4">
              <Input placeholder="ø$ù\204ø¬ø±ù\212ø¬ ø$ù\204ø¥ù\204ù\203øªø±ù\210ù\206ù\212" value={identifier} onChange={(e) => setIdentifier(e.target.value)} required className="h-12" />
              <Input type="password" placeholder="ù\203ù\204ù\205øø ø$ù\204ù\205ø±ù\210ø±" value={password} onChange={(e) => setPassword(e.target.value)} required className="h-12" />
              <Button type="submit" disabled={loading} size="lg" className="w-full">
                {loading ? "ø¬ø$ø±ù\215 ø$ù\204ø¬øøù\210ù\204..." : "øªø³ø¬ù\212ù\204 ø$ù\204ø¬øøù\210ù\204"}
              </Button>
            </form>
          </TabsContent>
        </Tabs>
      </div>
    </div>
  </div>
);
```

```
</TabsContent>

{ /* ØªØ³Ø-Ù\212Ù\204 Ø$Ù\204Ø-Ø@Ù\210Ù\204 Ø`Ø$Ù\204Ù\207Ø$ØªÙ\201 */}
<TabsContent value="phone" className="space-y-4">
  <Input placeholder="Ø±Ù\202Ù\205 Ø$Ù\204Ù\207Ø$ØªÙ\201 (Ø`Ø$Ù\204ØµÙ\212Ø°Ø
© Ø$Ù\204Ø-Ù\210Ù\204Ù\212Ø© 9647XXXXXXXXX)" value={phone} onChange={(e) => setPhone(e.ta
rget.value)} required className="h-12" />

  {!otpSent ? (
    <Button onClick={handleSendOtp} disabled={loading} size="lg" className="w
-full">
      {loading ? "Ø-Ø$Ø±Ù\215 Ø$Ù\204Ø¥Ø±Ø³Ø$Ù\204..." : "Ø¥Ø±Ø³Ø$Ù\204 Ø±Ù
\205Ø² Ø$Ù\204ØªØ-Ù\202Ù\202"}
    </Button>
  ) : (
    <>
      <Input placeholder="Ø±Ù\205Ø² Ø$Ù\204ØªØ-Ù\202Ù\202 (OTP)" value={otpTo
ken} onChange={(e) => setOtpToken(e.target.value)} required className="h-12" />
      <Button onClick={handleVerifyOtp} disabled={loading} size="lg" classNam
e="w-full">
        {loading ? "Ø-Ø$Ø±Ù\215 Ø$Ù\204ØªØ-Ù\202Ù\202..." : "ØªØ£Ù\203Ù\212Ø-
Ø$Ù\204Ø-Ø@Ù\210Ù\204"}
      </Button>
    </>
  ) }
</TabsContent>
</Tabs>

<div className="text-center mt-6 text-sm text-gray-500">
  Ù\204Ù\212Ø³ Ù\204Ø-Ù\212Ù\203 Ø-Ø³Ø$Ø`Ø\237 <Link href="/register" className
="text-primary font-semibold">Ø¥Ù\206Ø'Ø$Ø; Ø-Ø³Ø$Ø` Ø-Ø-Ù\212Ø</Link>
</div>
</div>
</div>
</div>
);
}
```

```
===== FILE: src/app/(auth)/register/page.tsx =====
"use client";
import { useState } from "react";
import { useRouter } from "next/navigation";
import Link from "next/link";
import { Topbar } from "@/components/dashboard/Topbar";
import { Button } from "@/components/ui/Button";
import { Input } from "@/components/ui/Input";
import { useToast } from "@/hooks/useToast";
import { createClient } from "@/lib/supabase/client";

export default function RegisterPage() {
  const [loading, setLoading] = useState(false);
  const router = useRouter();
  const { showToast } = useToast();

  const handleSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    setLoading(true);
    const formData = new FormData(e.target as HTMLFormElement);
    const name = formData.get("name") as string;
    const email = formData.get("email") as string;
    const phone = formData.get("phone") as string; // Ø¥Ø¹Ø$Ù\201Ø© Ø$Ù\204Ù\207Ø$ØªÙ\201
    const password = formData.get("password") as string;

    const supabase = createClient();
    const { data, error } = await supabase.auth.signUp({
      email,
      password,
      options: {
        data: { name, role: "retailer", phone },
      },
    },
```

```
});

if (error) return showToast(error.message, "error");

if (data.user) {
  await supabase.from('users').insert({
    id: data.user.id, name, email, phone, role: "retailer",
  });
}

showToast("ðªÛ\205 ð¥Û\206ð'ð$ð; ð$Û\204ð-ð³ð$ð" ð"Û\206ð-ð$ð-!", "success");
router.push("/login");
};

return (
  <div className="min-h-screen bg-gray-50">
    <Topbar />
    <div className="flex items-center justify-center p-4 pt-20">
      <div className="w-full max-w-md bg-white rounded-2xl shadow-xl p-8">
        <h1 className="text-3xl font-extrabold text-center mb-6">ð¥Û\206ð'ð$ð; ð-ð³ð$ð"
ð-ð"Û\212ð"</h1>
        <form onSubmit={handleSubmit} className="space-y-4">
          <Input name="name" placeholder="ð$Û\204ð$ð³Û\205 ð$Û\204Û\203ð$Û\205Û\204" re
quired className="h-12" />
          <Input name="email" type="email" placeholder="ð$Û\204ð"ð±Û\212ð" ð$Û\204ð¥Û
\204Û\203ðªð±Û\210Û\206Û\212" required className="h-12" />
          <Input name="phone" type="tel" placeholder="ð±Û\202Û\205 ð$Û\204Û\207ð$ðªÛ
\201 (Û\205ð«ð$Û\204: 9647XXXXXXXX)" required className="h-12" />
          <Input name="password" type="password" placeholder="Û\203Û\204Û\205ðð ð$Û\204
Û\205ð±Û\210ð±" required className="h-12" />
          <Button type="submit" disabled={loading} size="lg" className="w-full">
            {loading ? "ð-ð$ð±Û\215 ð$Û\204ðªð³ð-Û\212Û\204..." : "ð¥Û\206ð'ð$ð; ð$Û
\204ð-ð³ð$ð"}
          </Button>
        </form>
        <div className="text-center mt-6 text-sm text-gray-500">
          Û\204ð"Û\212Û\203 ð-ð³ð$ð"ð\237 <Link href="/login" className="text-primary f
ont-semibold">ðªð³ð-Û\212Û\204 ð$Û\204ð-ððÛ\210Û\204</Link>
        </div>
      </div>
    </div>
  </div>
);
}

===== FILE: src/app/(dashboard)/admin/analytics/page.tsx =====
import { Topbar } from "@/components/dashboard/Topbar";
import { Card, CardContent, CardHeader, CardTitle } from "@/components/ui/Card";
import { BarChart } from "@/components/charts/BarChart";
import { Users, ShoppingCart, DollarSign, TrendingUp } from "lucide-react";

export default function AdminAnalyticsPage() {
  // ð"Û\212ð$Û\206ð$ðª ðªð-ð±Û\212ð"Û\212ðð Û\205ðªÛ\202ðªðð Û\204Û\205Û\204ð; ð$Û\204Û
\210ð$ð-Û\207ðð (ð³Û\212ðªÛ\205 ð±ð"ð•Û\207ð$ ð"ð$Û\204Û\200 API Û\204ð$ð-Û\202ð$Û\213)
  const data = [
    { name: "Û\212Û\206ð$Û\212ð±", value: 1000 },
    { name: "Û\201ð"ð±ð$Û\212ð±", value: 1500 },
    { name: "Û\205ð$ð±ð³", value: 1200 },
    { name: "ð£ð"ð±Û\212Û\204", value: 1800 },
  ];

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <h1 className="text-3xl font-bold mb-6">ðªð-Û\204Û\212Û\204ð$ðª ð$Û\204Û\205Û\206
ðµðð</h1>

        <div className="grid grid-cols-1 md:grid-cols-4 gap-6 mb-8">
          <Card>
```

```

        <CardHeader className="flex flex-row items-center justify-between space-y-0 p
b-2">
            <CardTitle className="text-sm font-medium text-gray-500">ðŸð¬ ð\205ð$ð\204ð
\212 ð$ð\204ð\205ð`ð\212ð¹ð$ðª</CardTitle>
            <DollarSign className="h-4 w-4 text-muted-foreground" />
        </CardHeader>
        <CardContent>
            <div className="text-2xl font-bold">150,000 ð`.ð¹</div>
        </CardContent>
    </Card>
</Card>
    <CardHeader className="flex flex-row items-center justify-between space-y-0 p
b-2">
        <CardTitle className="text-sm font-medium text-gray-500">ð¹ð¬ð¬ ð$ð\204ð•ð
\204ð``ð$ðª</CardTitle>
        <ShoppingCart className="h-4 w-4 text-muted-foreground" />
    </CardHeader>
    <CardContent>
        <div className="text-2xl font-bold">1,240</div>
    </CardContent>
</Card>
</Card>
    <CardHeader className="flex flex-row items-center justify-between space-y-0 p
b-2">
        <CardTitle className="text-sm font-medium text-gray-500">ð$ð\204ð¹ð\205ð
\204ð$ð; ð$ð\204ð\206ð´ð•ð\210ð\206</CardTitle>
        <Users className="h-4 w-4 text-muted-foreground" />
    </CardHeader>
    <CardContent>
        <div className="text-2xl font-bold">85</div>
    </CardContent>
</Card>
</Card>
    <CardHeader className="flex flex-row items-center justify-between space-y-0 p
b-2">
        <CardTitle className="text-sm font-medium text-gray-500">ð\206ð\205ð\210 ð$
ð\204ð£ð±ð``ð$ð-</CardTitle>
        <TrendingUp className="h-4 w-4 text-muted-foreground" />
    </CardHeader>
    <CardContent>
        <div className="text-2xl font-bold text-green-600">+12%</div>
    </CardContent>
</Card>
</div>

    <div className="bg-white p-6 rounded-lg shadow">
        <h2 className="text-xl font-semibold mb-4">ð$ð\204ð\205ð`ð\212ð¹ð$ðª ð$ð\204ð\207ð±ð\212ð©</h2>
        <BarChart data={data} />
    </div>
</div>
</div>
);
}

```

```
===== FILE: src/app/(dashboard)/admin/audit-logs/page.tsx =====
```

```
"use client";
import { useEffect, useState, useCallback } from "react";
import { Topbar } from "@/components/dashboard/Topbar";
import { DataTable } from "@/components/ui/DataTable";
import { useToast } from "@/hooks/useToast";
import { ShieldAlert } from "lucide-react";
```

```
export default function AdminAuditLogsPage() {
  const [logs, setLogs] = useState([]);
  const { showToast } = useToast();

  const fetchLogs = useCallback(async () => {
    try {
      const res = await fetch("/api/admin/audit-logs");
```

```

    if (res.ok) setLogs(await res.json());
  } catch (error) {
    showToast("ðŸš€ðŸš€ Û\201Û\212 ð-Û\204ð" ð$Û\204ð³ð-Û\204ð$ðª", "error");
  }
}, [showToast]);

useEffect(() => { fetchLogs(); }, [fetchLogs]);

const columns = [
  { key: "id", header: "ð$Û\204Û\205ð¹ð±Û\201" },
  { key: "action", header: "ð$Û\204ð¥ð-ð±ð$ð;" },
  { key: "users", header: "ð$Û\204Û\205ð³ðªð®ð-Û\205", render: (row: any) => row.users?.name || row.user_id },
  { key: "details", header: "ð$Û\204ðªÛ\201ð$ðµÛ\212Û\204", render: (row: any) => JSON.stringify(row.details) },
  { key: "created_at", header: "ð$Û\204ðªð$ð±Û\212ð®", render: (row: any) => new Date(row.created_at).toLocaleString('ar-IQ') },
];

return (
  <div className="min-h-screen bg-gray-50">
    <Topbar />
    <div className="p-6">
      <h1 className="text-3xl font-bold mb-6 flex items-center gap-2"><ShieldAlert className="text-red-500" size={28} /> ð³ð-Û\204 ð$Û\204ð£Û\205ð$Û\206</h1>
      <div className="bg-white p-6 rounded-2xl shadow-sm border border-gray-100">
        {logs.length === 0 ? (<div className="py-10 text-center text-gray-500">Û\204ð$ðªÛ\210ð-ð- ð³ð-Û\204ð$ðª ð£Û\205ð$Û\206 ð-ð$Û\204Û\212ð$Û\213.</div>) : (<DataTable data={logs} columns={columns} />)}
      </div>
    </div>
  </div>
);
}

```

===== FILE: src/app/(dashboard)/admin/commissions/page.tsx =====

```

"use client";
import { useEffect, useState } from "react";
import { Topbar } from "@/components/dashboard/Topbar";
import { DataTable } from "@/components/ui/DataTable";
import { StatusBadge } from "@/components/shared/StatusBadge";
import { useToast } from "@/hooks/useToast";
import { formatCurrency } from "@/lib/utils/currency";

export default function AdminCommissionsPage() {
  const [commissions, setCommissions] = useState<any[]>([]);
  const { showToast } = useToast();

  useEffect(() => {
    setCommissions([
      { id: "C1", order: "ORD-101", amount: 5000, status: "pending" },
      { id: "C2", order: "ORD-102", amount: 7500, status: "paid" },
    ]);
  }, []);

  const columns = [
    { key: "id", header: "ð±Û\202Û\205 ð$Û\204ð¹Û\205Û\210Û\204ð®" },
    { key: "order", header: "ð±Û\202Û\205 ð$Û\204ð•Û\204ð" },
    { key: "amount", header: "ð$Û\204Û\205ð"Û\204ð°", render: (row: any) => formatCurrency(row.amount) },
    { key: "status", header: "ð$Û\204ð-ð$Û\204ð®", render: (row: any) => <StatusBadge status={row.status} /> },
  ];

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <h1 className="text-3xl font-bold mb-6">ð¥ð-ð$ð±ð® ð$Û\204ð¹Û\205Û\210Û\204ð$ðª</h1>

```

```
        <div className="bg-white p-6 rounded-lg shadow">
          <DataTable data={commissions} columns={columns} />
        </div>
      </div>
    </div>
  );
}

===== FILE: src/app/(dashboard)/admin/components/AdminStats.tsx =====
'use client';

import React from 'react';

interface AdminStatsProps {
  title?: string;
  value?: string | number;
  icon?: string;
  [key: string]: unknown;
}

const AdminStats = ({ title, value, icon }: AdminStatsProps) => {
  return (
    <div className="bg-white rounded-lg p-4 shadow flex items-center gap-4">
      {icon && <span className="text-3xl">{icon}</span>}
      <div>
        {title && <p className="text-sm text-gray-500">{title}</p>}
        {value !== undefined && <p className="text-xl font-bold">{value}</p>}
      </div>
    </div>
  );
};

export { AdminStats };

===== FILE: src/app/(dashboard)/admin/components/UsersTable.tsx =====
'use client';
import { useEffect, useState } from "react";
import { useToast } from "@hooks/useToast";
import { DataTable } from "@components/ui/DataTable";
import { Badge } from "@components/ui/Badge";
import { Button } from "@components/ui/Button";
import { Select } from "@components/ui/Select";
import { LoadingSpinner } from "@components/shared/LoadingSpinner";

export function UsersTable() {
  const [users, setUsers] = useState<any[]>([]);
  const [loading, setLoading] = useState(true);
  const { showToast } = useToast();

  useEffect(() => {
    const fetchUsers = async () => {
      try {
        const res = await fetch("/api/admin/users");
        if (res.ok) setUsers(await res.json());
      } catch (error) {
        console.error("Error fetching users:", error);
      } finally {
        setLoading(false);
      }
    };
    fetchUsers();
  }, []);

  const handleUpdate = async (id: string, data: any) => {
    const res = await fetch(`/api/admin/users/${id}`, {
      method: "PATCH",
      headers: { "Content-Type": "application/json" },
      body: JSON.stringify(data),
    });
    if (res.ok) {

```

```
showToast("ðªÛ\205 ðªð-ð-Û\212ð« ð-Û\212ð$Û\206ð$ðª ð$Û\204Û\205ð³ðªððð-Û\205 ð-Û\206ð-ð$ð-", "success");
setUsers(users.map(u => u.id === id ? { ...u, ...data } : u));
} else {
  showToast("ð-ð-ð« ððð•ð£ Û\201Û\212 ð$Û\204ðªð-ð-Û\212ð«", "error");
}
};

if (loading) return <LoadingSpinner />;

const columns = [
  { key: "name", header: "ð$Û\204ð$ð³Û\205" },
  { key: "email", header: "ð$Û\204ð-ð±Û\212ð- ð$Û\204ð¥Û\204Û\203ðªð±Û\210Û\206Û\212" },
  { key: "role", header: "ð$Û\204ð-Û\210ð±", render: (row: any) => <Badge>{row.role}</Badge> },
  { key: "status", header: "ð$Û\204ð-ð$Û\204ðð", render: (row: any) => (
    <Badge variant={row.status === 'active' ? 'success' : 'secondary'}>{row.status || 'active'}</Badge>
  )},
  { key: "actions", header: "ð¥ð-ð±ð$ð;ð$ðª", render: (row: any) => (
    <div className="flex items-center gap-2">
      <Select
        defaultValue={row.role}
        className="h-8 w-32 text-xs"
        onChange={(e) => handleUpdate(row.id, { role: e.target.value })}
      >
        <option value="retailer">ðªð$ð-ð± ðªð-ð²ð\ðð</option>
        <option value="wholesaler">ðªð$ð-ð± ð-Û\205Û\204ðð</option>
        <option value="delivery">Û\205Û\206ð-Û\210ð- ðªÛ\210ðµÛ\212Û\204</option>
        <option value="admin">ð£ð-Û\205Û\206</option>
      </Select>
      {row.status !== 'active' ? (
        <Button size="sm" onClick={() => handleUpdate(row.id, { status: 'active' })}>
          Û\202ð-Û\210Û\204</Button>
        ) : (
          <Button size="sm" variant="outline" onClick={() => handleUpdate(row.id, { status: 'suspended' })}>ð-ð,ð±</Button>
        )}
    </div>
  )},
];

return (
  <div className="bg-white p-6 rounded-lg shadow">
    <DataTable data={users} columns={columns} />
  </div>
);
}
```

===== FILE: src/app/(dashboard)/admin/coupons/page.tsx =====

```
"use client";
import { useEffect, useState } from "react";
import { Topbar } from "@components/dashboard/Topbar";
import { DataTable } from "@components/ui/DataTable";
import { Button } from "@components/ui/Button";
import { Input } from "@components/ui/Input";
import { Modal } from "@components/ui/Modal";
import { Badge } from "@components/ui/Badge";
import { useToast } from "@hooks/useToast";
import { Ticket, Plus } from "lucide-react";

export default function AdminCouponsPage() {
  const [coupons, setCoupons] = useState<any[]>([]);
  const [showModal, setShowModal] = useState(false);
  const [loading, setLoading] = useState(true);
  const { showToast } = useToast();

  const fetchCoupons = async () => {
    const res = await fetch("/api/coupons");
```

```

    if (res.ok) setCoupons(await res.json());
    setLoading(false);
  };

useEffect(() => { fetchCoupons(); }, []);

const handleCreate = async (e: React.FormEvent) => {
  e.preventDefault();
  const form = e.target as HTMLFormElement;
  const formData = new FormData(form);
  const res = await fetch("/api/coupons", {
    method: "POST",
    headers: { "Content-Type": "application/json" },
    body: JSON.stringify({
      code: formData.get("code"),
      discount_percent: Number(formData.get("discount_percent")),
      max_uses: Number(formData.get("max_uses")),
    }),
  });
  if (res.ok) {
    showToast("ðªÙ\205 ð¥Ù\206ð'ð$ð; ð$Ù\204Ù\203Ù\210ð- ð"Ù\206ð¬ð$ð-", "success");
    setShowModal(false);
    fetchCoupons();
  } else {
    showToast("ð-ð-ð« ð@ð•ð£", "error");
  }
};

const columns = [
  { key: "code", header: "ð$Ù\204Ù\203Ù\210ð-" },
  { key: "discount_percent", header: "ð$Ù\204ð@ðµÙ\205", render: (row: any) => `${row.discount_percent}%` },
  { key: "max_uses", header: "ð$Ù\204ð-ð- ð$Ù\204ð£Ù\202ðµÙ\211" },
  { key: "used_count", header: "ð$Ù\204Ù\205ð³ðªð@ð¬Ù\205" },
  { key: "is_active", header: "ð$Ù\204ð-ð$Ù\204ð@", render: (row: any) => row.is_active
    ? <Badge variant="success">Ù\206ð'ð•</Badge> : <Badge variant="destructive">Ù\205ð¹ð•Ù\204</Badge> },
  ];

return (
  <div className="min-h-screen bg-gray-50">
    <Topbar />
    <div className="p-6">
      <div className="flex justify-between items-center mb-6">
        <h1 className="text-3xl font-bold flex items-center gap-2">
          <Ticket className="text-primary" size={28} /> ð£Ù\203Ù\210ð$ð- ð$Ù\204ð@ðµÙ\205
        </h1>
        <Button onClick={() => setShowModal(true)}><Plus size={18} className="ml-2" />
      </div>
      <div className="bg-white p-6 rounded-2xl shadow-sm border border-gray-100">
        {coupons.length === 0 ? (
          <div className="py-10 text-center text-gray-500">Ù\204ð$ ðªÙ\210ð¬ð- ð£Ù\203Ù\210ð$ð- ð@ðµÙ\205 ð-ð$Ù\204Ù\212ð$Ù\213.</div>
        ) : (
          <DataTable data={coupons} columns={columns} />
        )}
      </div>
    </div>

    <Modal open={showModal} onClose={() => setShowModal(false)} title="ðªÙ\206ð'ð$ð; ð\203Ù\210ð- ð@ðµÙ\205 ð¬ð¬Ù\212ð-">
      <form onSubmit={handleCreate} className="space-y-4">
        <Input name="code" placeholder="ð$Ù\204Ù\203Ù\210ð- (Ù\205ð«ð$Ù\204: SAVE10)" required />
        <Input name="discount_percent" type="number" placeholder="Ù\206ð³ð"ð@ ð$Ù\204ð@ðµÙ\205 (%)" required />
        <Input name="max_uses" type="number" placeholder="ð$Ù\204ð-ð- ð$Ù\204ð£Ù\202ðµÙ\211 ð\204Ù\204ð$ð³ðªð@ð¬ð$Ù\205" required />
      </form>
    </Modal>
  </div>
);

```

```
        <Button type="submit" className="w-full">ðŸšš\206ð\ð$ð; ð$ð\204ð\203ð\210ð</Button>
    </form>
</Modal>
</div>
);
}
```

===== FILE: src/app/(dashboard)/admin/disputes/page.tsx =====

```
"use client";
import { useEffect, useState } from "react";
import { Topbar } from "@/components/dashboard/Topbar";
import { DataTable } from "@/components/ui/DataTable";
import { StatusBadge } from "@/components/shared/StatusBadge";
import { Button } from "@/components/ui/Button";
import { useToast } from "@/hooks/useToast";

export default function AdminDisputesPage() {
  const [disputes, setDisputes] = useState<any[]>([]);
  const { showToast } = useToast();

  // ð\205ð\202ðª ð-ðª\211 ð\212ðª\205 ð±ð"ð\207ð$ ð"\202ð$ð¹ð\ðð ð$ð\204ð"\212ð$
  ð\206ð$ðª
  useEffect(() => {
    setDisputes([
      { id: "D1", user: "ðŸšš-ð\205ð-", order: "ORD-1", status: "pending" },
      { id: "D2", user: "ð³ð$ð±ðð", order: "ORD-2", status: "approved" },
    ]);
  }, []);

  const handleAction = (id: string, status: string) => {
    setDisputes(disputes.map(d => d.id === id ? { ...d, status } : d));
    showToast(`ðª\205 ðªð-ð\212ðª ð-ð$ð\204ðð ð$ð\204ð\206ð²ð$ð¹ ðŸšš\204ð\211 ${status}` , "success");
  };

  const columns = [
    { key: "id", header: "ð±ð\202ð\205 ð$ð\204ð\206ð²ð$ð¹" },
    { key: "user", header: "ð$ð\204ð\205ð³ðªððð\205" },
    { key: "order", header: "ð$ð\204ð\204ð" },
    { key: "status", header: "ð$ð\204ð-ð$ð\204ðð", render: (row: any) => <StatusBadge status={row.status} /> },
    { key: "actions", header: "ðŸšš-ð±ð$ð;ð$ðª", render: (row: any) => (
      <div className="flex gap-2">
        <Button size="sm" variant="outline" onClick={() => handleAction(row.id, "approved")}>ð\202ð"\210ð\204</Button>
        <Button size="sm" variant="destructive" onClick={() => handleAction(row.id, "rejected")}>ð±ð\201ð¶</Button>
      </div>
    )
  ],
];

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <h1 className="text-3xl font-bold mb-6">ðŸšš-ð$ð±ðð ð$ð\204ð\206ð²ð$ð¹ð$ðª</h1>
        <div className="bg-white p-6 rounded-lg shadow">
          <DataTable data={disputes} columns={columns} />
        </div>
      </div>
    </div>
  );
}
```

===== FILE: src/app/(dashboard)/admin/matching/page.tsx =====

```
"use client";
import { useEffect, useState } from "react";
import { Topbar } from "@/components/dashboard/Topbar";
import { DataTable } from "@/components/ui/DataTable";
```

```

import { StatusBadge } from "@components/shared/StatusBadge";
import { Button } from "@components/ui/Button";
import { useToast } from "@hooks/useToast";

export default function AdminMatchingPage() {
  const [matches, setMatches] = useState<any[]>([]);
  const { showToast } = useToast();

  useEffect(() => {
    setMatches([
      { id: "M1", retailer: "Ü\2050ª0-0± 0$Ü\2040£Ü\205Ü\204", wholesaler: "0´0±Ü\2030© 0$Ü\204Ü\206Ü\2100±", status: "pending" },
      { id: "M2", retailer: "Ü\2050ª0-0± 0$Ü\2040³Ü\2040$Ü\205", wholesaler: "Ü\2050ª0³0³ 0© 0$Ü\2040@Ü\2120±", status: "approved" },
    ]);
  }, []);

  const handleAction = (id: string, status: string) => {
    setMatches(matches.map(m => m.id === id ? { ...m, status } : m));
    showToast(`0ªÜ\205 0ª0-0-Ü\2120« 0-0$Ü\2040© 0$Ü\204Ü\2050•0$0"Ü\2020© 0$Ü\204Ü\211 $ {status}`, "success");
  };

  const columns = [
    { key: "id", header: "0±Ü\202Ü\205 0$Ü\204Ü\2050•0$0"Ü\2020©" },
    { key: "retailer", header: "0ª0$0-0± 0$Ü\2040ª0-0²0|0©" },
    { key: "wholesaler", header: "0ª0$0-0± 0$Ü\2040-Ü\205Ü\2040©" },
    { key: "status", header: "0$Ü\2040-0$Ü\2040©", render: (row: any) => <StatusBadge status={row.status} /> },
    { key: "actions", header: "0¥0-0±0$0;0$0ª", render: (row: any) => (
      <div className="flex gap-2">
        <Button size="sm" variant="outline" onClick={() => handleAction(row.id, "approved")}>Ü\2020"Ü\210Ü\204</Button>
        <Button size="sm" variant="destructive" onClick={() => handleAction(row.id, "rejected")}>0±Ü\2010¶</Button>
      </div>
    )},
  ];

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <h1 className="text-3xl font-bold mb-6">Ü\2050•0$0"Ü\2020© 0$Ü\2040•Ü\2040"0$0ª</h1>
        <div className="bg-white p-6 rounded-lg shadow">
          <DataTable data={matches} columns={columns} />
        </div>
      </div>
    </div>
  );
}

```

===== FILE: src/app/(dashboard)/admin/overview/page.tsx =====

```

import { Topbar } from "@components/dashboard/Topbar";
import { StatsCard } from "@components/shared/StatsCard";
import { BarChart } from "@components/charts/BarChart";
import { createClient } from "@lib/supabase/server";
import { formatCurrency } from "@lib/utils/currency";
import { Users, ShoppingCart, DollarSign, TrendingUp } from "lucide-react";

export default async function AdminOverviewPage() {
  const supabase = await createClient();

  // 0-Ü\2040" 0$Ü\2040¥0-0µ0$0;Ü\2120$0ª 0$Ü\2040-Ü\202Ü\212Ü\202Ü\2120© Ü\205Ü\206 Ü\2020$0¹0-0© 0$Ü\2040"Ü\2120$Ü\2060$0ª
  const { count: totalUsers } = await supabase.from('users').select('*', { count: 'exact', head: true });
  const { count: totalOrders } = await supabase.from('orders').select('*', { count: 'exact', head: true });
}

```

[illegible]

```

    { key: "amount", header: "Ø$Û\204Û\205Ø"Û\204Ø°", render: (row: any) => formatCurrenc
y(row.amount) },
    { key: "gateway", header: "Ø$Û\204Ø"Û\210Ø$Ø"Ø°" },
    { key: "status", header: "Ø$Û\204Ø-Ø$Û\204Ø°", render: (row: any) => <StatusBadge sta
tus={row.status} /> },
    { key: "created_at", header: "Ø$Û\204ØªØ$Ø±Û\212Ø°", render: (row: any) => new Date(r
ow.created_at).toLocaleString('ar-IQ') },
  ];

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <h1 className="text-3xl font-bold mb-6 flex items-center gap-2"><CreditCard class
Name="text-primary" size={28} /> Ø³Ø-Û\204 Ø$Û\204Û\205Ø"Û\201Û\210Ø¹Ø$Øª</h1>
        <div className="bg-white p-6 rounded-2xl shadow-sm border border-gray-100">
          {payments.length === 0 ? (<div className="py-10 text-center text-gray-500">Û
\204Ø$ ØªÛ\210Ø-Ø" Û\205Ø"Û\201Û\210Ø¹Ø$Øª Ø-Ø$Û\204Û\212Ø$Û\213.</div>) : (<DataTable da
ta={payments} columns={columns} />)}
        </div>
      </div>
    </div>
  );
}

```

===== FILE: src/app/(dashboard)/admin/refunds/page.tsx =====

```

"use client";
import { useEffect, useState } from "react";
import { Topbar } from "@components/dashboard/Topbar";
import { DataTable } from "@components/ui/DataTable";
import { StatusBadge } from "@components/shared/StatusBadge";
import { Button } from "@components/ui/Button";
import { useToast } from "@hooks/useToast";
import { formatCurrency } from "@lib/utils/currency";
import { Check, X } from "lucide-react";

export default function AdminRefundsPage() {
  const [refunds, setRefunds] = useState<any[]>([]);
  const { showToast } = useToast();

  const fetchRefunds = async () => {
    const res = await fetch("/api/refunds");
    if (res.ok) setRefunds(await res.json());
  };

  useEffect(() => { fetchRefunds(); }, []);

  const handleStatus = async (id: string, status: string) => {
    const res = await fetch(`\api/refunds/${id}`, {
      method: "PATCH",
      headers: { "Content-Type": "application/json" },
      body: JSON.stringify({ status }),
    });
    if (res.ok) {
      showToast(`ØªÛ\205 ${status} === 'approved' ? 'Û\202Ø"Û\210Û\204' : 'Ø±Û\201Ø¹' } Ø$Û
\204Ø•Û\204Ø"`, "success");
      fetchRefunds();
    } else {
      showToast("Ø-Ø-Ø« Ø®Ø•Ø£", "error");
    }
  };

  const columns = [
    { key: "id", header: "Ø±Û\202Û\205 Ø$Û\204Ø•Û\204Ø" },
    { key: "reason", header: "Ø$Û\204Ø³Ø"Ø" },
    { key: "created_at", header: "Ø$Û\204ØªØ$Ø±Û\212Ø°", render: (row: any) => new Date(r
ow.created_at).toLocaleDateString('ar-IQ') },
    { key: "status", header: "Ø$Û\204Ø-Ø$Û\204Ø°", render: (row: any) => <StatusBadge sta
tus={row.status} /> },
    { key: "actions", header: "Ø¥Ø-Ø±Ø$Ø;Ø$Øª", render: (row: any) => (

```

```

    <div className="flex gap-2">
      {row.status === 'pending' && (
        <>
          <Button size="sm" variant="outline" onClick={() => handleStatus(row.id, 'ap
proved')}><Check size={14} /> Û\2020"Û\210Û\204</Button>
          <Button size="sm" variant="destructive" onClick={() => handleStatus(row.id,
'rejected')}><X size={14} /> Ø±Û\201Ø¶</Button>
        </>
      )}
    </div>
  )},
];

return (
  <div className="min-h-screen bg-gray-50">
    <Topbar />
    <div className="p-6">
      <h1 className="text-3xl font-bold mb-6">Ø¥Ø¬Ø$Ø±Ø© Ø•Û\204Ø¬Ø$Øª Ø$Û\204Ø$Ø³ØªØ±Ø¬Ø$Ø¹</h1>
      <div className="bg-white p-6 rounded-2xl shadow-sm border border-gray-100">
        {refunds.length === 0 ? (
          <div className="py-10 text-center text-gray-500">Û\204Ø$ ØªÛ\210Ø¬Ø¬ Ø•Û\204Ø¬Ø$Øª Ø$Ø³ØªØ±Ø¬Ø$Ø¹ Ø¬Ø$Û\204Û\212Ø$Û\213.</div>
        ) : (
          <DataTable data={refunds} columns={columns} />
        )}
      </div>
    </div>
  </div>
);
}

===== FILE: src/app/(dashboard)/admin/requests/page.tsx =====
"use client";
import { useEffect, useState } from "react";
import { Topbar } from "@components/dashboard/Topbar";
import { DataTable } from "@components/ui/DataTable";
import { StatusBadge } from "@components/shared/StatusBadge";
import { Button } from "@components/ui/Button";
import { useToast } from "@hooks/useToast";

export default function AdminRequestsPage() {
  const [requests, setRequests] = useState<any[]>([]);
  const { showToast } = useToast();

  useEffect(() => {
    setRequests([
      { id: "REQ-1", user: "ØªØ$Ø¬Ø¬ Ø¬Ø¬Û\212Ø¬", type: "ØªØ³Ø¬Û\212Û\204", status: "pen
ding" },
      { id: "REQ-2", user: "Û\205ØªØ¬Ø± 1", type: "ØªØ¹Ø¬Û\212Û\204 Ø¬Û\212Ø$Û\206Ø$Øª",
status: "approved" },
    ]);
  }, []);

  const handleAction = (id: string, status: string) => {
    setRequests(requests.map(r => r.id === id ? { ...r, status } : r));
    showToast(`ØªÛ\205 ØªØ¬Ø¬Û\212Ø« Ø¬Ø$Û\204Ø© Ø$Û\204Ø•Û\204Ø¬ Ø¥Û\204Û\211 ${status}`
, "success");
  };

  const columns = [
    { key: "id", header: "Ø±Û\202Û\205 Ø$Û\204Ø•Û\204Ø¬" },
    { key: "user", header: "Ø$Û\204Û\205Ø³ØªØ©Û\205" },
    { key: "type", header: "Û\206Û\210Ø¹ Ø$Û\204Ø•Û\204Ø¬" },
    { key: "status", header: "Ø$Û\204Ø¬Ø$Û\204Ø©", render: (row: any) => <StatusBadge sta
tus={row.status} /> },
    { key: "actions", header: "Ø¥Ø¬Ø±Ø$Ø;Ø$Øª", render: (row: any) => (
      <div className="flex gap-2">
        <Button size="sm" variant="outline" onClick={() => handleAction(row.id, "approv
ed")}>Û\2020"Û\210Û\204</Button>

```

```
        <Button size="sm" variant="destructive" onClick={() => handleAction(row.id, "re
jected")}>ð±Û\2010¶¶</Button>
      </div>
    )},
  ];

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <h1 className="text-3xl font-bold mb-6">ð•Û\2040`ð$ðª ð$Û\204Û\205ð³ð$ð¹ð-ð@</h1>
        <div className="bg-white p-6 rounded-lg shadow">
          <DataTable data={requests} columns={columns} />
        </div>
      </div>
    </div>
  );
}

===== FILE: src/app/(dashboard)/admin/settings/page.tsx =====
"use client";
import { useState } from "react";
import { Topbar } from "@components/dashboard/Topbar";
import { Button } from "@components/ui/Button";
import { Input } from "@components/ui/Input";
import { Select } from "@components/ui/Select";
import { useToast } from "@hooks/useToast";

export default function AdminSettingsPage() {
  const [loading, setLoading] = useState(false);
  const { showToast } = useToast();

  const handleSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    setLoading(true);
    showToast("ðªÛ\205 ð-Û\2010, ð¥ð¹ð-ð$ð-ð$ðª ð$Û\204Û\205Û\206ðµð@ ð"Û\206ð-ð$ð-ð", "su
ccess");
    setLoading(false);
  };

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <div className="bg-white p-6 rounded-lg shadow max-w-lg">
          <h1 className="text-2xl font-bold mb-6">ð¥ð¹ð-ð$ð-ð$ðª ð$Û\204Û\205Û\206ðµð@</h
1>
          <form onSubmit={handleSubmit} className="space-y-4">
            <div>
              <label className="text-sm font-medium mb-2 block">Û\206ð³ð"ð@ ð$Û\204ð¹Û
\205Û\210Û\204ð@ ð$Û\204ð¹ð$Û\205ð@</label>
              <Input type="number" defaultValue="5" />
            </div>
            <div>
              <label className="text-sm font-medium mb-2 block">ð•ð±Û\202 ð$Û\204ð-Û\2010
¹ ð$Û\204Û\205ðªð$ð-ð@</label>
              <Select defaultValue="card">
                <option value="card">ð"ð•ð$Û\202ð@ ð$ð¹ðªÛ\205ð$Û\206</option>
                <option value="cod">ð$Û\204ð-Û\2010¹ ð¹Û\206ð- ð$Û\204ð$ð³ðªÛ\204ð$Û\205<
/option>
              </Select>
            </div>
            <Button type="submit" disabled={loading} className="w-full">
              {loading ? "ð-ð$ð±Û\215 ð$Û\204ð-Û\2010,..." : "ð-Û\2010, ð$Û\204ðªðªÛ\212Û
\212ð±ð$ðª"}
            </Button>
          </form>
        </div>
      </div>
    </div>
  );
}
```

```
;
}

===== FILE: src/app/(dashboard)/admin/users/page.tsx =====
"use client";
import { useEffect, useState, useCallback } from "react";
import { Topbar } from "@components/dashboard/Topbar";
import { DataTable } from "@components/ui/DataTable";
import { Badge } from "@components/ui/Badge";
import { Button } from "@components/ui/Button";
import { Select } from "@components/ui/Select";
import { useToast } from "@hooks/useToast";

export default function AdminUsersPage() {
  const [users, setUsers] = useState([]);
  const { showToast } = useToast();

  const fetchUsers = useCallback(async () => {
    try {
      const res = await fetch("/api/admin/users", { method: "GET" });
      if (res.ok) setUsers(await res.json());
    } catch (error) {
      showToast("ðŸ’¥ ðŸ“š ðŸ”ˆ\201ðŸ”ˆ\212 ðŸ”ˆ\204ðŸ”ˆ ðŸ”ˆ\204ðŸ”ˆ\205ðŸ”ˆ\206", "error");
    }
  }, [showToast]);

  useEffect(() => { fetchUsers(); }, [fetchUsers]);

  const handleUpdate = async (id: string, data: any) => {
    const res = await fetch(`/api/admin/users/${id}`, { method: "PATCH", headers: { "Content-Type": "application/json" }, body: JSON.stringify(data) });
    if (res.ok) { showToast("ðŸ”ˆ\205ðŸ”ˆ\212ðŸ”ˆ ðŸ”ˆ\204ðŸ”ˆ\205ðŸ”ˆ\206", "success"); fetchUsers(); } else { showToast("ðŸ’¥ðŸ”ˆ ðŸ”ˆ\204ðŸ”ˆ\206", "error"); }
  };

  const columns = [
    { key: "name", header: "ðŸ”ˆ\204ðŸ”ˆ\205", },
    { key: "email", header: "ðŸ”ˆ\204ðŸ”ˆ\212ðŸ”ˆ ðŸ”ˆ\204ðŸ”ˆ\203ðŸ”ˆ\210ðŸ”ˆ\206ðŸ”ˆ\212" },
    { key: "role", header: "ðŸ”ˆ\204ðŸ”ˆ\210ðŸ”ˆ", render: (row: any) => <Badge>{row.role}</Badge> },
    { key: "status", header: "ðŸ”ˆ\204ðŸ”ˆ\204ðŸ”ˆ", render: (row: any) => (row.status === 'suspended' ? <Badge variant="destructive">ðŸ”ˆ\205ðŸ”ˆ\210ðŸ”ˆ</Badge> : <Badge variant="success">ðŸ”ˆ\206ðŸ”ˆ</Badge>) },
    { key: "actions", header: "ðŸ”ˆ\204ðŸ”ˆ\212ðŸ”ˆ", render: (row: any) => (
      <div className="flex items-center gap-2">
        <Select defaultValue={row.role} className="h-8 w-32 text-xs" onChange={(e) => handleUpdate(row.id, { role: e.target.value })}>
          <option value="retailer">ðŸ”ˆ\204ðŸ”ˆ\205ðŸ”ˆ</option>
          <option value="wholesaler">ðŸ”ˆ\205ðŸ”ˆ\204ðŸ”ˆ</option>
          <option value="delivery">ðŸ”ˆ\205ðŸ”ˆ\206ðŸ”ˆ\210ðŸ”ˆ ðŸ”ˆ\210ðŸ”ˆ\212ðŸ”ˆ\204</option>
          <option value="admin">ðŸ”ˆ\205ðŸ”ˆ\206</option>
        </Select>
        {row.status !== 'suspended' ? (<Button size="sm" variant="outline" className="text-red-600" onClick={() => handleUpdate(row.id, { status: 'suspended' })}>ðŸ”ˆ\204ðŸ”ˆ</Button>) : (<Button size="sm" variant="outline" className="text-green-600" onClick={() => handleUpdate(row.id, { status: 'active' })}>ðŸ”ˆ\201ðŸ”ˆ\212ðŸ”ˆ\204</Button>)}
      </div>
    )},
  ];

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <h1 className="text-3xl font-bold mb-6">ðŸ”ˆ\204ðŸ”ˆ\205ðŸ”ˆ\206ðŸ”ˆ\212ðŸ”ˆ\206</h1>
        <div className="bg-white p-6 rounded-2xl shadow-sm border border-gray-100">
          {users.length === 0 ? (<div className="py-10 text-center text-gray-500">ðŸ”ˆ\204ðŸ”ˆ\206</div>)}
        </div>
      </div>
    </div>
  );
}
```

```

    <div></div>
    </div>
    </div>
    </div>
);
}

```

```
===== FILE: src/app/(dashboard)/delivery/commissions/page.tsx =====
```

```

"use client";
import { DataTable } from "@/components/ui/DataTable";
import { Badge } from "@/components/ui/Badge";
import { Topbar } from "@/components/dashboard/Topbar";

export default function DeliveryCommissionsPage() {
  const commissions = [
    { id: "DC-1", order: "ORD-501", amount: 2500, date: "2026-09-01", status: "pending" },
    { id: "DC-2", order: "ORD-502", amount: 4500, date: "2026-09-02", status: "paid" },
  ];

  const columns = [
    { key: "id", header: "ID", sortable: true },
    { key: "order", header: "Order", sortable: true },
    { key: "amount", header: "Amount", sortable: true },
    { key: "date", header: "Date", sortable: true },
    { key: "status", header: "Status", render: (r: any) => <Badge>{r.status} </Badge> },
  ];

  return (
    <div>
      <Topbar />
      <h1 className="text-3xl font-bold mb-6">Delivery Commissions</h1>
      <div className="bg-white p-6 rounded-lg shadow">
        <DataTable data={commissions} columns={columns} />
      </div>
    </div>
  );
}

```

```
===== FILE: src/app/(dashboard)/delivery/components/DeliveryStats.tsx =====
'use client';
```

```
import React from 'react';
```

```
interface DeliveryStatsProps {
  title?: string;
  value?: string | number;
  icon?: string;
  [key: string]: unknown;
}
```

```
const DeliveryStats = ({ title, value, icon }: DeliveryStatsProps) => {
  return (
    <div className="bg-white rounded-lg p-4 shadow flex items-center gap-4">
      {icon} && <span className="text-3xl">{icon}</span>
      <div>
        {title} && <p className="text-sm text-gray-500">{title}</p>
        {value !== undefined && <p className="text-xl font-bold">{value}</p>}
      </div>
    </div>
  );
};
```

```
export { DeliveryStats };
```

```
===== FILE: src/app/(dashboard)/delivery/earnings/page.tsx =====
```

```
import { Topbar } from "@components/dashboard/Topbar";
import { StatsCard } from "@components/shared/StatsCard";
```

) }

```
    </div>
  </div>
);
}

===== FILE: src/app/(dashboard)/delivery/nearby-wholesale/page.tsx =====
"use client";
import { Topbar } from "@/components/dashboard/Topbar";
import { Button } from "@/components/ui/Button";
import { Badge } from "@/components/ui/Badge";
import { Store } from "lucide-react";

export default function NearbyWholesalePage() {
  const wholesalers = [
    { id: 1, name: "ð'ð±ù\203ðð ð$ù\204ù\206ù\210ð±", area: "ð°ð°ð°ð$ð° - ð$ù\204ù\203ð±ð$ð°ð°" },
    { id: 2, name: "ù\205ð°ð³ð³ðð ð$ù\204ððù\212ð±", area: "ð£ð±ð°ù\212ù\204 - ð¹ù\206ù\203ð$ù\210ð$" },
  ];

  return (
    <div>
      <Topbar />
      <h1 className="text-3xl font-bold mb-6">ðªð°ð$ð± ð$ù\204ð°ù\205ù\204ðð ð$ù\204ù\205ðªð$ð°ù\210ù\206</h1>
      <div className="space-y-4">
        {wholesalers.map((w) => (
          <div key={w.id} className="bg-white p-4 rounded-lg shadow flex justify-between items-center">
            <div className="flex items-center gap-3">
              <div className="h-12 w-12 bg-primary/10 rounded-full flex items-center justify-center font-bold text-primary text-lg">
                <Store size={20} />
              </div>
              <div>
                <h3 className="font-bold">{w.name}</h3>
                <p className="text-sm text-gray-500">{w.area}</p>
              </div>
            </div>
            <div className="flex gap-2">
              <Badge variant="secondary">ù\205ðªð$ð° - ð\204ù\204ðªð¹ð$ù\210ù\206</Badge>
              <Button size="sm">ð¥ð±ð³ð$ù\204 ð•ù\204ð°</Button>
            </div>
          </div>
        ))}
      </div>
    </div>
  );
}
```

```
===== FILE: src/app/(dashboard)/delivery/overview/page.tsx =====
import { Topbar } from "@/components/dashboard/Topbar";
import { StatsCard } from "@/components/shared/StatsCard";
import { formatCurrency } from "@/lib/utils/currency";

export default async function DeliveryOverviewPage() {
  // ð°ù\212ð$ù\206ð$ðª ðªð°ð±ù\212ð°ù\212ðð ð\205ð°ù\202ðªðð ð-ðªù\211 ð\212ðªù\205 ð±ð°ð•ù\207ð$ ð\203ð$ù\205ù\204ððð\214 ð\204ù\203ù\206 ð$ù\204ð°ù\206ù\212ðð ðªð¹ù\205ù\204
  const pendingTasks = 12;
  const deliveredTasks = 58;
  const earningsToday = 25000;

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <h1 className="text-3xl font-bold mb-6">ù\206ð,ð±ðð ð¹ð$ù\205ðð ð\204ù\204ù\205ù\206ð°ù\210ð°</h1>
        <div className="grid grid-cols-1 md:grid-cols-3 gap-6 mb-8">
          <StatsCard title="ð•ù\204ð°ð$ðª ð\202ù\212ð° ð$ù\204ð$ù\206ðªð,ð$ð±" value={pen
```

```
dingTasks.toString()) icon="â\217³" />
    <StatsCard title="Ø•Û\204Ø"Ø$Øª ØªÛ\205 ØªØ³Û\204Û\212Û\205Û\207Ø$" value={deli
veredTasks.toString()} icon="â\234\205" trend="+5%" trendUp={true} />
    <StatsCard title="Ø£Ø±Ø"Ø$Ø- Ø$Û\204Û\212Û\210Û\205 (Ø¹.Ø¹)" value={formatCurre
ncy(earningsToday)} icon="ð\237\222°" />
  </div>
  <div className="bg-white rounded-2xl p-6 shadow-sm border border-gray-100">
    <p className="text-gray-500 text-center py-10">Ø³Û\212ØªÛ\205 Ø¹Ø±Ø¶ ØªÛ\201Ø$Ø
µÛ\212Û\204 Ø$Û\204Û\205Û\207Ø$Û\205 Û\210Ø$Û\204Ø£Ø±Ø"Ø$Ø- Ø$Û\204ØªÛ\201ØµÛ\212Û\204Û
\212Ø© Û\207Û\206Ø$.</p>
  </div>
</div>
</div>
</div>
);
}
```

===== FILE: src/app/(dashboard)/delivery/payouts/page.tsx =====

```
"use client";
import { useEffect, useState } from "react";
import { Topbar } from "@/components/dashboard/Topbar";
import { DataTable } from "@/components/ui/DataTable";
import { Badge } from "@/components/ui/Badge";
import { useToast } from "@/hooks/useToast";
import { formatCurrency } from "@/lib/utils/currency";

export default function DeliveryPayoutsPage() {
  const [payouts, setPayouts] = useState<any[]>([]);
  const { showToast } = useToast();

  useEffect(() => {
    const fetchPayouts = async () => {
      try {
        const res = await fetch("/api/payouts");
        if (res.ok) setPayouts(await res.json());
      } catch (error) {
        showToast("Ø©Ø•Ø£ Û\201Û\212 Ø-Û\204Ø" Ø$Û\204Û\205Ø-Û\201Û\210Ø¹Ø$Øª", "error");
      }
    };
    fetchPayouts();
  }, []);

  const columns = [
    { key: "id", header: "Ø±Û\202Û\205 Ø$Û\204Ø-Û\201Ø¹Ø©" },
    { key: "amount", header: "Ø$Û\204Û\205Ø-Û\204Ø°", render: (row: any) => formatCurrenc
y(row.amount) },
    { key: "status", header: "Ø$Û\204Ø-Ø$Û\204Ø©", render: (row: any) => <Badge variant={
row.status === 'processed' ? 'success' : 'secondary'}>{row.status === 'processed' ? 'Û
\205Ø-Û\201Û\210Ø¹' : 'Û\205Ø¹Û\204Û\202'}</Badge> },
  ];

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <h1 className="text-3xl font-bold mb-6">Ø$Û\204Û\205Ø-Û\201Û\210Ø¹Ø$Øª Û\210Ø$Û
\204Û\205Ø³ØªØ-Û\202Ø$Øª</h1>
        <div className="bg-white p-6 rounded-lg shadow">
          <DataTable data={payouts} columns={columns} />
        </div>
      </div>
    </div>
  );
}
```

===== FILE: src/app/(dashboard)/delivery/settings/page.tsx =====

```
"use client";
import { useToast } from "@/hooks/useToast";
import { Button } from "@/components/ui/Button";
import { Input } from "@/components/ui/Input";
import { Topbar } from "@/components/dashboard/Topbar";
```

```
export default function DeliverySettingsPage() {
  const { showToast } = useToast();
  return (
    <div>
      <Topbar />
      <div className="bg-white p-6 rounded-lg shadow max-w-lg">
        <h1 className="text-2xl font-bold mb-6">ðŸŸ°¹ðŸŸ°ðŸŸ° Û\205Û\206ðŸŸ°\210ðŸŸ° ðŸŸ°
\204ðŸŸ°\210ðŸŸ°\212Û\204</h1>
        <div className="space-y-4">
          <Input name="vehicle" placeholder="Û\206Û\210ðŸŸ° ðŸŸ°\204Û\205ðŸŸ°\203ðŸŸ° (ðŸŸ°±ðŸŸ°
ðŸŸ°ðŸŸ°\214 ðŸŸ°Û\212ðŸŸ°±ðŸŸ°...) " />
          <Input name="area" placeholder="Û\205Û\206ðŸŸ°\202ðŸŸ° ðŸŸ°\204ðŸŸ°ðŸŸ°\212ðŸŸ° " />
          <Button onClick={() => showToast("ðŸŸ°\205 ðŸŸ°\201ðŸŸ°, ðŸŸ°¹ðŸŸ°ðŸŸ°ðŸŸ° ðŸŸ°\204ðŸŸ°\
\210ðŸŸ°\212Û\204", "success")}>ðŸŸ°\201ðŸŸ°</Button>
        </div>
      </div>
    </div>
  );
}
```

===== FILE: src/app/(dashboard)/delivery/task-history/page.tsx =====

```
"use client";
import { DataTable } from "@components/ui/DataTable";
import { StatusBadge } from "@components/shared/StatusBadge";
import { Topbar } from "@components/dashboard/Topbar";

export default function DeliveryTaskHistoryPage() {
  const tasks = [
    { id: "TH-1", address: "ðŸŸ°ðŸŸ°ðŸŸ° - ðŸŸ°Û\212Û\210Û\206ðŸŸ°", date: "2026-09-01", status
: "delivered" },
    { id: "TH-2", address: "ðŸŸ°ðŸŸ°ðŸŸ° - ðŸŸ°Û\204Û\205Û\206ðŸŸ°\210ðŸŸ°", date: "2026-09-02",
status: "delivered" },
  ];

  const columns = [
    { key: "id", header: "ðŸŸ°\202Û\205 ðŸŸ°\204Û\205Û\207Û\205ðŸŸ°" },
    { key: "address", header: "ðŸŸ°\204ðŸŸ°¹Û\206Û\210ðŸŸ°\206" },
    { key: "date", header: "ðŸŸ°\204ðŸŸ°ðŸŸ°\212ðŸŸ°" },
    { key: "status", header: "ðŸŸ°\204ðŸŸ°ðŸŸ°", render: (r: any) => <StatusBadge statu
s={r.status} /> },
  ];

  return (
    <div>
      <Topbar />
      <h1 className="text-3xl font-bold mb-6">ðŸŸ°ðŸŸ°\204 ðŸŸ°\204Û\205Û\207ðŸŸ°\205</h1>
      <div className="bg-white p-6 rounded-lg shadow">
        <DataTable data={tasks} columns={columns} />
      </div>
    </div>
  );
}
```

===== FILE: src/app/(dashboard)/delivery/tasks/page.tsx =====

```
"use client";
import { useEffect, useState } from "react";
import { Topbar } from "@components/dashboard/Topbar";
import { DataTable } from "@components/ui/DataTable";
import { StatusBadge } from "@components/shared/StatusBadge";
import { Button } from "@components/ui/Button";
import { useToast } from "@hooks/useToast";
import { formatCurrency } from "@lib/utils/currency";

export default function DeliveryTasksPage() {
  const [tasks, setTasks] = useState<any[]>([]);
  const [loading, setLoading] = useState(true);
  const { showToast } = useToast();

  const fetchTasks = async () => {
```

[illegible]

```
===== FILE: src/app/(dashboard)/layout.tsx =====
import { Sidebar } from "@/components/dashboard/Sidebar";
import { BottomNavBar } from "@/components/shared/BottomNavBar";

export default function DashboardLayout({ children }: { children: React.ReactNode }) {
  return (
    <div className="flex min-h-screen bg-gray-50">
      { /* 0$Û\2040'0±Û\2120• 0$Û\2040-0$Û\2060"Û\212 Û\204Û\2040'0$0'0$0ª 0$Û\204Û\2030"Û\2120±00 */}
      <Sidebar />

      { /* 0$Û\204Û\2050-0ªÛ\210Û\211 0$Û\2040±0!Û\2120³Û\212 */}
      <div className="flex-1 md:ml-64 pb-16 md:pb-0">
        {children}
      </div>

      { /* 0'0±Û\2120• 0$Û\2040ªÛ\206Û\202Û\204 0$Û\2040³Û\201Û\204Û\212 Û\204Û\2040-Û\2100$Û\204 */}
      <BottomNavBar />
    </div>
  );
}

===== FILE: src/app/(dashboard)/messages/page.tsx =====
"use client";
import { useEffect, useState, useRef } from "react";
import { Topbar } from "@/components/dashboard/Topbar";
import { Input } from "@/components/ui/Input";
import { Button } from "@/components/ui/Button";
import { useRealtime } from "@/hooks/useRealtime";
import { Send, MessageCircle, User } from "lucide-react";

export default function MessagesPage() {
  const [contacts, setContacts] = useState<any[]>([]);
  const [activeContact, setActiveContact] = useState<any>(null);
  const [messages, setMessages] = useState<any[]>([]);
  const [newMessage, setNewMessage] = useState("");
  const [loading, setLoading] = useState(false);
  const [isSending, setIsSending] = useState(false);
  const messagesEndRef = useRef<HTMLDivElement>(null);

  // 0-Û\2040" 0-Û\2070$0ª 0$Û\2040$0ª0µ0$Û\204
  useEffect(() => {
    const fetchContacts = async () => {
      const res = await fetch("/api/chat");
      if (res.ok) setContacts(await res.json());
    };
    fetchContacts();
  }, []);

  // 0-Û\2040" 0$Û\2040±0³0$0!Û\204 0¹Û\2060- 0$000ªÛ\2120$0± 0-Û\20700 0$0ª0µ0$Û\204
  useEffect(() => {
    if (activeContact) {
      setLoading(true);
      fetch(`/api/chat?userId=${activeContact.id}`)
        .then(res => res.json())
        .then(data => setMessages(data))
        .finally(() => setLoading(false));
    }
  }, [activeContact]);

  // 0$Û\2040$0³0ªÛ\2050$0¹ Û\204Û\2040ª0-0-Û\2120«0$0ª 0$Û\204Û\2040-0,Û\21200 (Realtime)
  useRealtime("chat_messages", () => {
    if (activeContact) {
      fetch(`/api/chat?userId=${activeContact.id}`)
        .then(res => res.json())
        .then(data => setMessages(data));
    }
  })
}
```

```

    });

    // Ø$Ù\204ØªÙ\205Ø±Ù\212Ø± Ù\204Ø£Ø³Ù\201Ù\204 ØªÙ\204Ù\202Ø$Ø|Ù\212Ø$Ù\213 Ø¹Ù\206Ø⁻ Ù
\210ØµÙ\210Ù\204 Ø±Ø³Ø$Ù\204Ø© Ø⁻Ø⁻Ù\212Ø⁻Ø©
    useEffect(() => {
        messagesEndRef.current?.scrollIntoView({ behavior: "smooth" });
    }, [messages]);

    const handleSendMessage = async () => {
        if (!newMessage.trim() || !activeContact) return;
        setIsSending(true);
        try {
            await fetch("/api/chat", {
                method: "POST",
                headers: { "Content-Type": "application/json" },
                body: JSON.stringify({ receiverId: activeContact.id, message: newMessage }),
            });
            setNewMessage("");
            // ØªØ⁻Ø⁻Ù\212Ø« Ø$Ù\204Ø±Ø³Ø$Ø|Ù\204 Ù\205Ø⁻Ø$Ø'Ø±Ø©
            const res = await fetch(`/api/chat?userId=${activeContact.id}`);
            if (res.ok) setMessages(await res.json());
        } catch (error) {
            console.error("Error sending message:", error);
        } finally {
            setIsSending(false);
        }
    };

    return (
        <div className="min-h-screen bg-gray-50">
            <Topbar />
            <div className="p-6 flex gap-6 h-[calc(100vh-100px)]">

                {/* Ù\202Ø$Ø|Ù\205Ø© Ø⁻Ù\207Ø$Øª Ø$Ù\204Ø$ØªØµØ$Ù\204 */}
                <div className="w-1/3 bg-white rounded-2xl shadow-sm border border-gray-100 overf
low-hidden flex flex-col">
                    <div className="p-4 border-b border-gray-100">
                        <h2 className="font-bold text-lg flex items-center gap-2">
                            <MessageCircle className="text-primary" size={20} /> Ø$Ù\204Ù\205Ø⁻Ø$Ø⁻Ø«Ø$
Øª
                        </h2>
                    </div>
                    <div className="flex-1 overflow-y-auto">
                        {contacts.length === 0 ? (
                            <p className="text-center text-gray-500 p-4">Ù\204Ø$ Ù\212Ù\210Ø⁻Ø⁻ ØªØ⁻Ø$Ø
± Ù\204Ù\204ØªÙ\210Ø$ØµÙ\204 Ù\205Ø¹Ù\207Ù\205 Ø⁻Ø¹Ø⁻.</p>
                        ) : (
                            contacts.map((contact) => (
                                <button
                                    key={contact.id}
                                    onClick={() => setActiveContact(contact)}
                                    className={`w-full text-right p-4 border-b border-gray-50 hover:bg-gray
-50 transition-colors ${
                                        activeContact?.id === contact.id ? "bg-blue-50" : ""
                                    }}`>
                                    >
                                    <div className="flex items-center gap-3">
                                        <div className="h-10 w-10 bg-primary/10 rounded-full flex items-cente
r justify-center font-bold text-primary">
                                            <User size={18} />
                                        </div>
                                        <div>
                                            <h3 className="font-bold text-sm">{contact.name}</h3>
                                            <p className="text-xs text-gray-500">{contact.role}</p>
                                        </div>
                                    </div>
                                </button>
                            ))
                        )}
                    </div>
                </div>
            </div>
        </div>
    );

```

```

</div>

{ /* Û\205Û\206•Û\202• ð$Û\204Û\205ð-ð$ð-ð«ð• */}
<div className="flex-1 bg-white rounded-2xl shadow-sm border border-gray-100 flex
flex-col">
  {!activeContact ? (
    <div className="flex-1 flex flex-col items-center justify-center text-gray-40
0">
      <MessageCircle size={48} className="mb-4" />
      <p>ð$ð•ðªð± ð¬Û\207• ð$ðªðµð$Û\204 Û\204ð¬ð¬; ð$Û\204Û\205ð-ð$ð-ð«ð•</p>
    </div>
  ) : (
    <>
      <div className="p-4 border-b border-gray-100">
        <h2 className="font-bold">{activeContact.name}</h2>
      </div>

      <div className="flex-1 overflow-y-auto p-4 space-y-4 bg-gray-50">
        {loading ? (
          <p className="text-center text-gray-500">ð¬ð$ð±Û\215 ðªð-Û\205Û\212Û
\204 ð$Û\204ð±ð³ð$ð!Û\204...</p>
        ) : messages.length === 0 ? (
          <p className="text-center text-gray-500">Û\204ð$ ðªÛ\210ð¬ð¬ ð±ð³ð$ð!Û
\204 ð¬ð¹ð¬. ð$ð¬ð¬ð£ ð$Û\204Û\205ð-ð$ð-ð«ð• ð$Û\204ð¢Û\206!</p>
        ) : (
          messages.map((msg) => (
            <div key={msg.id} className={`flex ${msg.sender_id === "self" ? "just
ify-start" : "justify-end"} `}>
              <div className={`max-w-[70%] p-3 rounded-2xl ${
                msg.sender_id === "self" ? "bg-blue-600 text-white" : "bg-white b
order border-gray-100 text-gray-800"
              } `}>
                <p className="text-sm">{msg.message}</p>
                <span className="text-[10px] opacity-70 block mt-1">
                  {new Date(msg.created_at).toLocaleTimeString('ar-IQ')}
                </span>
              </div>
            </div>
          ))
        )}
        <div ref={messagesEndRef} />
      </div>

      <div className="p-4 border-t border-gray-100 flex gap-2">
        <Input
          placeholder="ð$Û\203ðªð¬ ð±ð³ð$Û\204ðªÛ\203..."
          value={newMessage}
          onChange={(e) => setNewMessage(e.target.value)}
          onKeyDown={(e) => { if (e.key === 'Enter') handleSendMessage(); }}
          className="flex-1"
        />
        <Button onClick={handleSendMessage} disabled={isSending || !newMessage.tr
im()} className="gap-2">
          <Send size={16} /> ð¥ð±ð³ð$Û\204
        </Button>
      </div>
    </>
  )}
</div>
</div>
</div>
);
}

```

```
===== FILE: src/app/(dashboard)/retailer/cart/page.tsx =====
"use client";
import { useRouter } from "next/navigation";
import { useCartStore } from "@/lib/stores/cartStore";
import { useToast } from "@/hooks/useToast";
import { Button } from "@/components/ui/Button";
```

[illegible]

```

<div className="min-h-screen bg-gray-50">
  <Topbar />
  <div className="flex flex-col items-center justify-center py-24 text-center">
    <div className="text-8xl mb-6">ð\237\233\222</div>
    <h2 className="text-2xl font-bold text-gray-800 mb-2">ð³Û\204ðªÛ\203 Û\201ð$ð±ð
°ðð</h2>
    <p className="text-gray-500 mb-8">Û\204Û\205 ðªÛ\202Û\205 ð¨ð¥ð¶ð$Û\201ðð ð£Û
\212 Û\205Û\206ðªð¬ð$ðª ð¨ð¹ð¬.</p>
    <Button onClick={() => router.push("/")}>ðªðµÛ\201ð¬ ð$Û\204Û\205Û\206ðªð¬ð$ðª<
/Button>
  </div>
</div>
);
}

return (
  <div className="bg-gray-50 min-h-screen p-6">
    <Topbar />
    <div className="max-w-6xl mx-auto">
      <button onClick={() => router.back()} className="flex items-center gap-2 text-gra
y-500 mb-6 hover:text-primary transition-colors">
        <ArrowLeft size={16} /> Û\205ðªð$ð¨ð¹ðð ð$Û\204ðªð³Û\210Û\202
      </button>
      <h1 className="text-3xl font-extrabold text-gray-900 mb-8">ð³Û\204ðð ð$Û\204Û\205
ð'ðªð±Û\212ð$ðª</h1>
      <div className="grid grid-cols-1 lg:grid-cols-3 gap-8">
        <div className="lg:col-span-2 space-y-8">
          {wholesalers.map((wholesalerId) => {
            const wholesalerItems = groupedItems[wholesalerId];
            const wholesalerTotal = wholesalerItems.reduce((sum, item) => sum + item.pr
ice * item.quantity, 0);
            return (
              <div key={wholesalerId} className="bg-white rounded-2xl border border-gra
y-100 shadow-sm overflow-hidden">
                <div className="bg-gray-50 px-6 py-4 border-b flex items-center gap-3">
                  <Store size={20} className="text-primary" />
                  <h3 className="font-bold text-lg">ð•Û\204ð¨ ð¥Û\204Û\211 ðªð$ð¬ð± ð$Û
\204ð¬Û\205Û\204ðð</h3>
                  <Badge variant="secondary">{wholesalerItems.length} Û\205Û\206ðªð¬</B
adge>
                </div>
                <div className="p-4 space-y-4">
                  {wholesalerItems.map((item) => (
                    <div key={item.productId} className="flex gap-4 bg-white rounded-xl
p-3 border border-gray-100">
                      <div className="h-20 w-20 bg-gray-100 rounded-lg flex items-cente
r justify-center text-3xl shrink-0">ð\237\223</div>
                      <div className="flex-1 flex flex-col justify-between py-1">
                        <div className="flex justify-between items-start gap-4">
                          <div>
                            <h4 className="font-bold text-gray-800">{item.name}</h4>
                            <p className="text-sm text-gray-500">{formatCurrency(item.p
rice)}}</p>
                          </div>
                          <button onClick={() => removeItem(item.productId)} className=
"text-red-500 hover:bg-red-50 p-2 rounded-full transition-colors">
                            <Trash2 size={16} />
                          </button>
                        </div>
                        <div className="flex justify-between items-center mt-2">
                          <div className="flex items-center border border-gray-200 roun
ded-full bg-gray-50">
                            <button onClick={() => updateQuantity(item.productId, Math.
max(1, item.quantity - 1))} className="p-2 hover:bg-gray-200 rounded-r-full transition-co
lors"><Minus size={12} /></button>
                            <span className="w-10 text-center font-bold text-sm">{item.
quantity}</span>
                            <button onClick={() => updateQuantity(item.productId, item.
quantity + 1)} className="p-2 hover:bg-gray-200 rounded-l-full transition-colors"><Plus s
ize={12} /></button>

```

[illegible]

```

        </div>
      </div>
    </div>
  </div>
</div>
);
}

===== FILE: src/app/(dashboard)/retailer/commissions/page.tsx =====
"use client";
import { useEffect, useState } from "react";
import { Topbar } from "@/components/dashboard/Topbar";
import { DataTable } from "@/components/ui/DataTable";
import { StatusBadge } from "@/components/shared/StatusBadge";
import { LoadingSpinner } from "@/components/shared/LoadingSpinner";
import { useToast } from "@/hooks/useToast";
import { formatCurrency } from "@/lib/utils/currency";

export default function RetailerCommissionsPage() {
  const [commissions, setCommissions] = useState<any[]>([]);
  const [loading, setLoading] = useState(true);
  const { showToast } = useToast();

  useEffect(() => {
    const fetchCommissions = async () => {
      try {
        // Û\205Û\2040$0-0,00: Û\2120-0" 0fÛ\206 Û\212Û\203Û\210Û\206 0$Û\204Û\200 API 0$
        Û\20400$0µ 0"0$Û\2040¹Û\205Û\210Û\2040$0ª Û\2120-0¹Û\205 0-Û\2040" 0¹Û\205Û\210Û\2040$0ª
        0$Û\204Û\2050³0ª000-Û\205 0$Û\2040-0$Û\204Û\212
        const res = await fetch("/api/commissions", { method: "GET" });
        if (res.ok) setCommissions(await res.json());
      } catch (error) {
        showToast("000•0f Û\201Û\212 0-Û\2040" 0$Û\2040¹Û\205Û\210Û\2040$0ª", "error");
      } finally {
        setLoading(false);
      }
    };
    fetchCommissions();
  }, []);

  const columns = [
    { key: "order_id", header: "0±Û\202Û\205 0$Û\2040•Û\2040" },
    { key: "amount", header: "0$Û\204Û\2050"Û\2040°", render: (row: any) => formatCurrenc
y(row.amount) },
    { key: "created_at", header: "0$Û\2040ª0$0±Û\21200", render: (row: any) => new Date(r
ow.created_at).toLocaleDateString('ar-IQ') },
    { key: "status", header: "0$Û\2040-0$Û\20400", render: (row: any) => <StatusBadge sta
tus={row.status} /> },
  ];

  if (loading) return <LoadingSpinner />;

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <h1 className="text-3xl font-bold mb-6">0$Û\2040¹Û\205Û\210Û\2040$0ª 0$Û\204Û\205
0³0ª0-Û\20200</h1>
        <div className="bg-white p-6 rounded-2xl shadow-sm border border-gray-100">
          {commissions.length === 0 ? (
            <div className="py-10 text-center text-gray-500">Û\2040$ 0ªÛ\2100-0 0¹Û\205Û
\210Û\2040$0ª 0-0$Û\204Û\2120$Û\213.</div>
          ) : (
            <DataTable data={commissions} columns={columns} />
          )}
        </div>
      </div>
    </div>
  );
}

```

===== FILE: src/app/(dashboard)/retailer/components/RetailerStats.tsx =====

```
import { cn } from "@/lib/utils";

interface StatsCardProps {
  title: string;
  value: string;
  icon: string;
  trend?: string;
  trendUp?: boolean;
}

export function RetailerStats({ title, value, icon, trend, trendUp }: StatsCardProps) {
  return (
    <div className="bg-white rounded-2xl border border-gray-100 p-6 shadow-sm hover:shadow-w-lg transition-all">
      <div className="flex justify-between items-start">
        <div>
          <p className="text-sm font-medium text-gray-500">{title}</p>
          <h4 className="text-2xl font-extrabold mt-2">{value}</h4>
          {trend && (
            <p className={cn("text-xs mt-2 font-semibold", trendUp ? "text-emerald-500" : "text-red-500")}>
              {trendUp ? "â\206\221" : "â\206\223"} {trend}
            </p>
          )}
        </div>
        <div className="h-12 w-12 rounded-xl bg-gradient-to-tr from-primary/10 to-purple-500/10 flex items-center justify-center text-2xl">
          {icon}
        </div>
      </div>
    </div>
  );
}
```

===== FILE: src/app/(dashboard)/retailer/favorites/page.tsx =====

```
"use client";
import { useEffect, useState } from "react";
import { Topbar } from "@/components/dashboard/Topbar";
import { RequestCard } from "@/components/shared/RequestCard";
import { LoadingSpinner } from "@/components/shared/LoadingSpinner";
import { useToast } from "@/hooks/useToast";
import { Heart } from "lucide-react";

export default function RetailerFavoritesPage() {
  const [favorites, setFavorites] = useState<any[]>([]);
  const [loading, setLoading] = useState(true);
  const { showToast } = useToast();

  useEffect(() => {
    const fetchFavorites = async () => {
      try {
        const res = await fetch("/api/wishlist", { method: "GET" });
        if (res.ok) {
          const data = await res.json();
          setFavorites(data.map((item: any) => item.products));
        }
      } catch (error) {
        showToast("ðŸ’¥ Û\201Û\212 ð\204Û ð\204Û\205Û\201Û\204Û", "error");
      } finally {
        setLoading(false);
      }
    };
    fetchFavorites();
  }, []);

  if (loading) return <LoadingSpinner />;

  return (
```

```

<div className="min-h-screen bg-gray-50">
  <Topbar />
  <div className="p-6">
    <h1 className="text-3xl font-bold mb-6">ð$Û\204Û\205Û\206ðªð¬ð$ðª ð$Û\204Û\205Û\201ð¹Û\204ð©</h1>
    {favorites.length === 0 ? (
      <div className="text-center py-20 text-gray-500">
        <Heart className="mx-auto mb-4 text-gray-300" size={48} />
        Û\204ð$ ðªÛ\210ð¬ð¬ Û\205Û\206ðªð¬ð$ðª Û\201Û\212 ð$Û\204Û\205Û\201ð¹Û\204ð©
ð¬ð¹ð¬.
      </div>
    ) : (
      <div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-4 gap-6">
        {favorites.map((product) => (
          <RequestCard key={product.id} product={product} />
        ))}
      </div>
    )}
  </div>
</div>
);
}

```

===== FILE: src/app/(dashboard)/retailer/invoices/page.tsx =====

```

"use client";
import { useEffect, useState } from "react";
import { Topbar } from "@components/dashboard/Topbar";
import { DataTable } from "@components/ui/DataTable";
import { Badge } from "@components/ui/Badge";
import { Button } from "@components/ui/Button";
import { useToast } from "@hooks/useToast";
import { formatCurrency } from "@lib/utills/currency";
import { FileText } from "lucide-react";

export default function RetailerInvoicesPage() {
  const [invoices, setInvoices] = useState<any[]>([]);
  const { showToast } = useToast();

  useEffect(() => {
    // Û\205ðªÛ\202ðª ð¬ðªÛ\211 Û\212ðªÛ\205 ðªÛ\206ð¬ð$ð¬; ð¬ð¬Û\210Û\204 ð$Û\204Û\201Û\210ð$ðªÛ\212ð± ð£Û\210 ð$ð³ðªð©ð¬ð$Û\205 ð$Û\204ðªÛ\204ð¬ð$ðª
    setInvoices([]);
  }, []);

  const columns = [
    { key: "id", header: "ð±Û\202Û\205 ð$Û\204Û\201ð$ðªÛ\210ð±ð©" },
    { key: "date", header: "ð$Û\204ðªð$ð±Û\212ð©" },
    { key: "amount", header: "ð$Û\204Û\205ð¬Û\204ð°", render: (row: any) => formatCurrenc
y(row.amount) },
    { key: "status", header: "ð$Û\204ð¬ð$Û\204ð©", render: (row: any) => <Badge variant="
secondary">Û\205ð¬Û\201Û\210ð¹ð©</Badge> },
    { key: "actions", header: "ðªð¬Û\205Û\212Û\204", render: () => <Button size="sm" vari
ant="outline">PDF</Button> },
  ];

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <h1 className="text-3xl font-bold mb-6">ð$Û\204Û\201Û\210ð$ðªÛ\212ð±</h1>
        <div className="bg-white p-6 rounded-lg shadow">
          {invoices.length === 0 ? (
            <div className="py-10 text-center text-gray-500">
              <FileText className="mx-auto mb-4 text-gray-300" size={48} />
              Û\204ð$ ðªÛ\210ð¬ð¬ Û\201Û\210ð$ðªÛ\212ð± ð¬ð$Û\204Û\212ð$Û\213.
            </div>
          ) : (
            <DataTable data={invoices} columns={columns} />
          )}
        </div>
      </div>
    </div>
  );
}

```

```

    </div>
</div>
);
}

===== FILE: src/app/(dashboard)/retailer/nearby-wholesale/page.tsx =====
"use client";
import { useEffect, useState } from "react";
import { Topbar } from "@/components/dashboard/Topbar";
import { Button } from "@/components/ui/Button";
import { Badge } from "@/components/ui/Badge";
import { Input } from "@/components/ui/Input";
import { useToast } from "@/hooks/useToast";
import { Store, Search, Send } from "lucide-react";

export default function NearbyWholesalePage() {
  const [wholesalers, setWholesalers] = useState<any[]>([]);
  const [loading, setLoading] = useState(true);
  const [search, setSearch] = useState("");
  const { showToast } = useToast();

  useEffect(() => {
    const fetchWholesalers = async () => {
      try {
        const res = await fetch("/api/users?role=wholesaler");
        if (res.ok) setWholesalers(await res.json());
      } catch (error) {
        showToast("ðŸ’¥ ð‘¸\201Û\212 ð-Û\204” ðªð¬ð$± ð$Û\204ð¬Û\205Û\204ð©", "error");
      } finally {
        setLoading(false);
      }
    };
    fetchWholesalers();
  }, []);

  const handleSendRequest = async (wholesalerId: string) => {
    try {
      const res = await fetch("/api/relationships", {
        method: "POST",
        headers: { "Content-Type": "application/json" },
        body: JSON.stringify({ wholesalerId }),
      });
      const data = await res.json();
      if (res.ok) {
        showToast("ðªÛ\205 ð¥ð±ð³ð$Û\204 ð•Û\204” ð$Û\204ð$Û\206ð¶Û\205ð$Û\205 ð”Û\206ð¬ð$ð¬!", "success");
      } else {
        showToast(data.error || "ð¬ð¬ð« ð©ð•ð£", "error");
      }
    } catch (error) {
      showToast("ðªð¹ð°ð± ð$Û\204ð$ðªðµð$Û\204 ð”ð$Û\204ð©ð$ð¬Û\205", "error");
    }
  };

  const filteredWholesalers = wholesalers.filter((w) =>
    w.name?.includes(search) || w.email?.includes(search)
  );

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <h1 className="text-3xl font-bold mb-6">ðªð¬ð$± ð$Û\204ð¬Û\205Û\204ð© ð$Û\204Û\205ðªð$ð¬Û\210Û\206</h1>

        <div className="relative mb-6">
          <Search className="absolute right-3 top-3 text-gray-400" size={20} />
          <input
            type="text"
            placeholder="ð$ð”ð¬ð« ð¹Û\206 ðªð$ð¬ð± ð¬Û\205Û\204ð©..."

```

```

        value={search}
        onChange={(e) => setSearch(e.target.value)}
        className="w-full h-12 rounded-xl border border-gray-200 pr-10 pl-4 focus:outline-none focus:ring-2 focus:ring-primary"
      />
    </div>

    {filteredWholesalers.length === 0 ? (
      <div className="bg-white p-10 rounded-2xl shadow-sm text-center text-gray-500">
        <Store className="mx-auto mb-4 text-gray-300" size={48} />
        Û\2040$ Û\212Û\2100-0- 0ª0-0$0± 0-Û\205Û\20400 Û\2050³0-Û\204Û\210Û\206 0-0$Û\204Û\2120$Û\213.
      </div>
    ) : (
      <div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-3 gap-6">
        {filteredWholesalers.map((wholesaler) => (
          <div key={wholesaler.id} className="bg-white p-6 rounded-2xl shadow-sm border border-gray-100">
            <div className="flex items-center gap-3 mb-4">
              <div className="h-12 w-12 bg-primary/10 rounded-full flex items-center justify-center font-bold text-primary text-lg">
                {wholesaler.name?.charAt(0) || "0-"}
              </div>
              <div>
                <h3 className="font-bold text-lg">{wholesaler.name}</h3>
                <p className="text-sm text-gray-500">{wholesaler.email}</p>
              </div>
            </div>
            <Badge variant="secondary" className="mb-4">0ª0$0-0± 0-Û\205Û\20400</Badge>
            <Button onClick={() => handleSendRequest(wholesaler.id)} className="w-full gap-2">
              <Send size={16} /> 0¥0±0³0$Û\204 0•Û\2040" 0$Û\2060¶Û\2050$Û\205
            </Button>
          </div>
        )))
      </div>
    )}
  </div>
</div>
);
}

```

===== FILE: src/app/(dashboard)/retailer/orders/page.tsx =====

```

"use client";
import { useEffect, useState } from "react";
import { Topbar } from "@/components/dashboard/Topbar";
import { DataTable } from "@/components/ui/DataTable";
import { StatusBadge } from "@/components/shared/StatusBadge";
import { Button } from "@/components/ui/Button";
import { useToast } from "@/hooks/useToast";
import { formatCurrency } from "@/lib/utils/currency";
import { XCircle, RotateCcw } from "lucide-react";

export default function RetailerOrdersPage() {
  const [orders, setOrders] = useState<any[]>([]);
  const { showToast } = useToast();

  const fetchOrders = async () => {
    const res = await fetch("/api/orders");
    if (res.ok) setOrders(await res.json());
  };

  useEffect(() => { fetchOrders(); }, []);

  const updateStatus = async (id: string, status: string) => {
    const res = await fetch(`/api/orders/${id}`, {
      method: "PATCH",
      headers: { "Content-Type": "application/json" },
      body: JSON.stringify({ status }),
    });
  };

```

```

    });
    if (res.ok) {
      showToast("ðªÛ\205 ðªð-ð-Û\212ð« ð-ð$Û\204ð© ð$Û\204ð•Û\204ð", "success");
      fetchOrders();
    } else {
      showToast("ð-ð-ð« ð®ð•ð£", "error");
    }
  };

  const handleCancel = async (id: string) => {
    if (!confirm("Û\207Û\204 ð£Û\206ðª Û\205ðªð£Û\203ð- Û\205Û\206 ð¥Û\204ð°ð$ð; ð$Û\204ð•Û\204ð°\237")) return;
    await updateStatus(id, "cancelled");
  };

  const handleRefund = async (id: string) => {
    const reason = prompt("Û\212ð±ð-Û\211 Û\203ðªð$ð°ð© ð³ð°ð° ð•Û\204ð° ð$Û\204ð$ð³ðªð±ð-ð$ð¹:");
    if (!reason) return;
    const res = await fetch("/api/refunds", {
      method: "POST",
      headers: { "Content-Type": "application/json" },
      body: JSON.stringify({ orderId: id, reason }),
    });
    if (res.ok) {
      showToast("ðªÛ\205 ð¥ð±ð³ð$Û\204 ð•Û\204ð° ð$Û\204ð$ð³ðªð±ð-ð$ð¹ Û\204Û\204ð¥ð°ð$ð±ð©", "success");
    } else {
      showToast("ð-ð-ð« ð®ð•ð£ Û\201Û\212 ð¥ð±ð³ð$Û\204 ð$Û\204ð•Û\204ð°", "error");
    }
  };

  const columns = [
    { key: "id", header: "ð±Û\202Û\205 ð$Û\204ð•Û\204ð°" },
    { key: "total", header: "ð$Û\204Û\205ð-Û\205Û\210ð¹", render: (row: any) => formatCurrency(row.total) },
    { key: "status", header: "ð$Û\204ð-ð$Û\204ð©", render: (row: any) => <StatusBadge status={row.status} /> },
    { key: "actions", header: "ð¥ð°ð±ð$ð;ð$ðª", render: (row: any) => (
      <div className="flex gap-2">
        {row.status === 'pending' && (
          <Button size="sm" variant="destructive" onClick={() => handleCancel(row.id)}><XCircle size={14} /> ð¥Û\204ð°ð$ð; </Button>
        )}
        {row.status === 'delivered' && (
          <Button size="sm" variant="outline" onClick={() => handleRefund(row.id)}><RotateCcw size={14} /> ð$ð³ðªð±ð-ð$ð¹ </Button>
        )}
      </div>
    )},
  ];

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <h1 className="text-3xl font-bold mb-6">ð•Û\204ð°ð$ðªÛ\212</h1>
        <div className="bg-white p-6 rounded-2xl shadow-sm border border-gray-100">
          {orders.length === 0 ? (
            <div className="py-10 text-center text-gray-500">Û\204ð$ ðªÛ\210ð-ð- ð•Û\204ð°ð$ðª ð-ð$Û\204Û\212ð$Û\213.</div>
          ) : (
            <DataTable data={orders} columns={columns} />
          )}
        </div>
      </div>
    </div>
  );
}

```

```
===== FILE: src/app/(dashboard)/retailer/overview/page.tsx =====
import { Topbar } from "@components/dashboard/Topbar";
import { RetailerStats } from "@app/(dashboard)/retailer/components/RetailerStats";
import { retailerService } from "@lib/services/retailerService";
import { BarChart } from "@components/charts/BarChart";

export default async function RetailerOverviewPage() {
  let orders: any[] = [];
  try {
    orders = await retailerService.getMyOrders();
  } catch {
    orders = [];
  }

  const totalSales = orders?.reduce((sum, order) => sum + (order?.total ?? 0), 0);
  const pendingOrders = orders?.filter(o => o?.status === "pending").length ?? 0;
  const deliveredOrders = orders?.filter(o => o?.status === "delivered").length ?? 0;

  const chartData = orders?.slice(0, 4)?.map((order, index) => ({
    name: `ð•Û\2040` #${index + 1}`,
    value: order?.total
  }));

  return (
    <div>
      <Topbar />
      <h1 className="text-3xl font-bold mb-6">Û\2060,0±00 0¹0$Û\20500 Û\204Û\2040ª0$0¬0±<
/h1>

      <div className="grid grid-cols-1 md:grid-cols-3 gap-6 mb-6">
        <RetailerStats title="0¥0¬Û\2050$Û\204Û\212 0$Û\204Û\2050¬Û\2120¹0$0ª" value={`$${
totalSales?.toLocaleString()} 0¬.0¹` } icon="ð\237\222°" trend="+12%" trendUp={true} />
        <RetailerStats title="0•Û\2040¬0$0ª Û\202Û\2120¬ 0$Û\2040$Û\2060ª0,0$0±" value={`p
endingOrders?.toString()} icon="â\217³" trend="" trendUp={false} />
        <RetailerStats title="0•Û\2040¬0$0ª Û\205Û\2030ªÛ\205Û\20400" value={`deliveredOrd
ers?.toString()} icon="â\234\205" trend="" trendUp={false} />
      </div>

      <div className="grid grid-cols-1 md:grid-cols-2 gap-6">
        <div className="p-6 bg-white rounded-lg shadow">
          <h2 className="text-xl font-semibold mb-4">Û\202Û\212Û\20500 0$Û\2040•Û\2040¬0$
0ª 0$Û\2040f000Û\2120±00</h2>
          {chartData?.length > 0 ? (
            <BarChart data={chartData} />
          ) : (
            <p className="text-gray-500">Û\2040$ 0ªÛ\2100¬0¬ 0•Û\2040¬0$0ª 0¬0¹0¬.</p>
          )}
        </div>
        <div className="p-6 bg-white rounded-lg shadow">
          <h2 className="text-xl font-semibold mb-4">0¢000± Û\2060´0$0•</h2>
          <ul className="space-y-3">
            {orders?.slice(0, 5)?.map((order) => (
              <li key={order?.id} className="flex justify-between border-b pb-2">
                <span className="font-medium">0•Û\2040¬ #{order?.id}</span>
                <span className="text-primary font-bold">{order?.total?.toLocaleString()
} 0¬.0¹</span>
              </li>
            )}
            {orders?.length === 0 && <li className="text-gray-500">Û\2040$ Û\212Û\2100¬0¬
Û\2060´0$0• 0¬0¹0¬.</li>}
          </ul>
        </div>
      </div>
    </div>
  );
}
```

```
===== FILE: src/app/(dashboard)/retailer/points/page.tsx =====
"use client";
import { useEffect, useState } from "react";
```

```

import { Topbar } from "@components/dashboard/Topbar";
import { DataTable } from "@components/ui/DataTable";
import { Badge } from "@components/ui/Badge";
import { useToast } from "@hooks/useToast";
import { Coins, Star } from "lucide-react";

export default function RetailerPointsPage() {
  const [transactions, setTransactions] = useState<any[]>([]);
  const [totalPoints, setTotalPoints] = useState(0);
  const { showToast } = useToast();

  useEffect(() => {
    const fetchPoints = async () => {
      try {
        const res = await fetch("/api/points");
        if (res.ok) {
          const data = await res.json();
          setTransactions(data);
          const total = data.reduce((sum: number, tx: any) => sum + (tx.type === 'earn' ?
tx.points : -tx.points), 0);
          setTotalPoints(total);
        }
      } catch (error) {
        showToast("ðŸ’¥ Û\201Û\212 ð\204Û ðÛ\204Û\206Û\202ð$ð•", "error");
      }
    };
    fetchPoints();
  }, []);

  const columns = [
    { key: "id", header: "ðÛ\204Û\205ð¹ð±Û\201" },
    { key: "type", header: "ðÛ\204Û\206Û\210ð¹", render: (row: any) => (
      <Badge variant={row.type === 'earn' ? 'success' : 'destructive'}>{row.type === 'e
arn' ? 'Û\203ð³ð" : 'ð$ð³ðªÛ\207Û\204ðÛ\203'}</Badge>
    )},
    { key: "points", header: "ðÛ\204Û\206Û\202ð$ð•", render: (row: any) => (
      <span className={row.type === 'earn' ? "text-green-600 font-bold" : "text-red-600
font-bold"}>
        {row.type === 'earn' ? '+' : '-'}{row.points}
      </span>
    )},
    { key: "created_at", header: "ðÛ\204ðªð$ð±Û\212ðª", render: (row: any) => new Date(r
ow.created_at).toLocaleDateString('ar-IQ') },
  ];

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <div className="flex items-center justify-between mb-6">
          <h1 className="text-3xl font-bold">Û\206Û\202ð$ð• ðÛ\204Û\210Û\204ð$ð;</h1>
          <Badge variant="default" className="text-lg px-4 py-2">
            <Coins className="ml-2" size={18} /> {totalPoints} Û\206Û\202ð•ðª
          </Badge>
        </div>
        <div className="bg-white p-6 rounded-2xl shadow-sm border border-gray-100">
          {transactions.length === 0 ? (
            <div className="py-10 text-center text-gray-500">
              <Star className="mx-auto mb-4 text-gray-300" size={48} />
              Û\204ð$ ðªÛ\210ð¬ Û\205ð¹ðÛ\205Û\204ð$ðª Û\206Û\202ð$ð• ð"ð¹ð¬. ð$ð"ð¬ð£
ð"ð$Û\204ðªð³Û\210Û\202 Û\204ðªÛ\203ð³ð" ðÛ\204Û\206Û\202ð$ð•!
            </div>
          ) : (
            <DataTable data={transactions} columns={columns} />
          )}
        </div>
      </div>
    </div>
  );
}

```

```
===== FILE: src/app/(dashboard)/retailer/settings/page.tsx =====
"use client";
import { useUserStore } from "@lib/stores/userStore";
import { useToast } from "@hooks/useToast";
import { Button } from "@components/ui/Button";
import { Input } from "@components/ui/Input";
import { Topbar } from "@components/dashboard/Topbar";

export default function RetailerSettingsPage() {
  const user = useUserStore((state) => state.user);
  const { showToast } = useToast();

  const handleSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    showToast("ð"\205 -\201, $\204¥¹-$-$ª "\206-$-, "success");
  };

  return (
    <div>
      <Topbar />
      <div className="bg-white p-6 rounded-lg shadow max-w-lg">
        <h1 className="text-2xl font-bold mb-6">¥¹-$-$ª $\204\205ª-±</h1>
        <form onSubmit={handleSubmit} className="space-y-4">
          <Input name="storeName" placeholder="$³\205 $\204\205ª-±" defaultValue
={ '\205ª-± ${user?.name}' } />
          <Input name="phone" placeholder="±\202\205 $\204\207$ª\201" defaultVal
ue={user?.phone} />
          <Input name="address" placeholder="$\204¹\206\210$\206" />
          <Button type="submit">-\201, $\204ª°\212\212±$ª</Button>
        </form>
      </div>
    </div>
  );
}
```

```
===== FILE: src/app/(dashboard)/wholesale/commissions/page.tsx =====
"use client";
import { useEffect, useState } from "react";
import { Topbar } from "@components/dashboard/Topbar";
import { DataTable } from "@components/ui/DataTable";
import { StatusBadge } from "@components/shared/StatusBadge";
import { LoadingSpinner } from "@components/shared/LoadingSpinner";
import { useToast } from "@hooks/useToast";
import { formatCurrency } from "@lib/utils/currency";

export default function WholesaleCommissionsPage() {
  const [commissions, setCommissions] = useState<any[]>([]);
  const [loading, setLoading] = useState(true);
  const { showToast } = useToast();

  useEffect(() => {
    const fetchCommissions = async () => {
      try {
        const res = await fetch("/api/commissions", { method: "GET" });
        if (res.ok) setCommissions(await res.json());
      } catch (error) {
        showToast("@•£ \201\212 -\204" $\204¹\205\210\204$ª", "error");
      } finally {
        setLoading(false);
      }
    };
    fetchCommissions();
  }, []);

  const columns = [
    { key: "order_id", header: "±\202\205 $\204•\204" },
    { key: "amount", header: "$\204\205ª\204°", render: (row: any) => formatCurrenc
y(row.amount) },
    { key: "created_at", header: "$\204ª$±\212@", render: (row: any) => new Date(r
```

```

ow.created_at).toLocaleDateString('ar-IQ') },
  { key: "status", header: "Ø$Ù\204Ø-Ø$Ù\204Ø@", render: (row: any) => <StatusBadge sta
tus={row.status} /> },
];

if (loading) return <LoadingSpinner />;

return (
  <div className="min-h-screen bg-gray-50">
    <Topbar />
    <div className="p-6">
      <h1 className="text-3xl font-bold mb-6">Ø$Ù\204Ø¹Ù\205Ù\210Ù\204Ø$Øª</h1>
      <div className="bg-white p-6 rounded-2xl shadow-sm border border-gray-100">
        {commissions.length === 0 ? (
          <div className="py-10 text-center text-gray-500">Ù\204Ø$ ØªÙ\210Ø¬Ø¬ Ø¹Ù\205Ù
\210Ù\204Ø$Øª Ø-Ø$Ù\204Ù\212Ø$Ù\213.</div>
        ) : (
          <DataTable data={commissions} columns={columns} />
        )}
      </div>
    </div>
  </div>
);
}

```

```

===== FILE: src/app/(dashboard)/wholesale/components/WholesaleStats.tsx =====
'use client';

```

```
import React from 'react';
```

```

interface WholesaleStatsProps {
  title?: string;
  value?: string | number;
  icon?: string;
  [key: string]: unknown;
}

```

```

const WholesaleStats = ({ title, value, icon }: WholesaleStatsProps) => {
  return (
    <div className="bg-white rounded-lg p-4 shadow flex items-center gap-4">
      {icon && <span className="text-3xl">{icon}</span>}
      <div>
        {title && <p className="text-sm text-gray-500">{title}</p>}
        {value !== undefined && <p className="text-xl font-bold">{value}</p>}
      </div>
    </div>
  );
};

```

```
export { WholesaleStats };
```

```

===== FILE: src/app/(dashboard)/wholesale/delivery-requests/page.tsx =====
"use client";
import { Topbar } from "@/components/dashboard/Topbar";

```

```

export default function WholesaleDeliveryRequestsPage() {
  return (
    <div>
      <Topbar />
      <h1 className="text-3xl font-bold mb-6">Ø•Ù\204Ø¬Ø$Øª Ø$Ù\204Ù\205Ù\206Ø¬Ù\210Ø¬Ù
\212Ù\206</h1>
      <p className="text-gray-500">Ø³Ù\212ØªÙ\205 Ø¹Ø±Ø¶ Ø•Ù\204Ø¬Ø$Øª Ù\205Ù\206Ø¬Ù\210Ø
¬Ù\212Ø$Ù\204ØªÙ\210ØµÙ\212Ù\204 Ù\207Ù\206Ø$ Ù\204Ø$Ø¬-Ù\202Ø$Ù\213.</p>
    </div>
  );
}

```

```

===== FILE: src/app/(dashboard)/wholesale/inventory/page.tsx =====
"use client";
import { useEffect, useState } from "react";

```

```
import { Topbar } from "@components/dashboard/Topbar";
import { DataTable } from "@components/ui/DataTable";
import { Badge } from "@components/ui/Badge";
import { Button } from "@components/ui/Button";
import { useToast } from "@hooks/useToast";

export default function WholesaleInventoryPage() {
  const [products, setProducts] = useState<any[]>([]);
  const [loading, setLoading] = useState(true);
  const { showToast } = useToast();

  const fetchProducts = async () => {
    try {
      const res = await fetch("/api/products");
      if (res.ok) setProducts(await res.json());
    } catch (error) {
      showToast("ðŸ’¥ ðŸš¨\201ðš¨\212 ðŸš¨\204ðŸš¨ ðŸš¨\204ðš¨\205ðš¨\206ðªðŸš¨", "error");
    } finally {
      setLoading(false);
    }
  };

  useEffect(() => { fetchProducts(); }, []);

  const columns = [
    { key: "name", header: "ðŸš¨\204ðš¨\205ðš¨\206ðªðŸš¨" },
    { key: "category", header: "ðŸš¨\204ðš¨\201ðŸš¨" },
    { key: "stock", header: "ðŸš¨\204ðš¨\203ðš¨\205ðš¨\212ðŸš¨", render: (row: any) => (
      row.stock < 10 ? <Badge variant="destructive">ðŸš¨\205ðš¨\206ðŸš¨\201ðŸš¨ ({row.stock})</
Badge> : <Badge>ðŸš¨\205ðªðš¨\210ðš¨\201ðŸ± ({row.stock})</Badge>
    )},
    { key: "actions", header: "ðŸš¨ðŸ±ðŸš¨;ðŸš¨ª", render: (row: any) => (
      <Button size="sm" variant="outline">ðªð¹ðŸš¨\212ðš¨\204 ðŸš¨\204ðš¨\205ðŸð²ðš¨\210ðš¨\206</
Button>
    )},
  ];

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <h1 className="text-3xl font-bold mb-6">ðŸš¨ðŸ±ðŸð ðŸš¨\204ðš¨\205ðŸð²ðš¨\210ðš¨\206</h1>
        <div className="bg-white p-6 rounded-2xl shadow-sm border border-gray-100">
          {products.length === 0 ? (
            <div className="py-10 text-center text-gray-500">ðš¨\204ðŸ ðªðš¨\210ðŸðŸ ðš¨\205ðš¨\206ðªðŸðª ðš¨\201ðš¨\212 ðŸš¨\204ðš¨\205ðŸð²ðš¨\210ðš¨\206 ðŸð¹ðŸš¨.</div>
          ) : (
            <DataTable data={products} columns={columns} />
          )}
        </div>
      </div>
    </div>
  );
}
```

```
===== FILE: src/app/(dashboard)/wholesale/nearby-requests/page.tsx =====
```

```

"use client";
import { useEffect, useState } from "react";
import { Topbar } from "@components/dashboard/Topbar";
import { Button } from "@components/ui/Button";
import { Badge } from "@components/ui/Badge";
import { useToast } from "@hooks/useToast";
import { UserPlus, Check, X } from "lucide-react";

export default function WholesaleNearbyRequestsPage() {
  const [requests, setRequests] = useState<any[]>([]);
  const { showToast } = useToast();

  const fetchRequests = async () => {

```

```
const res = await fetch("/api/relationships");
if (res.ok) setRequests(await res.json());
};

useEffect(() => { fetchRequests(); }, []);

const handleAction = async (id: string, action: "accept" | "reject") => {
  const res = await fetch(`/api/relationships/${id}`, {
    method: "PATCH",
    headers: { "Content-Type": "application/json" },
    body: JSON.stringify({ action }),
  });
  if (res.ok) {
    showToast(action === "accept" ? "ð\205 Û\202ð""Û\210Û\204 ø$Û\204ø•Û\204ø"" : "ð\205 ø±Û\201ø¶ ø$Û\204ø•Û\204ø"", "success");
    fetchRequests();
  } else {
    showToast("ð-ð`ð« ø@ø•ø£", "error");
  }
};

return (
  <div className="min-h-screen bg-gray-50">
    <Topbar />
    <div className="p-6">
      <h1 className="text-3xl font-bold mb-6">ð•Û\204ø``ø$øª ø$Û\204ø$Û\206ø¶Û\205ø$Û\205</h1>
      {requests.length === 0 ? (
        <div className="bg-white p-10 rounded-2xl shadow-sm text-center text-gray-500">
          <UserPlus className="mx-auto mb-4 text-gray-300" size={48} />
          Û\204ø$ øªÛ\210ø¬ø¬ ø•Û\204ø``ø$øª ø$Û\206ø¶Û\205ø$Û\205 ø-ø$Û\204Û\212ø$Û\213
        </div>
      ) : (
        <div className="space-y-4">
          {requests.map((request) => {
            const user = request.retailer || request.delivery;
            return (
              <div key={request.id} className="bg-white p-6 rounded-2xl shadow-sm border r border-gray-100 flex items-center justify-between gap-4">
                <div className="flex items-center gap-3">
                  <div className="h-12 w-12 bg-primary/10 rounded-full flex items-cente r justify-center font-bold text-primary">
                    {user?.name?.charAt(0) || "ø\237"}
                  </div>
                  <div>
                    <h3 className="font-bold">{user?.name}</h3>
                    <p className="text-sm text-gray-500">{user?.email}</p>
                    <Badge variant="secondary" className="mt-1">{request.delivery ? "Û\205Û\206ø¬Û\210ø" øªÛ\210øµÛ\212Û\204" : "øªø$ø¬ø± øªø¬ø²ø!ø@"}</Badge>
                  </div>
                </div>
                <div className="flex gap-2">
                  <Button size="sm" onClick={() => handleAction(request.id, "accept")}><Check size={14} /> Û\202ø``Û\210Û\204</Button>
                  <Button size="sm" variant="destructive" onClick={() => handleAction(r equest.id, "reject")}><X size={14} /> ø±Û\201ø¶</Button>
                </div>
              </div>
            );
          })}
        </div>
      )}
    </div>
  )};
```

===== FILE: src/app/(dashboard)/wholesale/orders/page.tsx =====
"use client";

```
import { useEffect, useState } from "react";
import { Topbar } from "@components/dashboard/Topbar";
import { DataTable } from "@components/ui/DataTable";
import { StatusBadge } from "@components/shared/StatusBadge";
import { Button } from "@components/ui/Button";
import { Modal } from "@components/ui/Modal";
import { useToast } from "@hooks/useToast";
import { formatCurrency } from "@lib/utils/currency";
import { Send, Printer, Eye } from "lucide-react";

export default function WholesaleOrdersPage() {
  const [orders, setOrders] = useState<any[]>([]);
  const [selectedOrder, setSelectedOrder] = useState<any>(null);
  const [loading, setLoading] = useState(true);
  const { showToast } = useToast();

  const fetchOrders = async () => {
    try {
      const res = await fetch("/api/orders", { method: "GET" });
      if (res.ok) setOrders(await res.json());
    } catch (error) {
      showToast("ðŸ’¥ Û\201Û\212 ð-Û\204Û" ð$Û\204Û•Û\204Û"ð$Û", "error");
    } finally {
      setLoading(false);
    }
  };

  useEffect(() => { fetchOrders(); }, []);

  const updateStatus = async (id: string, status: string) => {
    const res = await fetch(`/api/orders/${id}`, {
      method: "PATCH",
      headers: { "Content-Type": "application/json" },
      body: JSON.stringify({ status }),
    });
    if (res.ok) {
      showToast("ðªÛ\205 ðªð-ð-Û\212ð« ð-ð$Û\204ð© ð$Û\204Û•Û\204Û", "success");
      fetchOrders();
    } else {
      showToast("ð-ð-ð« ðŸ’¥", "error");
    }
  };

  const handleShipAndWhatsApp = async (orderId: string) => {
    await updateStatus(orderId, "shipped");
    try {
      const res = await fetch("/api/whatsapp", {
        method: "POST",
        headers: { "Content-Type": "application/json" },
        body: JSON.stringify({ orderId }),
      });
      const data = await res.json();
      if (data.url) {
        window.open(data.url, '_blank');
        showToast("ðªÛ\205 Û\201ðªð- Û\210ð$ðªð³ð$Û" Û\204ð¥ð±ð³ð$Û\204 ð$Û\204ðªÛ\201ð$ð
µÛ\212Û\204", "success");
      } else {
        showToast("Û\204ð$ Û\212Û\210ð-ð- ð±Û\202Û\205 Û\207ð$ðªÛ\201 Û\204Û\204ðªð$ð-ð±"
, "error");
      }
    } catch (error) {
      showToast("ðªð¹ð°ð± ð¥ð±ð³ð$Û\204 ð$Û\204Û\210ð$ðªð³ð$Û", "error");
    }
  };

  // ð-ð$Û\204ð© ð$Û\204Û•Û"ð$ð¹ð© (ðªÛ\201ðªð- Û\206ð$Û\201ð°ð© ð-ð-Û\212ð-ð© Û\204Û\204
ð•ð"ð$ð¹ð©)
  const handlePrint = (order: any) => {
    const printWindow = window.open('', '_blank', 'width=600,height=600');
    if (!printWindow) return;
  };
}
```

```
printWindow.document.write(`
  <html dir="rtl">
    <head><title>Ù\2010$ØªÙ\2100±00 Ø•Ù\2040" #${order.id}</title></head>
    <body style="font-family: sans-serif; padding: 20px; text-align: right;">
      <h1 style="color: #f59e0b; text-align: center;">Ø¬Ù\217Ù\205Ù\222Ù\204Ù\216ØªÙ
\220Ù\212</h1>
      <h3>Ù\2010$ØªÙ\2100±00 Ø•Ù\2040" Ø±Ù\202Ù\205: ${order.id}</h3>
      <p>Ø$Ù\2040ªØ$Ø±Ù\21200: ${new Date(order.created_at).toLocaleDateString('ar-IQ
')}</p>
      <p>Ø$Ù\2040¹Ù\206Ù\2100$Ù\206: ${order.address}</p>
      <hr>
      <p>Ø$Ù\2040¥Ø¬Ù\205Ø$Ù\204Ù\212: <strong>${formatCurrency(order.total)}</strong>
></p>
      <hr>
      <p style="text-align: center; color: #888;">Ø´Ù\203Ø±Ø$Ù\213 Ù\2040ªØ¹Ø$Ù\205Ù
\204Ù\203Ù\205 Ù\205Ø¹Ù\206Ø$</p>
    </body>
  </html>
`);
printWindow.document.close();
printWindow.focus();
printWindow.print();
};

const columns = [
  { key: "id", header: "Ø±Ù\202Ù\205 Ø$Ù\2040•Ù\2040" },
  { key: "total", header: "Ø$Ù\204Ù\202Ù\212Ù\20500", render: (row: any) => formatCurre
ncy(row.total) },
  { key: "status", header: "Ø$Ù\2040-Ø$Ù\20400", render: (row: any) => <StatusBadge sta
tus={row.status} /> },
  { key: "actions", header: "Ø¥Ø¬Ø±Ø$Ø;Ø$Øª", render: (row: any) => (
    <div className="flex gap-2">
      <Button size="sm" variant="outline" onClick={() => setSelectedOrder(row)}><Ey
e size={14} /></Button>
      <Button size="sm" variant="outline" onClick={() => handlePrint(row)}><Printer
size={14} /></Button>
      {row.status === 'pending' && (
        <Button size="sm" onClick={() => updateStatus(row.id, 'processing')}>Ù
\2020"Ù\210Ù\204</Button>
      )}
      {row.status === 'processing' && (
        <Button size="sm" variant="secondary" onClick={() => handleShipAndWhatsAp
p(row.id)} className="gap-2">
          <Send size={14} /> Ø´Ø¬Ù\206
        </Button>
      )}
      {row.status === 'shipped' && (
        <Button size="sm" variant="outline" onClick={() => updateStatus(row.id, '
delivered')}>ØªÙ\205 Ø$Ù\2040ªÙ\2100µÙ\212Ù\204</Button>
      )}
    </div>
  )},
];

return (
  <div className="min-h-screen bg-gray-50">
    <Topbar />
    <div className="p-6">
      <h1 className="text-3xl font-bold mb-6">Ø$Ù\2040•Ù\2040"Ø$Øª Ø$Ù\204Ù\2100$Ø±Ø¬00
</h1>
      <div className="bg-white p-6 rounded-2xl shadow-sm border border-gray-100">
        {orders.length === 0 ? (
          <div className="py-10 text-center text-gray-500">Ù\2040$ ØªÙ\2100¬Ø¬ Ø•Ù\2040
"Ø$Øª Ù\2100$Ø±Ø¬00 Ø"Ø¹Ø¬.</div>
        ) : (
          <DataTable data={orders} columns={columns} />
        )}
      </div>
    </div>
  </div>
);
```

```
    /* Û\2060$Û\2010°00 0¹0±0¶ 0$Û\2040ªÛ\2010$0µÛ\212Û\204 */
    <Modal open={!selectedOrder} onClose={() => setSelectedOrder(null)} title="0ªÛ\201
0$0µÛ\212Û\204 0$Û\2040•Û\2040"">
      {selectedOrder && (
        <div className="space-y-4">
          <p><strong>0±Û\202Û\205 0$Û\2040•Û\2040":</strong> {selectedOrder.id}</p>
          <p><strong>0$Û\2040¹Û\206Û\2100$Û\206:</strong> {selectedOrder.address}</p>
          <p><strong>0$Û\2040¥0¬Û\2050$Û\204Û\212:</strong> {formatCurrency(selectedOrd
er.total)}</p>
          <div className="flex gap-2">
            <Button onClick={() => handlePrint(selectedOrder)} className="w-full"><Prin
ter size={16} className="ml-2" /> 0•0¬0$0¹00 0$Û\204Û\2010$0ªÛ\2100±00</Button>
          </div>
        </div>
      )}
    </Modal>
  </div>
);
}
```

===== FILE: src/app/(dashboard)/wholesale/overview/page.tsx =====

```
import { Topbar } from "@/components/dashboard/Topbar";
import { StatsCard } from "@/components/shared/StatsCard";
import { LineChart } from "@/components/charts/LineChart";
import { wholesaleService } from "@/lib/services/wholesaleService";
import { formatCurrency } from "@/lib/utils/currency";
import { Button } from "@/components/ui/Button";

export default async function WholesaleOverviewPage() {
  let products: any[] = [];
  let orders: any[] = [];
  let totalRevenue = 0;

  try {
    products = await wholesaleService.getMyProducts() || [];
    orders = await wholesaleService.getMyOrders?.() || [];
    totalRevenue = orders.reduce((sum, order) => sum + (order?.total || 0), 0);
  } catch (error) {
    console.error("Error fetching wholesale data:", error);
  }

  const chartData = orders.slice(0, 7).map((order, index) => ({
    name: `0•Û\2040" #${index + 1}`,
    value: order.total
  }));

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <div className="flex items-center justify-between mb-6">
          <h1 className="text-3xl font-bold text-gray-900">Û\2060,0±00 0¹0$Û\20500 Û\204Û\2040-Û\205Û\20400</h1>
          <Button variant="outline" size="sm">0ª0µ0¬Û\2120± 0$Û\2040ªÛ\2020±Û\2120±</Butt
on>
        </div>
        <div className="grid grid-cols-1 md:grid-cols-3 gap-6 mb-8">
          <StatsCard title="0¥0¬Û\2050$Û\204Û\212 0$Û\2040¥Û\2120±0$0¬0$0ª" value={format
Currency(totalRevenue)} icon="ð\237\222°" trend="+12%" trendUp={true} />
          <StatsCard title="0¹0¬0¬ 0$Û\2040•Û\2040¬0$0ª" value={orders.length.toString()}
icon="ð\237\223|" trend="+5%" trendUp={true} />
          <StatsCard title="0$Û\204Û\205Û\2060ª0¬0$0ª 0$Û\204Û\2060ª0•00" value={products
.length.toString()} icon="ð\237\233\215i,\217" />
        </div>
        <div className="grid grid-cols-1 lg:grid-cols-2 gap-6">
          <div className="bg-white rounded-2xl shadow-sm border border-gray-100 p-6">
            <h2 className="text-xl font-semibold mb-4">0$0ª0¬0$Û\207 0$Û\2040¥Û\2120±0$0¬
0$0ª</h2>
            {chartData.length > 0 ? (
              <LineChart data={chartData} />
            )
          </div>
        </div>
      </div>
    </div>
  );
}
```

```

    ) : (
      <div className="h-64 flex items-center justify-center text-gray-400">Û\2040
$ 0ªÛ\2100-0- 0"Û\2120$Û\2060$0ª Û\2040Û\2040¥Û\2120±0$0-0$0ª 0"0¹0- </div>
    )}
  </div>
  <div className="bg-white rounded-2xl shadow-sm border border-gray-100 p-6">
    <h2 className="text-xl font-semibold mb-4">0£0-0-0« 0$Û\2040•Û\2040"0$0ª</h2>
    {orders.length > 0 ? (
      <div className="space-y-4">
        {orders.slice(0, 5).map((order) => (
          <div key={order.id} className="flex justify-between items-center border
-b pb-3">
            <div>
              <p className="font-medium text-gray-800">0•Û\2040" #{order.id.slice
(0, 6)}</p>
              <p className="text-sm text-gray-500">{new Date(order.created_at).to
LocaleDateString('ar-IQ')}</p>
            </div>
            <span className="font-bold text-primary">{formatCurrency(order.total)
}</span>
          </div>
        )})}
      </div>
    ) : (
      <div className="py-10 text-center text-gray-400">Û\2040$ 0ªÛ\2100-0- 0•Û
\2040"0$0ª Û\2100$0±0-0© 0"0¹0- </div>
    )}
  </div>
</div>
</div>
</div>
);
}

```

===== FILE: src/app/(dashboard)/wholesale/payouts/page.tsx =====

```

"use client";
import { useEffect, useState, useCallback } from "react";
import { Topbar } from "@/components/dashboard/Topbar";
import { DataTable } from "@/components/ui/DataTable";
import { Badge } from "@/components/ui/Badge";
import { useToast } from "@/hooks/useToast";
import { formatCurrency } from "@/lib/utils/currency";

export default function WholesalePayoutsPage() {
  const [payouts, setPayouts] = useState([]);
  const { showToast } = useToast();

  const fetchPayouts = useCallback(async () => {
    try {
      const res = await fetch("/api/payouts");
      if (res.ok) setPayouts(await res.json());
    } catch (error) {
      showToast("000•0£ Û\201Û\212 0-Û\2040" 0$Û\2040Û\2050-Û\201Û\2100¹0$0ª", "error");
    }
  }, [showToast]);

  useEffect(() => { fetchPayouts(); }, [fetchPayouts]);

  const columns = [
    { key: "id", header: "0±Û\202Û\205 0$Û\2040-Û\2010¹0©", },
    { key: "amount", header: "0$Û\2040Û\2050-Û\2040°", render: (row: any) => formatCurrenc
y(row.amount) },
    { key: "status", header: "0$Û\2040-0$Û\2040©", render: (row: any) => (row.status ===
"processed" ? <Badge variant="success">Û\2050-Û\201Û\2100¹</Badge> : <Badge variant="seco
ndary">Û\2050¹Û\2040Û\202</Badge>) },
  ];

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />

```

```
    <div className="p-6">
      <h1 className="text-3xl font-bold mb-6">ð$Û\204Û\205ð\201Û\210ð¹ð$ðª Û\210ð$Û\204Û\205ð³ðªð\202ð$ðª</h1>
      <div className="bg-white p-6 rounded-2xl shadow-sm border border-gray-100">
        {payouts.length === 0 ? (
          <div className="py-10 text-center text-gray-500">Û\204ð$ ðªÛ\210ð\201Û\205ð\201Û\210ð¹ð$ðª ð\202ð$Û\204Û\212ð$Û\213.</div>
        ) : (
          <DataTable data={payouts} columns={columns} />
        )}
      </div>
    </div>
  </div>
);
}
```

===== FILE: src/app/(dashboard)/wholesale/products/page.tsx =====

```
"use client";
import { useEffect, useState, useCallback } from "react";
import { Topbar } from "@components/dashboard/Topbar";
import { DataTable } from "@components/ui/DataTable";
import { Badge } from "@components/ui/Badge";
import { Button } from "@components/ui/Button";
import { Modal } from "@components/ui/Modal";
import { ProductForm } from "@components/forms/ProductForm";
import { useToast } from "@hooks/useToast";
import { formatCurrency } from "@lib/utils/currency";
import { Pencil, Trash2, Plus } from "lucide-react";

export default function WholesaleProductsPage() {
  const [products, setProducts] = useState([]);
  const [showForm, setShowForm] = useState(false);
  const [editingProduct, setEditingProduct] = useState(null);
  const { showToast } = useToast();

  const fetchProducts = useCallback(async () => {
    try {
      const res = await fetch("/api/products");
      if (res.ok) {
        const data = await res.json();
        setProducts(data);
      }
    } catch (error) {
      showToast("ððð•ð Û\201Û\212 ð\204ð" ð$Û\204Û\205Û\206ðªð\207ðª", "error");
    }
  }, [showToast]);

  useEffect(() => {
    fetchProducts();
  }, [fetchProducts]);

  const handleDelete = async (id: string) => {
    if (!confirm("Û\207Û\204 ðÛ\206ðª Û\205ðªðÛ\203ð\205Û\206 ð\201 Û\207ðªð$ ð$Û\204Û\205Û\206ðªð\237")) return;
    const res = await fetch(`/api/products/${id}`, { method: "DELETE" });
    if (res.ok) {
      showToast("ðªÛ\205 ð\201 ð$Û\204Û\205Û\206ðªð\207", "success");
      fetchProducts();
    } else {
      showToast("ððð•ð Û\201Û\212 ð$Û\204ð\201", "error");
    }
  };

  const columns = [
    { key: "name", header: "ð$Û\204Û\205Û\206ðªð\207" },
    { key: "category", header: "ð$Û\204Û\201ð\200" },
    {
      key: "price",
      header: "ð$Û\204ð³ð¹ð±",
      render: (row: any) => formatCurrency(row.price),
    },
  ];
```

```

    },
    {
      key: "stock",
      header: "Ø$Û\204Û\203Û\205Û\212Ø",
      render: (row: any) =>
        row.stock < 10 ? (
          <Badge variant="destructive">Û\205Û\206Ø@Û\201Ø¶ ({row.stock})</Badge>
        ) : (
          <Badge>{row.stock}</Badge>
        ),
    },
  ],
  {
    key: "actions",
    header: "Ø¥Ø¬Ø±Ø$Ø;Ø$Øª",
    render: (row: any) => (
      <div className="flex gap-2">
        <Button
          size="sm"
          variant="outline"
          onClick={() => {
            setEditingProduct(row);
            setShowForm(true);
          }}
        >
          <Pencil size={14} />
        </Button>
        <Button
          size="sm"
          variant="destructive"
          onClick={() => handleDelete(row.id)}
        >
          <Trash2 size={14} />
        </Button>
      </div>
    ),
  },
];

return (
  <div className="min-h-screen bg-gray-50">
    <Topbar />
    <div className="p-6">
      <div className="flex justify-between items-center mb-6">
        <h1 className="text-3xl font-bold">Ø¥Ø¬Ø$Ø±Ø@ Û\205Û\206ØªØ¬Ø$Øª Ø$Û\204Ø¬Û\205Û\204Ø@</h1>
        <Button
          onClick={() => {
            setEditingProduct(null);
            setShowForm(true);
          }}
        >
          <Plus size={18} className="ml-2" /> Ø¥Ø¶Ø$Û\201Ø@ Û\205Û\206ØªØ¬
        </Button>
      </div>
      <div className="bg-white p-6 rounded-2xl shadow-sm border border-gray-100">
        {products.length === 0 ? (
          <p className="text-center text-gray-500 py-10">
            Û\204Û\205 ØªÛ\202Û\205 Ø¬Ø¥Ø¶Ø$Û\201Ø@ Ø£Û\212 Û\205Û\206ØªØ¬Ø$Øª Ø¬Ø¹Ø¬.
            Ø$Ø¶Ø°Ø• Ø¹Û\204Û\211 Ø²Ø± Ø¥Ø¶Ø$Û\201Ø@ Û\205Û\206ØªØ¬ Û\204Û\204Ø¬Ø¬Ø;
          </p>
        ) : (
          <DataTable data={products} columns={columns} />
        )}
      </div>
    </div>
    <Modal
      open={showForm}
      onClose={() => setShowForm(false)}
      title={editingProduct ? "ØªØ¹Ø¬Û\212Û\204 Û\205Û\206ØªØ¬" : "Ø¥Ø¶Ø$Û\201Ø@ Û\205Û\206ØªØ¬ Ø¬Ø¬Û\212Ø¬"}
    />
  </div>
);

```

```

    >
    <ProductForm
      initData={editingProduct}
      onSuccess={() => {
        setShowForm(false);
        fetchProducts();
      }}
    />
  </Modal>
</div>
);
}

===== FILE: src/app/(dashboard)/wholesale/settings/page.tsx =====
"use client";
import { useState } from "react";
import { Topbar } from "@/components/dashboard/Topbar";
import { Button } from "@/components/ui/Button";
import { Input } from "@/components/ui/Input";
import { useToast } from "@/hooks/useToast";

export default function WholesaleSettingsPage() {
  const [loading, setLoading] = useState(false);
  const { showToast } = useToast();

  const handleSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    setLoading(true);
    // Û\207Û\206Ø$ Û\212ØªÛ\205 Ø¥Ø±Ø³Ø$Û\204 Ø$Û\204Ø¥Ø¹Ø-Ø$Ø-Ø$Øª Ø¥Û\204Û\211 Ø$Û\204
Û\200 API Ø$Û\204Û\205Ø@Øµµ Û\204Ø$Ø-Û\202Ø$Û\213
    showToast("ØªÛ\205 Ø-Û\201Ø. Ø$Û\204Ø¥Ø¹Ø-Ø$Ø-Ø$Øª Ø¨Û\206Ø¬Ø$Ø-", "success");
    setLoading(false);
  };

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="p-6">
        <div className="bg-white p-6 rounded-lg shadow max-w-lg">
          <h1 className="text-2xl font-bold mb-6">Ø¥Ø¹Ø-Ø$Ø-Ø$Øª Ø$Û\204Ø¬Û\205Û\204Ø@</h1>
          <form onSubmit={handleSubmit} className="space-y-4">
            <Input name="companyName" placeholder="Ø$Ø³Û\205 Ø$Û\204Ø´Ø±Û\203Ø@" />
            <Input name="commercialLicense" placeholder="Ø±Û\202Û\205 Ø$Û\204Ø³Ø¬Û\204 Ø$
Û\204ØªØ¬-Ø$Ø±Û\212" />
            <Input name="phone" placeholder="Ø±Û\202Û\205 Ø$Û\204Û\207Ø$ØªÛ\201 (Ø¨Ø$Û
\204ØµÛ\212Ø°Ø@ Ø$Û\204Ø¬Û\210Û\204Û\212Ø@)" />
            <Button type="submit" disabled={loading} className="w-full">
              {loading ? "Ø¬Ø$Ø±Û\215 Ø$Û\204Ø¬Û\201Ø,..." : "Ø¬Û\201Ø. Ø$Û\204Ø¥Ø¹Ø-Ø$Ø-
Ø$Øª"}
            </Button>
          </form>
        </div>
      </div>
    </div>
  );
}

```

```
===== FILE: src/app/(public)/about/page.tsx =====
import { Topbar } from "@/components/dashboard/Topbar";
import { Store, Truck, Users } from "lucide-react";

export default function AboutPage() {
  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="container mx-auto px-4 py-16 max-w-3xl text-center">
        <h1 className="text-4xl font-bold mb-6">ð¹Û\206 ð-Û\217Û\205Û\222Û\204Û\216ðªÛ
\220Û\212</h1>
        <p className="text-lq text-gray-600 leading-relaxed mb-10">
```

Ø-Ù\217Ù\205Ù\222Ù\204Ù\216ØªÙ\220Ù\212 Ù\207Ù\212 Ù\205Ù\206ØµØ Ø¹Ø±Ø\$Ù\202Ù
\212Ø Ø\205ØªÙ\203Ø\$Ù\205Ù\204Ø ØªÙ\207Ø-Ù\201 Ø¥Ù\204Ù\211 Ø±Ø¨Ø• ØªØ¬Ø\$Ø± Ø\$Ù\204ØªØ¬
Ø²Ø¡Ø Ø\205Ø¹ ØªØ¬Ø\$Ø± Ø\$Ù\204Ø¬Ù\205Ù\204Ø Ø\210Ø\$Ù\204Ù\205Ù\210Ø±Ø¬Ù\212Ù\206 Ø\$Ù
\204Ù\205Ø-Ù\204Ù\212Ù\212Ù\206 Ø¨Ø•Ø±Ù\212Ù\202Ø Ø³Ù\207Ù\204Ø Ø\210Ø±Ù\205Ù\206Ø.
</p>

```
<div className="grid grid-cols-1 md:grid-cols-3 gap-8 text-center">
  <div className="bg-white p-6 rounded-2xl shadow-sm">
    <Store className="mx-auto mb-4 text-primary" size={32} />
    <h3 className="font-bold text-lg mb-2">ØªØ¬Ø$Ø±Ø Ø$Ù\204Ø¬Ù\205Ù\204Ø</h3>
    <p className="text-gray-500 text-sm">ØªÙ\210Ù\201Ù\212Ø± Ø£Ù\201Ø¶Ù\204 Ø$Ù
\204Ø£Ø³Ø¹Ø$Ø± Ø¨Ù\204Ø$ Ù\210Ø³Ø•Ø$Ø¡.</p>
  </div>
  <div className="bg-white p-6 rounded-2xl shadow-sm">
    <Truck className="mx-auto mb-4 text-primary" size={32} />
    <h3 className="font-bold text-lg mb-2">ØªÙ\210ØµÙ\212Ù\204 Ù\205Ù\210Ø«Ù\210Ù
\202</h3>
    <p className="text-gray-500 text-sm">Ø'Ø¨Ù\203Ø Ø\205Ù\206Ø¬Ù\210Ø¨Ù\212 ØªÙ
\210ØµÙ\212Ù\204 Ù\205Ø±ØªØ¨Ø•Ø Ø\205Ø¨Ø$Ø'Ø±Ø.</p>
  </div>
  <div className="bg-white p-6 rounded-2xl shadow-sm">
    <Users className="mx-auto mb-4 text-primary" size={32} />
    <h3 className="font-bold text-lg mb-2">Ø¹Ù\204Ø$Ù\202Ø$Øª Ø±Ù\205Ù\206Ø</h3>
    <p className="text-gray-500 text-sm">Ø$Ù\204Ø¹Ø$Ù\204Ù\205 Ø$Ù\204Ù\205ØµØ±
Ù\212Ø-Ù\205Ù\212 Ø¨Ù\212Ø$Ù\206Ø$Øª Ø$Ù\204ØªØ¬Ø$Ø±.</p>
  </div>
</div>
</div>
</div>
);
}
```

===== FILE: src/app/(public)/checkout/page.tsx =====

```
"use client";
import { useState } from "react";
import { useRouter } from "next/navigation";
import { useCartStore } from "@/lib/stores/cartStore";
import { useToast } from "@/hooks/useToast";
import { Button } from "@/components/ui/Button";
import { Input } from "@/components/ui/Input";
import { Select } from "@/components/ui/Select";
import { formatCurrency } from "@/lib/utils/currency";
import { ArrowLeft, CreditCard, Wallet, MapPin, ShieldCheck, Lock } from "lucide-react";
import { Topbar } from "@/components/dashboard/Topbar";

export default function CheckoutPage() {
  const { items, getTotal, clearCart } = useCartStore();
  const { showToast } = useToast();
  const router = useRouter();
  const [loading, setLoading] = useState(false);
  const [address, setAddress] = useState("");
  const [phone, setPhone] = useState("");
  const [name, setName] = useState("");

  if (items.length === 0) {
    return (
      <div className="min-h-screen flex items-center justify-center bg-gray-50">
        <Topbar />
        <div className="text-center bg-white p-10 rounded-3xl shadow-sm">
          <div className="text-6xl mb-4">ð\237$¼</div>
          <h2 className="text-2xl font-bold text-gray-800 mb-2">Ù\204Ø$ Ù\212Ù\210Ø¬Ø¬ Ø•
Ù\204Ø¨ Ù\204Ù\204Ù\205ØªØ$Ø¨Ø¹Ø</h2>
          <Button onClick={() => router.push("/")}>ØªØµÙ\201Ø- Ø$Ù\204Ù\205ØªØ¬Ø±</Button>
        </div>
      </div>
    );
  }

  const handleSubmit = async (e: React.FormEvent) => {
```

```
e.preventDefault();
if (!address || !phone || !name) return showToast("ð\212ð±ð~ð\211 ð\205ð\204ð; ð~ð\205ð\212ð¹ ð$ð\204ð~ð\202ð\210ð\204", "error");
setLoading(true);
try {
  const res = await fetch("/api/orders", {
    method: "POST",
    headers: { "Content-Type": "application/json" },
    body: JSON.stringify({
      items: items.map(i => ({ productId: i.productId, quantity: i.quantity, wholesalerId: i.wholesalerId, price: i.price })),
      address, phone, name
    })),
  });
  const data = await res.json();
  if (!res.ok) throw new Error(data.error || "ð-ð~ð« ððð•ðf");
  clearCart();
  showToast("ðªð\205 ðªð£ð\203ð\212ð~ ð$ð\204ð•ð\204ð~!", "success");
  router.push("/dashboard/retailer/orders");
} catch (error: any) {
  showToast(error.message, "error");
} finally {
  setLoading(false);
}
};

return (
  <div dir="rtl" className="min-h-screen bg-gray-50 py-10 px-4">
    <Topbar />
    <div className="max-w-6xl mx-auto pt-10">
      <button onClick={() => router.back()} className="flex items-center gap-2 text-gray-500 mb-8 hover:text-primary transition-colors">
        <ArrowLeft size={18} /> ð$ð\204ð¹ð\210ð~ðð ð\204ð\204ð³ð\204ðð
      </button>
      <h1 className="text-4xl font-extrabold text-gray-900 mb-10">ð¥ðªð\205ð$ð\205 ð¹ð\205ð\204ð\212ðð ð$ð\204ð'ð±ð$ð;</h1>
      <form onSubmit={handleSubmit} className="grid grid-cols-1 lg:grid-cols-3 gap-8">
        <div className="lg:col-span-2 space-y-6">
          <div className="bg-white rounded-2xl border border-gray-100 shadow-sm p-6">
            <h2 className="text-xl font-bold mb-6 flex items-center gap-3 text-gray-800"><MapPin className="text-primary" size={20} /> ð¹ð\206ð\210ð$ð\206 ð$ð\204ðªð\210ðµð\212ð\204</h2>
            <div className="grid grid-cols-1 md:grid-cols-2 gap-4">
              <Input name="name" placeholder="ð$ð\204ð$ð³ð\205 ð$ð\204ð\203ð$ð\205ð\204" value={name} onChange={(e) => setName(e.target.value)} required />
              <Input name="phone" placeholder="ð±ð\202ð\205 ð$ð\204ð\207ð$ðªð\201" value={phone} onChange={(e) => setPhone(e.target.value)} required />
              <div className="md:col-span-2"><Input name="address" placeholder="ð$ð\204ð¹ð\206ð\210ð$ð\206 ð$ð\204ð\203ð$ð\205ð\204" value={address} onChange={(e) => setAddress(e.target.value)} required /></div>
              <div className="md:col-span-2">
                <Select name="governorate" defaultValue="ð~ð°ð~ð$ð~">
                  <option value="ð~ð°ð~ð$ð~">ð~ð°ð~ð$ð~</option>
                  <option value="ð$ð\204ð~ðµð±ðð">ð$ð\204ð~ðµð±ðð</option>
                  <option value="ð£ð±ð~ð\212ð\204">ð£ð±ð~ð\212ð\204</option>
                </Select>
              </div>
            </div>
            <div className="bg-white rounded-2xl border border-gray-100 shadow-sm p-6">
              <h2 className="text-xl font-bold mb-6 flex items-center gap-3 text-gray-800"><CreditCard className="text-primary" size={20} /> ð•ð±ð\212ð\202ðð ð$ð\204ð~ð\201ð¹</h2>
              <div className="space-y-3">
                <label className="flex items-center gap-4 border-2 border-primary/50 bg-primary/5 rounded-xl p-4 cursor-pointer">
                  <input type="radio" name="payment" defaultChecked className="accent-primary scale-125" />
                  <Wallet size={24} className="text-primary" />
                  <span className="flex-1 font-semibold">ð$ð\204ð~ð\201ð¹ ð¹ð\206ð~ ð$ð
```

```
\2040$0³0ªÛ\2040$Û\205</span>
    </label>
  </div>
</div>
</div>
<div className="lg:col-span-1">
  <div className="bg-white rounded-2xl border border-gray-100 shadow-sm p-6 sti
cky top-24">
    <h2 className="text-xl font-bold mb-6 border-b pb-4">Û\205Û\204000µ 0$Û\204
0ªÛ\2040ª</h2>
    <div className="flex justify-between items-center mb-6"><span className="te
xt-lg font-bold">0$Û\2040¥0ªÛ\2050$Û\204Û\212</span><span className="text-2xl font-extrab
old text-primary">{formatCurrency(getTotal())}</span></div>
    <Button type="submit" size="lg" disabled={loading} className="w-full justif
y-center gap-2"><Lock size={18} /> {loading ? "0ª0$0±Û\215 0$Û\2040ª0ªÛ\203Û\2120ª"... :
"0ª0ªÛ\203Û\2120ª 0$Û\2040ªÛ\2040ª"}</Button>
    <div className="flex items-center justify-center gap-2 mt-4 text-xs text-gr
ay-400"><ShieldCheck size={14} className="text-emerald-500" /> 0ªÛ\2120$Û\2060$0ªÛ\203 Û
\2050ªÛ\205Û\2120ª</div>
  </div>
</div>
</form>
</div>
</div>
);
}

===== FILE: src/app/(public)/contact/page.tsx =====
"use client";
import { useState } from "react";
import { Topbar } from "@/components/dashboard/Topbar";
import { Button } from "@/components/ui/Button";
import { Input } from "@/components/ui/Input";
import { Textarea } from "@/components/ui/Textarea";
import { useToast } from "@/hooks/useToast";

export default function ContactPage() {
  const [loading, setLoading] = useState(false);
  const { showToast } = useToast();

  const handleSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    setLoading(true);
    showToast("0ªÛ\205 0¥0±0³0$Û\204 0±0³0$Û\2040ªÛ\203 0ªÛ\2060ª0$0ª!", "success");
    setLoading(false);
  };

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="container mx-auto px-4 py-16 max-w-lg">
        <h1 className="text-4xl font-bold mb-6 text-center">0$0ª0µÛ\204 0ªÛ\2060$</h1>
        <form onSubmit={handleSubmit} className="space-y-4 bg-white p-6 rounded-2xl shado
w-sm border border-gray-100">
          <Input name="name" placeholder="0$Û\2040$0³Û\205" required />
          <Input name="email" type="email" placeholder="0$Û\2040ª0ªÛ\2120ª 0$Û\2040¥Û\204
Û\2030ª0ªÛ\210Û\206Û\212" required />
          <Textarea name="message" placeholder="0±0³0$Û\2040ªÛ\203..." rows={5} required
/>
          <Button type="submit" disabled={loading} className="w-full">
            {loading ? "0ª0$0±Û\215 0$Û\2040¥0±0³0$Û\204..." : "0¥0±0³0$Û\204 0$Û\2040±0³
0$Û\2040ª"}
          </Button>
        </form>
      </div>
    </div>
  );
}
```

===== FILE: src/app/(public)/offers/page.tsx =====

```

"use client";
import { useEffect, useState, useCallback } from "react";
import { Topbar } from "@/components/dashboard/Topbar";
import { Badge } from "@/components/ui/Badge";
import { useToast } from "@/hooks/useToast";
import { Tag, Percent } from "lucide-react";

export default function OffersPage() {
  const [offers, setOffers] = useState([]);
  const { showToast } = useToast();

  const fetchOffers = useCallback(async () => {
    try {
      const res = await fetch("/api/offers");
      if (res.ok) setOffers(await res.json());
    } catch (error) {
      showToast("ðŸ’¥ðŸ’¥ðŸ’¥ Û\201Û\212 ð-Û\204ð" ð$Û\204ð¹ð±Û\210ð¶", "error");
    }
  }, [showToast]);

  useEffect(() => { fetchOffers(); }, [fetchOffers]);

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="container mx-auto py-12 px-4">
        <h1 className="text-3xl font-bold mb-8">ð$Û\204ð¹ð±Û\210ð¶ ð$Û\204ðªð±Û\210Û\212ð-Û\212ðð</h1>
        {offers.length === 0 ? (
          <div className="bg-white p-10 text-center text-gray-500 border border-dashed border-gray-300 rounded-xl">
            <Tag className="mx-auto mb-4 text-gray-300" size={48} />
            Û\204ð$ ðªÛ\210ð-ð- ð¹ð±Û\210ð¶ Û\205ðªð$ð-ðð ð-ð$Û\204Û\212ð$Û\213.
          </div>
        ) : (
          <div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-3 gap-6">
            {offers.map((offer: any) => (
              <div key={offer.id} className="bg-white p-6 rounded-2xl shadow-sm border border-gray-100">
                <div className="flex items-center gap-2 mb-4"><Percent className="text-primary" size={24} /><h3 className="font-bold text-lg">{offer.title}</h3></div>
                <p className="text-gray-600 mb-4">{offer.description}</p>
                <div className="flex items-center justify-between"><Badge variant="secondary">{offer.discount_percent}% ðððµÛ\205</Badge><span className="text-sm text-gray-500">ð-ðªÛ\211 {new Date(offer.end_date).toLocaleDateString('ar-IQ')}</span></div>
              </div>
            ))}
          </div>
        )}
      </div>
    </div>
  );
}

```

===== FILE: src/app/(public)/products/[slug]/page.tsx =====

```

"use client";
import { useEffect, useState } from "react";
import { useParams } from "next/navigation";
import { useCartStore } from "@/lib/stores/cartStore";
import { useToast } from "@/hooks/useToast";
import { Button } from "@/components/ui/Button";
import { formatCurrency } from "@/lib/utls/currency";
import { Minus, Plus, ShoppingCart } from "lucide-react";
import { Topbar } from "@/components/dashboard/Topbar";

export default function ProductPage() {
  const params = useParams();
  const slug = Array.isArray(params.slug) ? params.slug[0] : params.slug;
  const [quantity, setQuantity] = useState(1);
  const addItem = useCartStore((state) => state.addItem);
  const { showToast } = useToast();

```

```

const product = {
  id: slug || "unknown",
  wholesalerId: "demo-wholesaler",
  name: "ð³ð$ð¹ð  ð°ù\203ù\212ð ù\201ð$ðð±ð",
  price: 85000,
  description: "ð³ð$ð¹ð  ð°ù\203ù\212ð ð°ù\205ð²ð$ù\212ð$ ù\205ðªð•ù\210ð±ð.",
};

const handleAddToCart = () => {
  addItem({ productId: product.id, wholesalerId: product.wholesalerId, name: product.name, price: product.price, quantity });
  showToast("ðªù\205ðª ð$ù\204ð¥ð¹ð$ù\201ð  ð¥ù\204ù\211 ð$ù\204ð³ù\204ð@!", "success");
};

return (
  <div className="min-h-screen bg-gray-50">
    <Topbar />
    <div className="max-w-4xl mx-auto pt-10 pb-20 px-4">
      <div className="bg-white rounded-3xl shadow-xl border border-gray-100 overflow-hidden grid grid-cols-1 md:grid-cols-2 gap-10 p-8">
        <div className="aspect-square bg-gray-100 rounded-2xl flex items-center justify-center text-9xl">â\214\232</div>
        <div className="flex flex-col justify-center">
          <h1 className="text-3xl font-extrabold mb-4">{product.name}</h1>
          <p className="text-gray-600 mb-6">{product.description}</p>
          <div className="text-4xl font-black text-primary mb-8">{formatCurrency(product.price)}</div>
          <div className="flex items-center gap-6 mb-8">
            <div className="flex items-center border-2 border-gray-200 rounded-full">
              <button onClick={() => setQuantity(Math.max(1, quantity - 1))} className="p-3"><Minus size={16} /></button>
              <span className="w-12 text-center font-bold">{quantity}</span>
              <button onClick={() => setQuantity(quantity + 1)} className="p-3"><Plus size={16} /></button>
            </div>
            <div>
              <Button onClick={handleAddToCart} size="lg" className="gap-2"><ShoppingCart size={20} /> ð£ð¹ù\201 ð¥ù\204ù\211 ð$ù\204ð³ù\204ð@</Button>
            </div>
          </div>
        </div>
      </div>
    </div>
  );
}

===== FILE: src/app/(public)/products/page.tsx =====
import { Topbar } from "@/components/dashboard/Topbar";
import { RequestCard } from "@/components/shared/RequestCard";
import { productService } from "@/lib/services/productService";
import { Package, Search } from "lucide-react";

export default async function ProductsPage() {
  // ð-ù\204ð° ð-ù\205ù\212ð¹ ð$ù\204ù\205ù\206ðªð¬ð$ðª ð$ù\204ù\206ð°ð•ð
  let products: any[] = [];
  try {
    products = await productService.getAllProducts();
  } catch (error) {
    console.error("Error fetching products:", error);
  }

  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="container mx-auto py-12 px-4">
        <h1 className="text-3xl font-bold mb-8">ð-ù\205ù\212ð¹ ð$ù\204ù\205ù\206ðªð¬ð$ðª<
/h1>

        {/* ð°ð±ù\212ð• ð°ð-ð« ð°³ù\212ð• */}

```

```

    <div className="relative mb-8">
      <Search className="absolute right-3 top-3 text-gray-400" size={20} />
      <input type="text" placeholder="ð$ð`ð-ð« ð¹Û\206 Û\205Û\206ðªð¬..." className="w-full h-12 rounded-xl border border-gray-200 pr-10 pl-4 focus:outline-none focus:ring-2 focus:ring-primary" />
    </div>

    {products.length === 0 ? (
      <div className="bg-white p-10 text-center text-gray-500 border border-dashed border-gray-300 rounded-xl">
        <Package className="mx-auto mb-4 text-gray-300" size={48} />
        Û\204ð$ ðªÛ\210ð¬ð¬ Û\205Û\206ðªð¬ð$ðª Û\205ðªð$ð¬ðð ð¬ð$Û\204Û\212ð$Û\213.
      </div>
    ) : (
      <div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-4 gap-6">
        {products.map((product) => (
          <RequestCard key={product.id} product={product} />
        ))}
      </div>
    )}
  </div>
</div>
);
}

```

===== FILE: src/app/(public)/store/[slug]/page.tsx =====

```

import { createClient } from "@lib/supabase/server";
import { RequestCard } from '@components/shared/RequestCard';
import { Topbar } from "@components/dashboard/Topbar";
import { notFound } from "next/navigation";

export default async function StorePage({ params }: { params: Promise<{ slug: string }> }) {
  const { slug } = await params;
  const supabase = await createClient(); // ðªð¹ð¬Û\212Û\204 Û\205Û\207Û\205 ð¬ð¬ð$Û\213
  const { data: store } = await supabase.from("stores").select("*").eq("slug", slug).single();

  if (!store) notFound();

  const { data: products } = await supabase.from("products").select("*").eq("store_id", store.id);

  return (
    <div className="container mx-auto py-12">
      <Topbar />
      <h1 className="text-3xl font-bold mb-8">{store.name}</h1>
      <div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-4 gap-6">
        {products?.map((product) => (
          <RequestCard key={product.id} product={product} />
        ))}
      </div>
    </div>
  );
}

```

===== FILE: src/app/(public)/terms/page.tsx =====

```

import { Topbar } from "@components/dashboard/Topbar";

export default function TermsPage() {
  return (
    <div className="min-h-screen bg-gray-50">
      <Topbar />
      <div className="container mx-auto py-12 px-4 max-w-3xl">
        <h1 className="text-4xl font-bold mb-6">ð$Û\204ð¬ð±Û\210ð• Û\210ð$Û\204ð£ð¬Û\203ð$Û\205</h1>
        <div className="space-y-6 text-gray-700 leading-relaxed">
          <p>ð¬ð$ð³ðªððð¬ð$Û\205Û\203 Û\205Û\206ðµðð ð¬Û\217Û\205Û\222Û\204Û\216ðªÛ\220Û\212ð\214 Û\201ð¥Û\206Û\203 ðªÛ\210ð$Û\201Û\202 ð¹Û\204Û\211 ð¬Û\205Û\212ð¹ ð$Û\204ð¬ð±Û\210ð• Û\210ð$Û\204ð£ð¬Û\203ð$Û\205 ð$Û\204ðªð$Û\204Û\212ðð:</p>

```

```
<h2 className="text-2xl font-bold">1. Ø$Û\204Ø$Û\204ØªØ²Ø$Û\205 Ø"Ø$Û\204Û\202Û\210Ø$Û\206Û\212Û\206</h2>
<p>Û\212Ø-Ø" Ø¹Û\204Û\211 Ø-Û\205Û\212Ø¹ Ø$Û\204ØªØ-Ø$Ø± Û\210Ø$Û\204Û\205Û\206
Ø-Û\210Ø"Û\212Û\206 Ø$Û\204Ø$Û\204ØªØ²Ø$Û\205 Ø"Ø$Û\204Û\202Û\210Ø$Û\206Û\212Û\206 Ø$Û
\204Ø¹Ø±Ø$Û\202Û\212Ø© Ø$Û\204Û\205Ø¹Û\205Û\210Û\204 Ø"Û\207Ø$.</p>
<h2 className="text-2xl font-bold">2. Ø$Û\204Ø-Ø³Ø$Ø"Ø$Øª Û\210Ø$Û\204Û\205Ø³Øª
Û\210Û\204Û\212Ø©</h2>
<p>ØfÛ\206Øª Û\205Ø³ØªÛ\210Û\204 Û\205Ø³ØªÛ\210Û\204Û\212Ø© Û\203Ø$Û\205Û\204Ø©
Ø¹Û\206 Ø$Û\204Ø-Û\201Ø$Ø, Ø¹Û\204Û\211 Ø³Ø±Û\212Ø© Ø"Û\212Ø$Û\206Ø$Øª Ø-Ø³Ø$Ø"Û\203.</p>
<h2 className="text-2xl font-bold">3. Ø$Û\204Ø¹Û\205Û\210Û\204Ø$Øª Û\210Ø$Û\204
Ø±Ø³Û\210Û\205</h2>
<p>ØªØ-ØªÛ\201Ø, Ø$Û\204Û\205Û\206ØµØ© Ø-Ø-Û\202Û\207Ø$ Û\201Û\212 Ø$Û\202ØªØ•Ø
$Ø¹ Û\206Ø³Ø"Ø© Ø¹Û\205Û\210Û\204Ø© Û\205Ø-Ø-Ø-Ø© Û\205Û\206 Û\203Û\204 Ø¹Û\205Û\204Û\212
Ø© Ø"Û\212Ø¹.</p>
<h2 className="text-2xl font-bold">4. Ø$Û\204Û\206Ø²Ø$Ø¹Ø$Øª</h2>
<p>Û\212Ø-Û\202 Û\204Ø¥Ø-Ø$Ø±Ø© Ø$Û\204Û\205Û\206ØµØ© Ø$Û\204ØªØ-Ø©Û\204 Û\204Ø
-Û\204 Ø$Û\204Û\206Ø²Ø$Ø¹ Ø"Ø¹Û\203Û\204 Ø¹Ø$Ø-Û\204.</p>
</div>
</div>
</div>
);
}
```

===== FILE: src/app/(root)/page.tsx =====

```
// This file is intentionally unused.
// The root page is served by src/app/page.tsx
// This file exists due to sandbox constraints (files cannot be deleted).
export { default } from "@app/page";
```

===== FILE: src/app/api/addresses/index.ts =====

===== FILE: src/app/api/addresses/route.ts =====

```
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';
import { addressSchema } from '@lib/validations/address.schema';
import { addressService } from '@lib/services/addressService';

export async function GET() {
  try {
    const data = await addressService.getMyAddresses();
    return NextResponse.json(data);
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}
```

```
export async function POST(req: Request) {
  try {
    const body = await req.json();
    const parsed = addressSchema.parse(body);
    const data = await addressService.addAddress(parsed);
    return NextResponse.json(data, { status: 201 });
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 400 });
  }
}
```

===== FILE: src/app/api/admin/[di]/route.ts =====

```
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';

export async function PATCH(req: Request, { params }: { params: Promise<{ di: string }> }) {
  const supabase = await createClient();
  const { data: { user } } = await supabase.auth.getUser();
  if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

  const { data: adminCheck } = await supabase.from('users').select('role').eq('id', user.id).single();
```

```
if (adminCheck?.role !== 'admin') return NextResponse.json({ error: 'Forbidden' }, { status: 403 });

const { di } = await params;
const body = await req.json();
const { data, error } = await supabase.from('users').update(body).eq('id', di).select().single();
if (error) return NextResponse.json({ error: error.message }, { status: 500 });
return NextResponse.json(data);
}
```

===== FILE: src/app/api/admin/audit-logs/route.ts =====

```
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';

export async function GET() {
  try {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

    // Ø$Ù\204ØªØ-Ù\202Ù\202 Ù\205Ù\206 ØµÙ\204Ø$Ø-Ù\212Ø$Øª Ø$Ù\204Ø£Ø-Ù\205Ù\206
    const { data: adminCheck } = await supabase.from('users').select('role').eq('id', user.id).single();
    if (adminCheck?.role !== 'admin') return NextResponse.json({ error: 'Forbidden' }, { status: 403 });

    const { data, error } = await supabase
      .from('audit_logs')
      .select('*', users(name))
      .order('created_at', { ascending: false });

    if (error) return NextResponse.json({ error: error.message }, { status: 500 });
    return NextResponse.json(data);
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}
```

===== FILE: src/app/api/admin/payments/route.ts =====

```
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';

export async function GET() {
  try {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

    const { data: adminCheck } = await supabase.from('users').select('role').eq('id', user.id).single();
    if (adminCheck?.role !== 'admin') return NextResponse.json({ error: 'Forbidden' }, { status: 403 });

    const { data, error } = await supabase
      .from('payments')
      .select('*')
      .order('created_at', { ascending: false });

    if (error) return NextResponse.json({ error: error.message }, { status: 500 });
    return NextResponse.json(data);
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}
```

===== FILE: src/app/api/admin/users/[id]/route.ts =====

```
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';
```

```
export async function PATCH(req: Request, { params }: { params: Promise<{ id: string }> }) {
  try {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

    const { data: adminCheck } = await supabase.from('users').select('role').eq('id', user.id).single();
    if (adminCheck?.role !== 'admin') return NextResponse.json({ error: 'Forbidden' }, { status: 403 });

    const { id } = await params;
    const body = await req.json();
    const { data, error } = await supabase.from('users').update(body).eq('id', id).select().single();
    if (error) return NextResponse.json({ error: error.message }, { status: 500 });

    return NextResponse.json(data);
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}
```

===== FILE: src/app/api/admin/users/route.ts =====

```
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';

export async function GET() {
  try {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

    // 0$0`2040^0-0`0`2020`202 0`2050`206 0000`206 0$0`2040`2050^0^000-0`205 0$0`2040-0$0`
    \2040`212 0`2070`210 0000-0`2050`206
    const { data: adminCheck } = await supabase.from('users').select('role').eq('id', user.id).single();
    if (adminCheck?.role !== 'admin') return NextResponse.json({ error: 'Forbidden' }, { status: 403 });

    const { data, error } = await supabase.from('users').select('*').order('created_at', { ascending: false });
    if (error) return NextResponse.json({ error: error.message }, { status: 500 });

    return NextResponse.json(data);
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}
```

===== FILE: src/app/api/auth/login/route.ts =====

```
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';
import { loginSchema } from '@lib/validations/auth.schema';
import { authService } from '@lib/services/authService';

export async function POST(req: Request) {
  try {
    const body = await req.json();
    const parsed = loginSchema.parse(body);

    // 0$0^0^000-0$0`205 0$0`2040000-0`20500 0$0`2040^0`2030`21200 0`2040^0-0`0`2120- 0$0`
    \2040`0000`2120- 0000`210 0$0`2040`2070$0^0`201
    const data = await authService.login(parsed.identifier, parsed.password);

    return NextResponse.json({ user: data.user }, { status: 200 });
  } catch (error: any) {
    return NextResponse.json({ error: error.message || '0`0`2120$0`2060$0^ 0^0`2120± 000$
    0`2040-00' }, { status: 400 });
  }
}
```

```
}
}

===== FILE: src/app/api/auth/phone/route.ts =====
import { NextResponse } from 'next/server';
import { phoneAuthService } from '@lib/services/phoneAuthService';

export async function POST(req: Request) {
  try {
    const body = await req.json();
    const { action, phone, token } = body;

    if (action === 'send') {
      await phoneAuthService.sendOtp(phone);
      return NextResponse.json({ success: true, message: 'ðªÙ\205 ð¥ð±ð³ð$Ù\204 ð±Ù\205ð²
ð$Ù\204ðªð-Ù\202Ù\202' });
    }

    if (action === 'verify') {
      const data = await phoneAuthService.verifyOtp(phone, token);
      return NextResponse.json({ user: data.user });
    }

    return NextResponse.json({ error: 'Action not found' }, { status: 400 });
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 400 });
  }
}

===== FILE: src/app/api/auth/register/route.ts =====
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';
import { registerSchema } from '@lib/validations/auth.schema';

export async function POST(req: Request) {
  try {
    const body = await req.json();
    const parsed = registerSchema.parse(body);
    const supabase = await createClient();

    const { data, error } = await supabase.auth.signUp({
      email: parsed.email,
      password: parsed.password,
      options: {
        data: { name: parsed.name, role: parsed.role },
      },
    });

    if (error) return NextResponse.json({ error: error.message }, { status: 400 });

    return NextResponse.json({ user: data.user }, { status: 201 });
  } catch (error) {
    return NextResponse.json({ error: 'ðªÙ\212ð$Ù\206ð$ðª ðªÙ\212ð± ðµð$Ù\204ð-ð©' }, { s
tatus: 400 });
  }
}

===== FILE: src/app/api/chat/index.ts =====

===== FILE: src/app/api/chat/route.ts =====
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';
import { chatService } from '@lib/services/chatService';

export async function GET(req: Request) {
  try {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });
```

```
const { searchParams } = new URL(req.url);
const userId = searchParams.get('userId');

// 0x0°0$ 0^Û\205 0^Û\2050±Û\2120± userId0\214 Û\2060-Û\2040" 0$Û\204Û\2050-0$0-0«0©
0"Û\212Û\206 0$Û\2040•0±Û\201Û\212Û\206
if (userId) {
  const messages = await chatService.getConversation(userId);
  return NextResponse.json(messages);
}

// 0x0°0$ Û\204Û\205 Û\2120^Û\205 0^Û\2050±Û\2120± userId0\214 Û\2060-Û\2040" Û\2020$
0|Û\2050© 0-Û\2070$0^ 0$Û\2040$0^0μ0$Û\204 0$Û\204Û\2050-0^Û\205Û\2040©
const { data: contacts, error } = await supabase
  .from('users')
  .select('id, name, role')
  .neq('id', user.id)
  .order('name', { ascending: true });

if (error) return NextResponse.json({ error: error.message }, { status: 500 });
return NextResponse.json(contacts);
} catch (error: any) {
  return NextResponse.json({ error: error.message }, { status: 500 });
}
}

export async function POST(req: Request) {
  try {
    const { receiverId, message } = await req.json();
    const chat = await chatService.sendMessage(receiverId, message);
    return NextResponse.json(chat, { status: 201 });
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 400 });
  }
}

===== FILE: src/app/api/commissions/calculate/route.ts =====
import { NextResponse } from 'next/server';
import { commissionService } from '@lib/services/commissionService';

export async function POST(req: Request) {
  try {
    const { orderTotal } = await req.json();
    const commission = await commissionService.calculateCommission(orderTotal);
    return NextResponse.json({ commission }, { status: 200 });
  } catch (error) {
    return NextResponse.json({ error: '0@0•0£ Û\201Û\212 0$Û\2040-0³0$0"" }, { status: 40
0 });
  }
}

===== FILE: src/app/api/commissions/route.ts =====
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';

export async function GET() {
  const supabase = await createClient(); // 0^0¹0-Û\212Û\204
  const { data, error } = await supabase.from('commissions').select('*');
  if (error) return NextResponse.json({ error: error.message }, { status: 500 });
  return NextResponse.json(data);
}

===== FILE: src/app/api/coupons/route.ts =====
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';
import { couponService } from '@lib/services/couponService';

export async function GET() {
  try {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
```

```
    if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

    const { data: adminCheck } = await supabase.from('users').select('role').eq('id', user.id).single();
    if (adminCheck?.role !== 'admin') return NextResponse.json({ error: 'Forbidden' }, { status: 403 });

    const coupons = await couponService.getAllCoupons();
    return NextResponse.json(coupons);
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}

export async function POST(req: Request) {
  try {
    const { code, discount_percent, max_uses } = await req.json();
    const coupon = await couponService.createCoupon(code, discount_percent, max_uses);
    return NextResponse.json(coupon, { status: 201 });
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}

===== FILE: src/app/api/coupons/validate/route.ts =====
import { NextResponse } from 'next/server';
import { couponService } from '@lib/services/couponService';

export async function POST(req: Request) {
  try {
    const { code } = await req.json();
    if (!code) return NextResponse.json({ error: 'Code required' }, { status: 400 });

    const coupon = await couponService.validateCoupon(code);
    return NextResponse.json({ valid: true, discount_percent: coupon.discount_percent, coupon });
  } catch (error: any) {
    return NextResponse.json({ valid: false, error: error.message }, { status: 400 });
  }
}

===== FILE: src/app/api/delivery/tasks/route.ts =====
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';

export async function GET() {
  try {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

    const { data, error } = await supabase
      .from("orders")
      .select("*")
      .eq("delivery_id", user.id)
      .or("status.eq.processing,status.eq.shipped")
      .order("created_at", { ascending: false });

    if (error) return NextResponse.json({ error: error.message }, { status: 500 });
    return NextResponse.json(data);
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}

export async function PATCH(req: Request) {
  try {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });
```

```

const { id, status } = await req.json();
const { error } = await supabase
  .from("orders")
  .update({ status })
  .eq("id", id);

if (error) return NextResponse.json({ error: error.message }, { status: 500 });
return NextResponse.json({ success: true });
} catch (error: any) {
  return NextResponse.json({ error: error.message }, { status: 500 });
}
}

===== FILE: src/app/api/matching/route.ts =====
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';

export async function GET() {
  const supabase = await createClient(); // ØªØ¹Ø²Û\212Û\204
  const { data, error } = await supabase.from('matches').select('*');
  if (error) return NextResponse.json({ error: error.message }, { status: 500 });
  return NextResponse.json(data);
}

===== FILE: src/app/api/notifications/route.ts =====
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';
import { notificationService } from '@lib/services/notificationService';

export async function GET() {
  const supabase = await createClient(); // ØªØ¹Ø²Û\212Û\204
  const { data: { user } } = await supabase.auth.getUser();
  if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

  const { data, error } = await supabase.from('notifications').select('*').eq('user_id', user.id).order('created_at', { ascending: false });
  if (error) return NextResponse.json({ error: error.message }, { status: 500 });
  return NextResponse.json(data);
}

export async function POST(req: Request) {
  try {
    const body = await req.json();
    await notificationService.notify(body);
    return NextResponse.json({ success: true }, { status: 201 });
  } catch (error) {
    return NextResponse.json({ error: 'Û\201Ø²Û\204 Ø¥Ø±Ø³Ø$Û\204 Ø$Û\204Ø¥Ø²Ø¹Ø$Ø±' }, { status: 400 });
  }
}

===== FILE: src/app/api/offers/index.ts =====

===== FILE: src/app/api/offers/route.ts =====
import { NextResponse } from 'next/server';
import { offerService } from '@lib/services/offerService';

export async function GET() {
  try {
    const data = await offerService.getActiveOffers();
    return NextResponse.json(data);
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}

===== FILE: src/app/api/orders/[id]/route.ts =====
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';

```

```
export async function PATCH(req: Request, { params }: { params: Promise<{ id: string }> }) {
  try {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

    const { id } = await params;
    const body = await req.json();
    const { status } = body;

    const { data, error } = await supabase
      .from('orders')
      .update({ status })
      .eq('id', id)
      .select()
      .single();

    if (error) throw new Error(error.message);
    return NextResponse.json(data);
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 400 });
  }
}
```

```
===== FILE: src/app/api/orders/route.ts =====
```

```
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';
import { retailerService } from '@lib/services/retailerService';
import { commissionService } from '@lib/services/commissionService';
import { notificationService } from '@lib/services/notificationService';
import { couponService } from '@lib/services/couponService';
import { createOrderSchema } from '@lib/validations/order.schema';
```

```
export async function POST(req: Request) {
  try {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return NextResponse.json({ error: 'ð\212ð¬ð" ðªð³ð¬ð\212ð\204 ð$ð\204ð¬ðð\210ð\204 ð£ð\210ð\204ð$ð\213' }, { status: 401 });

    const body = await req.json();
    const parsed = createOrderSchema.parse(body);

    // ðªð•ð¬ð\212ð\202 ð\203ð\210ð¬ ð$ð\204ðððµð\205 ð¥ð\206 ð\210ð¬ð¬
    let discountPercent = 0;
    let appliedCouponId = null;
    if (parsed.coupon_code) {
      const coupon = await couponService.validateCoupon(parsed.coupon_code);
      discountPercent = coupon.discount_percent;
      appliedCouponId = coupon.id;
      await couponService.incrementUsage(coupon.id);
    }

    // ðªð¬ð\205ð\212ð¹ ð$ð\204ð¹ð\206ð$ðµð± ð¬ð³ð¬ ðªð$ð¬ð± ð$ð\204ð¬ð\205ð\204ðð
    const groupedItems: { [wholesalerId: string]: typeof parsed.items } = {};
    for (const item of parsed.items) {
      if (!groupedItems[item.wholesalerId]) groupedItems[item.wholesalerId] = [];
      groupedItems[item.wholesalerId].push(item);
    }

    const retailerId = user.id;
    const createdOrders = [];

    for (const [wholesalerId, items] of Object.entries(groupedItems)) {
      const subtotal = items.reduce((sum, item) => sum + (item.price * item.quantity), 0)
      ;

      // ðªð•ð¬ð\212ð\202 ð$ð\204ðððµð\205 ð¹ð\204ð\211 ð¥ð¬ð\205ð$ð\204ð\212 ð\203ð\204
ð¬ð\205ð\204ðð
    }
  }
}
```

```
const total = subtotal - (subtotal * discountPercent) / 100;

const order = await retailerService.createOrder({
  user_id: retailerId,
  wholesaler_id: wholesalerId,
  items: items,
  total: total,
  address: parsed.address,
});

await commissionService.createCommission(order.id, retailerId, total);
await notificationService.notify({
  userId: wholesalerId,
  type: "order",
  title: "ð•Û\2040" ð-ð-Û\2120- Û\205Û\206 ðªð$ð-ð± ðªð-ð²ð!ð@!",
  message: `ð•Û\2040" ð-Û\202Û\212Û\205ð@ ${total.toLocaleString()} ð-.ð¹ ð-ð$Û\206
ðªð,ð$ð± Û\205ð¹ð$Û\204ð-ðªÛ\203.` ,
});

createdOrders.push(order);
}

return NextResponse.json({ success: true, orders: createdOrders }, { status: 201 });
} catch (error: any) {
  return NextResponse.json({ error: error.message || 'Û\201ð-Û\204 ð$Û\206ð-ð$ð; ð$Û
\204ð•Û\2040"' }, { status: 400 });
}
}

===== FILE: src/app/api/payments/route.ts =====
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';
import { paymentService } from '@lib/services/paymentService';

export async function POST(req: Request) {
  try {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

    const { orderId, amount, gateway } = await req.json();
    if (!orderId || !amount) return NextResponse.json({ error: 'Missing data' }, { status
: 400 });

    // ð$Û\206ð-ð$ð; ð³ð-Û\204 ð$Û\204ð-Û\201ð¹
    const payment = await paymentService.createPayment(orderId, amount, gateway || "cod")
;

    // Û\205Û\204ð$ð-ð,ð@: Û\207Û\206ð$ ð³Û\206ð¹Û\212Û\201 Û\205Û\206ð•Û\202 ð$Û\206ð-ð$
ð; ð±ð$ð-ð• ð-Û\210ð$ð-ð@ SindiPay Û\204ð$ð-ð²ð$Û\213 ð¹Û\206ð- ðªÛ\210Û\201ð± ð$Û\204
Û\205Û\201ð$ðªÛ\212ð-
    // ð-ð$Û\204Û\212ð$Û\213ð\214 Û\206ð¹Û\212ð- success Û\205ð¹ ð-Û\212ð$Û\206ð$ðª ð$Û
\204ð-Û\201ð¹
    return NextResponse.json({ success: true, payment, gateway: gateway || "cod" }, { sta
tus: 201 });
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}

===== FILE: src/app/api/payments/webhook/route.ts =====
import { NextResponse } from 'next/server';
import { paymentService } from '@lib/services/paymentService';

export async function POST(req: Request) {
  try {
    const body = await req.json();
    const { paymentId, status, transactionId } = body;

    if (!paymentId || !status) return NextResponse.json({ error: 'Missing data' }, { stat
```

```
us: 400 });
```

```
    const payment = await paymentService.handleWebhook(paymentId, status, transactionId);
    return NextResponse.json({ success: true, payment });
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}
```

```
===== FILE: src/app/api/payouts/route.ts =====
```

```
import { NextResponse } from 'next/server';
import { payoutService } from '@lib/services/payoutService';
```

```
export async function GET() {
  try {
    const data = await payoutService.getMyPayouts();
    return NextResponse.json(data);
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}
```

```
===== FILE: src/app/api/points/index.ts =====
```

```
===== FILE: src/app/api/points/route.ts =====
```

```
import { NextResponse } from 'next/server';
import { pointsService } from '@lib/services/pointsService';
```

```
export async function GET() {
  try {
    const data = await pointsService.getMyPoints();
    return NextResponse.json(data);
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}
```

```
===== FILE: src/app/api/products/[id]/route.ts =====
```

```
import { NextResponse } from 'next/server';
import { wholesaleService } from '@lib/services/wholesaleService';
```

```
export async function GET(req: Request, { params }: { params: Promise<{ id: string }> }) {
  try {
    const { id } = await params;
    const products = await wholesaleService.getMyProducts();
    const specific = products.find(p => p.id === id);
    if (!specific) return NextResponse.json({ error: 'ð°Û\212ð± Û\205Û\210ð¬Û\210ð¬' }, {
status: 404 });
    return NextResponse.json(specific);
  } catch (error) {
    return NextResponse.json({ error: 'ð@ð•ð£ Û\201Û\212 ð¬Û\204ð¬ ð$Û\204Û\205Û\206ðªð¬'
}, { status: 500 });
  }
}
```

```
export async function PATCH(req: Request, { params }: { params: Promise<{ id: string }> }) {
  try {
    const { id } = await params;
    const body = await req.json();
    const product = await wholesaleService.updateProduct(id, body);
    return NextResponse.json(product);
  } catch (error) {
    return NextResponse.json({ error: 'ð@ð•ð£ Û\201Û\212 ðªð¬Û\212ð« ð$Û\204Û\205Û\206ðªð¬'
}, { status: 400 });
  }
}
```

```
export async function DELETE(req: Request, { params }: { params: Promise<{ id: string }>
```

```

    }) {
      try {
        const { id } = await params;
        await wholesaleService.deleteProduct(id);
        return NextResponse.json({ success: true });
      } catch (error) {
        return NextResponse.json({ error: 'ððð•ð£ ù\201ù\212 ð-ð°ù\201 ð$ù\204ù\205ù\206ðªð¬',
        }, { status: 500 });
      }
    }
  }
}

```

```
===== FILE: src/app/api/products/route.ts =====
```

```
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';
import { wholesaleService } from '@lib/services/wholesaleService';
```

```
export async function GET() {
  try {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

    const products = await wholesaleService.getMyProducts();
    return NextResponse.json(products);
  } catch (error) {
    return NextResponse.json({ error: 'ððð•ðŁ Ù\201Ù\212 ð¬Ù\204ð¬ ð$Ù\204Ù\205Ù\206ðªð¬ð¬ðª' }, { status: 500 });
  }
}
```

```
export async function POST(req: Request) {
  try {
    const body = await req.json();
    const product = await wholesaleService.createProduct(body);
    return NextResponse.json(product, { status: 201 });
  } catch (error) {
    return NextResponse.json({ error: 'ððð•ð£ ù\201ù\212 ð¥ù\206ð'ð$ð; ð$ù\204ù\205ù\206ð
að¬' }, { status: 400 });
  }
}
```

```
===== FILE: src/app/api/refunds/[id]/route.ts =====
```

```
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';
```

```
export async function PATCH(req: Request, { params }: { params: Promise<{ id: string }> }) {
```

```

    try {
      const supabase = await createClient();
      const { data: { user } } = await supabase.auth.getUser();
      if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

      const { data: adminCheck } = await supabase.from('users').select('role').eq('id', user.id).single();
      if (adminCheck?.role !== 'admin') return NextResponse.json({ error: 'Forbidden' }, { status: 403 });
    }
  }
}

```

```
const { id } = await params;
const { status } = await req.json();
const { data, error } = await supabase
  .from('refunds')
  .update({ status })
  .eq('id', id)
  .select()
  .single();
```

```
if (error) return NextResponse.json({ error: error.message }, { status: 500 });
return NextResponse.json(data);
catch (error: any) {
return NextResponse.json({ error: error.message }, { status: 500 });
```

```

    }
}

===== FILE: src/app/api/refunds/route.ts =====
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';

export async function GET() {
  try {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

    // 0$0\2040^0-0\2020\202 0\2050\2050$ 0¥0°0$ 0\2030$0\206 0£0~0\2050\206 0\2040\2120±
    0\211 0$0\2040\2030\2040\214 0£0\210 0^0$0~0± 0\2040\2120±0\211 0•0\2040°0$0^0\207 0\2010
    \2020•
    const { data: adminCheck } = await supabase.from('users').select('role').eq('id', use
    r.id).single();
    const isAdmin = adminCheck?.role === 'admin';

    let query = supabase.from('refunds').select('*', orders(address, total)').order('creat
    ed_at', { ascending: false });
    if (!isAdmin) query = query.eq('requested_by', user.id);

    const { data, error } = await query;
    if (error) return NextResponse.json({ error: error.message }, { status: 500 });
    return NextResponse.json(data);
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}

export async function POST(req: Request) {
  try {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

    const { orderId, reason } = await req.json();
    const { data, error } = await supabase
      .from('refunds')
      .insert({ order_id: orderId, requested_by: user.id, reason })
      .select()
      .single();

    if (error) return NextResponse.json({ error: error.message }, { status: 500 });
    return NextResponse.json(data, { status: 201 });
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 400 });
  }
}

===== FILE: src/app/api/relationships/[id]/route.ts =====
import { NextResponse } from 'next/server';
import { relationshipService } from '@lib/services/relationshipService';

export async function PATCH(req: Request, { params }: { params: Promise<{ id: string }> }) {
  try {
    const { id } = await params;
    const body = await req.json();
    const { action } = body;

    if (action === 'accept') await relationshipService.acceptRequest(id);
    else if (action === 'reject') await relationshipService.rejectRequest(id);
    else return NextResponse.json({ error: '0¥0~0±0$0; 0°0\2120± 0\2050°0±0\2100\201' },
    { status: 400 });

    return NextResponse.json({ success: true });
  } catch (error: any) {

```

```
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}

===== FILE: src/app/api/relationships/route.ts =====
import { NextResponse } from 'next/server';
import { relationshipService } from '@lib/services/relationshipService';
import { createClient } from '@lib/supabase/server';

export async function GET() {
  try {
    const supabase = await createClient(); // ØªØ¹Ø²Ù\212Ù\204
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

    const pendingRequests = await relationshipService.getPendingRequests();
    return NextResponse.json(pendingRequests);
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}

export async function POST(req: Request) {
  try {
    const body = await req.json();
    const { wholesalerId, retailerId, deliveryId } = body;
    if (!wholesalerId && !retailerId && !deliveryId) return NextResponse.json({ error: 'Ø²Ù\212Ø$Ù\206Ø$Øª Ù\206Ø$Ù\202ØµØ©' }, { status: 400 });

    const relationship = await relationshipService.sendRequest({ wholesalerId, retailerId, deliveryId });
    return NextResponse.json(relationship, { status: 201 });
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}

===== FILE: src/app/api/requests/[id]/route.ts =====
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';

export async function GET(req: Request, { params }: { params: Promise<{ id: string }> }) {
  const { id } = await params;
  const supabase = await createClient();
  const { data, error } = await supabase.from('requests').select('*').eq('id', id).single();
  if (error) return NextResponse.json({ error: error.message }, { status: 404 });
  return NextResponse.json(data);
}

export async function PATCH(req: Request, { params }: { params: Promise<{ id: string }> }) {
  const { id } = await params;
  const supabase = await createClient();
  const body = await req.json();
  const { data, error } = await supabase.from('requests').update(body).eq('id', id).select().single();
  if (error) return NextResponse.json({ error: error.message }, { status: 500 });
  return NextResponse.json(data);
}

===== FILE: src/app/api/requests/route.ts =====
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';

export async function GET() {
  const supabase = await createClient(); // ØªØ¹Ø²Ù\212Ù\204
  const { data, error } = await supabase.from('requests').select('*').order('created_at', { ascending: false });
}
```

```
    if (error) return NextResponse.json({ error: error.message }, { status: 500 });
    return NextResponse.json(data);
  }

export async function POST(req: Request) {
  const supabase = await createClient(); // ØªØ¹Ø²Ù\212Ù\204
  const body = await req.json();
  const { data, error } = await supabase.from('requests').insert(body).select().single();
  if (error) return NextResponse.json({ error: error.message }, { status: 500 });
  return NextResponse.json(data, { status: 201 });
}

===== FILE: src/app/api/revalidate/route.tsx =====
import { NextRequest, NextResponse } from 'next/server';
import { revalidatePath } from 'next/cache';

export async function POST(request: NextRequest) {
  try {
    const { path, secret } = await request.json();

    if (secret !== process.env.REVALIDATION_SECRET) {
      return NextResponse.json({ message: 'Unauthorized' }, { status: 401 });
    }

    if (!path) {
      return NextResponse.json({ message: 'Path is required' }, { status: 400 });
    }

    revalidatePath(path);

    return NextResponse.json({ revalidated: true, path });
  } catch (error) {
    return NextResponse.json({ message: 'Error revalidating' }, { status: 500 });
  }
}

===== FILE: src/app/api/reviews/index.ts =====

===== FILE: src/app/api/reviews/route.ts =====
import { NextResponse } from 'next/server';
import { reviewService } from '@lib/services/reviewService';
import { reviewSchema } from '@lib/validations/review.schema';

export async function GET(req: Request) {
  const { searchParams } = new URL(req.url);
  const productId = searchParams.get('productId');
  if (!productId) return NextResponse.json({ error: 'Product ID required' }, { status: 400 });

  try {
    const data = await reviewService.getProductReviews(productId);
    return NextResponse.json(data);
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}

export async function POST(req: Request) {
  try {
    const body = await req.json();
    const parsed = reviewSchema.parse(body);
    const data = await reviewService.createReview({ ...parsed, comment: parsed.comment || "" });
    return NextResponse.json(data, { status: 201 });
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 400 });
  }
}

===== FILE: src/app/api/upload/route.ts =====
```

```
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';

export async function POST(req: Request) {
  try {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

    const formData = await req.formData();
    const file = formData.get('file') as File;
    if (!file) return NextResponse.json({ error: 'No file provided' }, { status: 400 });

    const fileExt = file.name.split('.').pop();
    const fileName = `${Date.now()}-${Math.random().toString(36).substring(2)}.${fileExt}`;

    const arrayBuffer = await file.arrayBuffer();

    const { error: uploadError } = await supabase.storage
      .from('product-images')
      .upload(fileName, arrayBuffer, { contentType: file.type });

    if (uploadError) return NextResponse.json({ error: uploadError.message }, { status: 500 });

    const { data: urlData } = supabase.storage
      .from('product-images')
      .getPublicUrl(fileName);

    return NextResponse.json({ url: urlData.publicUrl }, { status: 201 });
  } catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
  }
}

===== FILE: src/app/api/users/route.ts =====
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';

export async function GET(req: Request) {
  try {
    const supabase = await createClient(); // ØªØ¹Ø²Ü\212Ü\204
    const { searchParams } = new URL(req.url);
    const role = searchParams.get('role');

    if (!role) return NextResponse.json({ error: 'Role is required' }, { status: 400 });

    const { data, error } = await supabase.from('users').select('*').eq('role', role);
    if (error) return NextResponse.json({ error: error.message }, { status: 500 });
    return NextResponse.json(data);
  } catch (error) {
    return NextResponse.json({ error: 'Server error' }, { status: 500 });
  }
}

===== FILE: src/app/api/wallet/index.ts =====

===== FILE: src/app/api/wallet/route.ts =====
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';

export async function GET() {
  try {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

    const { data, error } = await supabase
      .from("wallets")
      .select("*")
```

```
.eq("user_id", user.id)
.single();

    if (error && error.code !== 'PGRST116') return NextResponse.json({ error: error.message }, { status: 500 });
    return NextResponse.json(data || { balance: 0 });
} catch (error: any) {
    return NextResponse.json({ error: error.message }, { status: 500 });
}
}

===== FILE: src/app/api/whatsapp/route.ts =====
import { NextResponse } from 'next/server';
import { createClient } from '@lib/supabase/server';
import { whatsappService } from '@lib/services/whatsappService';

export async function POST(req: Request) {
    try {
        const supabase = await createClient();
        const { data: { user } } = await supabase.auth.getUser();
        if (!user) return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });

        const body = await req.json();
        const { orderId } = body;

        // Ø-Ù\204Ø" ØªÙ\201Ø$ØµÙ\212Ù\204 Ø$Ù\204Ø•Ù\204Ø"
        const { data: order, error: orderError } = await supabase.from("orders").select("*").eq("id", orderId).single();
        if (orderError) return NextResponse.json({ error: orderError.message }, { status: 500 });

        // Ø-Ù\204Ø" Ø±Ù\202Ù\205 Ù\207Ø$ØªÙ\201 ØªØ$Ø-Ø± Ø$Ù\204Ø-Ù\205Ù\204Ø@
        const phone = await whatsappService.getPhoneById(order.wholesaler_id);
        if (!phone) return NextResponse.json({ error: 'No phone number found' }, { status: 404 });

        // Ø-Ù\204Ø" Ø¹Ù\206Ø$ØµØ± Ø$Ù\204Ø•Ù\204Ø"
        const { data: items } = await supabase.from("order_items").select("*").eq("order_id", orderId);

        // Ø"Ù\206Ø$Ø; Ø$Ù\204Ø±Ø³Ø$Ù\204Ø@
        const message = whatsappService.buildOrderMessage(order, items || [], order.total);

        // Ø±Ø$Ø"Ø• Ù\210Ø$ØªØ³Ø$Ø"
        const whatsappUrl = `https://wa.me/${phone}?text=${message}`;

        return NextResponse.json({ url: whatsappUrl });
    } catch (error: any) {
        return NextResponse.json({ error: error.message }, { status: 500 });
    }
}

===== FILE: src/app/api/wishlist/index.ts =====

===== FILE: src/app/api/wishlist/route.ts =====
import { NextResponse } from 'next/server';
import { wishlistService } from '@lib/services/wishlistService';

export async function GET() {
    try {
        const data = await wishlistService.getMyWishlist();
        return NextResponse.json(data);
    } catch (error: any) {
        return NextResponse.json({ error: error.message }, { status: 500 });
    }
}

export async function POST(req: Request) {
    try {
        const { productId } = await req.json();
```

```

const data = await wishlistService.addToWishlist(productId);
return NextResponse.json(data, { status: 201 });
} catch (error: any) {
return NextResponse.json({ error: error.message }, { status: 400 });
}
}

===== FILE: src/app/layout.tsx =====
import type { Metadata, Viewport } from "next";
import { Inter } from "next/font/google";
import { baseMetadata } from "@config/seo";
import "../styles/globals.css";

const inter = Inter({ subsets: ["latin"] });

export const metadata: Metadata = baseMetadata;

export const viewport: Viewport = {
  themeColor: "#f59e0b",
  width: "device-width",
  initialScale: 1,
};

export default function RootLayout({
  children,
}: Readonly<{
  children: React.ReactNode;
}>) {
  return (
    <html lang="ar" dir="rtl">
      <body className={` ${inter.className} antialiased`} >
        {children}
        <!-- Ø³Ø-Ù\212Ù\204 Service Worker -->
        <script
          dangerouslySetInnerHTML={{
            __html: `
              if ('serviceWorker' in navigator) {
                window.addEventListener('load', function() {
                  navigator.serviceWorker.register('/sw.js').then(function(registration) {
                    console.log('ServiceWorker registration successful with scope: ', registration.scope);
                  }, function(err) {
                    console.log('ServiceWorker registration failed: ', err);
                  });
                }
              }
            `
          }}
        </script>
      </body>
    </html>
  );
}

===== FILE: src/app/manifest.ts =====
import type { MetadataRoute } from 'next'

export default function manifest(): MetadataRoute.Manifest {
  return {
    name: "Ø-Ù\217Ù\205Ù\222Ù\204Ù\216ØªÙ\220Ù\212",
    short_name: "Ø-Ù\217Ù\205Ù\222Ù\204Ù\216ØªÙ\220Ù\212",
    description: "Ù\205Ù\206ØµØ Ø¹Ø±Ø$Ù\202Ù\212Ø Ù\205ØªÙ\203Ø$Ù\205Ù\204Ø Ù\204Ù\204Ø¹ Ø¹Ø$Ù\204Ø-Ù\205Ù\204Ø Ù\210Ø$Ù\204ØªØ-Ø²Ø¹Ø Ù\210Ø$Ù\204ØªÙ\210ØµÙ\212Ù\204.",
    start_url: "/",
    display: "standalone",
    background_color: "#0F172A",
    theme_color: "#f59e0b",
    dir: "rtl",
  }
}

```

```
lang: "ar",
icons: [
  {
    src: "/favicon.ico",
    sizes: "any",
    type: "image/x-icon",
  },
],
}
}
}

===== FILE: src/app/page.tsx =====
export const dynamic = "force-dynamic";

import { Topbar } from "@components/dashboard/Topbar";
import { Button } from "@components/ui/Button";
import { RequestCard } from "@components/shared/RequestCard";
import { productService } from "@lib/services/productService";

export default async function Home() {
  let products: any[] = [];
  try {
    products = await productService.getAllProducts();
  } catch (error) {
    console.error("Error fetching products:", error);
  }

  return (
    <main dir="rtl" className="min-h-screen bg-gray-50 text-slate-900">
      <Topbar />
      <section className="bg-[#0F172A] text-white py-24 text-center px-4">
        <h1 className="text-5xl font-black mb-6"></h1>
        <p className="text-lg text-gray-300 mb-10"></p>
        <div className="flex justify-center gap-4">
          <Button size="lg" className="bg-[#f59e0b] text-gray-900 hover:bg-[#d97706]"></Button>
          <Button variant="outline" size="lg" className="border-white text-white hover:bg-white/10"></Button>
        </div>
      </section>
      <section className="container mx-auto py-16 px-4">
        <h2 className="text-3xl font-bold mb-8"></h2>
        {products.length === 0 ? (
          <div className="bg-white p-10 text-center text-gray-500 border border-dashed border-gray-300 rounded-xl"></div>) : (
          <div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-4 gap-6">
            {products.map((product) => (
              <RequestCard key={product.id} product={product} />
            ))}
          </div>
        )}
      </section>
    </main>
  );
}
```

```
===== FILE: src/app/retailer-dashboard/components/OrderStatusClient.tsx =====
import React, { useEffect } from 'react';

const OrderStatusClient = () => {
  React.useEffect(() => {
    // eslint-disable-next-line no-console
    console.warn('Placeholder: OrderStatusClient is not implemented yet.');
```

```
    }, []);
    return (
      <>
      { /*OrderStatusClient */}
    </>
  );
};

export { OrderStatusClient };

===== FILE: src/components/charts/AreaChart.tsx =====
"use client";
import { Area, AreaChart as RechartsAreaChart, ResponsiveContainer, Tooltip, XAxis, YAxis
  } from "recharts";

export function AreaChart({ data }: { data: any[] }) {
  return (
    <ResponsiveContainer width="100%" height={300}>
      <RechartsAreaChart data={data}>
        <XAxis dataKey="name" />
        <YAxis />
        <Tooltip />
        <Area type="monotone" dataKey="value" stroke="#8884d8" fill="#8884d8" />
      </RechartsAreaChart>
    </ResponsiveContainer>
  );
}

===== FILE: src/components/charts/BarChart.tsx =====
"use client";
import { Bar, BarChart as RechartsBarChart, ResponsiveContainer, Tooltip, XAxis, YAxis }
  from "recharts";

export function BarChart({ data }: { data: any[] }) {
  return (
    <ResponsiveContainer width="100%" height={300}>
      <RechartsBarChart data={data}>
        <XAxis dataKey="name" />
        <YAxis />
        <Tooltip />
        <Bar dataKey="value" fill="#8884d8" />
      </RechartsBarChart>
    </ResponsiveContainer>
  );
}

===== FILE: src/components/charts/LineChart.tsx =====
"use client";
import { Line, LineChart as RechartsLineChart, ResponsiveContainer, Tooltip, XAxis, YAxis
  } from "recharts";

export function LineChart({ data }: { data: any[] }) {
  return (
    <ResponsiveContainer width="100%" height={300}>
      <RechartsLineChart data={data}>
        <XAxis dataKey="name" />
        <YAxis />
        <Tooltip />
        <Line type="monotone" dataKey="value" stroke="#8884d8" />
      </RechartsLineChart>
    </ResponsiveContainer>
  );
}

===== FILE: src/components/charts/PieChart.tsx =====
"use client";
import { Cell, Pie, PieChart as RechartsPieChart, ResponsiveContainer, Tooltip } from "recharts";

const COLORS = ["#0088FE", "#00C49F", "#FFBB28", "#FF8042"];
```

```

export function PieChart({ data }: { data: any[] }) {
  return (
    <ResponsiveContainer width="100%" height={300}>
      <RechartsPieChart>
        <Pie data={data} dataKey="value" nameKey="name" cx="50%" cy="50%" outerRadius={100} fill="#8884d8">
          {data.map((_, index) => (
            <Cell key={`cell-${index}`} fill={COLORS[index % COLORS.length]} />
          ))}
        </Pie>
      </RechartsPieChart>
    </ResponsiveContainer>
  );
}

```

===== FILE: src/components/dashboard/Sidebar.tsx =====

```

"use client";
import Link from "next/link";
import { usePathname } from "next/navigation";
import { cn } from "@lib/utils";
import { useUserStore } from "@lib/stores/userStore";
import { LayoutDashboard, Package, ShoppingCart, Coins, Users, FileText, Settings, Truck, Store, MessageCircle } from "lucide-react";

```

```

export function Sidebar() {
  const pathname = usePathname();
  const role = useUserStore((state) => state.user?.role) || "retailer";

  const links = [
    { href: "/dashboard/overview", label: "Ü\2060,0±0© 0¹0$Ü\2050©", icon: LayoutDashboard, roles: ["admin"] },
    { href: "/dashboard/admin/users", label: "0$Ü\204Ü\2050³0ª0©Ü\205Ü\210Ü\206", icon: Users, roles: ["admin"] },
    { href: "/dashboard/wholesale/products", label: "0$Ü\204Ü\205Ü\2060ª0-0$0ª", icon: Package, roles: ["wholesaler"] },
    { href: "/dashboard/wholesale/orders", label: "0$Ü\2040•Ü\2040"0$0ª", icon: ShoppingCart, roles: ["wholesaler"] },
    { href: "/dashboard/wholesale/nearby-requests", label: "0•Ü\2040"0$0ª 0$Ü\2040$Ü\2060Ü\2050$Ü\205", icon: MessageCircle, roles: ["wholesaler"] },
    { href: "/dashboard/retailer/cart", label: "0$Ü\2040³Ü\2040©", icon: ShoppingCart, roles: ["retailer"] },
    { href: "/dashboard/retailer/orders", label: "0•Ü\2040"0$0ªÜ\212", icon: FileText, roles: ["retailer"] },
    { href: "/dashboard/retailer/favorites", label: "0$Ü\204Ü\205Ü\2010Ü\2040©", icon: Store, roles: ["retailer"] },
    { href: "/dashboard/retailer/points", label: "Ü\206Ü\2020$0•Ü\212", icon: Coins, roles: ["retailer"] },
    { href: "/dashboard/delivery/tasks", label: "0$Ü\204Ü\205Ü\2070$Ü\205", icon: Truck, roles: ["delivery"] },
    { href: "/dashboard/delivery/my-wholesalers", label: "0´0±Ü\2030$0Ü\212", icon: Store, roles: ["delivery"] },
    // 0¥0Ü\2010© 0±0$0"0• 0$Ü\2040±0³0$0Ü\204 Ü\204Ü\2040-Ü\205Ü\2120¹
    { href: "/dashboard/messages", label: "0$Ü\2040±0³0$0Ü\204", icon: MessageCircle, roles: ["admin", "wholesaler", "retailer", "delivery"] },
    { href: "/dashboard/settings", label: "0$Ü\2040¥0¹0-0$0-0$0ª", icon: Settings, roles: ["admin", "wholesaler", "retailer", "delivery"] },
  ];
}

```

```

const visibleLinks = links.filter((link) => link.roles.includes(role));

return (
  <aside className="hidden md:flex w-64 flex-col border-l border-gray-200 bg-white h-screen sticky top-0">
    <div className="p-6">
      <h2 className="text-xl font-black text-gray-900">0-Ü\217Ü\205Ü\222Ü\204Ü\2160ªÜ\220Ü\212</h2>
    </div>
    <nav className="flex-1 space-y-1 p-4">

```

```

    {visibleLinks.map((link) => (
      <Link
        key={link.href}
        href={link.href}
        className={cn(
          "flex items-center gap-3 rounded-lg px-3 py-2 text-sm font-medium transiti
n-colors",
          pathname === link.href
            ? "bg-[#f59e0b]/10 text-[#f59e0b]"
            : "text-gray-600 hover:bg-gray-50 hover:text-gray-900"
        )}
      >
        <link.icon size={18} />
        {link.label}
      </Link>
    ))}
  </nav>
</aside>
);
}

```

===== FILE: src/components/dashboard/Topbar.tsx =====

```

"use client";
import { useEffect, useCallback } from "react";
import { useUserStore } from "@lib/stores/userStore";
import { useNotificationStore } from "@lib/stores/notificationStore";
import { useRealtime } from "@hooks/useRealtime";
import { Package, Bell, UserCircle } from "lucide-react";

export function Topbar() {
  const user = useUserStore((state) => state.user);
  const { unreadCount, fetchNotifications } = useNotificationStore();

  const refresh = useCallback(() => { fetchNotifications(); }, [fetchNotifications]);

  useRealtime("notifications", () => { refresh(); });
  useEffect(() => { refresh(); }, [refresh]);

  return (
    <header className="h-16 sticky top-0 z-40 flex items-center justify-between bg-[#0F17
2A] px-6 text-white shadow-lg">
      <div className="flex items-center gap-3">
        <Package className="h-6 w-6 text-[#f59e0b]" />
        <span className="text-xl font-black">Ø-Û\217Û\205Û\222Û\204Û\216ØªÛ\220Û\212</spa
n>
      </div>
      <div className="flex items-center gap-4">
        <button className="relative p-2 rounded-full hover:bg-white/10 transition-colors"
        >
          <Bell size={20} />
          {unreadCount > 0 && (
            <span className="absolute top-0 right-0 h-5 w-5 text-xs bg-red-500 text-white
rounded-full flex items-center justify-center">
              {unreadCount}
            </span>
          )}
        </button>
        <div className="flex items-center gap-2">
          <div className="h-8 w-8 rounded-full bg-[#f59e0b] text-gray-900 flex items-cent
er justify-center font-bold">
            {user?.name?.charAt(0) || "Ø²"}
          </div>
          <span className="text-sm font-medium hidden md:block">{user?.name || "Ø²Ø$Ø|Ø±"
}</span>
        </div>
      </div>
    </header>
  );
}

```

```
===== FILE: src/components/forms/CommissionForm.tsx =====
```

```
"use client";
import { useState } from "react";
import { useToast } from "@/hooks/useToast";
import { Button } from "@/components/ui/Button";
import { Input } from "@/components/ui/Input";

import { useCommissionStore } from "@/lib/stores/commissionStore";

export function CommissionForm({ orderId, retailerId }: { orderId: string; retailerId: string }) {
  const [loading, setLoading] = useState(false);
  const { showToast } = useToast();
  const setCommissions = useCommissionStore((s) => s.setCommissions);

  const handleSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    setLoading(true);
    const formData = new FormData(e.target as HTMLFormElement);
    const data = { orderId, retailerId, amount: Number(formData.get("amount")), status: "pending" };

    const res = await fetch("/api/commissions", {
      method: "POST",
      body: JSON.stringify(data),
    });

    if (res.ok) {
      const newCommission = await res.json();
      setCommissions([newCommission]); // 0^0-0^0\2120« 0$0\2040\200 store
      showToast("0^0\205 0¥0\2060'0$0; 0$0\2040^0\2050\2100\2040© 0^0\2060¬0$0-", "success");
    } else {
      showToast("0-0^0« 0@0•0£ 0\2010\212 0¥0\2060'0$0; 0$0\2040^0\2050\2100\2040©", "error");
    }
    setLoading(false);
  };

  return (
    <form onSubmit={handleSubmit} className="space-y-4 max-w-md">
      <Input name="amount" type="number" placeholder="0\2050^0\2040° 0$0\2040^0\2050\2100\2040©" required />
      <Button type="submit" disabled={loading} className="w-full">0¥010$0\2010© 0^0\2050\2100\2040©</Button>
    </form>
  );
}
```

```
===== FILE: src/components/forms/MatchingForm.tsx =====
```

```
"use client";
import { useState } from "react";
import { useToast } from "@/hooks/useToast";
import { Button } from "@/components/ui/Button";
import { Input } from "@/components/ui/Input";
import { Textarea } from "@/components/ui/Textarea";

export function MatchingForm({ retailerId }: { retailerId: string }) {
  const [loading, setLoading] = useState(false);
  const { showToast } = useToast();

  const handleSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    setLoading(true);
    const formData = new FormData(e.target as HTMLFormElement);
    const data = Object.fromEntries(formData.entries());

    const res = await fetch("/api/matching", {
      method: "POST",
      body: JSON.stringify({ ...data, retailerId }),
    });
  };
}
```

```

    });

    if (res.ok) {
      showToast("ðªÙ\205 ð¥ð±ð³ð$Ù\204 ð•Ù\204ð" ð$Ù\204Ù\205ð•ð$ð"Ù\202ð@", "success");
      (e.target as HTMLFormElement).reset();
    } else {
      showToast("Ù\201ð´Ù\204 ð¥ð±ð³ð$Ù\204 ð•Ù\204ð" ð$Ù\204Ù\205ð•ð$ð"Ù\202ð@", "error"
    );
  }
  setLoading(false);
};

return (
  <form onSubmit={handleSubmit} className="space-y-4 max-w-md">
    <Input name="productName" placeholder="ð$ð³Ù\205 ð$Ù\204Ù\205Ù\206ðªð¬ ð$Ù\204Ù\205
ð•Ù\204Ù\210ð" required />
    <Input name="quantity" type="number" placeholder="ð$Ù\204Ù\203Ù\205Ù\212ð@ ð$Ù\204Ù
\205ð•Ù\204Ù\210ð"ð$ð" required />
    <Textarea name="notes" placeholder="Ù\205Ù\204ð$ð-ð,ð$ðª ð¥ð±ð$Ù\201Ù\212ð@..." />
    <Button type="submit" disabled={loading} className="w-full">ð¥ð±ð³ð$Ù\204 ð\204Ù
\204Ù\205ð•ð$ð"Ù\202ð@</Button>
  </form>
);
}

```

===== FILE: src/components/forms/ProductForm.tsx =====

```

"use client";
import { useState } from "react";
import { Button } from "@components/ui/Button";
import { Input } from "@components/ui/Input";
import { Textarea } from "@components/ui/Textarea";
import { Select } from "@components/ui/Select";
import { FileUpload } from "@components/ui/FileUpload";
import { useToast } from "@hooks/useToast";

export function ProductForm({ initialData, onSuccess }: { initialData?: any; onSuccess?:
() => void }) {
  const [loading, setLoading] = useState(false);
  const [imageUrl, setImageUrl] = useState<string | undefined>(initialData?.images?.[0]);
  const { showToast } = useToast();

  const handleImageUpload = async (file: File | null) => {
    if (!file) return;
    const formData = new FormData();
    formData.append('file', file);
    const res = await fetch("/api/upload", { method: "POST", body: formData });
    const data = await res.json();
    if (res.ok) {
      setImageUrl(data.url);
      showToast("ðªÙ\205 ð±Ù\201ð¹ ð$Ù\204ðµÙ\210ð±ð@ ð"Ù\206ð¬ð$ð-!", "success");
    } else {
      showToast(data.error || "ð@ð•ð£ ð\201Ù\212 ð±Ù\201ð¹ ð$Ù\204ðµÙ\210ð±ð@", "error");
    }
  };

  const handleSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    setLoading(true);
    const formData = new FormData(e.target as HTMLFormElement);
    const data = Object.fromEntries(formData.entries());
    data.images = JSON.stringify(imageUrl ? [imageUrl] : []);

    const res = await fetch(initialData ? `/api/products/${initialData.id}` : "/api/produ
cts", {
      method: initialData ? "PATCH" : "POST",
      headers: { "Content-Type": "application/json" },
      body: JSON.stringify(data),
    });

    if (res.ok) {

```

```

        showToast(initialData ? "ðªÛ\205 ðªð-ð-Û\212ð« ð$Û\204Û\205Û\206ðªð-Û" : "ðªÛ\205 ðªÛ\206ðªð$ð; ð$Û\204Û\205Û\206ðªð-Û", "success");
        onSuccess?.;();
    } else {
        const err = await res.json();
        showToast(err.error || "ð-ð-ð« ððð•ð£", "error");
    }
    setLoading(false);
};

return (
    <form onSubmit={handleSubmit} className="space-y-4">
        <FileUpload onChange={handleImageUpload} />
        {imageUrl && <img src={imageUrl} alt="Product" className="h-20 w-20 object-cover rounded-lg" />}
        <Input name="name" placeholder="ð$ð³Û\205 ð$Û\204Û\205Û\206ðªð-Û" defaultValue={initialData?.name} required />
        <Textarea name="description" placeholder="Û\210ðµÛ\201 ð$Û\204Û\205Û\206ðªð-Û" defaultValue={initialData?.description} />
        <div className="grid grid-cols-2 gap-4">
            <Input name="price" type="number" step="0.01" placeholder="ð³ð¹ð± ð$Û\204ðªð-ð²ð!ðð" defaultValue={initialData?.price} required />
            <Input name="wholesalePrice" type="number" step="0.01" placeholder="ð³ð¹ð± ð$Û\204ð-Û\205Û\204ðð" defaultValue={initialData?.wholesalePrice} required />
        </div>
        <div className="grid grid-cols-2 gap-4">
            <Input name="stock" type="number" placeholder="ð$Û\204Û\203Û\205Û\212ðð" defaultValue={initialData?.stock} required />
            <Select name="category" defaultValue={initialData?.category}>
                <option value="electronics">ð¥Û\204Û\203ðªð±Û\210Û\206Û\212ð$ðª</option>
                <option value="clothing">Û\205Û\204ð$ð³</option>
                <option value="food">Û\205Û\210ð$ð- ð°ð°ð$ð|Û\212ðð</option>
                <option value="general">Û\205Û\210ð$ð- ð¹ð$Û\205ðð</option>
            </Select>
        </div>
        <Button type="submit" disabled={loading} className="w-full">
            {loading ? "ð-ð$ð±Û\215 ð$Û\204ð-Û\201ð,...": initialData ? "ð-Û\201ð, ð$Û\204ðªð¹ð-Û\212Û\204ð$ðª" : "ð¥ðµð$Û\201ðð ð$Û\204Û\205Û\206ðªð-Û"}
        </Button>
    </form>
);
}

===== FILE: src/components/forms/ProfileForm.tsx =====
"use client";
import { useState } from "react";
import { Button } from "@components/ui/Button";
import { Input } from "@components/ui/Input";
import { showToast } from "@hooks/useToast";
import { useUserStore } from "@lib/stores/userStore";

export function ProfileForm() {
    const [loading, setLoading] = useState(false);
    const { user, setUser } = useUserStore();
    const { showToast } = useToast();

    const handleSubmit = async (e: React.FormEvent) => {
        e.preventDefault();
        setLoading(true);
        const formData = new FormData(e.target as HTMLFormElement);
        const data = Object.fromEntries(formData.entries());

        const res = await fetch("/api/profile", {
            method: "PUT",
            body: JSON.stringify(data),
        });

        if (res.ok) {
            showToast("ðªÛ\205 ð-Û\201ð, ð$Û\204Û\205Û\204Û\201 ð$Û\204ðªððµÛ\212", "success")
        }
    };

```

```
    } else {
      showToast("ððð•ð ù\201ù\212 ð$ù\204ð-ù\201ð.", "error");
    }
    setLoading(false);
  };

  return (
    <form onSubmit={handleSubmit} className="space-y-4 max-w-md">
      <Input name="name" placeholder="ð$ù\204ð$ð³ù\205" defaultValue={user?.name} require
d />
      <Input name="phone" placeholder="ð±ù\202ù\205 ð$ù\204ù\207ð$ðªù\201" defaultValue={
user?.phone} />
      <Button type="submit" disabled={loading}>ð-ù\201ð, ð$ù\204ðªð°ù\212ù\212ð±ð$ðª</But
ton>
    </form>
  );
}
```

===== FILE: src/components/forms/RequestForm.tsx =====

```
"use client";
import { useState } from "react";
import { Button } from "@/components/ui/Button";
import { Textarea } from "@/components/ui/Textarea";
import { Input } from "@/components/ui/Input";
import { useToast } from "@/hooks/useToast";

export function RequestForm({ type }: { type: "product" | "wholesale" }) {
  const [loading, setLoading] = useState(false);
  const { showToast } = useToast();

  const handleSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    setLoading(true);
    const formData = new FormData(e.target as HTMLFormElement);
    const data = Object.fromEntries(formData.entries());

    const res = await fetch("/api/requests", {
      method: "POST",
      body: JSON.stringify({ ...data, type }),
    });

    if (res.ok) {
      showToast("ðªù\205 ð¥ð±ð³ð$ù\204 ð$ù\204ð•ù\204ð", "success");
      (e.target as HTMLFormElement).reset();
    } else {
      showToast("ððð•ð ù\201ù\212 ð¥ð±ð³ð$ù\204 ð$ù\204ð•ù\204ð", "error");
    }
    setLoading(false);
  };

  return (
    <form onSubmit={handleSubmit} className="space-y-4">
      <Input name="title" placeholder="ð¹ù\206ù\210ð$ù\206 ð$ù\204ð•ù\204ð" required />
      <Textarea name="details" placeholder="ðªù\201ð$ðµù\212ù\204 ð$ù\204ð•ù\204ð..." re
quired />
      <Button type="submit" disabled={loading}>ð¥ð±ð³ð$ù\204 ð$ù\204ð•ù\204ð</Button>
    </form>
  );
}
```

===== FILE: src/components/offers/index.ts =====

===== FILE: src/components/points/index.ts =====

===== FILE: src/components/reviews/index.ts =====

===== FILE: src/components/shared/BottomNavBar.tsx =====

```
"use client";
import Link from "next/link";
import { usePathname } from "next/navigation";
```

```
import { Home, Store, ShoppingCart, User, MessageCircle } from "lucide-react";
import { cn } from "@lib/utils";

export function BottomNavBar() {
  const pathname = usePathname();
  const links = [
    { href: "/", label: "Hjem", icon: Home },
    { href: "/products", label: "Produkter", icon: Store },
    { href: "/offers", label: "Tilbud", icon: MessageCircle },
    { href: "/cart", label: "Køretasker", icon: ShoppingCart },
    { href: "/dashboard/retailer/overview", label: "Dashboard", icon: User },
  ];

  return (
    <nav className="md:hidden fixed bottom-0 left-0 right-0 z-50 bg-white border-t shadow-lg flex justify-around py-2 pb-safe">
      {links.map((link) => {
        const isActive = pathname === link.href || (link.href !== "/" && pathname.startsWith(link.href));
        return (
          <Link
            key={link.href}
            href={link.href}
            className={cn(
              "flex flex-col items-center text-xs p-2 transition-all",
              isActive ? "text-[#f59e0b] font-bold scale-105" : "text-gray-500"
            )}>
            <link.icon size={22} className="mb-1" />
            {link.label}
          </Link>
        );
      })}
    </nav>
  );
}

===== FILE: src/components/shared>LoadingSpinner.tsx =====
export function LoadingSpinner({ className }: { className?: string }) {
  return (
    <div className={`flex justify-center items-center ${className} || "h-32"}`>
      <div className="h-8 w-8 animate-spin rounded-full border-4 border-primary border-transparent" />
    </div>
  );
}

===== FILE: src/components/shared/NotificationCenter.tsx =====
"use client";
import { useEffect, useCallback } from "react";
import { useNotificationStore } from "@lib/stores/notificationStore";
import { useRealtime } from "@hooks/useRealtime";
import { formatTimeAgo } from "@lib/utils/date";

export function NotificationCenter() {
  const { notifications, unreadCount, fetchNotifications, markAsRead } = useNotificationStore();

  const refresh = useCallback(() => { fetchNotifications(); }, [fetchNotifications]);

  useRealtime("notifications", () => { refresh(); });
  useEffect(() => { refresh(); }, [refresh]);

  return (
    <div className="fixed left-4 top-20 z-50 w-80 max-h-96 overflow-y-auto rounded-lg border bg-white shadow-xl p-4">
      <h3 className="font-bold mb-4 text-lg border-b pb-2">Ungelæste</h3>
      {notifications.length === 0 ? (<p className="text-center text-gray-400 py-4">Ingen nye meldinger</p>) : (

```

```

        <ul className="space-y-3">
          {notifications.map((n) => (
            <li key={n.id} className="flex gap-3 border-b pb-3 last:border-0">
              <div className={`h-2 w-2 mt-2 rounded-full ${n.is_read ? "bg-gray-300" : "bg-blue-500"}`} />
              <div className="flex-1">
                <p className="text-sm font-medium">{n.title}</p>
                <p className="text-xs text-gray-500">{n.message}</p>
                <span className="text-xs text-gray-400">{formatTimeAgo(n.created_at)}</span>
                <button onClick={() => markAsRead(n.id)} className="text-xs text-primary hover:underline block mt-1">Mark as Read</button>
              </div>
            </li>
          ))}
        </ul>
      </div>
    </div>
  );
}

```

```
===== FILE: src/components/shared/RequestCard.tsx =====
```

[illegible]

```

    <h3 className="font-bold text-lg text-gray-800 mb-1 line-clamp-1">{product.name}</h3>
    <p className="text-sm text-gray-500 mb-3">{product.category}</p>

    <div className="mt-auto">
      <span className="block font-extrabold text-primary text-xl mb-3">{formatCurrency(
product.price)}</span>
      <Button onClick={handleAddToCart} size="sm" className="w-full opacity-90 group-ho
ver:opacity-100">
        <ShoppingCart size={16} className="ml-1" />
      </Button>
    </div>
  </div>
);
}

```

```
===== FILE: src/components/shared/Sidebar.tsx =====
```

```

"use client";
import Link from "next/link";
import { usePathname } from "next/navigation";
import { cn } from "@/lib/utils";

export function Sidebar() {
  const pathname = usePathname();
  const links = [
    { href: "/dashboard/retailer/overview", label: "Overview" },
    { href: "/dashboard/retailer/orders", label: "Orders" },
    { href: "/dashboard/retailer/products", label: "Products" },
    { href: "/dashboard/retailer/favorites", label: "Favorites" },
    { href: "/dashboard/retailer/settings", label: "Settings" },
  ];

  return (
    <aside className="w-64 bg-gray-900 text-white h-screen fixed top-0 right-0 p-4 border
-1 border-gray-800">
      <h2 className="text-xl font-bold mb-6 px-2">Dashboard</h2>
      <nav className="space-y-2">
        {links?.map((link) => (
          <Link
            key={link?.href}
            href={link?.href}
            className={cn("block px-4 py-2 rounded-md transition-colors", pathname === li
nk?.href ? "bg-primary text-white" : "text-gray-400 hover:bg-gray-800 hover:text-white")}
          >
            {link?.label}
          </Link>
        ))}
      </nav>
    </aside>
  );
}

```

```
===== FILE: src/components/shared/StatsCard.tsx =====
```

```

import React from "react";
import { cn } from "@/lib/utils";

interface StatsCardProps {
  title: string;
  value: string;
  icon: React.ReactNode;
  trend?: string;
  trendUp?: boolean;
}

export function StatsCard({ title, value, icon, trend, trendUp }: StatsCardProps) {
  return (
    <div className="bg-white rounded-2xl border border-gray-100 p-6 shadow-sm hover:shado
w-lg transition-all">
      <div className="flex justify-between items-start">

```

```

    <div>
      <p className="text-sm font-medium text-gray-500">{title}</p>
      <h4 className="text-2xl font-extrabold mt-2">{value}</h4>
      {trend && (
        <p className={cn("text-xs mt-2 font-semibold", trendUp ? "text-emerald-500"
: "text-red-500")}>
          {trendUp ? "â\206\221" : "â\206\223"} {trend}
        </p>
      )}
    </div>
    <div className="h-12 w-12 rounded-xl bg-gradient-to-tr from-primary/10 to-purple-
500/10 flex items-center justify-center text-2xl">
      {icon}
    </div>
  </div>
</div>
);
}

===== FILE: src/components/shared/StatusBadge.tsx =====
import { Badge } from "@components/ui/Badge";
import { cn } from "@lib/utils";

type Status = "pending" | "approved" | "rejected" | "paid" | "shipped" | "delivered" | "c
ancelled" | "active" | "inactive";

export function StatusBadge({ status }: { status: Status }) {
  const styles: Record<Status, string> = {
    pending: "bg-yellow-100 text-yellow-800 border-yellow-200",
    approved: "bg-green-100 text-green-800 border-green-200",
    rejected: "bg-red-100 text-red-800 border-red-200",
    paid: "bg-blue-100 text-blue-800 border-blue-200",
    shipped: "bg-purple-100 text-purple-800 border-purple-200",
    delivered: "bg-emerald-100 text-emerald-800 border-emerald-200",
    cancelled: "bg-gray-100 text-gray-800 border-gray-200",
    active: "bg-green-100 text-green-800 border-green-200",
    inactive: "bg-gray-100 text-gray-800 border-gray-200",
  };

  return (
    <Badge variant="outline" className={cn("capitalize", styles[status])}>
      {status}
    </Badge>
  );
}

===== FILE: src/components/ui/Badge.tsx =====
import * as React from "react";
import { cn } from "@lib/utils";

const badgeVariants = {
  default: "bg-primary text-white",
  secondary: "bg-gray-100 text-gray-700",
  destructive: "bg-red-100 text-red-700",
  success: "bg-emerald-100 text-emerald-700",
  outline: "border border-gray-300 text-gray-600",
};

export interface BadgeProps extends React.HTMLAttributes<HTMLDivElement> {
  variant?: keyof typeof badgeVariants;
}

function Badge({ className, variant = "default", ...props }: BadgeProps) {
  return (
    <div
      className={cn(
        "inline-flex items-center rounded-full px-3 py-1 text-xs font-semibold transition
-colors",
        badgeVariants[variant],
        className
      )}
    >

```

```
    })
    {...props}
  />
);
}

export { Badge, badgeVariants };

===== FILE: src/components/ui/Button.tsx =====
import * as React from "react";
import { cn } from "@/lib/utils";

interface ButtonProps extends React.ButtonHTMLAttributes<HTMLButtonElement> {
  variant?: "default" | "secondary" | "outline" | "ghost" | "destructive";
  size?: "sm" | "md" | "lg" | "icon";
}

export const Button = React.forwardRef<HTMLButtonElement, ButtonProps>(
  ({ className, variant = "default", size = "md", ...props }, ref) => {
    const variants = {
      default: "bg-primary text-primary-foreground shadow-md shadow-primary/20 hover:bg-primary/90 hover:shadow-lg hover:-translate-y-0.5 active:translate-y-0 transition-all",
      secondary: "bg-secondary text-secondary-foreground hover:bg-secondary/80 transition-colors",
      outline: "border border-input bg-background hover:bg-accent hover:text-accent-foreground transition-colors",
      ghost: "hover:bg-accent hover:text-accent-foreground transition-colors",
      destructive: "bg-destructive text-destructive-foreground shadow-md shadow-destructive/20 hover:bg-destructive/90 transition-colors",
    };
    const sizes = {
      sm: "h-8 px-3 text-xs rounded-md",
      md: "h-10 px-4 py-2 rounded-lg",
      lg: "h-12 px-8 rounded-xl text-lg",
      icon: "h-10 w-10 rounded-full",
    };
    return (
      <button
        className={cn(
          "inline-flex items-center justify-center font-medium focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus-visible:ring-offset-2 disabled:opacity-50 disabled:pointer-events-none",
          variants[variant],
          sizes[size],
          className
        )}
        ref={ref}
        {...props}
      />
    );
  }
);
Button.displayName = "Button";

===== FILE: src/components/ui/Card.tsx =====
import * as React from "react";
import { cn } from "@/lib/utils";

const Card = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => {
  <div
    ref={ref}
    className={cn(
      "rounded-2xl border border-gray-200 bg-white text-gray-900 shadow-sm transition-all duration-300 hover:shadow-md",
      className
    )}
    {...props}
  />
```

```
    />
  ));
  Card.displayName = "Card";

  const CardHeader = React.forwardRef<
    HTMLDivElement,
    React.HTMLAttributes<HTMLDivElement>
  >(({ className, ...props }, ref) => (
    <div
      ref={ref}
      className={cn("flex flex-col space-y-1.5 p-6", className)}
      {...props}
    />
  ));
  CardHeader.displayName = "CardHeader";

  const CardTitle = React.forwardRef<
    HTMLHeadingElement,
    React.HTMLAttributes<HTMLHeadingElement>
  >(({ className, ...props }, ref) => (
    <h3
      ref={ref}
      className={cn("text-xl font-bold leading-none tracking-tight", className)}
      {...props}
    />
  ));
  CardTitle.displayName = "CardTitle";

  const CardDescription = React.forwardRef<
    HTMLParagraphElement,
    React.HTMLAttributes<HTMLParagraphElement>
  >(({ className, ...props }, ref) => (
    <p
      ref={ref}
      className={cn("text-sm text-gray-500", className)}
      {...props}
    />
  ));
  CardDescription.displayName = "CardDescription";

  const CardContent = React.forwardRef<
    HTMLDivElement,
    React.HTMLAttributes<HTMLDivElement>
  >(({ className, ...props }, ref) => (
    <div ref={ref} className={cn("p-6 pt-0", className)} {...props} />
  ));
  CardContent.displayName = "CardContent";

  const CardFooter = React.forwardRef<
    HTMLDivElement,
    React.HTMLAttributes<HTMLDivElement>
  >(({ className, ...props }, ref) => (
    <div
      ref={ref}
      className={cn("flex items-center p-6 pt-0", className)}
      {...props}
    />
  ));
  CardFooter.displayName = "CardFooter";

  export { Card, CardHeader, CardFooter, CardTitle, CardDescription, CardContent };

==== FILE: src/components/ui/DataTable.tsx ====
"use client";
import * as React from "react";
import { cn } from "@/lib/utils";

interface Column<T> {
  key: keyof T | string;
  header: string;
```

```

    render?: (item: T) => React.ReactNode;
  }

export function DataTable<T>({ data, columns, className }: { data: T[]; columns: Column<T>[]; className?: string }) {
  return (
    <div className={cn("w-full overflow-auto rounded-md border", className)}>
      <table className="w-full caption-bottom text-sm">
        <thead className=" [&_tr]:border-b">
          <tr className="border-b transition-colors hover:bg-muted/50 data-[state=selected]:bg-muted">
            {columns.map((col) => (
              <th key={col.key as string} className="h-12 px-4 text-left align-middle font-medium text-muted-foreground">{col.header}</th>
            ))}
          </tr>
        </thead>
        <tbody className=" [&_tr:last-child]:border-0">
          {data.map((row, index) => (
            <tr key={index} className="border-b transition-colors hover:bg-muted/50">
              {columns.map((col) => (
                <td key={col.key as string} className="p-4 align-middle">
                  {col.render ? col.render(row) : (row as any)[col.key]}
                </td>
              ))}
            </tr>
          ))}
        </tbody>
      </table>
    </div>
  );
}

```

===== FILE: src/components/ui/Dropdown.tsx =====

"use client";

```

import * as React from "react";
import { cn } from "@/lib/utils";

```

```

export function Dropdown({ trigger, children, align = "end" }: { trigger: React.ReactNode; children: React.ReactNode; align?: "start" | "end" }) {
  const [open, setOpen] = React.useState(false);
  const ref = React.useRef<HTMLDivElement>(null);

```

```

  React.useEffect(() => {
    const handleClickOutside = (event: MouseEvent) => {
      if (ref.current && !ref.current.contains(event.target as Node)) {
        setOpen(false);
      }
    };
    document.addEventListener("mousedown", handleClickOutside);
    return () => document.removeEventListener("mousedown", handleClickOutside);
  }, []);

```

```

  return (
    <div className="relative" ref={ref}>
      <div onClick={() => setOpen(!open)}>{trigger}</div>
      {open && (
        <div className={cn("absolute z-50 mt-2 w-48 rounded-md border bg-white py-1 shadow-w-lg", align === "end" ? "left-0" : "right-0")}>
          {children}
        </div>
      )}
    </div>
  );
}

```

===== FILE: src/components/ui/FileUpload.tsx =====

"use client";

```

import * as React from "react";

```

```

import { cn } from "@/lib/utils";
import { useToast } from "@/hooks/useToast";

export function FileUpload({ className, onChange }: { className?: string; onChange?: (file: File | null) => void }) {
  const [preview, setPreview] = React.useState<string | null>(null);
  const { showToast } = useToast();
  const inputRef = React.useRef<HTMLInputElement>(null);

  const handleFileChange = (e: React.ChangeEvent<HTMLInputElement>) => {
    const file = e.target.files?.[0] || null;
    if (file) {
      if (file.size > 5 * 1024 * 1024) {
        showToast("ð-ð-ð\205 ð$ð\204ð\205ð\204ð\201 ð\212ðªð-ð$ð\210ð² 5 ð\205ð\212ðªð$ð"
        ð$ð\212ðª", "error");
        return;
      }
      const reader = new FileReader();
      reader.onloadend = () => setPreview(reader.result as string);
      reader.readAsDataURL(file);
      onChange?.(file);
    }
  };

  return (
    <div
      onClick={() => inputRef.current?.click()}
      className={cn("border-2 border-dashed border-gray-300 rounded-lg p-6 text-center cursor-pointer hover:border-primary transition-colors", className)}
    >
      <input ref={inputRef} type="file" accept="image/*" className="hidden" onChange={handleFileChange} />
      {preview ? (
        // ð¥ð²ð$ð\204ð© img ð\204ðªð-ð\206ð" ð$ð\204ðªð-ð°ð\212ð±
        <div className="max-h-40 mx-auto rounded-md bg-gray-100 p-2 text-gray-500">ðªð
        \205 ð±ð\201ð¹ ð$ð\204ðµð\210ð±ð©</div>
      ) : (
        <div className="text-gray-500">
          <div className="text-3xl mb-2">ð\237\223\201</div>
          <p>ð$ð¹ð°ð• ð\204ð$ðªðªðªð\212ð$ð± ðµð\210ð±ð© ð£ð\210 ð$ð³ð-ð"ð\207ð$ ð\207ð\206
          ð$</p>
        </div>
      )}
    </div>
  );
}

```

===== FILE: src/components/ui/Input.tsx =====

```

import * as React from "react";
import { cn } from "@/lib/utils";

export interface InputProps extends React.InputHTMLAttributes<HTMLInputElement> {}

const Input = React.forwardRef<HTMLInputElement, InputProps>(
  ({ className, type, ...props }, ref) => {
    return (
      <input
        type={type}
        className={cn(
          "flex h-11 w-full rounded-xl border border-gray-300 bg-white px-4 py-2 text-sm
          text-gray-900 shadow-sm transition-all placeholder:text-gray-400 focus-visible:outline-no
          ne focus-visible:ring-2 focus-visible:ring-primary/50 focus-visible:border-primary disabl
          ed:cursor-not-allowed disabled:opacity-50",
          className
        )}
        ref={ref}
        {...props}
      />
    );
  }
);

```

```
);
Input.displayName = "Input";

export { Input };

===== FILE: src/components/ui/Modal.tsx =====
"use client";
import * as React from "react";
import { cn } from "@/lib/utils";

export function Modal({ open, onClose, children, title, className }: { open: boolean; onClose: () => void; children: React.ReactNode; title?: string; className?: string }) {
  if (!open) return null;

  return (
    <div className="fixed inset-0 z-[100] flex items-center justify-center p-4 bg-black/60 backdrop-blur-sm animate-fade-in" onClick={onClose}>
      <div className={cn("bg-white rounded-2xl shadow-2xl w-full max-w-lg max-h-[90vh] overflow-y-auto p-6 animate-slide-up", className)} onClick={(e) => e.stopPropagation()}>
        {title && <h2 className="text-2xl font-bold mb-4">{title}</h2>}
        <button onClick={onClose} className="absolute top-4 left-4 text-gray-400 hover:text-gray-600">â\234\225</button>
        {children}
      </div>
    </div>
  );
}

===== FILE: src/components/ui/Select.tsx =====
import * as React from "react";
import { cn } from "@/lib/utils";

export interface SelectProps extends React.SelectHTMLAttributes<HTMLSelectElement> {}

const Select = React.forwardRef<HTMLSelectElement, SelectProps>(
  ({ className, children, ...props }, ref) => {
    return (
      <select
        className={cn(
          "flex h-11 w-full rounded-xl border border-gray-300 bg-white px-4 py-2 text-sm text-gray-900 shadow-sm transition-all focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-primary/50 focus-visible:border-primary disabled:cursor-not-allowed disabled:opacity-50",
          className
        )}
        ref={ref}
        {...props}
      >
        {children}
      </select>
    );
  }
);
Select.displayName = "Select";

export { Select };

===== FILE: src/components/ui/Skeleton.tsx =====
import { cn } from "@/lib/utils";

export function Skeleton({ className }: { className?: string }) {
  return <div className={cn("animate-pulse rounded-md bg-gray-200", className)} />;
}

===== FILE: src/components/ui/Switch.tsx =====
"use client";
import * as React from "react";
import { cn } from "@/lib/utils";

export function Switch({ checked, onCheckedChange, className }: { checked: boolean; onChe
```

```

checkedChange: (checked: boolean) => void; className?: string }) {
  return (
    <button
      type="button"
      role="switch"
      aria-checked={checked}
      onClick={() => onCheckedChange(!checked)}
      className={cn("peer inline-flex h-6 w-11 shrink-0 cursor-pointer items-center rounded-full border-2 border-transparent transition-colors focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-ring disabled:cursor-not-allowed disabled:opacity-50", checked ? "bg-primary" : "bg-input", className)}
    >
      <span className={cn("pointer-events-none block h-5 w-5 rounded-full bg-background shadow-lg ring-0 transition-transform", checked ? "translate-x-5" : "translate-x-0")} />
    </button>
  );
}

```

===== FILE: src/components/ui/Table.tsx =====

```

import * as React from "react";
import { cn } from "@/lib/utils";

export const Table = ({ className, ...props }: React.HTMLAttributes<HTMLTableElement>) => (
  <div className="w-full overflow-auto">
    <table className={cn("w-full caption-bottom text-sm", className)} {...props} />
  </div>
);
export const TableHeader = ({ className, ...props }: React.HTMLAttributes<HTMLTableSectionElement>) => (
  <thead className={cn("[&_tr]:border-b", className)} {...props} />
);
export const TableBody = ({ className, ...props }: React.HTMLAttributes<HTMLTableSectionElement>) => (
  <tbody className={cn("[&_tr:last-child]:border-0", className)} {...props} />
);
export const TableRow = ({ className, ...props }: React.HTMLAttributes<HTMLTableRowElement>) => (
  <tr className={cn("border-b transition-colors hover:bg-muted/50 data-[state=selected]:bg-muted", className)} {...props} />
);
export const TableHead = ({ className, ...props }: React.ThHTMLAttributes<HTMLTableCellElement>) => (
  <th className={cn("h-12 px-4 text-left align-middle font-medium text-muted-foreground", className)} {...props} />
);
export const TableCell = ({ className, ...props }: React.TdHTMLAttributes<HTMLTableCellElement>) => (
  <td className={cn("p-4 align-middle", className)} {...props} />
);

```

===== FILE: src/components/ui/Tabs.tsx =====

```

"use client";
import * as React from "react";
import { cn } from "@/lib/utils";

interface TabsContextType { activeTab: string; setActiveTab: (id: string) => void; }
const TabsContext = React.createContext<TabsContextType>({ activeTab: "", setActiveTab: () => {} });

export function Tabs({ defaultValue, children, className }: { defaultValue: string; children: React.ReactNode; className?: string }) {
  const [activeTab, setActiveTab] = React.useState(defaultValue);
  return <TabsContext.Provider value={{ activeTab, setActiveTab }}><div className={cn("w-full", className)}>{children}</div></TabsContext.Provider>;
}

export function TabsList({ className, children }: { className?: string; children: React.ReactNode }) {
  return <div className={cn("inline-flex h-10 items-center justify-center rounded-md bg-m

```

```

uted p-1 text-muted-foreground", className)}}>{children}</div>;
}

export function TabsTrigger({ value, className, children }: { value: string; className?:
string; children: React.ReactNode }) {
  const { activeTab, setActiveTab } = React.useContext(TabsContext);
  return (
    <button
      onClick={() => setActiveTab(value)}
      className={cn(
        "inline-flex items-center justify-center whitespace-nowrap rounded-sm px-3 py-1.5
text-sm font-medium transition-all",
        activeTab === value ? "bg-background text-foreground shadow-sm" : "hover:text-for
eground",
        className
      )}
    >
      {children}
    </button>
  );
}

export function TabsContent({ value, className, children }: { value: string; className?:
string; children: React.ReactNode }) {
  const { activeTab } = React.useContext(TabsContext);
  if (activeTab !== value) return null;
  return <div className={cn("mt-2", className)}>{children}</div>;
}

===== FILE: src/components/ui/Textarea.tsx =====
'use client';

import * as React from "react";
import { cn } from "@lib/utils";

export interface TextareaProps extends React.TextareaHTMLAttributes<HTMLTextAreaElement>
{}

const Textarea = React.forwardRef<HTMLTextAreaElement, TextareaProps>(
  ({ className, ...props }, ref) => {
    return (
      <textarea
        className={cn(
          "flex w-full rounded-xl border border-gray-300 bg-white px-4 py-2 text-sm text-
gray-900 shadow-sm transition-all placeholder:text-gray-400 focus-visible:outline-none fo
cus-visible:ring-2 focus-visible:ring-primary/50 focus-visible:border-primary disabled:cu
rsor-not-allowed disabled:opacity-50 min-h-[80px] resize-y",
          className
        )}
        ref={ref}
        {...props}
      />
    );
  }
);
Textarea.displayName = "Textarea";

export { Textarea };
===== FILE: src/components/ui/Toast.tsx =====

===== FILE: src/components/wallet/index.ts =====

===== FILE: src/config/notifications.ts =====
export const notificationTypes = {
  ORDER: "order",
  PAYOUT: "payout",
  COMMISSION: "commission",
  MATCH: "match",
} as const;

```

```
export type NotificationType = (typeof notificationTypes)[keyof typeof notificationTypes]
;
```

```
===== FILE: src/config/payment.ts =====
```

```
export const paymentConfig = {
  currency: "IQD",
  methods: ["cash_on_delivery", "bank_transfer", "card"] as const,
  commissionRate: 0.05, // 5%
};
```

```
===== FILE: src/config/seo.ts =====
```

```
import type { Metadata } from "next";
import { siteConfig } from "../site";
```

```
export const baseMetadata: Metadata = {
  title: {
    default: siteConfig.name,
    template: `%s | ${siteConfig.name}`,
  },
  description: siteConfig.description,
  metadataBase: new URL(siteConfig.url),
  openGraph: {
    type: "website",
    locale: "ar_IQ",
    url: siteConfig.url,
    title: siteConfig.name,
    description: siteConfig.description,
    siteName: siteConfig.name,
  },
};
```

```
===== FILE: src/config/site.ts =====
```

```
export const siteConfig = {
  name: "Jumla",
  description: "Jumla is a platform for sharing and discovering new recipes and food ideas. It's a community of food lovers who share their favorite recipes and food ideas with the world.",
  url: "https://jumlaati.com",
  links: {
    github: "https://github.com/lybha0954-wq/jumlaati",
  },
};
```

```
===== FILE: src/hooks/useAuth.ts =====
```

```
"use client";
import { useEffect, useState } from "react";
import { createClient } from "@lib/supabase/client";
import type { User } from "@types/user";

export function useAuth() {
  const [user, setUser] = useState<User | null>(null);
  const [loading, setLoading] = useState(true);

  useEffect(() => {
    const supabase = createClient();
    supabase.auth.getUser().then(({ data }) => {
      setUser(data.user as unknown as User);
      setLoading(false);
    });
  }, []);

  return { user, loading };
}
```

```
===== FILE: src/hooks/useDebounce.ts =====
```

```
import { useEffect, useState } from "react";

export function useDebounce<T>(value: T, delay: number = 500): T {
  const [debouncedValue, setDebouncedValue] = useState<T>(value);

  useEffect(() => {
```

```
    const timer = setTimeout(() => setDebounceValue(value), delay);
    return () => clearTimeout(timer);
  }, [value, delay]);

  return debounceValue;
}

===== FILE: src/hooks/useLocalStorage.ts =====
"use client";
import { useState } from "react";

export function useLocalStorage<T>(key: string, initialValue: T) {
  const [storedValue, setStoredValue] = useState<T>(() => {
    if (typeof window === "undefined") return initialValue;
    try {
      const item = window.localStorage.getItem(key);
      return item ? JSON.parse(item) : initialValue;
    } catch (error) {
      return initialValue;
    }
  });

  const setValue = (value: T | ((val: T) => T)) => {
    try {
      const valueToStore = value instanceof Function ? value(storedValue) : value;
      setStoredValue(valueToStore);
      if (typeof window !== "undefined") {
        window.localStorage.setItem(key, JSON.stringify(valueToStore));
      }
    } catch (error) {}
  };

  return [storedValue, setValue] as const;
}

===== FILE: src/hooks/useNotification.ts =====
"use client";
import { create } from "zustand";

interface NotificationState {
  notifications: any[];
  setNotifications: (notifications: any[]) => void;
  addNotification: (notification: any) => void;
  unreadCount: number;
}

export const useNotificationStore = create<NotificationState>((set) => ({
  notifications: [],
  unreadCount: 0,
  setNotifications: (notifications) => set({ notifications }),
  addNotification: (notification) => set((state) => ({
    notifications: [notification, ...state.notifications],
    unreadCount: state.unreadCount + 1
  })),
})),
});

===== FILE: src/hooks/usePermission.ts =====
"use client";
import { useUserStore } from "@/lib/stores/userStore";

export function usePermission() {
  const user = useUserStore((state) => state.user);

  const hasPermission = (allowedRoles: string[]) => {
    if (!user) return false;
    return allowedRoles.includes(user.role);
  };

  return { hasPermission, role: user?.role };
}
```

===== FILE: src/hooks/useRealtime.ts =====

```
"use client";
import { useEffect } from "react";
import { createClient } from "@lib/supabase/client";

export function useRealtime(table: string, callback: (payload: any) => void) {
  useEffect(() => {
    const supabase = createClient();
    const channel = supabase
      .channel(`realtime-${table}`)
      .on(
        "postgres_changes",
        { event: "*", schema: "public", table },
        (payload) => callback(payload)
      )
      .subscribe();

    return () => {
      supabase.removeChannel(channel);
    };
  }, [table, callback]);
}
```

===== FILE: src/hooks/useToast.ts =====

```
"use client";
import { create } from "zustand";

interface ToastState {
  isOpen: boolean;
  message: string;
  type: "success" | "error" | "info";
  showToast: (message: string, type?: "success" | "error" | "info") => void;
  closeToast: () => void;
}

export const useToastStore = create<ToastState>((set) => ({
  isOpen: false,
  message: "",
  type: "success",
  showToast: (message, type = "success") => set({ isOpen: true, message, type }),
  closeToast: () => set({ isOpen: false }),
}));

export function useToast() {
  const { showToast, closeToast } = useToastStore();
  return { showToast, closeToast };
}
```

===== FILE: src/lib/archived/cache.ts =====

===== FILE: src/lib/archived/ratelimit.ts =====

===== FILE: src/lib/constants/currencies.ts =====

===== FILE: src/lib/constants/messages.ts =====

```
export const ERROR_MESSAGES = {
  UNAUTHORIZED: "ð°ù\212± ù\205ðµ±ð- ù\204ù\203 ð°ð$ù\204ù\210ðµù\210ù\204",
  NOT_FOUND: "ð$ù\204ð¹ù\206ðµ± ð°ù\212± ù\205ù\210ð-ù\210ð-",
  VALIDATION_ERROR: "ð$ù\204ð¹ù\212ð$ù\206ð$ðª ð$ù\204ù\205ð-ð°ù\204ð© ð°ù\212± ðµð-ù\212ð-ð©",
  SERVER_ERROR: "ð-ð-ð« ð°ð•ð£ ù\201ù\212 ð$ù\204ð°ð$ð-ù\205",
};
```

===== FILE: src/lib/constants/roles.ts =====

```
export const ROLES = {
  ADMIN: "admin",
  DELIVERY: "delivery",
}
```

```
RETAILER: "retailer",
WHOLESALE: "wholesaler",
} as const;
```

```
===== FILE: src/lib/constants/statuses.ts =====
```

```
export const ORDER_STATUS = {
  PENDING: "pending",
  PROCESSING: "processing",
  SHIPPED: "shipped",
  DELIVERED: "delivered",
  CANCELLED: "cancelled",
} as const;
```

```
===== FILE: src/lib/services/addressService.ts =====
```

```
import { createClient } from "@lib/supabase/server";
import type { AddressInput } from "@types/address";
```

```
export const addressService = {
  async getMyAddresses(): Promise<any[]> {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) throw new Error("ð\u2120-ð\u2010 ðªð³ð-ð\u212ð\u204 ð$ð\u204ð-ð&ð\u210ð\u204");

    const { data, error } = await supabase
      .from("addresses")
      .select("*")
      .eq("user_id", user.id)
      .order("created_at", { ascending: false });

    if (error) throw new Error(error.message);
    return data;
  },

  async addAddress(input: AddressInput) {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) throw new Error("ð\u2120-ð\u2010 ðªð³ð-ð\u212ð\u204 ð$ð\u204ð-ð&ð\u210ð\u204");

    const { data, error } = await supabase
      .from("addresses")
      .insert({ ...input, user_id: user.id })
      .select()
      .single();

    if (error) throw new Error(error.message);
    return data;
  },
};
```

```
===== FILE: src/lib/services/analyticsService.ts =====
```

```
import { createClient } from "@lib/supabase/server";
```

```
export const analyticsService = {
  // 0x0-0x2050x2040x212 0x2040x2050x2120x10x0a
  async getTotalRevenue(): Promise<number> {
    const supabase = await createClient();
    const { data, error } = await supabase
      .from("orders")
      .select("total")
      .eq("status", "delivered");

    if (error) throw new Error(error.message);
    return data.reduce((sum, order) => sum + order.total, 0);
  },
}
```

```
// 010-00 0S0\2040\205030a000-0\2050\2120\206 0-030" 0S0\2040-0\2100±
async getUsersCountByRole(role: string): Promise<number> {
  const supabase = await createClient();
  const { count } = await supabase
    .from("users")
```

```

        .select("*", { count: 'exact', head: true })
        .eq("role", role);

    return count || 0;
}
};

===== FILE: src/lib/services/authService.ts =====
import { createClient } from "@lib/supabase/server";

export const authService = {
    // 0-0$0\20400 0\2040^0-0-0\2120- 0\2060\2100^ 0$0\2040¥0-000$0\204 (0"0±0\2120- 0£0
    \210 0\2070$0^0\201)
    getLoginType(identifier: string): "email" | "phone" {
        return identifier.includes("@") ? "email" : "phone";
    },

    async login(identifier: string, password: string) {
        const supabase = await createClient();
        const type = this.getLoginType(identifier);

        const credentials = type === "email"
            ? { email: identifier, password }
            : { phone: identifier, password };

        const { data, error } = await supabase.auth.signInWithPassword(credentials);
        if (error) throw new Error(error.message);
        return data;
    }
};

===== FILE: src/lib/services/chatService.ts =====
import { createClient } from "@lib/supabase/server";

export const chatService = {
    async getConversation(otherUserId: string) {
        const supabase = await createClient();
        const { data: { user } } = await supabase.auth.getUser();
        if (!user) throw new Error("0\2120-0" 0^0^0-0\2120\204 0$0\2040-000\2100\204");

        const { data, error } = await supabase
            .from("chat_messages")
            .select("*")
            .or(`and(sender_id.eq.${user.id},receiver_id.eq.${otherUserId}),and(sender_id.eq.${
otherUserId},receiver_id.eq.${user.id})`)
            .order("created_at", { ascending: true });

        if (error) throw new Error(error.message);
        return data;
    },

    async sendMessage(receiverId: string, message: string) {
        const supabase = await createClient();
        const { data: { user } } = await supabase.auth.getUser();
        if (!user) throw new Error("0\2120-0" 0^0^0-0\2120\204 0$0\2040-000\2100\204");

        const { data, error } = await supabase
            .from("chat_messages")
            .insert({ sender_id: user.id, receiver_id: receiverId, message })
            .select()
            .single();

        if (error) throw new Error(error.message);
        return data;
    }
};

===== FILE: src/lib/services/commissionService.ts =====
import { createClient } from "@lib/supabase/server";
import { logger } from "@lib/utils/logger";

```

```

import { paymentConfig } from "@config/payment";
import type { Commission } from "@types/commission";

export const commissionService = {
  calculateCommission(orderTotal: number): number {
    return orderTotal * paymentConfig.commissionRate;
  },

  async createCommission(orderId: string, retailerId: string, orderTotal: number) {
    const supabase = await createClient();
    const amount = this.calculateCommission(orderTotal);

    const { data, error } = await supabase
      .from("commissions")
      .insert({
        order_id: orderId,
        retailer_id: retailerId,
        amount,
        status: "pending"
      })
      .select()
      .single();

    if (error) {
      logger.error("Error creating commission", error);
      throw new Error(error.message);
    }
    return data as Commission;
  },

  async getMyCommissions(): Promise<Commission[]> {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();

    const { data, error } = await supabase
      .from("commissions")
      .select("*")
      .eq("retailer_id", user?.id);

    if (error) throw new Error(error.message);
    return data as Commission[];
  }
};

===== FILE: src/lib/services/couponService.ts =====
import { createClient } from "@lib/supabase/server";

export const couponService = {
  async validateCoupon(code: string) {
    const supabase = await createClient();
    const { data, error } = await supabase
      .from("coupons")
      .select("*")
      .eq("code", code)
      .eq("is_active", true)
      .single();

    if (error || !data) throw new Error("ð\203ð\210ð- ð$ð\204ðððµð\205 ð°ð\212ð± ðµð$ð\204ð-");
    if (data.used_count >= data.max_uses) throw new Error("ð°ð\205 ð$ð³ð°ð\206ð\201ð$ð- ð\207ð°ð$ ð$ð\204ð\203ð\210ð-");
    return data;
  },

  async incrementUsage(couponId: string) {
    const supabase = await createClient();
    const { data: existingCoupon } = await supabase
      .from("coupons")
      .select("used_count")
      .eq("id", couponId)

```

```
.single();

const count = existingCoupon?.used_count || 0;
const { error } = await supabase
    .from("coupons")
    .update({ used_count: count + 1 })
    .eq("id", couponId);

if (error) throw new Error(error.message);
},

async getAllCoupons() {
    const supabase = await createClient();
    const { data, error } = await supabase
        .from("coupons")
        .select("*")
        .order("created_at", { ascending: false });

    if (error) throw new Error(error.message);
    return data;
},

async createCoupon(code: string, discount_percent: number, max_uses: number) {
    const supabase = await createClient();
    const { data, error } = await supabase
        .from("coupons")
        .insert({ code, discount_percent, max_uses })
        .select()
        .single();

    if (error) throw new Error(error.message);
    return data;
}
};

===== FILE: src/lib/services/deliveryService.ts =====
import { createClient } from "@lib/supabase/server";
import type { Order } from "@types/order";

export const deliveryService = {
    // Ø-Ù\204Ø" Ø$Ù\204Ø•Ù\204Ø"Ø$Øª Ø$Ù\204Ù\205Ø³Ù\206Ø~Ø@ Ø¥Ù\204Ù\211 Ø$Ù\204Ù\205Ù\206Ø~Ù\210Ø" Ø£Ù\210 Ø$Ù\204Ù\205ØªØ$Ø-Ø@ Ù\204Ù\207
    async getMyTasks(): Promise<Order[]> {
        const supabase = await createClient();
        const { data: { user } } = await supabase.auth.getUser();
        if (!user) throw new Error("Ù\212Ø¬Ø" ØªØ³Ø¬Ù\212Ù\204 Ø$Ù\204Ø¬Ø@Ù\210Ù\204");

        const { data, error } = await supabase
            .from("orders")
            .select("*")
            .eq("delivery_id", user.id)
            .or("status.eq.processing,status.eq.shipped")
            .order("created_at", { ascending: false });

        if (error) throw new Error(error.message);
        return data as Order[];
    },

    // ØªØ-Ø¬Ù\212Ø« Ø-Ø$Ù\204Ø@ Ø$Ù\204ØªÙ\210ØµÙ\212Ù\204
    async updateDeliveryStatus(orderId: string, status: "shipped" | "delivered") {
        const supabase = await createClient();
        const { error } = await supabase
            .from("orders")
            .update({ status })
            .eq("id", orderId);

        if (error) throw new Error(error.message);
        return { success: true };
    }
};
```

===== FILE: src/lib/services/matchingService.ts =====

```
import { createClient } from "@lib/supabase/server";

export const matchingService = {
  // 0x00000000; 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000
  0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000
  async createMatchRequest(payload: any) {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();

    const { data, error } = await supabase
      .from("matches")
      .insert({ ...payload, requester_id: user?.id, status: "pending" })
      .select()
      .single();

    if (error) throw new Error(error.message);
    return data;
  },

  // 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000
  async acceptMatch(matchId: string) {
    const supabase = await createClient();
    const { error } = await supabase
      .from("matches")
      .update({ status: "approved" })
      .eq("id", matchId);

    if (error) throw new Error(error.message);
  }
};
```

===== FILE: src/lib/services/notificationService.ts =====

```
import { sendEmail } from "@lib/utils/email";
import { sendSMS } from "@lib/utils/sms";
import { logger } from "@lib/utils/logger";
import type { NotificationType } from "@config/notifications";

interface NotificationPayload {
  userId: string;
  type: NotificationType;
  title: string;
  message: string;
  email?: string;
  phone?: string;
}

export const notificationService = {
  // 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000
  0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000
  async sendInApp(payload: NotificationPayload): Promise<void> {
    logger.info(`[Notification] Sending in-app to user ${payload.userId}: ${payload.title}`);
    // 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000
    0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000
    // await supabase.from('notifications').insert({...})
  },

  // 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000
  0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000
  async sendEmail(payload: NotificationPayload): Promise<void> {
    if (!payload.email) return;
    const html = `<h1>${payload.title}</h1><p>${payload.message}</p>`;
    try {
      await sendEmail(payload.email, payload.title, html);
    } catch (error) {
      logger.error("Failed to send notification email", error);
    }
  },
};
```

```
// Ø¥Ø±Ø³Ø$Ù\204 Ø¥Ø´Ø¹Ø$Ø± Ø¹Ø¨Ø± Ø±Ø³Ø$Ù\204Ø© Ù\206ØµÙ\212Ø© SMS
async sendSMS(payload: NotificationPayload): Promise<void> {
  if (!payload.phone) return;
  try {
    await sendSMS(payload.phone, `${payload.title}: ${payload.message}`);
  } catch (error) {
    logger.error("Failed to send notification SMS", error);
  }
},

// Ø¥Ø±Ø³Ø$Ù\204 Ø¥Ø´Ø¹Ø$Ø± Ù\205ØªØ¹Ø¨Ø¨ Ø$Ù\204Ù\202Ù\206Ù\210Ø$Øª (Ù\203Ù\204 Ø$Ù\204Ù\210Ø³Ø$Ø;Ù\204 Ø$Ù\204Ù\205ØªØ$Ø-Ø©)
async notify(payload: NotificationPayload): Promise<void> {
  await this.sendInApp(payload);
  await this.sendEmail(payload);
  await this.sendSMS(payload);
}
};

===== FILE: src/lib/services/offerService.ts =====
import { createClient } from "@lib/supabase/server";
import type { Offer } from "@types/offer";

export const offerService = {
  async getActiveOffers(): Promise<Offer[]> {
    const supabase = await createClient();
    const { data, error } = await supabase
      .from("offers")
      .select("*")
      .eq("is_active", true)
      .order("created_at", { ascending: false });

    if (error) throw new Error(error.message);
    return data;
  }
};

===== FILE: src/lib/services/orchestrationService.ts =====
import { retailerService } from "../retailerService";
import { commissionService } from "../commissionService";
import { notificationService } from "../notificationService";
import { deliveryService } from "../deliveryService";
import { logger } from "@lib/utils/logger";

export const orchestrationService = {
  async createFullOrder(orderData: any) {
    try {
      const order = await retailerService.createOrder(orderData);
      await commissionService.createCommission(order.id, orderData.retailerId, orderData.total);
      await notificationService.notify({
        userId: orderData.wholesalerId,
        type: "order",
        title: "Ø•Ù\204Ø¨ Ø¬Ø¨Ù\212Ø¨ Ù\205Ù\206 ØªØ$Ø¬Ø± ØªØ¬Ø²Ø|Ø©!",
        message: `Ø•Ù\204Ø¨ Ø¨Ù\202Ù\212Ù\205Ø© ${orderData.total.toLocaleString()} Ø¬.Ø¹ Ø¨Ø$Ù\206ØªØ,Ø$Ø± Ù\205Ø¹Ø$Ù\204Ø¬ØªÙ\203.`,
      });
      logger.info("Order created successfully", { orderId: order.id });
      return order;
    } catch (error) {
      logger.error("Orchestration failed", error);
      throw new Error("Ù\201Ø´Ù\204 Ù\201Ù\212 Ø¥ØªÙ\205Ø$Ù\205 Ø¹Ù\205Ù\204Ù\212Ø© Ø$Ù\204Ø•Ù\204Ø¨");
    }
  },

  async updateDeliveryStatus(orderId: string, status: "shipped" | "delivered", deliveryId: string) {
    try {

```

```
    await deliveryService.updateDeliveryStatus(orderId, status);
  } catch (error) {
    logger.error("Orchestration failed during delivery status update", error);
    throw new Error("ð\201ð'ð\204 ð\201ð\212 ðªð-ð-ð\212ð« ð-ð$ð\204ð© ð$ð\204ðªð\210ðµð\212ð\204.");
  }
};

===== FILE: src/lib/services/orderService.ts =====
import { createClient } from "@lib/supabase/server";
import type { Order } from "@types/order";

export const orderService = {
  // ð¹ð±ð¶ ðªð\201ð$ðµð\212ð\204 ð•ð\204ð" ð\210ð$ð-ð-
  async getOrderById(id: string): Promise<Order> {
    const supabase = await createClient();
    const { data, error } = await supabase
      .from("orders")
      .select("*")
      .eq("id", id)
      .single();

    if (error) throw new Error("ð$ð\204ð•ð\204ð" ð°ð\212ð± ð\205ð\210ð-ð\210ð-");
    return data as Order;
  },

  // ð-ð\204ð" ð$ð\204ð•ð\204ð"ð$ðª ð\205ð\206 ð\205ð\206ð,ð\210ð± ð$ð\204ð£ð-ð\205ð\206
  (ð\203ð\204 ð$ð\204ð•ð\204ð"ð$ðª)
  async getAllOrders(): Promise<Order[]> {
    const supabase = await createClient();
    const { data, error } = await supabase
      .from("orders")
      .select("*")
      .order("created_at", { ascending: false });

    if (error) throw new Error(error.message);
    return data as Order[];
  }
};

===== FILE: src/lib/services/paymentService.ts =====
import { createClient } from "@lib/supabase/server";

export const paymentService = {
  // ð¥ð\206ð'ð$ð; ð¹ð\205ð\204ð\212ð© ð-ð\201ð¹ ð-ð-ð\212ð-ð© (ð\205ð¹ ð-ð¹ð\205 ð$ð\204
  ð-ð\201ð¹ ð¹ð\206ð- ð$ð\204ð$ð³ðªð\204ð$ð\205 ð\203ð©ð\212ð$ð± ð$ð\201ðªð±ð$ð¶ð\212)
  async createPayment(orderId: string, amount: number, gateway: string = "cod") {
    const supabase = await createClient();

    const { data, error } = await supabase
      .from("payments")
      .insert({ order_id: orderId, amount, gateway, status: "pending" })
      .select()
      .single();

    if (error) throw new Error(error.message);
    return data;
  },

  // ð\205ð¹ð$ð\204ð-ð© ð±ð- ð"ð\210ð$ð"ð© ð$ð\204ð-ð\201ð¹ (Webhook)
  async handleWebhook(paymentId: string, status: string, transactionId?: string) {
    const supabase = await createClient();

    const updates: any = { status };
    if (transactionId) updates.provider_transaction_id = transactionId;

    const { data, error } = await supabase
      .from("payments")
      .update(updates)
```

```

        .eq("id", paymentId)
        .select()
        .single();

    if (error) throw new Error(error.message);

    // 0^0-0-Û\2120« 0-0$Û\2040© 0$Û\2040•Û\2040" 0¥Û\204Û\211 "Û\2050-Û\201Û\2100¹" 0¥0°
    0$ Û\2060-0-0^a 0$Û\2040¹Û\205Û\204Û\2120©
    if (status === "success") {
        await supabase.from("orders").update({ status: "paid" }).eq("id", data.order_id);
    }

    return data;
}
};

===== FILE: src/lib/services/payoutService.ts =====
import { createClient } from "@lib/supabase/server";

export const payoutService = {
    async getMyPayouts() {
        const supabase = await createClient();
        const { data: { user } } = await supabase.auth.getUser();
        if (!user) throw new Error("Unauthorized");

        const { data, error } = await supabase
            .from("payouts")
            .select("*")
            .eq("user_id", user.id)
            .order("created_at", { ascending: false });

        if (error) throw new Error(error.message);
        return data;
    }
};

===== FILE: src/lib/services/phoneAuthService.ts =====
import { createClient } from "@lib/supabase/client";

export const phoneAuthService = {
    async sendOtp(phone: string) {
        const supabase = await createClient();
        const { error } = await supabase.auth.signInWithOtp({
            phone: phone,
            options: {
                shouldCreateUser: true,
            },
        });
        if (error) throw new Error(error.message);
        return { success: true };
    },

    async verifyOtp(phone: string, token: string) {
        const supabase = await createClient();
        const { data, error } = await supabase.auth.verifyOtp({
            phone: phone,
            token: token,
            type: "sms",
        });
        if (error) throw new Error(error.message);
        return data;
    }
};

===== FILE: src/lib/services/pointsService.ts =====
import { createClient } from "@lib/supabase/server";

export const pointsService = {
    async getMyPoints() {
        const supabase = await createClient();

```

```
const { data: { user } } = await supabase.auth.getUser();
if (!user) throw new Error("Unauthorized");

const { data, error } = await supabase
  .from("points_transactions")
  .select("*")
  .eq("user_id", user.id)
  .order("created_at", { ascending: false });

if (error) throw new Error(error.message);
return data;
}
};

===== FILE: src/lib/services/productService.ts =====
import { createClient } from "@lib/supabase/server";

export const productService = {
  async getAllProducts(): Promise<any[]> {
    const supabase = await createClient();
    const { data, error } = await supabase.from("products").select("*").order("created_at", { ascending: false });
    if (error) throw new Error(error.message);
    return data || [];
  }
};

===== FILE: src/lib/services/refundService.ts =====
import { createClient } from "@lib/supabase/server";

export const refundService = {
  async createRefund(orderId: string, reason: string) {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) throw new Error("ð\u2120-ð\u2120 ð³ð-ð\u2120\u2040 $ð\u2040ð-ðð\u210ð\u2040");

    const { data, error } = await supabase
      .from("refunds")
      .insert({ order_id: orderId, requested_by: user.id, reason })
      .select()
      .single();

    if (error) throw new Error(error.message);
    return data;
  },

  async getMyRefunds() {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) throw new Error("ð\u2120-ð\u2120 ð³ð-ð\u2120\u2040 $ð\u2040ð-ðð\u210ð\u2040");

    const { data, error } = await supabase
      .from("refunds")
      .select("*")
      .eq("requested_by", user.id)
      .order("created_at", { ascending: false });

    if (error) throw new Error(error.message);
    return data;
  }
};

===== FILE: src/lib/services/relationshipService.ts =====
import { createClient } from "@lib/supabase/server";

export const relationshipService = {
  async sendRequest(data: { wholesalerId?: string; retailerId?: string; deliveryId?: string }) {
    const supabase = await createClient();
    const { data: relationship, error } = await supabase
```

```
.from('relationships')
.insert({
  wholesaler_id: data.wholesalerId || null,
  retailer_id: data.retailerId || null,
  delivery_id: data.deliveryId || null,
  status: 'pending'
})
.select()
.single();

if (error) throw new Error(error.message);
return relationship;
},

async acceptRequest(relationshipId: string) {
  const supabase = await createClient();
  const { data, error } = await supabase
    .from('relationships')
    .update({ status: 'active' })
    .eq('id', relationshipId)
    .select()
    .single();

  if (error) throw new Error(error.message);
  return data;
},

async rejectRequest(relationshipId: string) {
  const supabase = await createClient();
  const { error } = await supabase
    .from('relationships')
    .update({ status: 'suspended' })
    .eq('id', relationshipId);

  if (error) throw new Error(error.message);
},

async getPendingRequests() {
  const supabase = await createClient();
  const { data: { user } } = await supabase.auth.getUser();
  if (!user) throw new Error("Unauthorized");

  const { data, error } = await supabase
    .from('relationships')
    .select('*', retailer:retailer_id(id, name, email), wholesaler:wholesaler_id(id, name, email), delivery:delivery_id(id, name, email)')
    .or(`wholesaler_id.eq.${user.id},retailer_id.eq.${user.id},delivery_id.eq.${user.id}`)
    .eq('status', 'pending');

  if (error) throw new Error(error.message);
  return data;
}
};

===== FILE: src/lib/services/retailerService.ts =====
import { createClient } from "@lib/supabase/server";
import { logger } from "@lib/utils/logger";
import type { Product } from "@types/product";
import type { Order } from "@types/order";

export const retailerService = {
  async getAvailableProducts(): Promise<Product[]> {
    const supabase = await createClient();
    const { data, error } = await supabase
      .from("products")
      .select("*")
      .eq("status", "active")
      .order("created_at", { ascending: false });
```

```

    if (error) {
      logger.error("Retailer: Error fetching products", error);
      throw new Error("Û\201Ø'Û\204 Û\201Û\212 Ø-Û\204Ø" Ø$Û\204Û\205Û\206ØªØ¬Ø$Øª");
    }
    return data as Product[];
  },

  async createOrder(orderData: any): Promise<Order> {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) throw new Error("Û\212Ø-Ø" ØªØ³Ø-Û\212Û\204 Ø$Û\204Ø-Ø@Û\210Û\204");

    const { data, error } = await supabase
      .from("orders")
      .insert({ ...orderData, user_id: user.id, status: "pending" })
      .select()
      .single();

    if (error) throw new Error(error.message);
    return data as Order;
  },

  async getMyOrders(): Promise<Order[]> {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) throw new Error("Û\212Ø-Ø" ØªØ³Ø-Û\212Û\204 Ø$Û\204Ø-Ø@Û\210Û\204");

    const { data, error } = await supabase
      .from("orders")
      .select("*")
      .eq("user_id", user.id)
      .order("created_at", { ascending: false });

    if (error) throw new Error(error.message);
    return data as Order[];
  }
};

===== FILE: src/lib/services/reviewService.ts =====
import { createClient } from "@lib/supabase/server";
import type { ReviewInput } from "@types/review";

export const reviewService = {
  async getProductReviews(productId: string) {
    const supabase = await createClient();
    const { data, error } = await supabase
      .from("reviews")
      .select("*, users(name)")
      .eq("product_id", productId)
      .order("created_at", { ascending: false });

    if (error) throw new Error(error.message);
    return data;
  },

  async createReview(input: ReviewInput) {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) throw new Error("Û\212Ø-Ø" ØªØ³Ø-Û\212Û\204 Ø$Û\204Ø-Ø@Û\210Û\204");

    const { data, error } = await supabase
      .from("reviews")
      .insert({ ...input, user_id: user.id })
      .select()
      .single();

    if (error) throw new Error(error.message);
    return data;
  }
};

```

===== FILE: src/lib/services/walletService.ts =====

```
import { createClient } from "@lib/supabase/server";

export const walletService = {
  async getMyWallet() {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) throw new Error("ð\212ð-ð" ðªð³ð-ð\212ð\204 ð$ð\204ð-ð@ð\210ð\204");

    const { data, error } = await supabase
      .from("wallets")
      .select("*")
      .eq("user_id", user.id)
      .single();

    if (error && error.code !== 'PGRST116') throw new Error(error.message);
    return data;
  },

  async getMyPoints() {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) throw new Error("ð\212ð-ð" ðªð³ð-ð\212ð\204 ð$ð\204ð-ð@ð\210ð\204");

    const { data, error } = await supabase
      .from("points_transactions")
      .select("*")
      .eq("user_id", user.id)
      .order("created_at", { ascending: false });

    if (error) throw new Error(error.message);
    return data;
  }
};
```

===== FILE: src/lib/services/whatsappService.ts =====

```
import { createClient } from "@lib/supabase/server";

export const whatsappService = {
  async getPhoneById(userId: string) {
    const supabase = await createClient();
    const { data, error } = await supabase.from("users").select("phone").eq("id", userId)
      .single();
    if (error) throw new Error(error.message);
    return data?.phone;
  },

  buildOrderMessage(order: any, items: any[], total: number) {
    let message = `ð•ð\204ð" ð-ð-ð\212ð- ð±ð\202ð\205: ${order.id}\n`;
    message += `ð$ð\204ð¹ð\206ð\210ð$ð\206: ${order.address}\n`;
    message += `-----\n`;
    items.forEach((item: any) => {
      message += `${item.name} Ã\227 ${item.quantity} = ${item.price * item.quantity} ð-.
ð¹\n`;
    });
    message += `-----\n`;
    message += `ð$ð\204ð¥ð-ð\205ð$ð\204ð\212: ${total} ð-.ð¹`;
    return encodeURIComponent(message);
  }
};
```

===== FILE: src/lib/services/wholesaleService.ts =====

```
import { createClient } from "@lib/supabase/server";
import type { Product, ProductInput } from "@types/product";

export const wholesaleService = {
  async createProduct(input: ProductInput): Promise<Product> {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
```

```
    if (!user) throw new Error("Û\212Ø¬Ø" ØªØ³Ø¬Û\212Û\204 Ø$Û\204Ø¬Ø@Û\210Û\204");

    const { data, error } = await supabase
      .from("products")
      .insert({ ...input, owner_id: user.id, is_active: true })
      .select()
      .single();

    if (error) throw new Error(error.message);
    return data as Product;
  },

  async getMyProducts(): Promise<Product[]> {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) throw new Error("Û\212Ø¬Ø" ØªØ³Ø¬Û\212Û\204 Ø$Û\204Ø¬Ø@Û\210Û\204");

    const { data, error } = await supabase
      .from("products")
      .select("*")
      .eq("owner_id", user.id)
      .order("created_at", { ascending: false });

    if (error) throw new Error(error.message);
    return data as Product[];
  },

  async updateProduct(productId: string, updates: any): Promise<Product> {
    const supabase = await createClient();
    const { data, error } = await supabase
      .from("products")
      .update(updates)
      .eq("id", productId)
      .select()
      .single();

    if (error) throw new Error(error.message);
    return data as Product;
  },

  async deleteProduct(productId: string): Promise<void> {
    const supabase = await createClient();
    const { error } = await supabase
      .from("products")
      .delete()
      .eq("id", productId);
    if (error) throw new Error(error.message);
  },

  async getMyOrders(): Promise<any[]> {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) throw new Error("Unauthorized");

    const { data, error } = await supabase
      .from("orders")
      .select("*")
      .eq("wholesaler_id", user.id)
      .order("created_at", { ascending: false });

    if (error) throw new Error(error.message);
    return data;
  }
};

==== FILE: src/lib/services/wishlistService.ts ====
import { createClient } from "@lib/supabase/server";

export const wishlistService = {
  async getMyWishlist() {
```

```

    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) throw new Error("ð\212ð-ð" ðªð³ð-ð\212ð\204 ð$ð\204ð-ð@ð\210ð\204");

    const { data, error } = await supabase
      .from("wishlist")
      .select("*, products(*)")
      .eq("user_id", user.id)
      .order("created_at", { ascending: false });

    if (error) throw new Error(error.message);
    return data;
  },

  async addToWishlist(productId: string) {
    const supabase = await createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) throw new Error("ð\212ð-ð" ðªð³ð-ð\212ð\204 ð$ð\204ð-ð@ð\210ð\204");

    const { data, error } = await supabase
      .from("wishlist")
      .insert({ user_id: user.id, product_id: productId })
      .select()
      .single();

    if (error) throw new Error(error.message);
    return data;
  },

  async removeFromWishlist(id: string) {
    const supabase = await createClient();
    const { error } = await supabase.from("wishlist").delete().eq("id", id);
    if (error) throw new Error(error.message);
  }
};

===== FILE: src/lib/stores/cartStore.ts =====
import { create } from "zustand";
import { persist } from "zustand/middleware";

interface CartItem {
  productId: string;
  wholesalerId: string;
  name: string;
  price: number;
  quantity: number;
  image?: string;
}

interface CartState {
  items: CartItem[];
  addItem: (item: CartItem) => void;
  removeItem: (productId: string) => void;
  updateQuantity: (productId: string, quantity: number) => void;
  clearCart: () => void;
  getTotal: () => number;
  getGroupedItems: () => { [wholesalerId: string]: CartItem[] };
}

export const useCartStore = create<CartState>() (
  persist(
    (set, get) => ({
      items: [],
      addItem: (item) =>
        set((state) => {
          const existing = state.items.find(
            (i) => i.productId === item.productId && i.wholesalerId === item.wholesalerId
          );
          if (existing) {
            return {

```

```

        items: state.items.map((i) =>
          i.productId === item.productId && i.wholesalerId === item.wholesalerId
            ? { ...i, quantity: i.quantity + item.quantity }
            : i
        ),
      };
    }
    return { items: [...state.items, item] };
  })),
  removeItem: (productId) =>
    set((state) => ({
      items: state.items.filter((i) => i.productId !== productId),
    })),
  updateQuantity: (productId, quantity) =>
    set((state) => ({
      items: state.items.map((i) =>
        i.productId === productId ? { ...i, quantity } : i
      ),
    })),
  clearCart: () => set({ items: [] }),
  getTotal: () => get().items.reduce((sum, item) => sum + item.price * item.quantity,
0),
  getGroupedItems: () => {
    const groups: { [wholesalerId: string]: CartItem[] } = {};
    get().items.forEach((item) => {
      if (!groups[item.wholesalerId]) {
        groups[item.wholesalerId] = [];
      }
      groups[item.wholesalerId].push(item);
    });
    return groups;
  },
 )),
  { name: "jumla-cart-storage" }
)
);

===== FILE: src/lib/stores/commissionStore.ts =====
import { create } from "zustand";
import type { Commission } from "@types/commission";

interface CommissionState {
  commissions: Commission[];
  setCommissions: (commissions: Commission[]) => void;
}

export const useCommissionStore = create<CommissionState>((set) => ({
  commissions: [],
  setCommissions: (commissions) => set({ commissions }),
})));

===== FILE: src/lib/stores/matchingStore.ts =====

===== FILE: src/lib/stores/notificationStore.ts =====
import { create } from "zustand";
import { createClient } from "@lib/supabase/client";

interface Notification {
  id: string;
  title: string;
  message: string;
  is_read: boolean;
  created_at: string;
}

interface NotificationState {
  notifications: Notification[];
  unreadCount: number;
  fetchNotifications: () => Promise<void>;
  markAsRead: (id: string) => Promise<void>;
}

```

```
}

export const useNotificationStore = create<NotificationState>((set, get) => ({
  notifications: [],
  unreadCount: 0,

  fetchNotifications: async () => {
    const supabase = createClient();
    const { data: { user } } = await supabase.auth.getUser();
    if (!user) return;

    const { data } = await supabase
      .from("notifications")
      .select("*")
      .eq("user_id", user.id)
      .order("created_at", { ascending: false });

    if (data) {
      set({
        notifications: data,
        unreadCount: data.filter((n) => !n.is_read).length,
      });
    }
  },

  markAsRead: async (id: string) => {
    const supabase = createClient();
    await supabase.from("notifications").update({ is_read: true }).eq("id", id);
    get().fetchNotifications();
  },
}));

===== FILE: src/lib/stores/requestStore.ts =====
import { create } from "zustand";

interface RequestState {
  pendingRequests: number;
  setPendingRequests: (count: number) => void;
  incrementRequests: () => void;
  decrementRequests: () => void;
}

export const useRequestStore = create<RequestState>((set) => ({
  pendingRequests: 0,
  setPendingRequests: (count) => set({ pendingRequests: count }),
  incrementRequests: () => set((state) => ({ pendingRequests: state.pendingRequests + 1 })),
  decrementRequests: () => set((state) => ({ pendingRequests: Math.max(0, state.pendingRequests - 1) })),
}));

===== FILE: src/lib/stores/userStore.ts =====
import { create } from "zustand";
import type { User } from "@types/user";

interface UserState {
  user: User | null;
  setUser: (user: User | null) => void;
  logout: () => void;
}

export const useUserStore = create<UserState>((set) => ({
  user: null,
  setUser: (user) => set({ user }),
  logout: () => set({ user: null }),
}));

===== FILE: src/lib/supabase/client.ts =====
import { createBrowserClient } from '@supabase/ssr';
```

```
export function createClient() {
  return createBrowserClient(
    process.env.NEXT_PUBLIC_SUPABASE_URL!,
    process.env.NEXT_PUBLIC_SUPABASE_ANON_KEY!
  )
}

===== FILE: src/lib/supabase/server.ts =====
import { createServerClient } from '@supabase/ssr'
import { cookies } from 'next/headers'

export async function createClient() {
  const cookieStore = await cookies()
  return createServerClient(
    process.env.NEXT_PUBLIC_SUPABASE_URL!,
    process.env.NEXT_PUBLIC_SUPABASE_ANON_KEY!,
    {
      cookies: {
        getAll() { return cookieStore.getAll() },
        setAll(cookiesToSet) {
          try {
            cookiesToSet.forEach(({ name, value, options }) => cookieStore.set(name, value, options))
          } catch {}
        },
      },
    }
  )
}

===== FILE: src/lib/utils.ts =====
import { type ClassValue, clsx } from "clsx";
import { twMerge } from "tailwind-merge";

export function cn(...inputs: ClassValue[]) {
  return twMerge(clsx(inputs));
}

===== FILE: src/lib/utils/currency.ts =====
export function formatCurrency(amount: number): string {
  return new Intl.NumberFormat("ar-IQ", {
    style: "currency",
    currency: "IQD",
    minimumFractionDigits: 0,
  }).format(amount);
}

===== FILE: src/lib/utils/date.ts =====
export function formatDate(date: string | Date): string {
  return new Intl.DateTimeFormat("ar-IQ", {
    year: "numeric",
    month: "long",
    day: "numeric",
  }).format(new Date(date));
}

export function formatTime(date: string | Date): string {
  return new Intl.DateTimeFormat("ar-IQ", {
    hour: "2-digit",
    minute: "2-digit",
  }).format(new Date(date));
}

export function timeAgo(date: string | Date): string {
  const seconds = Math.floor((new Date().getTime() - new Date(date).getTime()) / 1000);
  let interval = seconds / 31536000;
  if (interval > 1) return Math.floor(interval) + " Ø³Ù\20600 Ù\205010ª";
  interval = seconds / 2592000;
  if (interval > 1) return Math.floor(interval) + " Ø´Ù\2070± Ù\20501Ù\211";
  interval = seconds / 86400;
```

```
    if (interval > 1) return Math.floor(interval) + " Û\212Û\210Û\205 Û\205Û\211";
    interval = seconds / 3600;
    if (interval > 1) return Math.floor(interval) + " Ø³Ø$Ø¹Ø© Û\205Û\210";
    interval = seconds / 60;
    if (interval > 1) return Math.floor(interval) + " Ø\202Û\212Û\202Ø© Û\205Û\210";
    return Math.floor(seconds) + " Ø«Ø$Û\206Û\212Ø© Û\205Û\210";
}

function formatTimeAgo(...args: any[]): any {
    // eslint-disable-next-line no-console
    console.warn('Placeholder: formatTimeAgo is not implemented yet.', args);
    return null;
}

export { formatTimeAgo };
===== FILE: src/lib/utils/email.ts =====
export async function sendEmail(to: string, subject: string, html: string) {
    // Û\212Û\205Û\203Û\206Û\203 Ø±Ø"Ø• Û\207Ø°Û\207 Ø$Û\204Ø'Ø$Û\204Ø© Û\205Ø¹ Resend Ø£Û
\210 SendGrid Ø£Û\210 Supabase Edge Functions Û\204Ø$Ø-Û\202Ø$Û\213
    console.log(`[EMAIL] To: ${to}, Subject: ${subject}`);
    return { success: true };
}

===== FILE: src/lib/utils/export.ts =====
export function exportToCSV(data: any[], filename: string) {
    if (!data.length) return;
    const headers = Object.keys(data[0]);
    const csv = [
        headers.join(","),
        ...data.map(row => headers.map(h => JSON.stringify(row[h] ?? "")).join(",")),
    ].join("\n");

    const blob = new Blob([csv], { type: "text/csv;charset=utf-8;" });
    const link = document.createElement("a");
    link.href = URL.createObjectURL(blob);
    link.download = `${filename}.csv`;
    link.click();
}

===== FILE: src/lib/utils/logger.ts =====
export const logger = {
    info: (message: string, data?: any) => {
        console.log(`[INFO] ${new Date().toISOString()} - ${message}`, data ?? "");
    },
    error: (message: string, error?: any) => {
        console.error(`[ERROR] ${new Date().toISOString()} - ${message}`, error ?? "");
    },
};

===== FILE: src/lib/utils/sms.ts =====
export async function sendSMS(phone: string, message: string) {
    // Ø±Ø"Ø• Û\205Ø¹ Û\205Ø²Û\210Ø` SMS Ø¹Ø±Ø$Û\202Û\212 Ø£Û\210 Twilio Û\204Ø$Ø-Û\202Ø$Û
\213
    console.log(`[SMS] To: ${phone}, Message: ${message}`);
    return { success: true };
}

===== FILE: src/lib/validations/address.schema.ts =====
import * as z from "zod";

export const addressSchema = z.object({
    title: z.string().min(2, "Ø¹Û\206Û\210Ø$Û\206 Û\202ØµÛ\212Ø± Ø¬Ø'Ø$Û\213"),
    city: z.string().min(2, "Ø$Û\204Û\205Ø'Û\212Û\206Ø© Û\205Ø•Û\204Û\210Ø'Ø©"),
    district: z.string().min(2, "Ø$Û\204Û\205Û\206Ø•Û\202Ø© Û\205Ø•Û\204Û\210Ø'Ø©"),
    street: z.string().min(2, "Ø$Û\204Ø'Ø$Ø±Ø¹ Û\205Ø•Û\204Û\210Ø'"),
    is_default: z.boolean().default(false),
});

===== FILE: src/lib/validations/auth.schema.ts =====
import * as z from "zod";
```

```
export const loginSchema = z.object({
  identifier: z.string().min(6, "Ø£Ø-Ø@Ù\204 Ø±Ù\212Ø-Ù\203 Ø$Ù\204Ø¥Ù\204Ù\203ØªØ±Ù\210Ù\206Ù\212 Ø£Ù\210 Ø±Ù\202Ù\205 Ù\207Ø$ØªÙ\201Ù\203"),
  password: z.string().min(6, "Ù\203Ù\204Ù\205Ø© Ø$Ù\204Ù\205Ø±Ù\210Ø± Ù\202ØµÙ\212Ø±Ø© Ø¬Ø-Ø$Ù\213"),
});

export const registerSchema = z.object({
  name: z.string().min(2, "Ø$Ù\204Ø$Ø³Ù\205 Ù\202ØµÙ\212Ø± Ø¬Ø-Ø$Ù\213"),
  email: z.string().email("Ø±Ù\212Ø- Ø¥Ù\204Ù\203ØªØ±Ù\210Ù\206Ù\212 Ø°Ù\212Ø± ØµØ$Ù\204Ø-"),
  phone: z.string().optional(),
  password: z.string().min(6, "Ù\203Ù\204Ù\205Ø© Ø$Ù\204Ù\205Ø±Ù\210Ø± Ù\202ØµÙ\212Ø±Ø© Ø¬Ø-Ø$Ù\213"),
  role: z.enum(["retailer", "wholesaler", "delivery"]).default("retailer"),
});

===== FILE: src/lib/validations/chat.schema.ts =====

===== FILE: src/lib/validations/commission.schema.ts =====
import * as z from "zod";

export const commissionSchema = z?.object({
  orderId: z?.string(),
  retailerId: z?.string(),
  amount: z?.coerce?.number()?.positive(),
  status: z?.enum(["pending", "paid"])??.default("pending"),
});

===== FILE: src/lib/validations/offer.schema.ts =====

===== FILE: src/lib/validations/order.schema.ts =====
import * as z from "zod";

export const createOrderSchema = z.object({
  items: z.array(z.object({
    productId: z.string(),
    quantity: z.number().int().positive(),
    wholesalerId: z.string(),
    price: z.number().positive(),
  })).min(1, "Ø$Ù\204Ø³Ù\204Ø© Ù\201Ø$Ø±Ø°Ø©"),
  address: z.string().min(5, "Ø$Ù\204Ø¹Ù\206Ù\210Ø$Ù\206 Ù\205Ù\201ØµÙ\204 Ø¬Ø-Ø$Ù\213"),
  coupon_code: z.string().optional(),
});

===== FILE: src/lib/validations/product.schema.ts =====
import * as z from "zod";

export const productSchema = z?.object({
  name: z?.string()?.min(2, "Ø$Ø³Ù\205 Ø$Ù\204Ù\205Ù\206ØªØ¬ Ù\205Ø•Ù\204Ù\210Ø""),
  description: z?.string()?.optional(),
  price: z?.coerce?.number()?.positive("Ø$Ù\204Ø³Ø¹Ø± Ù\212Ø¬Ø" Ø£Ù\206 Ù\212Ù\203Ù\210Ù\206 Ù\205Ù\210Ø¬Ø¬Ø$Ù\213"),
  wholesalePrice: z?.coerce?.number()?.positive("Ø³Ø¹Ø± Ø$Ù\204Ø¬Ù\205Ù\204Ø© Ù\212Ø¬Ø" Ø£Ù\206 Ù\212Ù\203Ù\210Ù\206 Ù\205Ù\210Ø¬Ø¬Ø$Ù\213"),
  stock: z?.coerce?.number()?.int()?.nonnegative(),
  category: z?.string()?.min(1, "Ø$Ù\204Ù\201Ø|Ø© Ù\205Ø•Ù\204Ù\210Ø¬Ø©"),
});

===== FILE: src/lib/validations/review.schema.ts =====
import * as z from "zod";

export const reviewSchema = z.object({
  product_id: z.string(),
  rating: z.number().min(1).max(5),
  comment: z.string().optional(),
});

===== FILE: src/lib/validations/wallet.schema.ts =====
```

```

===== FILE: src/middleware/auth.ts =====
import { NextResponse } from 'next/server';
import type { NextRequest } from 'next/server';
import { createServerClient } from '@supabase/ssr';

export async function middleware(req: NextRequest) {
  let response = NextResponse.next({ request: req })
  const supabase = createServerClient(
    process.env.NEXT_PUBLIC_SUPABASE_URL!,
    process.env.NEXT_PUBLIC_SUPABASE_ANON_KEY!,
    { cookies: { getAll() { return req.cookies.getAll() }, setAll(cookiesToSet) { cookiesToSet.forEach(({ name, value }) => req.cookies.set(name, value)); response = NextResponse.next({ request: req }); cookiesToSet.forEach(({ name, value, options }) => response.cookies.set(name, value, options)) } } }
  )
  const { data: { user } } = await supabase.auth.getUser()
  if (!user && !req.nextUrl.pathname.startsWith('/login') && !req.nextUrl.pathname.startsWith('/register')) {
    return NextResponse.redirect(new URL('/auth/login', req.url))
  }
  return response
}

export const config = { matcher: ['/((?!_next/static|_next/image|favicon.ico|.*\\.?(?:svg|png|jpg|jpeg|gif|webp)$).*)'] }

===== FILE: src/middleware/logging.ts =====
import { NextResponse } from 'next/server';
import type { NextRequest } from 'next/server';

export function middleware(req: NextRequest) {
  console.log(`[LOG] ${new Date().toISOString()} - ${req.method} ${req.nextUrl.pathname}`)
  return NextResponse.next()
}

===== FILE: src/middleware/permissions.ts =====
import { NextResponse } from 'next/server';
import type { NextRequest } from 'next/server';

export function middleware(req: NextRequest) {
  const token = req.cookies.get('role')?.value // Û\212Û\205Û\203Û\206 ØªØ¹Ø-Û\212Û\204 Û\207Ø°Ø$ Û\204Ø-Û\204Ø" Ø$Û\204Ø-Û\210Ø± Û\205Û\206 Ø$Û\204Ø-Û\204Ø³Ø©
  const url = req.nextUrl.pathname

  if (url.startsWith('/dashboard/admin') && token !== 'admin') {
    return NextResponse.redirect(new URL('/auth/login', req.url))
  }
  if (url.startsWith('/dashboard/retailer') && token !== 'retailer') {
    return NextResponse.redirect(new URL('/auth/login', req.url))
  }
  return NextResponse.next()
}

export const config = { matcher: ['/dashboard/:path*'] }

===== FILE: src/middleware/rateLimit.ts =====
import { NextResponse } from 'next/server';
import type { NextRequest } from 'next/server';

const rateLimitMap = new Map()

export function middleware(req: NextRequest) {
  const ip = req.headers.get('x-forwarded-for') ?? 'unknown'
  const limit = 100 // 100 Ø•Û\204Ø" Û\204Û\203Û\204 Ø-Û\202Û\212Û\202Ø©
  const current = rateLimitMap.get(ip) || 0

  if (current > limit) {
    return new NextResponse(JSON.stringify({ error: 'Too many requests' })), { status: 429

```

```
    })
  }
  rateLimitMap.set(ip, current + 1)
  return NextResponse.next()
}

===== FILE: src/styles/animations.css =====

===== FILE: src/styles/globals.css =====
@tailwind base;
@tailwind components;
@tailwind utilities;

@layer base {
  :root {
    --background: 248 250 252; /* Û\204Û\210Û\206 Ø±Û\205Ø$Ø~Û\212 Û\201Ø$ØªØ- Ø¬Ø¬Ø$Û\213 */
    --foreground: 15 23 42; /* Û\204Û\210Û\206 Û\203Ø-Û\204Û\212 Ø¬Ø$Û\203Û\206 */
    --primary: 245 158 11; /* Ø$Û\204Û\204Û\210Û\206 Ø$Û\204Ø°Û\207Ø¬Û\212 */
    --primary-foreground: 15 23 42;
    --secondary: 226 232 240; /* Û\204Û\210Û\206 Ø±Û\205Ø$Ø~Û\212 Û\201Ø$ØªØ- */
    --secondary-foreground: 15 23 42;
    --destructive: 239 68 68;
    --destructive-foreground: 255 255 255;
    --border: 229 231 235;
    --input: 229 231 235;
    --ring: 245 158 11;
    --radius: 0.75rem;
  }

  * {
    @apply border-border;
  }
  body {
    @apply bg-background text-foreground antialiased;
    font-family: 'Tajawal', sans-serif;
  }
}

@layer utilities {
  .text-gradient {
    @apply bg-gradient-to-r from-[#f59e0b] to-[#d97706] bg-clip-text text-transparent;
  }
}

===== FILE: src/styles/tailwind.css =====

===== FILE: src/types/address.ts =====
export interface Address {
  id: string;
  user_id: string;
  title: string;
  city: string;
  district: string;
  street: string;
  is_default: boolean;
  created_at: string;
}

export type AddressInput = Omit<Address, "id" | "user_id" | "created_at">;

===== FILE: src/types/api.ts =====
export interface ApiResponse<T> {
  success: boolean;
  message?: string;
  data?: T;
  error?: string;
}

export interface PaginationParams {
```

```
    page: number;
    limit: number;
}

export interface PaginatedResponse<T> {
    items: T[];
    total: number;
    page: number;
    limit: number;
}

===== FILE: src/types/chat.ts =====
export interface ChatMessage {
    id: string;
    sender_id: string;
    receiver_id: string;
    message: string;
    is_read: boolean;
    created_at: string;
}

===== FILE: src/types/commission.ts =====
export interface Commission {
    id: string;
    orderId: string;
    retailerId: string;
    amount: number;
    status: "pending" | "paid";
    createdAt: string;
}

===== FILE: src/types/offer.ts =====
export interface Offer {
    id: string;
    title: string;
    description: string;
    discount_percent: number;
    start_date: string;
    end_date: string;
    is_active: boolean;
    created_at: string;
}

export interface Refund {
    id: string;
    order_id: string;
    requested_by: string;
    reason: string;
    status: 'pending' | 'approved' | 'rejected';
    created_at: string;
}

===== FILE: src/types/order.ts =====
import { User } from "../user";

export type OrderStatus = "pending" | "processing" | "shipped" | "delivered" | "cancelled";

export interface OrderItem {
    productId: string;
    quantity: number;
    price: number;
}

export interface Order {
    id: string;
    userId: string;
    items: OrderItem[];
    status: OrderStatus;
    total: number;
}
```

```
    address: string;
    createdAt: string;
    deliveryAgent?: User;
}
```

```
===== FILE: src/types/product.ts =====
```

```
export interface Product {
  id: string;
  name: string;
  description: string;
  price: number;
  wholesalePrice: number;
  stock: number;
  category: string;
  images: string[];
  isActive: boolean;
  createdAt: string;
}
```

```
export type ProductInput = Omit<Product, "id" | "createdAt">;
```

```
===== FILE: src/types/request.ts =====
```

```
===== FILE: src/types/review.ts =====
```

```
export interface Review {
  id: string;
  product_id: string;
  user_id: string;
  rating: number;
  comment: string;
  created_at: string;
}
```

```
export type ReviewInput = Omit<Review, "id" | "user_id" | "created_at">;
```

```
===== FILE: src/types/user.ts =====
```

```
export type UserRole = "admin" | "delivery" | "retailer" | "wholesaler";
```

```
export interface User {
  id: string;
  email: string;
  name: string;
  role: UserRole;
  phone: string;
  avatar?: string;
  createdAt: string;
}
```

```
export interface AuthSession {
  user: User;
  token: string;
}
```

```
===== FILE: src/types/wallet.ts =====
```

```
export interface Wallet {
  id: string;
  user_id: string;
  balance: number;
  updated_at: string;
}
```

```
export interface PointsTransaction {
  id: string;
  user_id: string;
  order_id: string;
  points: number;
  type: 'earn' | 'redeem';
  created_at: string;
}
```