# Exercise 1

针对第十二讲代码优化(2)P55上流图,计算活跃变量数据流方程。




图 1: 第十二讲代码优化(2) P55 上流图

## 解 首先给出每个基本块的 use 和 def 集合

基本块	use	def
$B_1$	$use_1 = \{\}$	$\mathit{def}_1 = \{\mathtt{D}, \mathtt{G}\}$
$B_2$	$use_2 = \{D\}$	$\mathit{def}_2 = \{\mathtt{A},\mathtt{B},\mathtt{C}\}$
$B_3$	$use_3 = \{A, B, C, G\}$	$\mathit{def}_3 = \{\mathtt{F}\}$
$B_4$	$use_4 = \{\mathtt{A},\mathtt{B},\mathtt{C}\}$	$\mathit{def}_4 = \{\mathtt{F}\}$
$B_5$	$use_5 = \{\mathtt{B},\mathtt{C},\mathtt{D}\}$	$\mathit{def}_5 = \{\mathtt{G}\}$

初始值

$$IN[B_1] = IN[B_2] = IN[B_3] = IN[B_4] = IN[B_5] = \emptyset$$
  
 $OUT[B_5] = \emptyset$ 

#### 第一次迭代

$$\begin{array}{lll} \operatorname{OUT}[B_5] &= \operatorname{OUT}[B_5] \cup \operatorname{IN}[B_2] &= \{\} \cup \{\} &= \{\} \\ \operatorname{IN}[B_5] &= use_5 \cup (\operatorname{OUT}[B_5] - def_5) &= \{\operatorname{B},\operatorname{C},\operatorname{D}\} \cup (\{\} - \{\operatorname{G}\}) &= \{\operatorname{B},\operatorname{C},\operatorname{D}\} \\ \operatorname{OUT}[B_4] &= \operatorname{OUT}[B_4] \cup \operatorname{IN}[B_5] &= \{\} \cup \{\operatorname{B},\operatorname{C},\operatorname{D}\} &= \{\operatorname{B},\operatorname{C},\operatorname{D}\} \\ \operatorname{IN}[B_4] &= use_4 \cup (\operatorname{OUT}[B_4] - def_4) &= \{\operatorname{A},\operatorname{B},\operatorname{C}\} \cup (\{\operatorname{B},\operatorname{C},\operatorname{D}\} - \{\operatorname{F}\}) &= \{\operatorname{A},\operatorname{B},\operatorname{C},\operatorname{D}\} \\ \operatorname{OUT}[B_3] &= \operatorname{OUT}[B_3] \cup \operatorname{IN}[B_5] &= \{\} \cup \{\operatorname{B},\operatorname{C},\operatorname{D}\} &= \{\operatorname{B},\operatorname{C},\operatorname{D}\} \\ \operatorname{IN}[B_3] &= use_3 \cup (\operatorname{OUT}[B_3] - def_3) &= \{\operatorname{A},\operatorname{B},\operatorname{C},\operatorname{G}\} \cup (\{\operatorname{B},\operatorname{C},\operatorname{D}\} - \{\operatorname{F}\}) &= \{\operatorname{A},\operatorname{B},\operatorname{C},\operatorname{D},\operatorname{G}\} \\ \operatorname{OUT}[B_2] &= \operatorname{OUT}[B_2] \cup \operatorname{IN}[B_3] \cup \operatorname{IN}[B_4] &= \{\} \cup \{\operatorname{A},\operatorname{B},\operatorname{C},\operatorname{D},\operatorname{G}\} \cup \{\operatorname{A},\operatorname{B},\operatorname{C},\operatorname{D}\} &= \{\operatorname{A},\operatorname{B},\operatorname{C},\operatorname{D},\operatorname{G}\} \\ \operatorname{IN}[B_2] &= use_2 \cup (\operatorname{OUT}[B_2] - def_2) &= \{\operatorname{D}\} \cup (\{\operatorname{A},\operatorname{B},\operatorname{C},\operatorname{D},\operatorname{G}\} - \{\operatorname{A},\operatorname{B},\operatorname{C}\}) &= \{\operatorname{D},\operatorname{G}\} \\ \operatorname{OUT}[B_1] &= \operatorname{OUT}[B_1] \cup \operatorname{IN}[B_2] &= \{\} \cup \{\operatorname{A},\operatorname{D},\operatorname{G}\} &= \{\operatorname{D},\operatorname{G}\} \\ \operatorname{IN}[B_1] &= use_1 \cup (\operatorname{OUT}[B_1] - def_1) &= \{\} \cup (\{\operatorname{D},\operatorname{G}\} - \{\operatorname{D},\operatorname{G}\}) &= \{\} \\ \end{array}$$

#### 第二次迭代

### 第三次迭代

$$\begin{array}{lll} \operatorname{OUT}[B_5] &= \operatorname{OUT}[B_5] \cup \operatorname{IN}[B_2] &= \{\mathtt{D},\mathtt{G}\} \cup \{\mathtt{D},\mathtt{G}\} &= \{\mathtt{D},\mathtt{G}\} \\ \operatorname{IN}[B_5] &= use_5 \cup (\operatorname{OUT}[B_5] - def_5) &= \{\mathtt{B},\mathtt{C},\mathtt{D}\} \cup (\{\mathtt{D},\mathtt{G}\} - \{\mathtt{G}\}) &= \{\mathtt{B},\mathtt{C},\mathtt{D}\} \\ \operatorname{OUT}[B_4] &= \operatorname{OUT}[B_4] \cup \operatorname{IN}[B_5] &= \{\mathtt{B},\mathtt{C},\mathtt{D}\} \cup \{\mathtt{B},\mathtt{C},\mathtt{D}\} &= \{\mathtt{B},\mathtt{C},\mathtt{D}\} \\ \operatorname{IN}[B_4] &= use_4 \cup (\operatorname{OUT}[B_4] - def_4) &= \{\mathtt{A},\mathtt{B},\mathtt{C}\} \cup (\{\mathtt{B},\mathtt{C},\mathtt{D}\} - \{\mathtt{F}\}) &= \{\mathtt{A},\mathtt{B},\mathtt{C},\mathtt{D}\} \\ \operatorname{OUT}[B_3] &= \operatorname{OUT}[B_3] \cup \operatorname{IN}[B_5] &= \{\mathtt{B},\mathtt{C},\mathtt{D}\} \cup \{\mathtt{B},\mathtt{C},\mathtt{D}\} &= \{\mathtt{B},\mathtt{C},\mathtt{D}\} \\ \operatorname{IN}[B_3] &= use_3 \cup (\operatorname{OUT}[B_3] - def_3) &= \{\mathtt{A},\mathtt{B},\mathtt{C},\mathtt{G}\} \cup (\{\mathtt{B},\mathtt{C},\mathtt{D}\} - \{\mathtt{F}\}) &= \{\mathtt{A},\mathtt{B},\mathtt{C},\mathtt{D},\mathtt{G}\} \\ \operatorname{OUT}[B_2] &= \operatorname{OUT}[B_2] \cup \operatorname{IN}[B_3] \cup \operatorname{IN}[B_4] &= \{\mathtt{A},\mathtt{B},\mathtt{C},\mathtt{D},\mathtt{G}\} \cup \{\mathtt{A},\mathtt{B},\mathtt{C},\mathtt{D},\mathtt{G}\} \cup \{\mathtt{A},\mathtt{B},\mathtt{C},\mathtt{D},\mathtt{G}\} \\ \operatorname{IN}[B_2] &= use_2 \cup (\operatorname{OUT}[B_2] - def_2) &= \{\mathtt{D},\mathtt{G}\} \cup (\{\mathtt{A},\mathtt{B},\mathtt{C},\mathtt{D},\mathtt{G}\} - \{\mathtt{A},\mathtt{B},\mathtt{C}\}) &= \{\mathtt{D},\mathtt{G}\} \\ \operatorname{OUT}[B_1] &= \operatorname{OUT}[B_1] \cup \operatorname{IN}[B_2] &= \{\mathtt{D},\mathtt{G}\} \cup \{\mathtt{D},\mathtt{G}\} \\ \operatorname{IN}[B_1] &= use_1 \cup (\operatorname{OUT}[B_1] - def_1) &= \{\} \cup (\{\mathtt{D},\mathtt{G}\} - \{\mathtt{D},\mathtt{G}\}) &= \{\} \\ \end{array}$$

不再有 IN 值发生改变, 迭代终止。

$$ext{IN[EXIT]} = \emptyset$$
 $ext{OUT}[B] = \bigcup_{S \not\in B \pitchfork - \uparrow fix} ext{IN}[S]$ 
 $ext{IN}[B] = use_B \cup ( ext{OUT}[B] - def_B)$ 

- 1  $IN[EXIT] = \emptyset$
- 2 for 基本块 $B \neq EXIT$
- $3 \qquad \text{IN}[B] = \emptyset$
- 4 while 某个 IN 值发生了改变
- 5 **for** 基本块 $B \neq EXIT$
- 6  $OUT[B] = \bigcup_{S \in B \cap \uparrow f : \#} IN[S]$
- 7  $IN[B] = use_B \cup (OUT[B] def_B)$