# CS427 Final Project - Stream File Encryption & Key Management

Casey Colley Robert Detjens Lyell Read

CS 427, Winter 2022

## Contents

Primitives		 			 					 			
Formal Scheme Definition													
Main		 								 			
Security Proof and Reasoning		 								 			
ey Generation and Storage													
Primitives		 								 			
D 101 Devi										 			
Formal Scheme Definition	•	 	 •	 -									

## Abstract

placeholder

## Stream Encryption and Decryption (enc, dec)

placeholder

### **Primitives**

Our design utilizes F, a Block Cipher (PRP). F will be the AES block cipher with a 256-bit key. This key will be derived using a common hashing algorithm, SHA-256 based on the text password entered by the user.

- https://www.geeksforgeeks.org/advanced-encryption-standard-aes/
- https://nvlpubs.nist.gov/nistpubs/FIPS/NIST.FIPS.197.pdf

klen = 256	$F_{AES}(k,d)$ :
TODO: types declared here	TODO

### Formal Scheme Definition

Our symmetric encryption mode will be CTR mode.

```
\frac{\text{ENC}_{CTR}(k, m_1||...||m_l):}{r \leftarrow \{\mathbf{0}, \mathbf{1}\}^{blen}}
c_0 := r
\text{for } i = 1 \text{ to } l:
c_i := F(k, r) \oplus m_i
r := r + 1\%2^{blen}
\text{return } c_0||...||c_l
\frac{\text{DEC}_{CTR}(k, c_0||...||c_l):}{\text{TODO}}
```

The hashing function we will use is SHA-256.

```
klen = 256 \frac{\text{HASH}_{SHA-256}(m)}{\text{TODO}}: types declared here
```

### Main

```
from getpass import getpass
klen, blen = 256

# Stored persistently, in file or otherwise
s = ''
K = ''
H = ''

Init():
    k = KeyGen()
    s = KeyGen()
    print("You will make a new password.")
    H = Pass2Key()
```

```
print("You will enter the password again.")
K = EncKey()
print("Vault has been initialized.")

Main():
    if:
        Init()
k = DecKey()
# Decrypt vault with k
print("Vault has been decrypted.")

#Encryption and Decryption behavior here

# Re-encrypt vault files with k
# k is not persistant on shutdown
```

get pass: https://stackoverflow.com/questions/43673886/python-2-7-how-to-get-input-but-dont-show-keys-entered/43673912

## Security Proof and Reasoning

placeholder

## Key Generation and Storage (keygen)

### **Primitives**

placeholder

#### Formal Scheme Definition

```
k := DecKey()
s := KeyGen()
H := Pass2Key()
K := EncKey(h, k)
\frac{\text{KeyGen}():}{k \leftarrow \{0, 1\}^{klen}}
\text{return } k
\text{return } h
\frac{\text{Pass2Key}():}{p := get\_passphrase()}
h := Hash_{SHA-256}(p||s)
\text{return } K
\frac{\text{EncKey}(k):}{h := H}
K := Enc_{CTR}(h, k)
```

TODO: Define types and formalize scheme in tex

## Security Proof and Reasoning

Here we define a library of functions that will handle the generation and storage of the Master Key that will be used to encrypt and decrypt the stored keys in the manager. The Master Key is generated with function KeyGen, which samples a string of length klen. This sampling will come from the machine's built-in random device, such as /dev/urandom.

This Master Key will be stored on the machine, encrypted. The encryption and decryption of the Master Key will be done with a password and in the CTR mode, as shown in the remaining two functions, Pass2Key() and EncKey(). The correct, salted hash of the password will be stored alongside the encrypted Master Key.

EncKey() begins with Pass2Key(), where it will prompt the user for the password, salt it, and then return the SHA-256 hash. EncKey will compare this hash with the stored, correct hash. If they do not match (it is the wrong password), then an error is returned. Otherwise, EncKey will call the CTR mode, using the hashed password as a key/seed to the PRP F.

### Conclusion and Discussion

placeholder