

Prüfbericht 366-0577-15-WIRD
zur Erteilung der ECE (E1) 124R- 000845

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 16705112-59

Stand: 03.03.2016



Seite: 1 von 1

Manufacturer : AUDI**Wheel dates:**

Wheel size according to standard : 7 J X 16 H2

Off set(mm) : 40

Hole circle (mm)/number of holes : 112/5

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1872	R1-1872	Without	57		600	1927	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : AUDI

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **AUDI A3, S3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8V	e1*2007/46*0607*..	77	205/55R16 91H		1); 2); 33)
		77-135	205/55R16 91W		
		81-110	205/55R16 91V		
		81-135	205/55R16 M+S		

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.