

Programming Basics 3

Instructor Younghoon Kim



The background of the slide is a light blue gradient. In the top right corner, there is a close-up of a silver computer keyboard, showing keys like '<', '>', '<.', '>.', '? /', 'enter', 'return', 'delete', 'alt', and 'shift'. In the bottom left corner, there is a silver pen. In the bottom right corner, there is a spiral-bound notebook with a light blue cover. A large, dark blue rounded rectangle is positioned in the center of the slide, containing the text 'while statement' in white.

`while` **statement**

- **Program control**

- Specifying the order of statements for program execution

- **Sequential execution**

- Line-by-line execution
- Order of statements in a code is **equal** to the execution order.

- **Transfer of program control**

- Execution order is **different** from what you can see in the code.

- **Control flow**

- The order in which individual statements are executed or evaluated.

■ Three types of control structures

- Sequence structure
- Selection structure
 - » if, if...else, switch
- Iteration structure
 - » while, do...while, for
- C has only seven control statements.

■ Iteration statement

- makes an action to be repeated when a certain condition is true.
- **Loop condition:** A loop is a group of instructions that the computer executes repeatedly while its *loop condition* remains true.

■ Three means of repetition (iteration)

- Definite repetition: Exact number of iterations is known.
- Indefinite repetition: Number of iterations is determined on runtime.
- Infinite repetition: The number of iteration is infinite.
 - » Intentionally? A bug?

■ Three statements for iterations

- while, do...while, for

■ Syntax

- while

 Loop Conditions

```
while(logical_expression_1) {  
    /* When logical_expression_1 is true */  
    (statements to be repeated)  
}
```

- do-while

```
do {  
    /* Loop exits when logical_expression_1 is false */  
    (statements to be repeated)  
} while(logical_expression_1)
```

■ Execution order of while statement

- The loop-continuation condition is tested at the beginning of the loop before the body of the loop is performed.

```
while(logical_expression_1) {  
    /* When logical_expression_1 is true */  
    (statements to be repeated)  
}
```

- logical_expression_1 is evaluated first.
- If it is true, the body of the while statement is executed.
- After each iteration, logical_expression_1 is checked for true. The body is repeatedly executed under the true condition of logical_expression_1.
- When it becomes false, the program control escapes the loop and the next statement in order is executed.

■ Example: finding the first power of 3 larger than 100

```
product = 3;
while ( product <= 100 ) {
    product = 3 * product;
} // end while
```


- The loop starts with the product variable as 3.
- The loop condition is true for that value and the body of while is executed.
- The value of product increases as 9, 27 and 81.
- When product becomes 243, the loop condition becomes false, which terminates the iteration. (Check that this value is what we are looking for.)
- Program execution continues with the next statement after the while.

■ Easiest example with while

- Variations with different loop conditions and strides

```
#include <stdio.h>

int main() {
    int num = 1;
    while (num <= 10) {
        printf("%d\n", num);
        num = num + 1;
    }
    return 0;
}
```

A yellow sticky note with a black border and a wavy bottom edge, containing the numbers 1 through 10.

1
2
3
4
5
6
7
8
9
10

▪ Example: finding the first power of 3 larger than 100

```
#include <stdio.h>

int main() {
    int product = 3;
    while ( product <= 100 ) {
        product = 3 * product;
    } // end while

    printf("%d\n", product);
    return 0;
}
```

243

■ Execution order of do...while statement

- The do...while statement tests the loop-continuation condition after the loop body is performed. (Very similar to the execution order of while statement, so not written here.)

```
do {  
    /* Loop exits when logical_expression_1 is false */  
    (statements to be repeated)  
} while(logical_expression_1);
```

■ Difference against the while statement

- while: the loop condition is tested first. The body might never be executed.
- do...while: the loop condition is checked after the body is performed.
The body has at least one chance to be executed.

■ Transition from while to do...while

- In most cases, converting while statements to do...while statements can be done easily.
- However, you need to be very cautious of the first execution of the body.

```
product = 3;  
while ( product <= 100 ) {  
    product = 3 * product;  
} // end while
```

With while



With do...while

```
product = 3;  
do {  
    product = 3 * product;  
} while( product <= 100 ) // end do...while
```


■ Example: finding the first power of 3 larger than 100

```
product = 3;  
do {  
    product = 3 * product;  
} while( product <= 100 ); // end do...while
```

- The loop starts with the product variable as 3 and the body is executed.
- The value of product increases as 9, 27 and 81.
- When the loop condition becomes false, which terminates the iteration.
- **CHECK:** What happens when the initial value of product is 243 instead of 3?

```
#include <stdio.h>

int main()
{
    int num = 1;
    do {
        printf("%d\n", num);
        num = num + 1;
    } while (num <= 10);
    return 0;
}
```

A yellow sticky note with a black border and a wavy bottom edge. It contains the numbers 1 through 10, each on a new line.

1
2
3
4
5
6
7
8
9
10

```
#include <stdio.h>

int main() {
    int product = 3;
    do {
        product = 3 * product;
    } while( product <= 100 ); // end do...while
    printf("%d\n", product);
    return 0;
}
```

243

■ Definite repetition

- Exact number of iterations is known.
- Counter-controlled iteration
 - » Counter: Specifying the number of times a set of statements should execute

```
int counter = 1;
while ( counter <= 10 ) {
    printf("%d\n", counter);
    counter++;
}
```


Types of iteration: Indefinite

■ Indefinite repetition

- Number of iterations is determined on runtime.
- Sentinel-Controlled Iteration
 - » Sentinel value: Indicating "end of data entry"
 - » Other names: a signal value, a dummy value, a flag value
 - » The sentinel value must be chosen so that it cannot be confused with an acceptable input value.

```
int num;
scanf("%d", &num);
while ( num != -1 ) {      // sentinel value is -1
    printf("%d\n", num);
    scanf("%d", &num);
}
```

■ Infinite repetition

- The number of iteration is infinite.
- When we use it in our program, we normally terminate the loop using ***break*** statement under some specific conditions.

```
// An erroneous example
while ( 1 ) {
    printf("while (1)");
}
```

- **break and continue are used for managing program control explicitly.**
- **break breaks loops.**
 - break has two usages.
 - With loops: Exiting from innermost one
 - » The program control resumes at the next statement following the loop
 - With switch: Termination of a case
- **continue continues loops.**
 - With continue, loop continues next iteration ignoring following code in the code block.
 - In while and do...while statements, the loop-continuation test is evaluated immediately after the continue statement is executed.

```
#include <stdio.h>
int main()
{
    int num = 0, sum = 0;
    while (num < 10) {
        sum += num++;
        printf("before if\n");
        if (sum < 20) {
            printf("num:%d sum:%d (continue)\n", num, sum);
            continue;
        } else {
            printf("num:%d sum:%d (break)\n", num, sum);
            break;
        }
        printf("after else\n");
    }
}
```

CHECK1: What is the first value added to sum?

CHECK2: Is the loop escaped by the loop-continuation condition?

CHECK3: Find a line never being executed.

Indefinite iteration example

DEMO

```
#include <stdio.h>

int main()
{
    int num = 1;
    while (num != 10) {
        printf("Input a number(for exit, type 10): ");
        scanf("%d", &num);
        printf("You type %d.\n", num);
    }
    return 0;
}
```

Exercise – Loop with increment op.

DEMO

- Fill in the blank to print the result on the right side.

```
#include <stdio.h>

int main() {
    int num = 1;
    while (num <= 10) {
        printf("%d\n", [BLANK] );
    }
    return 0;
}
```

1
2
3
4
5
6
7
8
9
10

- We have several candidate positions for '++' increment operator. (On 5th and 6th line, before and after num variable.) What will be the results for each position?

```
#include <stdio.h>

int main() {
    int num = 1;
    while (num <= 10) {
        printf("%d\n", num++);
    }
    return 0;
}
```

■ Basic concept for the while iteration statement


- An iteration statement allows you to specify that an action is to be repeated while some condition remains true. The pseudocode statement describes the iteration that occurs during a shopping trip. The condition, "there are more items on my shopping list" may be true or false. If it's true, then the action, "Purchase next item and cross it off my list" is performed. This action will be performed repeatedly while the condition remains true.

```
While there are more items on my shopping list  
    Purchase next item and cross it off my list
```

- Eventually, the condition will become false (when the last item on the shopping list has been purchased and crossed off the list). At this point, the iteration terminates, and the first pseudocode statement after the iteration structure is executed.


■ Example code and corresponding flowchart

```
product = 3;  
while ( product <= 100 ) {  
    product = 3 * product;  
} // end while
```



■ do...while Iteration Statement

- The do...while iteration statement is similar to the while statement. In the while statement, the loop-continuation condition is tested at the beginning of the loop before the body of the loop is performed. The do...while statement tests the loop-continuation condition after the loop body is performed. Therefore, the loop body will be executed at least once. When a do...while terminates, execution continues with the statement after the while clause.



Programming Basics 3

Instructor Younghoon Kim



The background of the slide is a light blue gradient. In the top right corner, there is a close-up of a white computer keyboard, showing keys like '<', '>', '"', '"', '?', 'alt', 'enter/return', and 'delete'. Below the keyboard is a white computer mouse. In the bottom left corner, there is a silver pen. In the bottom right corner, there is a spiral-bound notebook with a blue cover. A large, blue, rounded rectangular box is centered on the slide, containing the text 'for statement' in white.

for **statement**

■ Counter-controlled iteration

- Definite iteration (or definite repetition)
 - » vs. indefinite iteration (sentinel-controlled iteration)
- The exact number of loop execution is known in advance.

■ Counter-controlled iteration requires:

- The name of a control variable (or loop counter).
- The initial value of the control variable.
- The increment (or decrement) by which the control variable is modified each time through the loop.
- The condition that tests for the final value of the control variable (i.e., whether looping should continue).

- The for iteration statement handles all the details of counter-controlled iteration.
- Syntax

```
for(initialization; condition; increment) {  
    /* When condition is true */  
    (code block)  
}
```

- initialization
 - » executed first and once
 - » a name of a control variable and its initial value
 - Multiple control variables are acceptable.
- Condition
 - » loop condition

- The for iteration statement handles all the details of counter-controlled iteration.
- Syntax

```
for(initialization; condition; increment) {  
    /* When condition is true */  
    (code block)  
}
```

- Increment

- » update any loop control variables
- » Control variables are modified each time through the loop

- Execution order:

- » initialization → condition → code block → increment → condition → code block → increment → condition → code block → ...

- **Components of for statements are not mandatory.**

- Initialization can be omitted if we use already declared variables for the condition
- Loop-continuation condition can be omitted in two or more cases. When it is omitted, C assumes that the condition is always true.
 - » The condition is checked inside of the body with `break` and/or `continue`.
 - » The `for` statement intentionally runs infinitely.
- Increment part can be omitted when the variables are updated inside of the body.

```
// an extreme case
for( ; ; ) {
    (code block)
}
```


for **example** (a typical one)

DEMO

```
#include <stdio.h>

int main()
{
    for (int i = 0; i < 10; i++) {
        printf("%d\n", i);
    }
    return 0;
}
```

0
1
2
3
4
5
6
7
8
9

Variations will come up with demo

- You can check methods of varying the control variable in a for statement.

- CHECK: What are the semicolons for?

```
// Vary the control variable from 1 to 100 in increments of 1.
```

```
for (i = 1; i <= 100; i++);
```

```
// Vary the control variable from 100 to 1 in increments of -1 (decrements of 1).
```

```
for (i = 100; i >= 1; --i);
```

```
// Vary the control variable from 7 to 77 in steps of 7.
```

```
for (i = 7; i <= 77; i += 7);
```

```
// Vary the control variable from 20 to 2 in steps of -2.
```

```
for (i = 20; i >= 2; i -= 2);
```

```
// Vary the control variable over the following sequence of values: 2, 5, 8, 11, 14, 17.
```

```
for (j = 2; j <= 17; j += 3);
```

```
// Vary the control variable over the following sequence of values: 44, 33, 22, 11, 0.
```

```
for (j = 44; j >= 0; j -= 11);
```

■ continue continues loops.

- With continue, loop continues next iteration ignoring following code in the code block.
- In for statements, the increment expression is executed, then the loop-continuation test is evaluated.

```
#include <stdio.h>
int main()
{
    int num = 0, sum = 0;
    for(int i = 0; i < 10; i++) {
        if( i % 3 == 0 )
            continue;
        printf("%d ", i);
    }
    printf("\nContinue is used to skip printing multiples of 3.\n");
}
```

Exercise – Summing the Evens

DEMO

- Summing the Even Integers from 2 to 100

(intentionally blank box)

2550

Exercise – Summing the Evens

DEMO

■ Summing the Even Integers from 2 to 100

```
#include <stdio.h>

int main() {
    int sum = 0;
    for (int num = 2; num <= 100; num += 2) {
        sum += num;
    }

    printf("Sum: %d\n", sum);
    return 0;
}
```

2550

- **Program control:** order of statements for program execution
- **Sequential execution**
 - Line-by-line execution
- **Transfer of program control**
 - Execution order is **different** from what you can see in the code.
 - Selection structure: if, if else, switch
 - Iteration structure: while, do...while, for
- **C has only seven control statements.**
 - And we learned all of them.

■ General Format of a for Statement

- If the condition expression is omitted, C assumes that the condition is true, thus creating an infinite loop. You may omit the initialization expression if the control variable is initialized elsewhere in the program. The increment may be omitted if it's calculated by statements in the body of the for statement or if no increment is needed. This flowchart makes it clear that the initialization occurs only once and that incrementing occurs after the body statement is performed.

```
for (unsigned int counter = 1; counter <= 10; ++counter)
    printf("%u", counter);
```

Establish *initial*
value of control
variable

```
unsigned int counter = 1
```

counter <= 10

Determine if *final*
value of control
variable has been

true

```
printf("%u", counter);
```

Body of loop
(this may be many
statements)

```
++counter
```

Increment
the control
variable

