

# A Two-Page Abstract Using the New Article Format

Ben Trovato

Institute for Clarity in Documentation  
P.O. Box 1212  
Dublin, Ohio 43017-6221  
trovato@corporation.com

G.K.M. Tobin

Institute for Clarity in Documentation  
P.O. Box 1212  
Dublin, Ohio 43017-6221  
webmaster@marysville-ohio.com



**Figure 1:** (a) The overhead image is captured by an aerial device in a low altitude. (b) The point cloud is scanned by a laser device on the ground. We extract the roof contours (in different colors) according to the altitude histogram of points (c) The contours are matched with the overhead image respectively to achieve an initialization for optimizing the global matrix. (d) The camera pose is estimated after the iterative global matrix optimization. We project the contours on the overhead image to show the results.

## ABSTRACT

Lore ipsum dolor sit amet, consectetur adipiscing elit. Suspendisse eget lobortis orci. Proin pharetra ac nibh sed feugiat. Ut et est at mauris accumsan venenatis ut non quam. Maecenas vitae augue purus. Cras convallis vehicula molestie. Maecenas non vulputate diam, id mollis lorem. Nam consequat imperdiet lorem, a fermentum elit mollis vitae. Curabitur elit turpis, commodo quis vestibulum a, tristique eget felis. Nulla eu semper nulla. Sed nec libero eu tortor feugiat placerat a at ex. Sed quis venenatis orci. Proin sed nunc fringilla sapien tincidunt eleifend vel et elit. Sed mollis ante ornare arcu pharetra dignissim. Curabitur pretium viverra neque id facilisis. Nunc laoreet risus id ipsum ultrices tristique. Etiam sit amet euismod orci, eget tempus sapien.

## CCS CONCEPTS

- Computer systems organization → Embedded systems; Redundancy; Robotics;
- Networks → Network reliability;

## KEYWORDS

ACM proceedings, L<sup>A</sup>T<sub>E</sub>X, text tagging

## ACM Reference format:

Ben Trovato and G.K.M. Tobin. 2017. A Two-Page Abstract Using the New Article Format. In *Proceedings of SIGGRAPH 2017 Talks*, Los Angeles, CA, USA, August 2017, 2 pages.

DOI: 10.475/123\_4

---

SIGGRAPH 2017 Talks, Los Angeles, CA, USA

© 2017 Copyright held by the owner/author(s). This is the author's version of the work. It is posted here for your personal use. Not for redistribution. The definitive Version of Record was published in *Proceedings of SIGGRAPH 2017 Talks*, August 2017, [https://doi.org/10.475/123\\_4](https://doi.org/10.475/123_4).

## 1 INTRODUCTION


As a key technique to image-based navigation, augmented reality (AR) and 3D reconstruction, geo-localization has drawn massive attentions in the literature. When presenting a geo-localization problem, an image or a frame of video is often used as the query data, a 3D model is needed to provide a global coordinate, a sensor prior is optionally employed and the camera pose with respect to the global coordinate system is to be estimated.

In this work, we estimate the camera pose using an overhead image captured by a low-altitude aerial device as query and a corresponding building point cloud as 3D model. Comparing to existing methods using images captured on the ground [Arth et al. 2015] or in high altitude [Liu and Tuzel 2010], we are not able to take advantages of vanishing points and suffer from more critical perspective effect in the low-altitude overhead image. The building point clouds we deal with are scanned by a laser device, and only facades of buildings are able to be scanned.

There are two key observations that vertical facades of a point cloud correspond to edges of building roofs in the overhead image and that roofs at different altitudes are of different scales in the image, which inspire us to treat this geo-localization problem as a combination of a multi-layer shape matching problem and a global optimizing procedure.

## 2 OUR APPROACH

Given a building point cloud, we first extract contours of building roofs in different altitudes according to the altitude histogram of points, where each contour is fit into a set of line segments (Figure 1b). And then the contours are matched with the edge map of the overhead image respectively using a shape matching technique of [Liu and Tuzel 2010]. A local project matrix is achieved for each contour after shape matching (Figure 1c). Note that we need a global project matrix instead of local ones to estimate the camera pose.



**Figure 2: Finding paired 3D and 2D feature points:** for a 3D feature point, we project it on the overhead image (magenta points) using current project matrix and search in its  $k \times k$  neighborhood for a corner (cyan points). These 3D feature points and corresponding corners form pairs of feature points for next iteration of calculating project matrix.

So we treat the results of shape matching as the initialization of following global optimizing procedure.

To calculate the global project matrix between the whole point cloud and the overhead image, we need a series of paired 3D feature points and corresponding 2D feature points. We take the intersections of neighboring line segments of building roof contours as 3D feature points. And then we employ an iterative algorithm to optimize the global project matrix by alternatively finding corresponding 2D feature points and calculating the project matrix, where we utilize the results of shape matching as initial project matrix.

To be more specific, (1) as shown in Figure 2, for a 3D feature point we project it on the overhead image using current project matrix (magenta points) and search in its  $k \times k$  neighborhood for a corner (cyan points). These 3D feature points and corresponding corners form pairs of feature points for the next iteration of calculating project matrix. (2) With a set of paired 3D and 2D feature points, we can optimize a global project matrix by minimizing the average of distances between projected contours and the edges of the overhead image, which can be accelerated by distance transformation. And the newly calculated project matrix is used for the next iteration of finding paired feature points.

With the optimized global project matrix and pre-calibrated focal length of the camera, we can finally estimate the 6 degree-of-freedom camera pose of the overhead image in point cloud coordinate system.

### 3 EXPERIMENTS AND FUTURE WORK

We tested the proposed approach on a newly collected dataset, which contains several low-altitude overhead images and corresponding building point clouds. Figure 1(d) shows one of the results, where we project roof contours on the overhead image. Since most of the consuming time is spent in the shape matching stage and the optimizing stage is fast, we intend to implement a faster version of the algorithm and extend it to video-based problems.

### REFERENCES

- Clemens Arth, Christian Pirchheim, Jonathan Ventura, Dieter Schmalstieg, and Vincent Lepetit. 2015. Instant Outdoor Localization and SLAM Initialization from 2.5D Maps. *IEEE Transactions on Visualization and Computer Graphics* 21, 11 (2015), 1309–1318. DOI: <https://doi.org/10.1109/TVCG.2015.2459772>
- Ming-yu Liu and Oncel Tuzel. 2010. Fast Directional Chamfer Matching. *CVPR* (2010), 1696–1703.