

# verbose flag

It is a debugging setting that unlocks transparency, letting developers see the agent's internal "thought process" in real time.

When enabled, it outputs detailed logs showing prompt interpretations, considered actions, tool selections, and intermediate sub-tasks before the final response is delivered.

## Why?

- **Debugging and troubleshooting:** it helps identify where an agent get stuck, why it chose a specific tool (e.g., a search function or calculator), and where it might be hallucinating
- **Prompt refinement:** by seeing exactly how the agent parses instructions, you can tweak your system prompts to yield better results
- **Performance optimization:** helps track the exact execution flow and timing of multi-step processes.

## Implementations

- **LangChain:** Setting `verbose=True` prints out the prompt templates, tool inputs, and raw outputs for every step of the chain.
- **CrewAI:** Enabling `verbose=True` in an agent definition triggers detailed execution logs that show task transitions and tool usage
- **A2G (Formerly AutoGent):** Allows for distinct levels of verbosity, ranging from *low* (minimal responses) to *high* (step-by-step reasoning explanations).

## When to use it?

- **Local Development vs. Production:** Verbose mode is highly recommended during development and debugging. However, you should disable it in production to prevent log noise, save computing costs, and avoid accidentally logging sensitive data or system prompts.
- **Alternatives for Production:** For production environments, modern frameworks rely on dedicated telemetry tools like LangSmith or OpenTelemetry protocols to trace history silently without overwhelming the standard console logs