

Model

HDZN-104-261 Series

C&I Energy Storage Cabinet



* Image for reference only; actual product may vary.



Four Capacities
104 / 156
209 / 261 kWh



High-voltage
System Voltage
Up to 832 V



Liquid Cooling
Battery Modules &
Cabinet



Wide Discharge
Range -20~60°C



Hybrid Inverters
Growatt, Solis,
SOLINTEG,
SOSEN



LED Screen &
Remote Monitoring
CAN/RS485

Specifications



Model	HDZN-104-261 Series			
	HDZN-104	HDZN-156	HDZN-209	HDZN-261
Battery Configuration	((52S)2S)	((52S)3S)	((52S)4S)	((52S)5S)
Nominal Voltage	DC: 332.8 V	DC: 499.2 V	DC: 665.6 V	DC: 832 V
Rated Capacity	314 Ah	314 Ah	314 Ah	314 Ah
Rated Energy	104.499 kWh	156.748 kWh	208.998 kWh	261.248 kWh
Battery Operating Voltage Range	DC: 317.2 V~374.4 V	DC: 475.8 V~561.6 V	DC: 634.4 V~748.8 V	DC: 793 V~936 V
Maximum Charging Current	180 A	180 A	180 A	180 A
Maximum Discharging Current	180 A	180 A	180 A	180 A
Dimensions (W × D × H)	1000±2 × 1300±3 × 1610±3 mm		1000±2 × 1300±3 × 2110±3 mm	
Weight	1450±50 kg	1795±50 kg	2180±50 kg	2500±50 kg
Discharging Temperature Range	-20°C~60°C			
Charging Temperature Range	0°C~60°C			
Relative Humidity Range	0%RH~95%RH, No condensation			
Cooling Method	Liquid Cooling			
Fire Suppression Function	Support			
Display	LED screens			
Remote Monitoring	Support			
Installation Method	Floor-standing type, standard with fixed footing			
Communication	CAN/RS485			
Operating Altitude	≤4000 m (de-rating above 2000 m)			
IP Rating	IP55			