



Model

HDZN-H-16KWh-S

C&I HV Stacked Energy Storage System

* Image for reference only; actual product may vary.



HV Platform
System Voltage
up to 768 V



Steady 157 A
Charge/Discharge
Same Rating



Long-Life Cells
LiFePO₄



Wide Temperature
Discharge Range
-20~55°C



Expandable
15 per Cluster
Up to 4 Clusters
about
964.608 kWh



Large-Cell Design
314 Ah Cells
Lower System Cost

Specifications



Model	HDZN-H-16KWh-S
Battery Type	LiFePO ₄
Module Specification	16.076 kWh · 314 Ah · 51.2 V · 770×435×248 mm · 118 kg
Number of Modules	4 / 5 / 6 / 7
Grouping	(16S)4S ~ (16S)15S
Nominal Voltage	204.8 / 256 / 307.2 / 358.4 V
Battery Energy	64.307 / 80.384 / 96.46 / 112.537 kWh
Operating Voltage	182.4~227.2 / 228~284 / 273.6~340.8 / 319.2~397.6 V
Standard Charge/Discharge Current	157 A
Max. Continuous Charge/Discharge Current	157 A
Dimensions (W×D×H)	770×435×1242 / 1490 / 1738 / 1986 mm
Weight	Approx. 505 / 623 / 741 / 859 kg
Scalability	Supports up to 4 clusters in parallel (Max. approx. 964.608 kWh) Each rack supports up to 15 modules in series (Max. 241.152 kWh)
Operating Temperature	Charge: 0~55°C Discharge: -20~55°C
Storage Temperature	-20°C~40°C
Humidity	10%~90%RH, No condensation
Cooling Method	Natural Cooling
Communication	CAN/RS485
Installation	Floor-to-ceiling stacking
Depth of Discharge (DOD)	95%
Ingress Rating	IP20
Altitude	≤3000 m (de-rating above 2000 m)
Remote Control	WiFi (Optional)
Compatible Inverters	Deye/Solis/SOLINTEG/SOSEN...