



Model

HDZN-HV 125KW/261KWh-3P-N-A

C&I Liquid-Cooled All-in-One Cabinet

* Image for reference only; actual product may vary.



Full-Power
Off-Grid Backup



110% Sustained
Output Headroom



Detect & Suppress
Water Firefighting



Liquid Cooling
and Heating



All-in-One Design
Battery and PCS



Two-Hour Storage
125 kW Full Cycle

Specifications



Model	HDZN-HV-125KW/261KWh-3P-N-A
Dimensions (W × D × H)	1000×1300×2199 mm Ring hanger is not included 1000×1300×2271 mm Ring hanger is included
Weight	2500 kg±100 kg
Battery Configuration	1P260S
Nominal Voltage	DC: 832 V
Rated Capacity	314 Ah
Rated Energy	261.25 kWh
Battery Operating Voltage Range	DC: 650 V–949 V
Maximum Charge/Discharge Current	200 A
Round-Trip Efficiency	≥88%@25°C±2°C, 0.5P
Rated Voltage	AC: 400 V
Rated Power	125 kW@25°C±2°C
Rated Frequency	50 Hz/60 Hz
Total Harmonic Distortion (Voltage)	≤3% (linear load)
Grid Connection Type	(3W+N+PE) Three phase four wire
Off-grid Rated Power	125 kW@25°C
Cooling Method	Liquid Cooling
Heating Method	Liquid Heating
Fire Suppression Function	Supported (smoke and heat detection linked to audible/visual alarms and fire extinguishing device activation, with synchronised feedback signal output)
Water Fire Protection Function	Supported (with fire hydrant interfaces)
Explosion-proof Pressure Relief Window	Supported (explosion-proof pressure relief window on cabinet top, breaking on overpressure)
Low Temperature	Discharge: –30°C Charge: –30°C Storage: –20°C
High Temperature	Discharge: 55°C Charge: 55°C Storage: 35°C
Relative Humidity	0%~95%
IP Rating	IP55 (Battery compartment); IP54 (Electrical compartment)
Anti-corrosion Grade	C4H
Altitude	≤5000 m (de-rating above 2000 m)