



Model

HDZN-LV-16KWh-X

Residential Energy Storage System

* Image for reference only; actual product may vary.



High-Power Charge and Discharge up to 157 A



Wide Temperature Discharge Range -20°C to 45°C



Compact Floor-Standing Design with Adjustable Leveling Casters



Broad Inverter Compatibility Mainstream Brands Supported



95% Depth of Discharge More Usable Energy from Every Cycle



Supports Parallel Expansion of Multiple Units

Specifications



Model	HDZN-LV-16KWh-X
Dimensions (W × D × H)	W520×D240×H791 mm
Weight	Approx. 118 kg
Nominal Voltage	51.2 VDC
Rated Energy	16076.8 Wh
Discharging Voltage Range	58.4~43.2 VDC
Charging Voltage Range	43.2~58.4 VDC
Recommend Charge/Discharge Current	100 A
Maximum Charge/Discharge Current	157 A
Depth of Discharge	95%
Charging Temperature Range	0°C~45°C
Discharging Temperature Range	-20°C~45°C
Communication	CAN/RS485/RS232 WiFi/Bluetooth (optional)
Display	Yes, LCD touchscreen
IP Rating	IP20
Installation Method	Floor-standing style
Cooling Method	Natural Cooling
Mode of Movement	Adjustable Leveling Caster (Foot-master)
Storage Temperature	-15°C~60°C
Relative Humidity Range	10%~90%, No condensing
Operating Altitude	≤4000 m (>2000 m derating)
Compatible Inverters	Victron Energy/Deye/Voltronic/SMA/GoodWe/ Growatt/TBB/MUST/
Remote Monitoring	WiFi (Optional)
Fire Suppression Function	Support (Optional)