

1z0-808.examcollection.premium.exam.223q

Number: 1z0-808

Passing Score: 800

Time Limit: 120 min

File Version: 15.0



1z0-808

Java SE 8 Programmer I

Version 15.0

Exam A

QUESTION 1

Given:

```
class Product {  
    double price;  
}  
  
public class Test {  
    public void updatePrice(Product product, double price) {  
        price = price * 2;  
        product.price = product.price + price;  
    }  
    public static void main(String[] args) {  
        Product prt = new Product();  
        prt.price = 200;  
        double newPrice = 100;  
  
        Test t = new Test();  
        t.updatePrice(prt, newPrice);  
        System.out.println(prt.price + " : " + newPrice);  
    }  
}
```

What is the result?

- A. 200.0: 100.0
- B. 400.0: 200.0
- C. 400.0: 100.0
- D. Compilation fails.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 2

Which statement is true about the `switch` statement?

- A. It must contain the default section.
- B. The break statement, at the end of each case block, is optional.
- C. Its case label literals can be changed at runtime.
- D. Its expression must evaluate to a collection of values.

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 3

Given the code fragment:

```
public static void main(String[] args) {  
    String date = LocalDate  
        .parse("2014-05-04")  
        .format(DateTimeFormatter.ISO_DATE_TIME);  
    System.out.println(date);  
}
```

What is the result?

- A. May 04, 2014T00:00:00.000
- B. 2014-05-04T00:00: 00.000
- C. 5/4/14T00:00:00.000
- D. An exception is thrown at runtime.

Correct Answer: B → D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 4

Given the code fragment:

```
public static void main(String[] args) {  
    Short s1 = 200;  
    Integer s2 = 400;  
    Long s3 = (long) s1 + s2;           //line n1  
    String s4 = (String) (s3 * s2);     //line n2  
    System.out.println("Sum is " + s4);  
}
```

What is the result?

- A. Sum is 600
- B. Compilation fails at line n1.
- C. Compilation fails at line n2.
- D. A ClassCastException is thrown at line n1.
- E. A ClassCastException is thrown at line n2.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 5

What is the name of the Java concept that uses access modifiers to protect variables and hide them within a

class?

- A. Encapsulation
- B. Inheritance
- C. Abstraction
- D. Instantiation
- E. Polymorphism

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Using the private modifier is the main way that an object encapsulates itself and hide data from the outside world.

Reference: http://www.tutorialspoint.com/java/java_access_modifiers.htm

QUESTION 6

Given the code fragment:

```
abstract class Planet {  
    protected void revolve() { //line n1  
    }  
  
    abstract void rotate(); //line n2  
}  
  
class Earth extends Planet {  
    void revolve() { //line n3  
    }  
  
    protected void rotate() { //line n4  
    }  
}
```

Which two modifications, made independently, enable the code to compile? (Choose two.)

- A. Make the method at line n1 public.
- B. Make the method at line n2 public.
- C. Make the method at line n3 public.
- D. Make the method at line n3 protected.
- E. Make the method at line n4 public.

Correct Answer: CD

Section: (none)

Explanation

Explanation/Reference:

QUESTION 7

Given:

```

class Vehicle {
    String type = "4W";
    int maxSpeed = 100;

    Vehicle(String type, int maxSpeed) {
        this.type = type;
        this.maxSpeed = maxSpeed;
    }
    Vehicle() {}
}

class Car extends Vehicle {
    String trans;

    Car(String trans) {           //line n1
        this.trans = trans;
    }

    Car(String type, int maxSpeed, String trans) {
        super(type, maxSpeed);   // line n2
        this.trans = trans;
    }
}

```

And given the code fragment:

```

7. Car c1 = new Car("Auto");
8. Car c2 = new Car("4W", 150, "Manual");
9. System.out.println(c1.type + " " + c1.maxSpeed + " " + c1.trans);
10. System.out.println(c2.type + " " + c2.maxSpeed + " " + c2.trans);

```

What is the result?

- A. 4W 100 Auto
4W 150 Manual
- B. null 0 Auto
4W 150 Manual
- C. Compilation fails only at line n1
- D. Compilation fails only at line n2
- E. Compilation fails at both line n1 and line n2

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

QUESTION 8

Given:

```
class Caller {  
    private void init () {  
        System.out.println("Initialized");  
    }  
  
    private void start () {  
        init();  
        System.out.println("Started");  
    }  
}  
  
public class TestCall {  
    public static void main(String[] args) {  
        Caller c = new Caller();  
        c.start(); // line n1  
        c.init(); // line n2  
    }  
}
```

What is the result?

- A. Compilation fails at line n1.
- B. Initialized
 Started
 Initialized
- C. Initialized
 Started
- D. Compilation fails at line n2.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 9

Given these two classes:

```

public class Customer {
    ElectricAccount acct = new ElectricAccount();

    public void useElectricity(double kWh) {
        acct.addKWh(kWh);
    }
}

public class ElectricAccount {
    private double kWh;
    private double rate = 0.07;
    private double bill;

    //line n1
}

```

Any amount of electricity used by a customer (represented by an instance of the `Customer` class) must contribute to the customer's bill (represented by the member variable `bill`) through the `useElectricity` method.

An instance of the `Customer` class should never be able to tamper with or decrease the value of the member variable `bill`.

How should you write methods in the `ElectricAccount` class at line n1 so that the member variable `bill` is always equal to the value of the member variable `kwh` multiplied by the member variable `rate`?

- A.

```
public void addKWh(double kWh) {
    this.kWh += kWh;
    this.bill = this.kWh*this.rate;
}
```
- B.

```
public void addKWh(double kWh) {
    if (kWh > 0) {
        this.kWh += kWh;
        this.bill = this.kWh * this.rate;
    }
}
```
- C.

```
private void addKWh(double kWh) {
    if (kWh > 0) {
        this.kWh += kWh;
        this.bill = this.kWh*this.rate;
    }
}
```

```
D. public void addKWh(double kWh) {  
    if(kWh > 0) {  
        this.kWh += kWh;  
        setBill(this.kWh);  
    }  
}  
public void setBill(double kWh) {  
    bill = kWh*rate;  
}
```

Correct Answer: A → B

Section: (none) **Explanation**

Explanation/Reference:

QUESTION 10

Given the code fragment:

```
public static void main(String[] args) {  
    StringBuilder sb = new StringBuilder("Java");  
    String s = "Java";  
  
    if (sb.toString().equals(s.toString())) {  
        System.out.println("Match 1");  
    } else if (sb.equals(s)) {  
        System.out.println("Match 2");  
    } else {  
        System.out.println("No Match");  
    }  
}
```

What is the result?

- A. Match 1
- B. Match 2
- C. No Match
- D. A NullPointerException is thrown at runtime.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 11

Given:

```

interface Readable {
    public void readBook();
    public void setBookMark();
}

abstract class Book implements Readable { // line n1
    public void readBook() { }
    // line n2
}

class EBook extends Book { // line n3
    public void readBook() { }
    // line n4
}

```

And given the code fragment:

```
Book book1 = new EBook();
book1.readBook();
```

Which option enables the code to compile?

- A) Replace the code fragment at line n1 with:
`class Book implements Readable {`
 - B) At line n2 insert:
`public abstract void setBookMark();`
 - C) Replace the code fragment at line n3 with:
`abstract class EBook extends Book {`
 - D) At line n4 insert:
`public void setBookMark() { }`
- A. OptionA
B. OptionB
C. OptionC
D. OptionD

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 12

Given:

```
public static void main(String[] args) {  
    String ta = "A ";  
    ta = ta.concat("B ");  
    String tb = "C ";  
    ta = ta.concat(tb);  
    ta.replace('C', 'D');  
    ta = ta.concat(tb);  
    System.out.println(ta);  
}
```

What is the result?

- A. ABCD
- B. ACD
- C. ACDD
- D. ABD
- E. ABDC
- F. ABCC

Correct Answer: C → F

Section: (none) **Explanation**

Explanation/Reference:

QUESTION 13

Given:

```
class CD {  
    int r;  
    CD(int r){  
        this.r=r;  
    }  
}  
  
class DVD extends CD {  
    int c;  
    DVD(int r, int c) {  
        // line n1  
    }  
}
```

And given the code fragment:

```
DVD dvd = new DVD(10, 20);
```

Which code fragment should you use at line n1 to instantiate the dvd object successfully?

- A) super.r = r;
this.c = c;
- B) super(r);
this(c);
- C) super(r);
this.c = c;
- D) this.c = r;
super(c);

- A. OptionA
- B. OptionB
- C. OptionC
- D. OptionD

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 14

Given the code fragment:

```
int a[] = {1, 2, 3, 4, 5};  
for(XXX) {  
    System.out.print(a[e]);  
}
```

Which option can replace xxx to enable the code to print 135?

- A. int e = 0; e <= 4; e++
- B. int e = 0; e < 5; e += 2
- C. int e = 1; e <= 5; e += 1
- D. int e = 1; e < 5; e+=2

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 15

Which statement best describes encapsulation?

- A. Encapsulation ensures that classes can be designed so that only certain fields and methods of an object

- are accessible from other objects.
- B. Encapsulation ensures that classes can be designed so that their methods are inheritable.
 - C. Encapsulation ensures that classes can be designed with some fields and methods declared as abstract.
 - D. Encapsulation ensures that classes can be designed so that if a method has an argument MyType x, any subclass of MyType can be passed to that method.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 16

Given the code fragment from three files:

SalesMan.java:

```
package sales;
public class SalesMan { }
```

Product.java:

```
package sales.products;
public class Product { }
```

Market.java:

```
1. package market;
2. // insert code here
3. public class USMarket {
4.     SalesMan sm;
5.     Product p;
6. }
```

Which code fragment, when inserted at line 2, enables the code to compile?

- A) import sales.*;
- B) import java.sales.products.*;
- C) import sales;
 import sales.products;
- D) import sales.*;
 import products.*;
- E) import sales.*;
 import sales.products.*;

- A. Option A
- B. Option B
- C. Option C
- D. Option D
- E. Option E

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

QUESTION 17

Given this class:

```
public class CheckingAccount {  
    public int amount;  
    public CheckingAccount(int amount){  
        this.amount = amount;  
    }  
    public int getAmount(){ return amount; }  
    public void setAmount(int amount){ this.amount = amount; }  
    public void changeAmount(int x){  
        amount += x;  
    }  
}
```

And given this main method, located in another class:

```
public static void main(String[] args) {  
    CheckingAccount acct = new CheckingAccount((int)(Math.random()*1000));  
    //line n1  
    System.out.println(acct.getAmount());  
}
```

Which three lines, when inserted independently at line n1, cause the program to print a 0 balance? (Choose three.)

- A. acct.setAmount(-acct.getAmount());
- B. acct.amount = 0; <option D earlier>
- C. acct.setAmount(0);
- D. acct.getAmount() = 0; <option E earlier>
- E. this.amount = 0; <option A earlier>
- F. acct.changeAmount(0); <option F earlier>
- G. acct.changeAmount(-acct.amount); <option G earlier>

Correct Answer: BDF -> **BCG**

Section: (none) **Explanation**

Explanation/Reference:

QUESTION 18

Given the code fragment:

```
String shirts[][] = new String[2][2];
shirts[0][0] = "red";
shirts[0][1] = "blue";
shirts[1][0] = "small";
shirts[1][1] = "medium";
```

Which code fragment prints red:blue:small:medium?

- A.

```
for (int index = 1; index < 2; index++) {
    for (int idx = 1; idx < 2; idx++) {
        System.out.print(shirts[index][idx] + ":");

    }
}
```
- B.

```
for (int index = 0; index < 2; ++index) {
    for (int idx = 0; idx < index; ++idx) {
        System.out.print(shirts[index][idx] + ":");

    }
}
```
- C.

```
for (String [] c : shirts) {
    for (String s : c) {
        System.out.print(s + ":");

    }
}
```
- D.

```
for (int index = 0; index <=2;) {
    for (int idx = 0; idx <=2;) {
        System.out.print(shirts[index][idx] + ":");

        idx++;

    }
    index++;
}
```

Correct Answer: D → C

Section: (none) Explanation

Explanation/Reference:

QUESTION 19

Given the code fragment:

```

public class Test{

    void readCard(int cardNo) throws Exception {
        System.out.println("Reading Card");
    }

    void checkCard(int cardNo) throws RuntimeException { // line n1
        System.out.println("Checking Card");
    }

    public static void main(String[] args) {
        Test ex = new Test();
        int cardNo = 12344;
        ex.readCard(cardNo);                      //line n2
        ex.checkCard(cardNo);                     //line n3
    }
}

```

What is the result?

- A. Reading Card
Checking Card
- B. Compilation fails only at line n1.
- C. Compilation fails only at line n2.
- D. Compilation fails only at line n3.
- E. Compilation fails at both line n2 and line n3.

Correct Answer: D → C

Section: (none) **Explanation:**

Explanation/Reference:

QUESTION 20

Given the code fragment:

```

3. public static void main(String[] args) {
4.     int x = 5;
5.     while (isAvailable(x)) {
6.         System.out.print(x);
7.
8.     }
9. }
10.
11. public static boolean isAvailable(int x) {
12.     return x-- > 0 ? true : false;
13. }

```

Which modification enables the code to print 54321?

- A. Replace line 6 with System.out.print (--x);

- B. At line 7, insert `x --;`
- C. Replace line 6 with `--x`; and, at line 7, insert `System.out.print(x);`
- D. Replace line 12 with `return (x > 0) ? false: true;`

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 21

Given the code fragment:

```
4. public static void main(String[] args) {  
5.     boolean opt = true;  
6.     switch (opt) {  
7.         case true:  
8.             System.out.print("True");  
9.             break;  
10.        default:  
11.            System.out.print("****");  
12.        }  
13.        System.out.println("Done");  
14. }
```

Which modification enables the code fragment to print TrueDone?

- A. Replace line 5 With `String opt = "true";`
Replace line 7 with `case "true":`
- B. Replace line 5 with `boolean opt = 1;`
Replace line 7 with `case 1:`
- C. At line 9, remove the `break` statement.
- D. Remove the `default` section.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 22

Given the following main method:

```
public static void main(String[] args) {  
    int num = 5;  
    do {  
        System.out.print(num-- + " ");  
    } while (num == 0);  
}
```

What is the result?

- A. 5 4 3 2 1 0
- B. 5 4 3 2 1
- C. 4 2 1
- D. 5
- E. Nothing is printed

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 23

Given the code fragment:

```
int x = 100;
int a = x++;
int b = ++x;
int c = x++;
int d = (a < b) ? (a < c) ? a: (b < c )? b: c: x;
System.out.println(d);
```

What is the result?

- A. 100
- B. 101
- C. 102
- D. 103
- E. Compilation fails

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 24

Given the code fragment:

```
public static void main(String[] args) {
    Short s1 = 200;
    Integer s2 = 400;
    String s3 = (String) (s1 + s2);      //line n1
    Long s4 = (long) s1 + s2;           //line n2
    System.out.println("Sum is " + s4);
}
```

What is the result?

- A. Sum is 600
- B. Compilation fails at line n1.
- C. Compilation fails at line n2.
- D. A ClassCastException is thrown at line n1.
- E. A ClassCastException is thrown at line n2.

Correct Answer: E → B

Section: (none) Explanation

Explanation/Reference:

QUESTION 25

Given the code fragment:

```
public class Employee {  
    String name;  
    boolean contract;  
    double salary;  
    Employee() {  
        // line n1  
    }  
    public String toString(){  
        return name + ":" + contract + ":" + salary;  
    }  
    public static void main(String[] args) {  
        Employee e = new Employee();  
        // line n2  
        System.out.print(e);  
    }  
}
```

Which two modifications, when made independently, enable the code to print `joe:true: 100.0`? (Choose two.)

- A) Replace line n2 with:

```
e.name = "Joe";  
e.contract = true;  
e.salary = 100;
```
- B) Replace line n2 with:

```
this.name = "Joe";  
this.contract = true;  
this.salary = 100;
```
- C) Replace line n1 with:

```
this.name = new String("Joe");  
this.contract = new Boolean(true);  
this.salary = new Double(100);
```
- D) Replace line n1 with:

```
name = "Joe";  
contract = TRUE;  
salary = 100.0f;
```
- E) Replace line n1 with:

```
this("Joe", true, 100);
```

- A. OptionA
- B. OptionB
- C. OptionC
- D. OptionD
- E. OptionE

Correct Answer: AC

Section: (none)

Explanation

Explanation/Reference:

QUESTION 26

Given the code fragment:

```
public static void main(String[] args) {  
    List<String> names = new ArrayList<>();  
    names.add("Robb");  
    names.add("Bran");  
    names.add("Rick");  
    names.add("Bran");  
  
    if (names.remove("Bran")) {  
        names.remove("Jon");  
    }  
    System.out.println(names);  
}
```

What is the result?

- A. [Robb, Rick, Bran]
- B. [Robb, Rick]
- C. [Robb, Bran, Rick, Bran]
- D. An exception is thrown at runtime.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 27

Given:

```
class A {
    public A(){
        System.out.print("A ");
    }
}

class B extends A{
    public B() //line n1
        System.out.print("B ");
    }
}

class C extends B{
    public C() //line n2
        System.out.print("C ");
    }
    public static void main(String[] args) {
        C c = new C();
    }
}
```

What is the result?

- A. CBA
- B. C
- C. ABC
- D. Compilation fails at line n1 and line n2

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 28

Given:

```
class X {  
    static int i;  
    int j;  
    public static void main(String[] args) {  
        X x1 = new X();  
        X x2 = new X();  
        x1.i = 3;  
        x1.j = 4;  
        x2.i = 5;  
        x2.j = 6;  
        System.out.println(  
            x1.i + " " +  
            x1.j + " " +  
            x2.i + " " +  
            x2.j);  
    }  
}
```

What is the result?

- A. 3 4 5 6
- B. 3 4 3 6
- C. 5 4 5 6
- D. 3 6 4 6

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 29

Given the code fragment:

```
1. public class Test {  
2.     public static void main(String[] args) {  
3.         /* insert code here */  
4.         array[0]=10;  
5.         array[1]=20;  
6.         System.out.print(array[0]+":"+array[1]);  
7.     }  
8. }
```

Which code fragment, when inserted at line 3, enables the code to print 10:20?

- A. `int[] array = new int[1];`

- B. int[] array;
array = new int[2];
- C. int array = new int[2];
- D. int array[1];

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Your Code ...

```
1- public class Test {  
2-     public static void main (String[] args) {  
3-         int[] array;  
4-         array = new int[2];  
5-         array[0]=10;  
6-         array[1]=20;  
7-         System.out.print(array[0]+":"+array[1]);  
8-     }  
9- }  
10
```

CommandLine Arguments ...

Stdin Inputs...

Result...
CPU Time: 0.10 sec(s), Memory: 30316 kilobyte(s)

10:20

QUESTION 30

Given the code fragment:

```

public static void main(String[] args) {
    String[] arr = {"A", "B", "C", "D"};
    for (int i = 0; i < arr.length; i++) {
        System.out.print(arr[i] + " ");
        if (arr[i].equals("C")) {
            continue;
        }
        System.out.println("Work done");
        break;
    }
}

```

What is the result?

- A. A B C Work done
- B. A B C D Work done
- C. A Work done
- D. Compilation fails

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 31

Which three are advantages of the Java exception mechanism? (Choose three.)

- A. Improves the program structure because the error handling code is separated from the normal program function
- B. Provides a set of standard exceptions that covers all possible errors
- C. Improves the program structure because the programmer can choose where to handle exceptions
- D. Improves the program structure because exceptions must be handled in the method in which they occurred
- E. Allows the creation of new exceptions that are customized to the particular program being created

Correct Answer: ACE

Section: (none)

Explanation

Explanation/Reference:

Reference: <http://javajee.com/introduction-to-exceptions-in-java>

QUESTION 32

Given the code from the Greeting.Java file:

```

public class Greeting {
    public static void main(String[] args) {
        System.out.println("Hello " + args[0]);
    }
}

```

Which set of commands prints Hello Duke in the console?

- A) javac Greeting
java Greeting Duke
- B) javac Greeting.java Duke
java Greeting
- C) javac Greeting.java
java Greeting Duke
- D) javac Greeting.java
java Greeting.class Duke

- A. OptionA
- B. OptionB
- C. OptionC
- D. OptionD

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 33

Given:

```
class Alpha {  
    int ns;  
    static int s;  
    Alpha(int ns) {  
        if (s < ns) {  
            s = ns;  
            this.ns = ns;  
        }  
    }  
    void doPrint() {  
        System.out.println("ns = " + ns + " s = " + s);  
    }  
}
```

And:

```
public class TestA {  
    public static void main(String[] args) {  
        Alpha ref1 = new Alpha(100);  
        Alpha ref2 = new Alpha(50);  
        Alpha ref3 = new Alpha(125);  
        ref1.doPrint();  
        ref2.doPrint();  
        ref3.doPrint();  
    }  
}
```

What is the result?

- A) ns = 100 s = 125
ns = 0 s = 125
ns = 125 s = 125
- B) ns = 50 s = 125
ns = 125 s = 125
ns = 0 s = 125
- C) ns = 50 s = 50
ns = 125 s = 125
ns = 100 s = 100
- D) ns = 50 s = 50
ns = 125 s = 125
ns = 0 s = 125

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Result

CPU Time: 0.30 sec(s), Memory: 35948 kilobyte(s)

```
ns = 100 s = 125  
ns = 0 s = 125  
ns = 125 s = 125
```

QUESTION 34

Given the code fragment:

```
public static void main(String[] args) {
    int ii = 0;
    int jj = 7;
    for (ii = 0; ii < jj - 1; ii = ii + 2) {
        System.out.print(ii + " ");
    }
}
```

What is the result?

- A. 2 4
- B. 0 2 4 6
- C. 0 2 4
- D. Compilation fails

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 35

Given the code fragment:

```
LocalDate date1 = LocalDate.now();
LocalDate date2 = LocalDate.of(6, 20, 2014 );
LocalDate date3 = LocalDate.parse("2014-06-20", DateTimeFormatter.ISO_DATE);
System.out.println("date1 = " + date1);
System.out.println("date2 = " + date2);
System.out.println("date3 = " + date3);
```

Assume that the system date is June 20, 2014. What is the result?

- A. date1 = 2014-06-20
date2 = 2014-06-20
date3 = 2014-06-20
- B. date1 = 06/20/2014
date2 = 2014-06-20
date3 = Jun 20, 2014
- C. Compilation fails.
- D. An exception is thrown at runtime.

Correct Answer: A → D

Section: (none) Explanation

Explanation/Reference:

QUESTION 36

Given the code fragment:

```
7. StringBuilder sb1 = new StringBuilder("Duke");
8. String str1 = sb1.toString();
9. // insert code here
10. System.out.print(str1 == str2);
```

Which code fragment, when inserted at line 9, enables the code to print true?

- A. String str2 = str1;
- B. String str2 = new String(str1);
- C. String str2 = sb1.toString();
- D. String str2 = "Duke";

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 37

Given:

```
public class Test {
    public static void main(String[] args) {
        Test ts = new Test();
        System.out.print(isAvailable + " ");
        isAvailable= ts.doStuff();
        System.out.println(isAvailable);
    }
    public static boolean doStuff() {
        return !isAvailable;
    }
    static boolean isAvailable = false;
}
```

What is the result?

- A. Compilation fails.
- B. false true
- C. true false
- D. true true
- E. false false

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 38

Given the code fragment:

```
public static void main(String[] args) {
    double discount = 0;
    int qty = Integer.parseInt(args[0]);
    //line n1;
}
```

And given the requirements:

- If the value of the `qty` variable is greater than or equal to 90, `discount = 0.5`
- If the value of the `qty` variable is between 80 and 90, `discount = 0.2`

Which two code fragments can be independently placed at line n1 to meet the requirements? (Choose two.)

- A) `if (qty >= 90) { discount = 0.5; }`
`if (qty > 80 && qty < 90) { discount = 0.2; }`
- B) `discount = (qty >= 90) ? 0.5 : 0;`
`discount = (qty > 80) ? 0.2 : 0;`
- C) `discount = (qty >= 90) ? 0.5 : (qty > 80) ? 0.2 : 0;`
- D) `if (qty > 80 && qty < 90) {
 discount = 0.2;
 } else {
 discount = 0;
 }
 if (qty >= 90) {
 discount = 0.5;
 } else {
 discount = 0;
 }
}`
- E) `discount = (qty > 80) ? 0.2 : (qty >= 90) ? 0.5 : 0;`

- A. OptionA
- B. OptionB
- C. OptionC
- D. OptionD
- E. OptionE

Correct Answer: AC

Section: (none)

Explanation

Explanation/Reference:

QUESTION 39

Given:

```
public class Test {  
  
    public static void main(String[] args) {  
        if (args[0].equals("Hello") ? true : false) {  
            System.out.println("Success");  
        } else {  
            System.out.println("Failure");  
        }  
    }  
}
```

And given the commands:

```
javac Test.java  
Java Test Hello
```

What is the result?

- A. Success
- B. Failure
- C. Compilation fails.
- D. An exception is thrown at runtime

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 40

Which three statements describe the object-oriented features of the Java language? (Choose three.)

- A. Objects can be reused.
- B. A subclass must override the methods from a superclass.
- C. Objects can share behaviors with other objects.
- D. A package must contain a main class.
- E. Object is the root class of all other objects.
- F. A main method must be declared in every class.

Correct Answer:

BCF → ACE

Section: (none)

Explanation

Explanation/Reference:

Reference: <http://www.javaworld.com/article/2075459/java-platform/java-101--object-oriented-language-basics--part-5--object-and-its-methods.html> (see the sub title, Object is root of all classes not all other objects)

QUESTION 41

Given the following code:

```
public static void main(String[] args){  
    String[] planets = {"Mercury", "Venus", "Earth", "Mars");  
  
    System.out.println(planets.length);  
    System.out.println(planets[1].length());  
}
```

What is the output?

- A. 4
4
- B. 3
5
- C. 4
7
- D. 5
4
- E. 4
5
- F. 4
21

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

QUESTION 42

You are developing a banking module. You have developed a class named ccMask that has a maskcc method.

Given the code fragment:

```
class CCmask {  
    public static String maskCC(String creditCard) {  
        String x = "XXXX-XXXX-XXXX- ";  
        //line n1  
    }  
  
    public static void main(String[] args) {  
        System.out.println(maskCC("1234-5678-9101-1121"));  
    }  
}
```

You must ensure that the maskcc method returns a string that hides all digits of the credit card number except the four last digits (and the hyphens that separate each group of four digits).

Which two code fragments should you use at line n1, independently, to achieve this requirement? (Choose two.)

- A) `StringBuilder sb = new StringBuilder(creditCard);
 sb.substring(15, 19);
 return x + sb;`
- B) `return x + creditCard.substring(15, 19);`
- C) `StringBuilder sb = new StringBuilder(x);
 sb.append(creditCard, 15, 19);
 return sb.toString();`
- D) `StringBuilder sb = new StringBuilder(creditCard);
 StringBuilder s = sb.insert(0, x);
 return s.toString();`

- A. OptionA
- B. OptionB
- C. OptionC
- D. OptionD

Correct Answer: BC

Section: (none)

Explanation

Explanation/Reference:

QUESTION 43

Given:

```
Acc.java:  
package p1;  
public class Acc {  
    int p;  
    private int q;  
    protected int r;  
    public int s;  
}
```

Test.java:

```
package p2;  
import p1.Acc;  
public class Test extends Acc {  
    public static void main(String[] args) {  
        Acc obj = new Test();  
    }  
}
```

Which statement is true?

- A. Both p and s are accessible via obj.

- B. Only s is accessible via obj.
- C. Both r and s are accessible via obj.
- D. p, r, and s are accessible via obj.

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 44

Given:

Base.java:

```
class Base {  
    public void test(){  
        System.out.println("Base ");  
    }  
}
```

DerivedA.java:

```
class DerivedA extends Base {  
    public void test(){  
        System.out.println("DerivedA ");  
    }  
}
```

DerivedB.java:

```
class DerivedB extends DerivedA {  
    public void test(){  
        System.out.println("DerivedB ");  
    }  
    public static void main(String[] args) {  
        Base b1 = new DerivedB();  
        Base b2 = new DerivedA();  
        Base b3 = new DerivedB();  
        b1 = (Base) b3;  
        Base b4 = (DerivedA) b3;  
        b1.test();  
        b4.test();  
    }  
}
```

What is the result?

- A. Base
DerivedA

- B. Base
DerivedB
- C. DerivedB
DerivedB
- D. DerivedB
DerivedA
- E. A `ClassCastException` is thrown at runtime.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 45

Given the code fragment:

```
public static void main(String[] args) {  
    ArrayList myList = new ArrayList();  
    String[] myArray;  
    try {  
        while (true) {  
            myList.add("My String");  
        }  
    }  
    catch (RuntimeException re) {  
        System.out.println("Caught a RuntimeException");  
    }  
    catch (Exception e) {  
        System.out.println("Caught an Exception");  
    }  
    System.out.println("Ready to use");  
}
```

What is the result?

- A. Execution terminates in the first catch statement, and Caught a `RuntimeException` is printed to the console.
- B. Execution terminates in the second catch statement, and Caught an `Exception` is printed to the console.
- C. A runtime error is thrown in the thread "main".
- D. Execution completes normally, and Ready to use is printed to the console.
- E. The code fails to compile because a `throws` keyword is required.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 46

Given:

```
System.out.println("5 + 2 = " + 3 + 4);  
System.out.println("5 + 2 = " + (3 + 4));
```

What is the result?

- A) 5 + 2 = 34
5 + 2 = 34
- B) 5 + 2 + 3 + 4
5 + 2 = 7
- C) 7 = 7
7 + 7
- D) 5 + 2 = 34
5 + 2 = 7

- A. OptionA
- B. OptionB
- C. OptionC
- D. OptionD

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 47

Given the code fragments:

Person.java:

```
public class Person {  
    String name;  
    int age;  
  
    public Person(String n, int a) {  
        name = n;  
        age = a;  
    }  
  
    public String getName() {  
        return name;  
    }  
  
    public int getAge() {  
        return age;  
    }  
}
```

Test.java:

```
public static void checkAge(List<Person> list, Predicate<Person> predicate) {  
    for (Person p : list) {  
        if (predicate.test(p)) {  
            System.out.println(p.name + " ");  
        }  
    }  
}  
  
public static void main(String[] args) {  
    List<Person> iList = Arrays.asList(new Person("Hank", 45),  
                                         new Person("Charlie", 40),  
                                         new Person("Smith", 38));  
    //line n1  
}
```

Which code fragment, when inserted at line n1, enables the code to print Hank?

- A. `checkAge (iList, () -> p. get Age () > 40);`
- B. `checkAge(iList, Person p -> p.getAge() > 40);`
- C. `checkAge (iList, p -> p.getAge () > 40);`
- D. `checkAge(iList, (Person p) -> { p.getAge() > 40; });`

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 48

Given the code fragment:

```
public static void main(String[] args) {
    String[][] arr = {{"A", "B", "C"}, {"D", "E"}};
    for (int i = 0; i < arr.length; i++) {
        for (int j = 0; j < arr[i].length; j++) {
            System.out.print(arr[i][j] + " ");
            if (arr[i][j].equals("B")) {
                break;
            }
        }
        continue;
    }
}
```

What is the result?

- A. A B C
- B. A B C D E
- C. A B D E
- D. Compilation fails.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 49

Given the code fragment:

```
public static void main(String[] args) {
    String str = " ";
    str.trim();
    System.out.println(str.equals("") + " " + str.isEmpty());
}
```

What is the result?

- A. true true
- B. true false
- C. false false
- D. false true

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 50

Given the code fragment:

```

public class App {
    public static void main(String[] args) {
        String str1 = "Java";
        String str2 = new String("java");
        //line n1
        {
            System.out.println("Equal");
        } else {
            System.out.println("Not Equal");
        }
    }
}

```

Which code fragment, when inserted at line n1, enables the App class to print Equal?

- A) str1.toLowerCase();
 if (str1 == str2)
 - B) if (str2.equals(str1.toLowerCase()))
 - C) Str1.toLowerCase();
 if (str1.equals(str1.toLowerCase()))
 - D) if (str1.toLowerCase() == str2.toLowerCase())
- A. OptionA
 B. OptionB
 C. OptionC
 D. OptionD

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 51

Given the code fragment:

```

public static void main(String[] args) {
    int[] arr = {1, 2, 3, 4};
    int i = 0;
    do {
        System.out.print(arr[i] + " ");
        i++;
    } while (i < arr.length + 1);
}

```

What is the result?

- A. 1 2 3 4
 - followed by an `ArrayIndexOutOfBoundsException`
- B. 1 2 3
- C. 1 2 3 4
- D. Compilation fails.

Correct Answer: B → A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
Console 8 * Console 9 * Console 10 *
1 2 3
Completed with exit code: 0
```

QUESTION 52

Given the code fragment:

```
String[] strs = new String[2];
int idx = 0;
for (String s : strs) {
    strs[idx].concat(" element " + idx);
    idx++;
}
for (idx = 0; idx < strs.length; idx++) {
    System.out.println(strs[idx]);
}
```

What is the result?

- A. Element0
Element1
- B. Null element0
Null element1
- C. Null
Null
- D. A `NullPointerException` is thrown at runtime.

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 53

Given:

```
class Vehicle {
    int x;
    Vehicle(){
        this(10); // line n1
    }
    Vehicle(int x) {
        this.x = x;
    }
}

class Car extends Vehicle {
    int y;
    Car() {
        super();
        this(20); // line n2
    }
    Car(int y) {
        this.y = y;
    }
    public String toString() {
        return super.x + ":" + this.y;
    }
}
```

And given the code fragment:

And given the code fragment:

```
Vehicle y = new Car();
System.out.println(y);
```

What is the result?

- A. 10:20
- B. 0:20
- C. Compilation fails at line n1
- D. Compilation fails at line n2

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 54

Given the definitions of the MyString class and the Test class:

MyString.java:

```
package p1;
class MyString {
    String msg;
    MyString(String msg) {
        this.msg = msg;
    }
}
```

Test.java:

```
package p1;
public class Test {
    public static void main(String[] args) {
        System.out.println("Hello " + new StringBuilder("Java SE 8"));
        System.out.println("Hello " + new MyString("Java SE 8"));
    }
}
```

What is the result?

- A. Hello Java SE 8
Hello Java SE 8
- B. Hello java.lang.StringBuilder@<<hashcode1>>
Hello p1.MyString@<<hashcode2>>
- C. Hello Java SE 8
Hello p1.MyString@<<hashcode>>
- D. Compilation fails at the Test class

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 55

Given the code fragment:

```
3. public static void main(String[] args) {  
4.     int iVar = 100;  
5.     float fVar = 100.100f;  
6.     double dVar = 123;  
7.     fVar = iVar;  
8.     iVar = fVar;  
9.     fVar = dVar;  
10.    dVar = fVar;  
11.    iVar = dVar;  
12.    dVar = iVar;  
13. }
```

Which three lines fail to compile? (Choose three.)

- A. Line 7
- B. Line 8
- C. Line 9
- D. Line 10
- E. Line 11
- F. Line 12

Correct Answer: ADF → BCE

Section: (none) **Explanation**

Explanation/Reference:

QUESTION 56

Given:

MainTest.java:

```
public class MainTest {  
  
    public static void main(int[] args) {  
        System.out.println("int main " + args[0]);  
    }  
    public static void main(Object[] args) {  
        System.out.println("Object main " + args[0]);  
    }  
    public static void main(String[] args) {  
        System.out.println("String main " + args[0]);  
    }  
}
```

and commands:

```
javac MainTest.java  
java MainTest 1 2 3
```

What is the result?

- A. int main 1
- B. Object main 1
- C. String main 1
- D. Compilation fails
- E. An exception is thrown at runtime

Correct Answer: D → C

Section: (none) Explanation

Explanation/Reference:

QUESTION 57

Given the code fragment:

```
int num[][] = new int[1][3];  
for (int i = 0; i < num.length; i++) {  
    for (int j = 0; j < num[i].length; j++) {  
        num[i][j] = 10;  
    }  
}
```

Which option represents the state of the num array after successful completion of the outer loop?

- A. num[0][0]=10
num[0][1]=10
num[0][2]=10

- B. num[0][0]=10
num[1][0]=10
num[2][0]=10
- C. num[0][0]=10
num[0][1]=0
num[0][2]=0
- D. num[0][0]=10
num[0][1]=10
num[0][2]=10
num[0][3]=10
num[1][0]=0
num[1][1]=0
num[1][2]=0
num[1][3]=0

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 58

Given this code for a `Planet` object:

```
public class Planet {  
    public String name;  
    public int moons;  
  
    public Planet(String name, int moons) {  
        this.name = name;  
        this.moons = moons;  
    }  
}
```

And this method:

```
public static void main(String[] args){  
    Planet[] planets = {  
        new Planet("Mercury", 0),  
        new Planet("Venus", 0),  
        new Planet("Earth", 1),  
        new Planet("Mars", 2)  
    };  
  
    System.out.println(planets);  
    System.out.println(planets[2].name);  
    System.out.println(planets[2].moons);  
}
```

What is the output?

- A. planets
Earth
1
- B. [LPlanets.Planet;@15db9742
Earth
1
- C. [LPlanets.Planet;@15db9742
Planets.Planet@6d06d69c
1
- D. [LPlanets.Planet;@15db9742
Planets.Planet@6d06d69c
[LPlanets.Moon;@7852e922

E. [LPlanets.Planet;@15db9742
Venus
0

Correct Answer:

C → **B**

Section: (none)

Explanation

Explanation/Reference:

QUESTION 59

You are asked to develop a program for a shopping application, and you are given this information:

- The application must contain the classes Toy, EduToy, and ConsToy. The Toy class is the superclass of the other two classes.
- The int calculatePrice (Toy t) method calculates the price of a toy.
- The void printToy (Toy t) method prints the details of a toy.

Which definition of the Toy class adds a valid layer of abstraction to the class hierarchy?

- A.

```
public abstract class Toy{
    public abstract int calculatePrice(Toy t);
    public void printToy(Toy t) ( /* code goes here */ )
}
```
- B.

```
public abstract class Toy {
    public int calculatePrice(Toy t) ;
    public void printToy(Toy t) ;
}
```
- C.

```
public abstract class Toy {
    public int calculatePrice(Toy t);
    public final void printToy(Toy t)( /* code goes here */ )
}
```
- D.

```
public abstract class Toy {
    public abstract int calculatePrice(Toy t) ( /* code goes here */ )
    public abstract void printToy(Toy t) ( /* code goes here */ )
}
```

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 60

Given the following code:

```
int[] intArr = {15, 30, 45, 60, 75};
intArr[2] = intArr[4];
intArr[4] = 90;
```

What are the values of each element in intArr after this code has executed?

- A. 15, 60, 45, 90, 75
- B. 15, 90, 45, 90, 75
- C. 15, 30, 75, 60, 90
- D. 15, 30, 90, 60, 90
- E. 15, 4, 45, 60, 90

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 61

Given this array:

```
int[] intArr = {8, 16, 32, 64, 128};
```

Which two code fragments, independently, print each element in this array? (Choose two.)

- A.

```
for (int i : intArr) {
    System.out.print(intArr[i] + " ");}
}
```
- B.

```
for (int i : intArr) {
    System.out.print(i + " ");}
}
```
- C.

```
for (int i=0 : intArr) {
    System.out.print(intArr[i] + " ");
    i++;
}
}
```
- D.

```
for (int i=0; i < intArr.length; i++) {
    System.out.print(i + " ");}
}
```
- E.

```
for (int i=0; i < intArr.length; i++) {
    System.out.print(intArr[i] + " ");}
}
```
- F.

```
for (int i; i < intArr.length; i++) {
    System.out.print(intArr[i] + " ");}
}
```

Correct Answer: BE

Section: (none)

Explanation

Explanation/Reference:

QUESTION 62

Given the content of three files:

A.java:

```
public class A {  
    public void a() {}  
    int a;  
}
```

B.java:

```
public class B {  
    private int doStuff() {  
        private int x = 100;  
        return x++;  
    }  
}
```

C.java:

```
import java.io.*;  
package p1;  
class A {  
    public void main(String fileName) throws IOException {}  
}
```

Which statement is true?

- A. Only the A.java file compiles successfully.
- B. Only the B.java file compiles successfully.
- C. Only the C.java file compiles successfully.
- D. The A.java and B.java files compile successfully.
- E. The B.java and C.java files compile successfully.
- F. The A.java and C.java files compile successfully.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 63

Given the code fragment:

```
int[] array = {1, 2, 3, 4, 5};
```

And given the requirements:

1. Process all the elements of the array in the order of entry.
2. Process all the elements of the array in the reverse order of entry.
3. Process alternating elements of the array in the order of entry.

Which two statements are true? (Choose two.)

- A. Requirements 1, 2, and 3 can be implemented by using the enhanced for loop.
- B. Requirements 1, 2, and 3 can be implemented by using the standard for loop.
- C. Requirements 2 and 3 CANNOT be implemented by using the standard for loop.
- D. Requirement 1 can be implemented by using the enhanced for loop.
- E. Requirement 3 CANNOT be implemented by using either the enhanced for loop or the standard for loop.

Correct Answer:

DE → BD

Section: (none)

Explanation

Explanation/Reference:

QUESTION 64

Given:

```
public class TestScope {  
    public static void main(String[] args) {  
        int var1 = 200;  
        System.out.print(doCalc(var1));  
        System.out.print(" "+var1);  
    }  
    static int doCalc(int var1){  
        var1 = var1 * 2;  
        return var1;  
    }  
}
```

What is the result?

- A. 400 200
- B. 200 200
- C. 400 400
- D. Compilation fails.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 65

Given the following class declarations:

- public abstract class Animal
- public interface Hunter
- public class Cat extends Animal implements Hunter
- public class Tiger extends Cat

Which answer fails to compile?

- A) `ArrayList<Animal> myList = new ArrayList<>();
myList.add(new Tiger());`
- B) `ArrayList<Hunter> myList = new ArrayList<>();
myList.add(new Cat());`
- C) `ArrayList<Hunter> myList = new ArrayList<>();
myList.add(new Tiger());`
- D) `ArrayList<Tiger> myList = new ArrayList<>();
myList.add(new Cat());`
- E) `ArrayList<Animal> myList = new ArrayList<>();
myList.add(new Cat());`

- A. OptionA
- B. OptionB
- C. OptionC
- D. OptionD
- E. OptionE

Correct Answer:

E → **D**

Section: (none)

Explanation

Explanation/Reference:

QUESTION 66

Which statement is true about Java byte code?

- A. It can run on any platform.
- B. It can run on any platform only if it was compiled for that platform.
- C. It can run on any platform that has the Java Runtime Environment.
- D. It can run on any platform that has a Java compiler.
- E. It can run on any platform only if that platform has both the Java Runtime Environment and a Java compiler.

Correct Answer:

D → **C**

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Java bytecodes help make "write once, run anywhere" possible. You can compile your program into bytecodes on any platform that has a Java compiler. The bytecodes can then be run on any implementation of the Java VM. That means that as long as a computer has a Java VM, the same program written in the Java programming language can run on Windows 2000, a Solaris workstation, or on an iMac.

Reference: <http://www.math.uni-hamburg.de/doc/java/tutorial/getStarted/intro/definition.html>

QUESTION 67

Given:

```
public class MarkList {  
    int num;  
    public static void graceMarks(MarkList obj4) {  
        obj4.num += 10;  
    }  
    public static void main(String[] args) {  
        MarkList obj1 = new MarkList();  
        MarkList obj2 = obj1;  
        MarkList obj3 = null;  
        obj2.num = 60;  
        graceMarks(obj2);  
    }  
}
```

How many MarkList instances are created in memory at runtime?

- A. 1
- B. 2
- C. 3
- D. 4

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 68

Given:

```
public class Triangle {  
    static double area;  
    int b = 2, h = 3;  
    public static void main(String[] args) {  
        double p, b, h; //line n1  
        if (area == 0) {  
            b = 3;  
            h = 4;  
            p = 0.5;  
            area = p * b * h; //line n2  
        }  
        System.out.println("Area is " + area);  
    }  
}
```

What is the result?

- A. Area is 6.0
- B. Area is 3.0
- C. Compilation fails at line n1
- D. Compilation fails at line n2.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 69

Given the code fragment:

```
public class Test {  
    public static void main(String[] args) {  
        //line n1  
        switch (x) {  
            case 1:  
                System.out.println("One");  
                break;  
            case 2:  
                System.out.println("Two");  
                break;  
        }  
    }  
}
```

Which three code fragments can be independently inserted at line n1 to enable the code to print One? (Choose three.)

- A. byte x = 1;
- B. short x = 1;
- C. String x = "1";
- D. long x = 1;
- E. double x = 1;
- F. Integer x = new Integer("1");

Correct Answer: ABF

Section: (none)

Explanation

Explanation/Reference:

QUESTION 70

Given:

```

public class App {

    public static void main(String[] args) {
        Boolean[] bool = new Boolean[2];

        bool[0] = new Boolean(Boolean.parseBoolean("true"));
        bool[1] = new Boolean(null);

        System.out.println(bool[0] + " " + bool[1]);
    }
}

```

What is the result?

- A. True false
- B. True null
- C. Compilation fails
- D. A NullPointerException is thrown at runtime

Correct Answer: A

=> B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 71

Given the following code for the classes MyException and Test:

```

public class MyException extends RuntimeException {}

public class Test {
    public static void main(String[] args) {
        try {
            method1();
        }
        catch (MyException ne) {
            System.out.print("A");
        }
    }
    public static void method1() { // line n1
        try {
            throw Math.random() > 0.5 ?new MyException() :new RuntimeException();
        }
        catch (RuntimeException re) {
            System.out.print("B");
        }
    }
}

```

What is the result?

- A. A
- B. B
- C. Either A or B
- D. A B

E. A compile time error occurs at line n1

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 72

Given:

```
public class App {  
  
    String myStr = "7007";  
  
    public void doStuff(String str) {  
        int myNum = 0;  
        try {  
            String myStr = str;  
            myNum = Integer.parseInt(myStr);  
        } catch (NumberFormatException ne) {  
            System.err.println("Error");  
        }  
        System.out.println(  
            "myStr: " + myStr + ", myNum: " + myNum);  
    }  
  
    public static void main(String[] args) {  
        App obj = new App();  
        obj.doStuff("9009");  
    }  
}
```

What is the result?

- A. myStr: 9009, myNum: 9009
- B. myStr: 7007, myNum: 7007
- C. myStr: 7007, myNum: 9009
- D. Compilation fails

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 73

Which two are benefits of polymorphism? (Choose two.)

- A. Faster code at runtime

- B. More efficient code at runtime
- C. More dynamic code at runtime
- D. More flexible and reusable code
- E. Code that is protected from extension by other classes

Correct Answer: BD

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://www.cs.princeton.edu/courses/archive/fall98/cs441/mainus/node5.html>

QUESTION 74

Given the code fragment:

```
int nums1[] = {1, 2, 3};  
int nums2[] = {1, 2, 3, 4, 5};  
nums2 = nums1;  
for (int x : nums2){  
    System.out.print(x + ":");  
}
```

What is the result?

- A. 1:2:3:4:5:
- B. 1:2:3:
- C. Compilation fails.
- D. An `ArrayOutOfBoundsException` is thrown at runtime.

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 75

Given:

```
public class Product {  
    int id;  
    String name;  
    public Product(int id, String name) {  
        this.id = id;  
        this.name = name;  
    }  
}
```

And given the code fragment:

```
4. Product p1 = new Product(101, "Pen");  
5. Product p2 = new Product(101, "Pen");  
6. Product p3 = p1;  
7. boolean ans1 = p1 == p2;  
8. boolean ans2 = p1.name.equals(p2.name);  
9. System.out.print(ans1 + ":" + ans2);
```

What is the result?

- A. true:true
- B. true:false
- C. false:true
- D. false:false

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 76

Given the following classes:

```
public class Employee {  
    public int salary;  
}  
  
public class Manager extends Employee {  
    public int budget;  
}  
  
public class Director extends Manager {  
    public int stockOptions;  
}
```

And given the following main method:

```
public static void main(String[] args) {  
    Employee employee = new Employee();  
    Manager manager = new Manager();  
    Director director = new Director();  
    //line n1  
}
```

Which two options fail to compile when placed at line n1 of the main method? (Choose two.)

- A. employee.salary = 50_000;
- B. director.salary = 80_000;
- C. employee.budget = 200_000;
- D. manager.budget = 1_000_000;
- E. manager.stockOption = 500;
- F. director.stockOptions = 1_000;

Correct Answer: CE

Section: (none)

Explanation

Explanation/Reference:

QUESTION 7

Which one of the following code examples uses valid Java syntax?

```

A.
public class Boat {

    public static void main (String [] args) {
        System.out.println ("I float.");
    }
}

B.
public class Cake {
    public static void main (String [] ) {
        System.out.println ("Chocolate");
    }
}

C.
public class Dog {
    public void main (String [] args) {
        System.out.println ("Squirrel.");
    }
}

D.
public class Bank {
    public static void main (String () args) {
        System.out.println ("Earn interest.");
    }
}

```

- A. OptionA
- B. OptionB
- C. OptionC
- D. OptionD

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://docs.oracle.com/javase/tutorial/getStarted/application/>

QUESTION 78

Given the code fragment:

```
int n [] [] = {{1, 3}, {2, 4}};
for (int i = n.length-1; i >= 0; i--) {
    for (int y : n[i]) {
        System.out.print (y);
    }
}
```

What is the result?

- A. 1324
- B. 2313
- C. 3142
- D. 4231
- E. 2413

Correct Answer: D → E

Section: (none)

Explanation

Explanation/Reference:

QUESTION 79

Given:

```
class Caller {
    private void init () {
        System.out.println("Initialized");
    }

    private void start () {
        init();
        System.out.println("Started");
    }
}

public class TestCall {
    public static void main(String[] args) {
        Caller c = new Caller();
        c.start();
        c.init();
    }
}
```

What is the result?

- A. An exception is thrown at runtime.
- B. Initialized
 Started
 Initialized
- C. Initialized
 Started
- D. Compilation fails.

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 80

Given the code fragment:

```
public static void main(String[] args) {  
    try {  
        int num = 10;  
        int div = 0;  
        int ans = num / div;  
    } catch (ArithmeticeXception ae) {  
        ans = 0;                                // line n1  
    } catch (Exception e) {  
        System.out.println("Invalid calculation");  
    }  
    System.out.println("Answer = " + ans);      // line n2  
}
```

What is the result?

- A. Answer = 0
- B. Invalid calculation
- C. Compilation fails only at line n1.
- D. Compilation fails only at line n2.
- E. Compilation fails at line n1 and line2.

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

QUESTION 81

Given:

```
public class MyField {
    int x;
    int y;
    public void doStuff(int x, int y) {
        x = x;
        y = this.y;
    }
    public void display () {
        System.out.print(x + " " + y + " : ");
    }
    public static void main(String[] args) {
        MyField m1 = new MyField();
        m1.x = 100;
        m1.y = 200;
        MyField m2 = new MyField();
        m2.doStuff(m1.x, m1.y);
        m1.display();
        m2.display();
    }
}
```

What is the result?

- A. 100 200 : 0 0 :
- B. 100 200 : 100 0 :
- C. 100 200 : 100 200 :
- D. 0 0 : 100 0 :

Correct Answer: B

=> A Section:

(none)

Explanation

Explanation/Reference:

QUESTION 82

Given:

```

public class Vowel {
    private char var;
    public static void main(String[] args) {
        char var1 = 'a';
        char var2 = var1;
        var2 = 'e';

        Vowel obj1 = new Vowel();
        Vowel obj2 = obj1;
        obj1.var = 'o';
        obj2.var = 'i';

        System.out.println(var1 + ", " + var2);
        System.out.print(obj1.var + ", " + obj2.var);
    }
}

```

What is the result?

- A. a, e
 i, i
- B. a, e
 o, o
- C. e, e
 i, i
- D. a, a
 o, o

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 83

Given the code fragment:

```

if (aVar++ < 10) {
    System.out.println(aVar + " Hello Universe!");
} else {
    System.out.println(aVar + " Hello World!");
}

```

What is the result if the integer aVar is 9?

- A. Compilation fails.
- B. 10 Hello Universe!
- C. 10 Hello World!

D. 9 Hello World!

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 84

Given:

```
public class MyClass {  
    public static void main(String[] args) {  
        String s = "Java SE 8 1";  
        int len = s.trim().length();  
        System.out.print(len);  
    }  
}
```

What is the result?

- A. Compilation fails.
- B. 11
- C. 8
- D. 9
- E. 10

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 85

Given:

```
public class Test {  
    public static void main(String[] args) {  
        boolean a = new Boolean(Boolean.valueOf(args[0]));  
        boolean b = new Boolean(args[1]);  
        System.out.println(a + " " + b);  
    }  
}
```

And given the commands:

```
javac Test.java  
java Test 1 null
```

What is the result?

- A. 1 null
- B. true false
- C. false false
- D. true true
- E. A ClassCastException is thrown at runtime.

Correct Answer: D

=> C Section:

(none)

Explanation

Explanation/Reference:

QUESTION 86

Given the code fragment:

```
public static void main(String[] args) {  
    int[][] arr = new int [2] [4];  
    arr[0] = new int []{1, 3, 5, 7};  
    arr[1] = new int []{1, 3};  
    for (int[] a : arr) {  
        for (int i : a) {  
            System.out.print(i+ " ");  
        }  
        System.out.println();  
    }  
}
```

What is the result?

- A. Compilation fails.
- B. 1 3
1 3
- C. 1 3
followed by an ArrayIndexOutOfBoundsException
- D. 1 3
1 3 0 0
- E. 1 3 5 7
1 3

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Explanation:

The screenshot shows a Java code editor interface. In the 'Your Code' section, the following code is written:

```
1 public class MyClass {  
2     public static void main (String [] args) {  
3         int [] arr = new int [2] [4];  
4         arr[0] = new int [] {1, 3, 5, 7};  
5         arr[1] = new int [] {1, 3};  
6         for (int [] a : arr) {  
7             for (int i : a) {  
8                 System.out.print(i+ " ");  
9             }  
10            System.out.println ();  
11        }  
12    }  
13 }  
14 }
```

Below the code, there are sections for 'External Libraries' (with a link to 'Add External Library (from Maven Repo)'), 'CommandLine Arguments' (empty), and configuration options for 'Interactive mode' (OFF) and 'Version' (JDK 9.0.1). The 'Stdin Inputs...' field is also empty.

At the bottom, there are buttons for 'Execute', 'Save', 'My Projects', 'Recent', 'Collaborate', and 'More Options'. The 'Result...' section displays the output of the executed code:

CPU Time: 0.13 sec(s), Memory: 30680 kilobyte(s) compiled and executed in 0.705 sec(s)

```
1 3 5 7  
1 3
```

QUESTION 87

Which statement will empty the contents of a StringBuilder variable named sb?

- A. sb.deleteAll();
- B. sb.delete(0, sb.size());
- C. sb.delete(0, sb.length());
- D. sb.removeAll();

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 88

Given:

```
String stuff = "TV";
String res = null;

if (stuff.equals("TV")) {
    res = "Walter";
} else if (stuff.equals("Movie")) {
    res = "White";
} else {
    res = "No Result";
}
```

Which code fragment can replace the if block?

- A. stuff.equals ("TV") ? res= "Walter" : stuff.equals ("Movie") ?
res = "White" : res = "No Result";
- B. res = stuff.equals ("TV") ? "Walter" else stuff.equals
("Movie")? "White" : "No Result";
- C. res = stuff.equals ("TV") ? stuff.equals ("Movie")? "Walter" :
"White" : "No Result";
- D. res = stuff.equals ("TV")? "Walter" : stuff.equals ("Movie")?
"White" : "No Result";

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 89

Given:

```
class Patient {
    String name;
    public Patient (String name) {
        this.name = name;
    }
}
```

And the code fragment:

```
8. public class Test {  
9.     public static void main (String [] args) {  
10.         List ps = new ArrayList ();  
11.         Patient p2 = new Patient ("Mike");  
12.         ps.add(p2);  
13.  
14.         // insert code here  
15.  
16.         if (f >= 0) {  
17.             System.out.print ("Mike Found");  
18.         }  
19.     }  
20. }
```

Which code fragment, when inserted at line 14, enables the code to print Mike Found?

- A. int f = ps.indexOf (p2);
- B. int f = ps.indexOf (Patient ("Mike"));
- C. int f = ps.indexOf (new Patient "Mike"));
- D. Patient p = new Patient("Mike");
int f = ps.indexOf(p)

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 90

Which statement is true about the switch statement?

- A. It must contain the default section.
- B. The break statement, at the end of each case block, is mandatory.
- C. Its case label literals can be changed at runtime.
- D. Its expression must evaluate to a single value.

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:Reference: <http://www.dummies.com/programming/java/switch-statements-in-java/>**QUESTION 91**

Given:

```
class Animal {  
    String type = "Canine";  
    int maxSpeed = 60;  
  
    Animal () {}  
  
    Animal (String type, int maxSpeed) {  
        this.type = type;  
        this.maxSpeed = maxSpeed;  
    }  
}  
  
class WildAnimal extends Animal {  
    String bounds;  
  
    WildAnimal (String bounds) {  
        //line n1  
    }  
    WildAnimal (String type, int maxSpeed, String bounds) {  
        //line n2  
    }  
}
```

And given the code fragment:

```
7. WildAnimal wolf = new WildAnimal("Long");  
8. WildAnimal tiger = new WildAnimal("Feline", 80, "Short");  
9. System.out.println(wolf.type + " " + wolf.maxSpeed + " " + wolf.bounds);  
10. System.out.println(tiger.type + " " + tiger.maxSpeed + " " + tiger.bounds);
```

and this output:

Canine 60 Long

Feline 80 Short

Which two modifications enable the code to print this output? (Choose two.)

A. Replace line n1 with:

```
super ();  
this.bounds = bounds;
```

B. Replace line n1 with:

```
this.bounds = bounds;  
super();
```

C. Replace line n2 with:

```
super(type, maxSpeed);  
this(bounds);
```

D. Replace line n1 with:

```
this("Canine", 60);  
this.bounds = bounds;
```

E. Replace line n2 with:

```
super(type, maxSpeed);  
this.bounds = bounds;
```

Correct Answer: AE

Section: (none)

Explanation

Explanation/Reference:

QUESTION 92

Given the code fragment:

```
public static void main (String [] args) {  
    String names [] = {"Thomas", "Peter", "Joseph");  
    String pwd [] = new String [3];  
    int idx = 0;  
    try {  
        for (String n: names) {  
            pwd [idx] = n.substring (2, 6);  
            idx++;  
        }  
    }  
    catch (Exception e) {  
        System.out.println ("Invalid Name");  
    }  
    for (String p: pwd) {  
        System.out.println (p);  
    }  
}
```

What is the result?

- A. Invalid Name
- B. Invalid Name
omas
- C. Invalid Name
omas
null
null
- D. omas
ter
seph

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 93

Given the code fragment:

```
class Employee {  
    private String name;  
    private int age;  
    private int salary;  
  
    public Employee (String name, int age) {  
        setName (name)  
        setAge (age)  
        setSalary (2000);  
    }  
    public Employee (String name, int age, int salary) {  
        setSalary (salary);  
        this (name, age);  
    }  
    //getter and setter methods for attributes go here  
    public void printDetails () {  
        System.out.println (name + " : " + age + " : " + salary);  
    }  
}
```

Test.java

```
class Test {  
    public static void main(String[] args) {  
        Employee e1 = new Employee();  
        Employee e2 = new Employee("Jack", 50);  
        Employee e3 = new Employee("Chloe", 40, 5000);  
  
        e1.printDetails();  
        e2.printDetails();  
        e3.printDetails();  
    }  
}
```

Which is the result?

- A. Compilation fails in the Employee class.
- B. null : 0 : 0
Jack : 50 : 0
Chloe : 40 : 5000
- C. null : 0 : 0
Jack : 50 : 2000
Chloe : 40 : 5000
- D. Compilation fails in the Test class.
- E. Both the Employee class and the Test class fail to compile.

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

QUESTION 94

Given the code fragments:

A.java:

```
package p1;  
public class A {  
}
```

B.java:

```
package p1.p2;  
//line n1  
public class B {  
    public void doStuff() {  
        A b = new A();  
    }  
}
```

C.java:

```
package p3;  
//line n2  
public class C {  
    public static void main(String[] args) {  
        A o1 = new A();  
        B o2 = new B();  
    }  
}
```

Which modification enables the code to compile?

- A. Replace line n1 with:
`import p1.*;`
Replace line n2 with:
`import p1. p2.*;`
- B. Replace line n1 with:
`import p1. A;`
Replace line n2 with:
`import p1.*;`
- C. Replace line n1 with:
`import p1. A;`
Replace line n2 with:
`import p1. A;`
`import p1. p2.B ;`

D. Replace line n1 with:

```
import p1;  
Replace line n2 with:  
import p1;  
import p1. p2;
```

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 95

Given:

```
class A {  
    public void test () {  
        System.out.println ("A");  
    }  
}  
class B extends A {  
    public void test () {  
        System.out.println ("B");  
    }  
}  
public class C extends A {  
    public void test () {  
        System.out.println ("C");  
    }  
  
    public static void main (String [] args) {  
        A b1 = new A ();  
        A b2 = new C ();  
  
        b1 = (A) b2;                      //line n1  
        A b3 = (B) b2;                      //line n2  
        b1.test ();  
        b3.test ();  
    }  
}
```

What is the result?

- A. A
- B
- C
- B. A
- C
- C
- D. A ClassCastException is thrown only at line n1.
- E. A ClassCastException is thrown only at line n2.

Correct Answer: B

=> E Section:

(none)

Explanation

Explanation/Reference:

QUESTION 96

Given: public class SumTest {

```
    public static void doSum(Integer x, Integer y) {
        System.out.println("Integer sum is " + (x + y));
    }

    public static void doSum(double x, double y) {
        System.out.println("double sum is " + (x + y));
    }

    public static void doSum(float x, float y) {
        System.out.println("float sum is " + (x + y));
    }

    public static void doSum(int x, int y) {
        System.out.println("int sum is " + (x + y));
    }

    public static void main(String[] args) {
        doSum(10, 20);
        doSum(10.0, 20.0);
    }
}
```

What is the result?

- A. int sum is 30
float sum is 30.0
- B. int sum is 30
double sum is 30.0

- C. integer sum is 30
double sum is 30.0
- D. integer sum is 30
float sum is 30.0

Correct Answer: D

=> B Section:

(none)

Explanation

Explanation/Reference:

QUESTION 97

You are asked to create a method that accepts an array of integers and returns the highest value from that array.

Given the code fragment:

```
class Test{  
    public static void main(String[] args) {  
        int numbers[] = {12, 13, 42, 32, 15, 156, 23, 51, 12};  
        int[] keys = findMax(numbers);  
    }  
  
    /* line n1 */ {  
        int[] keys = new int[3];  
        /* code goes here*/  
        return keys;  
    }  
}
```

Which method signature do you use at line n1?

- A. public int findMax (int[] numbers)
- B. static int[] findMax (int[] max)
- C. static int findMax (int[] numbers)
- D. final int findMax (int[])

Correct Answer: C

=> B Section:

(none)

Explanation

Explanation/Reference:

QUESTION 98

Which three statements are true about the structure of a Java class? (Choose three.)

- A. A public class must have a main method.

- B. A class can have only one private constructor.
- C. A method can have the same name as a field.
- D. A class can have overloaded static methods.
- E. The methods are mandatory components of a class.
- F. The fields need not be initialized before use.

Correct Answer: ACE

=> CDF Section:

(none) Explanation

Explanation/Reference:

QUESTION 99

Given the code fragment:

```
Public static void main (String [] args) {  
    System.out.println ("Result A " + 0 + 1);  
    System.out.println ("Result B " + (1) + (2) );  
}
```

What is the result?

- A. Result A 01
Result B 3
- B. Result A 1
Result B 12
- C. Result A 1
Result B 3
- D. Result A 01
Result B 12

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 100

Given:

```
public class App {  
    int count;  
    public static void displayMsg () {  
        count++; // line n1  
        System.out.println ("Welcome "+"Visit Count: "+count); // line n2  
    }  
    public static void main (String [] args) {  
        App.displayMsg (); // line n3  
        App.displayMsg (); // line n4  
    }  
}
```

What is the result?

- A. Compilation fails at line n3 and line n4.
- B. Compilation fails at line n1 and line n2.
- C. Welcome Visit Count:1
 Welcome Visit Count: 1
- D. Welcome Visit Count:1
 Welcome Visit Count: 2

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 101

Given the code fragment:

```

public class Person {
    String name;
    int age = 25;

    Person(String name) { // line n1
        setName(name);
    }

    public Person(String name, int age) { // line n2
        Person(name);
        setAge(age);
    }

    //setter and getter methods go here

    public String show() {
        return name + " " + age;
    }

    public static void main(String[] args) {
        Person p1 = new Person("Jesse");
        Person p2 = new Person("Walter", 52);
        System.out.println(p1.show());
        System.out.println(p2.show());
    }
}

```

What is the result?

- A. Compilation fails at both line n1 and line n2.
- B. Compilation fails only at line n2.
- C. Compilation fails only at line n1.
- D. Jesse 25
Walter52

Correct Answer: A

=> B Section:

(none)

Explanation

Explanation/Reference:

QUESTION 102

Given the code fragment:

```
public class Test {  
  
    static int count = 0  
    int i = 0;  
  
    public void changeCount () {  
        while (i<5) {  
            i++;  
            count++;  
        }  
    }  
  
    public static void main (String [] args) {  
        Test check1 = new Test ();  
        Test check2 = new Test ();  
        check1.changeCount ();  
        check2.changeCount ();  
        System.out. print (check1.count + " : " + check2.count);  
    }  
}
```

What is the result?

- A. 5 : 5
- B. 10 : 10
- C. 5 : 10
- D. Compilation fails.

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Your Code ...

```

1- public class Test {
2
3     static int count = 0 ;
4     int i = 0;
5
6-     public void changeCount () {
7-         while (i<5) {
8-             i++;
9-             count++;
10        }
11    }
12-   public static void main (String [ ] args) {
13-       Test check1 = new Test () ;
14-       Test check2 = new Test () ;
15-       check1.changeCount () ;
16-       check2.changeCount () ;
17-       System.out. print (check1.count + " : " + check2.count) ;
18-   }
19 }
20

```

External Libraries ...

[Add External Library \(from Maven Repo\)](#)

cs1.keyboard

Input Arguments (args of Main Method)...

Interactive mode : OFF

Stdin Inputs...

[Execute](#)[Save](#)[My Projects](#)[Recent](#)[Collaborate](#)[Others](#) ▾[Goto Another Language/DB](#) ▾

Result...

compiled and executed in 1.357 second(s)

10 : 10

QUESTION 103

Given the code fragment:

```

public static void main(String[] args) {
    ArrayList<Integer> points = new ArrayList<>();
    points.add(1);
    points.add(2);
    points.add(3);
    points.add(4);
    points.add(null);
    points.remove(1);
    points.remove(null);
    System.out.println(points);
}

```

What is the result?

- A. A NullPointerException is thrown at runtime.
- B. [1, 2, 4]
- C. [1, 2, 4, null]
- D. [1, 3, 4, null]
- E. [1, 3, 4]
- F. Compilation fails.

Correct Answer: B

=> E Section:

(none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 104

Given:

```
class Test {  
    public static void main (String [] args) {  
        int numbers [ ];  
        numbers = new int [2];  
        numbers [0] = 10;  
        numbers [1] = 20;  
  
        numbers = new int [4];  
        numbers [2] = 30;  
        numbers [3] = 40;  
        for (int x : numbers) {  
            System.out.print (" " + x) ;  
        }  
    }  
}
```

What is the result?

- A. 10 20 30 40
- B. 0 0 30 40
- C. Compilation fails.
- D. An exception is thrown at runtime.

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 105

Which two code fragments cause a compilation error? (Choose two.)

- A. float flt = 100.00F;
- B. float flt = (float) 1_11.00;
- C. Float flt = 100.00;
- D. double y1 = 203.22;
 float flt = y1;
- E. int y2 = 100;
 float flt = (float) y2 ;

Correct Answer: AD

=> CD Section:

(none) Explanation

Explanation/Reference:

QUESTION 106

Given:

```
public class Fieldinit {  
    char c;  
    boolean b;  
    float f;  
    void printAll() {  
        System.out.println ("c = " + c);  
        System.out.println ("b = " + b);  
        System.out.println ("f = " + f);  
    }  
    public static void main (String [] args) {  
        FieldInit f = new FieldInit ();  
        f.printAll ();  
    }  
}
```

What is the result?

- A. `c=`
`b = false`
`f = 0.0`
- B. `c= null`
`b = true`
`f = 0.0`

C. `c=0`
`b = false`
`f = 0.0f`

D. `c= null`
`b = false`
`f = 0.0F`

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 107

Which three statements are true about exception handling? (Choose three.)

- A. Only unchecked exceptions can be rethrown.
- B. All subclasses of the `RuntimeException` class are not recoverable.
- C. The parameter in a catch block is of `Throwable` type.
- D. All subclasses of the `RuntimeException` class must be caught or declared to be thrown.
- E. All subclasses of the `RuntimeException` class are unchecked exceptions.
- F. All subclasses of the `Error` class are not recoverable.

Correct Answer: BCD

=> CEF Section:

(none) Explanation

Explanation/Reference:

QUESTION 108

Given the code fragment:

```
public static void main(String[] args) {  
    int[] stack = {10, 20, 30};  
    int size = 3;  
    int idx = 0;  
    /* line n1 */  
    System.out.print("The Top element: " + stack[idx]);  
}
```

Which code fragment, inserted at line n1, prints The Top element: 30?

- A. `do {`
 `idx++;`
`} while (idx >=size);`

- B.

```
while (idx < size) {  
    idx++;  
}
```
- C.

```
do {  
    idx++;  
} while (idx < size -1);
```
- D.

```
do {  
    idx++;  
} while (idx<= size);
```
- E.

```
while (idx <= size -1) {  
    idx++  
}
```

Correct Answer: E

=> C Section:

(none)

Explanation

Explanation/Reference:

QUESTION 109

Given the code fragment:

```
public static void main(String[] args) {  
    String myStr = "Hello World ";  
    myStr.trim();  
    int i1 = myStr.indexOf(" ");  
    System.out.println(i1);  
}
```

What is the result?

- A. An exception is thrown at runtime.
- B. -1
- C. 5
- D. 10

Correct Answer: A

=> C Section:

(none)

Explanation

Explanation/Reference:

QUESTION 110

Given:

```
class Equal {
    public static void main (String [] args) {
        String str1 = "Java";
        String [] str2 = { "J", "a", "v", "a"};
        String str3 = "";
        for (String str : str2) {
            str3 = str3+str;
        }
        boolean b1 = (str1.equals(str3));
        boolean b2 = (str1== str3);
        System.out.print (b1+", "+b2);
    }
}
```

What is the result?

- A. false, false
- B. false, true
- C. true, false
- D. true, true

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 111

Which two statements are true? (Choose two.)

- A. Error class is unextendable.
- B. Error class is extendable.
- C. Error is a RuntimeException.
- D. Error is an Exception.
- E. Error is a Throwable.

Correct Answer: BE

Section: (none)

Explanation

Explanation/Reference:

QUESTION 112

Given the code fragment:

```
public static void main(String[] args) {  
    int data[] = {2010, 2013, 2014, 2015, 2014};  
    int key = 2014;  
    int count = 0;  
    for (int e: data) {  
        if (e != key) {  
            continue;  
            count++;  
        }  
    }  
    System.out.print(count + " Found");  
}
```

What is the result?

- A. Compilation fails.
- B. 0 Found
- C. 1 Found
- D. 3 Found

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 113

Given the code fragment:

```
LocalDate Time dt= LocalDateTime.of (2014, 7, 31, 1, 1);  
dt.plusDays (30);  
dt. plusMonths (1);  
System.out.print (dt format (DateTimeFormatter. ISO_DATE) );
```

What is the result?

- A. An exception is thrown at runtime.
- B. 07-31-2014
- C. 2014-07-31
- D. 2014-09-30

Correct Answer: A

=> C Section:

(none)

Explanation

Explanation/Reference:

QUESTION 114

Given:

```
public class Test {
    public static final int MIN = 1;
    public static void main(String[] args) {
        int x = args.length;
        if(checkLimit(x)){      // line n1
            System.out.println("Java SE");
        } else {
            System.out.println("Java EE");
        }
    }
    public static boolean checkLimit(int x) {
        return (x >= MIN) ? true : false;
    }
}
```

And given the commands:

```
javac Test.java
java Test 1
```

What is the result?

- A. JavaSE
- B. JavaEE
- C. Compilation fails at line n1.
- D. A NullPointerException is thrown at runtime.

Correct Answer: B

=> A Section:

(none)

Explanation

Explanation/Reference:

QUESTION 115

Given this class:

```
public class CheckingAccount {
    public int amount;
    //line n1
}
```

And given this `main` method, located in another class:

```
public static void main(String[] args) {
    CheckingAccount acct = new CheckingAccount();
    //line n2
}
```

Which three pieces of code, when inserted independently, set the value of amount to 100?

A. At line n1 insert:

```
public CheckingAccount() {  
    amount = 100;  
}
```

B. At line n2 insert:

```
this.amount = 100;
```

C. At line n2 insert:

```
amount = 100;
```

D. At line n1 insert:

```
public CheckingAccount() {  
    this.amount = 100;  
}
```

E. At line n2 insert:

```
acct.amount = 100;
```

F. At line n1 insert:

```
public CheckingAccount() {  
    acct.amount = 100;  
}
```

Correct Answer: CDE

=> ADE Section:

(none) Explanation

Explanation/Reference:

QUESTION 116

Given the code fragments:

```
Interface Exportable {
    Void export();
}

class Tool implements Exportable {
    protected void export () {           //line n1
        System.out.println("Tool::export");
    }
}

class ReportTool extends Tool implements Exportable {

    public void export() {             //line n2
        System.out.println("RTool::export");
    }

    public static void main(String[] args) {
        Tool aTool = new ReportTool();
        Tool bTool = new Tool();
        callExport(aTool);
        callExport(bTool);
    }

    public static void callExport (Exportable ex) {
        ex.export();
    }
}
```

What is the result?

- A. Compilation fails only at line n2.
- B. RTool::export
Tool::export
- C. Tool::export
Tool:export
- D. Compilation fails only at line n1.
- E. Compilation fails at both line n1 and line n2.

Correct Answer: B

=> D Section:

(none)

Explanation

Explanation/Reference:

QUESTION 117

Given the code fragment:

```
24. float var1 = (12_345.01 <= 123_45.00) ? 12_456 : 124_56.02f;
25. float var2 = var1 + 1024;
26. System.out.print(var2);
```

What is the result?

- A. An exception is thrown at runtime.
- B. Compilation fails.
- C. 13480.0
- D. 13480.02

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 118

Given:

```
public class Test {
    public static int stVar = 100;
    public int var = 200;
    public String toString() {
        return stVar + ":" + var;
    }
}
```

And given the code fragment:

```
Test t1 = new Test();
t1.var = 300;
System.out.println(t1);
Test t2 = new Test();
t2.stVar = 300;
System.out.println(t2);
```

What is the result?

- A. 300:300
200:300
- B. 300:100
200:300
- C. 300:0

- 0:300
D. 100:300
300:200

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 119

Given:

```
class C2 {  
    public void displayC2() {  
        System.out.print("C2");  
    }  
}  
interface I {  
    public void displayI();  
}  
class C1 extends C2 implements I {  
    public void displayI() {  
        System.out.print("C1");  
    }  
}
```

And given the code fragment:

```
C2 obj1 = new C1();  
I obj2 = new C1();  
  
C2 s = obj2;  
I t = obj1;  
  
t.displayI();  
s.displayC2()
```

What is the result?

- A. C2C2
- B. C1C2
- C. C1C1
- D. Compilation fails

Correct Answer: B

=> D Section:

(none)

Explanation

Explanation/Reference:

QUESTION 120

Given:

```
package clothing;
public class Shirt {
    public static String getColor() {
        return "Green";
    }
}
```

Given the code fragment:

```
package clothing.pants;
// line n1
public class Jeans {
    public void matchShirt(){
        // line n2
        if(color.equals("Green")) {
            System.out.print("Fit");
        }
    }
    public static void main(String[] args) {
        Jeans trouser = new Jeans();
        trouser.matchShirt();
    }
}
```

Which two sets of actions, independently, enable the code fragment to print Fit?

- A. At line n1 insert: import clothing.Shirt;
At line n2 insert: String color = Shirt.getColor();
- B. At line n1 insert: import clothing;
At line n2 insert: String color = Shirt.getColor();
- C. At line n1 insert: import static clothing.Shirt.getColor;
At line n2 insert: String color = getColor();
- D. At line n1 no changes required.
At line n2 insert: String color = Shirt.getColor();
- E. At line n1 insert: import Shirt;
At line n2 insert: String color = Shirt.getColor();

Correct Answer: D

=> A, C Section:

(none)

Explanation

Explanation/Reference:

QUESTION 121

Given the code fragments:

```
class Student {  
    String name;  
    int age;  
}
```

And:

```
4. public class Test {  
5.     public static void main(String[] args) {  
6.         Student s1 = new Student();  
7.         Student s2 = new Student();  
8.         Student s3 = new Student();  
9.         s1 = s3;  
10.        s3 = s2;  
11.        s2 = null;  
12.    }  
13.}
```

Which statement is true?

- A. After line 11, three objects are eligible for garbage collection.
- B. After line 11, two objects are eligible for garbage collection.
- C. After line 11, one object is eligible for garbage collection.
- D. After line 11, none of the objects are eligible for garbage collection.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 122

Given the code fragment:

```
int wd = 0;
String days[] = {"sun", "mon", "wed", "sat"};
for (String s:days) {
    switch (s) {
        case "sat":
        case "sun":
            wd -= 1;
            break;
        case "mon":
            wd++;
        case "wed":
            wd += 2;
    }
}
System.out.println(wd);
```

What is the result?

- A. 3
- B. 4
- C. -1
- D. Compilation fails.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 123

Given the code fragment:

```
public static void main(String[] args) {
    LocalDate date = LocalDate.of(2012, 01, 32);
    date.plusDays(10);
    System.out.println(date);
}
```

What is the result?

- A. 2012-02-10
- B. 2012-02-11
- C. Compilation fails
- D. A DateTimeException is thrown at runtime.

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 124

Given:

```
public class App {  
    public static void main(String[] args) {  
        int i = 10;  
        int j = 20;  
        int k =(j += i)/ 5;  
        System.out.print(i + " : " + j + " : " + k);  
    }  
}
```

What is the result?

- A. 10 : 30 : 6
- B. 10 : 22 : 22
- C. 10 : 22 : 20
- D. 10 : 22 : 6

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 125

Given:

```
interface Downloadable {
    public void download();
}

interface Readable extends Downloadable {           // line n1
    public void readBook();
}

abstract class Book implements Readable {           // line n2
    public void readBook() {
        System.out.println("Read Book");
    }
}

class EBook extends Book {                         // line n3
    public void readBook() {
        System.out.println("Read E-Book");
    }
}
```

And given the code fragment:

```
Book book1 = new EBook();
book1.readBook();
```

What is the result?

- A. Compilation fails at line n2.
- B. Read Book
- C. Read E-Book
- D. Compilation fails at line n1.
- E. Compilation fails at line n3.

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

QUESTION 126

Given this class:

```
public class Rectangle {  
    private double length;  
    private double height;  
    private double area;  
  
    public void setLength(double length) {  
        this.length = length;  
    }  
    public void setHeight(double height) {  
        this.height = height;  
    }  
    public void setArea() {  
        area = length*height;  
    }  
}
```

Which two changes would encapsulate this class and ensure that the area field is always equal to `length * height` whenever the Rectangle class is used?

- A. Call the setArea method at the end of the setHeight method.
- B. Call the setArea method at the beginning of the setHeight method.
- C. Call the setArea method at the end of the setLength method.
- D. Call the setArea method at the beginning of the setLength method.
- E. Change the setArea method to private.
- F. Change the area field to public.

Correct Answer: AC

Section: (none)

Explanation

Explanation/Reference:

QUESTION 127

Given the code fragment:

```
13. List colors = new ArrayList();  
14. colors.add("green");  
15. colors.add ("blue");  
16. colors.add ("red");  
17. colors.add("yellow");  
18. colors.remove(2);  
19. colors.add(3, "cyan");  
20. System.out.print(colors);
```

What is the result?

- A. [green, red, yellow, cyan]
- B. [green, blue, yellow, cyan]
- C. [green, red, cyan, yellow]
- D. An `IndexOutOfBoundsException` is thrown at runtime.

Correct Answer: D

=> B Section:

(none)

Explanation

Explanation/Reference:

QUESTION 128

```
Given abstract class Toy {  
    int price;  
    // line n1  
}
```

Which three code fragments are valid at line n1? (Choose three.)

- A. `public static void insertToy() {
 /* code goes here */
}`
- B. `final Toy getToy() {
 return new Toy();
}`
- C. `public void printToy();`
- D. `public int calculatePrice() {
 return price;
}`
- E. `public abstract int computeDiscount();`

Correct Answer: ADE

Section: (none)

Explanation

Explanation/Reference:

QUESTION 129

Given:

```
public class Test {  
    int x, y;  
  
    public Test(int x, int y) {  
        initialize(x, y);  
    }  
  
    public void initialize(int x, int y) {  
        this.x = x * x;  
        this.y = y * y;  
    }  
  
    public static void main(String[] args) {  
        int x = 3, y = 5;  
        Test obj = new Test(x, y);  
        System.out.println(x + " " + y);  
    }  
}
```

What is the result?

- A. Compilation fails.
- B. 35
- C. 00
- D. 9 25

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 130

Given the code fragment:

```
public static void main(String[] args) {  
    int array[] = {10, 20, 30, 40, 50};  
    int x = array.length;  
    /* line n1 */  
}
```

Which two code fragments can be independently inserted at line n1 to enable the code to print the elements of the array in reverse order? (Choose two.)

- A.

```
while (x > 0) {
    x--;
    System.out.print(array[x]);
}
```
- B.

```
do {
    x--;
    System.out.print(array[x]);
} while (x >= 0);
```
- C.

```
while (x >= 0) {
    System.out.print(array[x]);
    x--;
}
```
- D.

```
do {
    System.out.print(array[x]);
    --x;
} while (x >= 0);
```
- E.

```
while (x > 0) {
    System.out.print(array[--x]);
}
```

Correct Answer: AE

Section: (none)

Explanation

Explanation/Reference:

QUESTION 131

Given:

```
class Test
    int a1;

    public static void doProduct(int a) {
        a = a * a;
    }

    public static void doString(String s) {
        s.concat(" " + s);
    }

    public static void main(String[] args) {
        Test item = new Test();
        item.a1 = 11;
        String sb = "Hello";
        Integer i = 10;
        doProduct(i);
        doString(sb);
        doProduct(item.a1);
        System.out.println(i + " " + sb + " " + item.a1);
    }
}
```

What is the result?

- A. 10 Hello Hello 11
- B. 10 Hello Hello 121
- C. 100 Hello 121
- D. 100 Hello Hello 121
- E. 10 Hello 11

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

QUESTION 132

Given the code fragment:

```
public static void main (String[] args) {  
    String[] arr = {"Hi", "How", "Are", "You");  
    List<String> arrList = new ArrayList<>(Arrays.asList(arr));  
    if (arrList.removeIf((String s) -> (return s.length() <= 2;))) {  
        System.out.println(s + "removed")  
    }  
}
```

What is the result?

- A. Compilation fails.
- B. Hi removed
- C. An UnsupportedOperationException is thrown at runtime.
- D. The program compiles, but it prints nothing.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 133

Which two class definitions fail to compile? (Choose two.)

- A.

```
abstract class A3 {  
    private static int i;  
    public void doStuff(){}  
    public A3(){}  
}
```
- B.

```
final class A1 {  
    public A1(){}  
}
```
- C.

```
private class A2 {  
    private static int i;  
    private A2(){}  
}
```
- D.

```
class A4 {  
    protected static final int i = 10;  
    private A4() {}  
}
```

E. final abstract class A5 {
 protected static int i;
 void doStuff(){}
 abstract void doIt();
}

Correct Answer: CD

=> CE Section:

(none) Explanation

Explanation/Reference:

QUESTION 134

Given:

```
class Student {  
    String name;  
    public Student(String name) {  
        this.name = name;  
    }  
}  
  
public class Test {  
    public static void main(String[] args) {  
        Student[] students = new Student[3];  
        students[1] = new Student("Richard");  
        students[2] = new Student("Donald");  
        for (Student s : students) {  
            System.out.println(" " + s.name);  
        }  
    }  
}
```

What is the result?

- A. null
 Richard
 Donald
- B. Richard
 Donald
- C. Compilation fails.
- D. An `ArrayIndexOutOfBoundsException` is thrown at runtime.
- E. A `NullPointerException` is thrown at runtime.

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:**QUESTION 135**

This grid shows the state of a 2D array:

0	0	
	X	0
X		X

The grid is created with this code:

```
char[][] grid = new char[3][3];
grid[1][1] = 'X';
grid[0][0] = '0';
grid[2][0] = 'X';
grid[0][1] = '0';
grid[2][2] = 'X';
grid[1][2] = '0';
//line n1
```

Which line of code, when inserted in place of //line n1, adds an X into the grid so that the grid contains three consecutive XS?

- A. grid[2][1] = 'X';
- B. grid[3][2] = 'X';
- C. grid[3][1] = 'X';
- D. grid[2][3] = 'X';

Correct Answer: D**=> A Section:****(none)****Explanation****Explanation/Reference:****QUESTION 136**

Given:

```
public class Test {
    public static void main(String[] args) {
        int x = 1;
        int y = 0;
        if(x++ > ++y) {
            System.out.print("Hello ");
        } else {
            System.out.print("Welcome ");
        }
        System.out.print("Log " + x + ":" + y);
    }
}
```

What is the result?

- A. Hello Log 1:0
- B. Hello Log 2:1
- C. Welcome Log 2:1
- D. Welcome Log 1:0

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 137

Given the code snippet from a compiled Java source file:

```
public class MyFile
{
    public static void main (String[] args)
    {
        String arg1 = args[1];
        String arg2 = args[2];
        String arg3 = args[3];
        System.out.println("Arg is " + arg3);
    }
}
```

Which command-line arguments should you pass to the program to obtain the following output?

Arg is 2

- A. java MyFile 1 3 2 2
- B. java MyFile 2 2 2
- C. java MyFile 1 2 2 3 4
- D. java MyFile 0 1 2 3

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 138

Given the code fragment:

```
4. class X {  
5.     public void printFileContent() {  
6.         /* code goes here */  
7.         throw new IOException();  
8.     }  
9. }  
10. public class Test {  
11.     public static void main(String[] args) {  
12.         X xobj = new X();  
13.         xobj.printFileContent();  
14.     }  
15. }
```

Which two modifications should you make so that the code compiles successfully? (Choose two.)

A. Replace line 13 with:

```
try {  
    xobj.printFileContent();  
}  
catch(Exception e) {}  
catch(IOException e) {}
```

B. Replace line 7 with `throw IOException ("Exception raised");`

C. Replace line 11 with `public static void main(String[] args) throws Exception {`

D. At line 14, insert `throw new IOException();`

E. Replace line 5 with `public void printFileContent() throws IOException {`

Correct Answer: CE

Section: (none)

Explanation

Explanation/Reference:

QUESTION 139

Given the code fragment:

```

public static void main(String[] args) {
    int[][] arr = new int[2][4];

    arr[0] = new int[]{1, 3, 5, 7};
    arr[1] = new int[]{1, 3};

    for (int[] a : arr) {
        for (int i=0; i < arr.length; i++) {
            System.out.print(a[i] + " ");
        }
        System.out.println();
    }
}

```

What is the result?

- A. 1 3 5 7
1 3
- B. 13
1 3
- C. 13
1 3 0 0
- D. 13
followed by an `ArrayIndexOutOfBoundsException`
- E. Compilation fails.

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```

1 class Main {
2     public static void main(String[] args) {
3         int[][] arr = new int[2][4];
4
5         arr[0] = new int[] {1, 2, 3, 5, 7};
6         arr[1] = new int[] {1, 3};
7
8         for (int[] a : arr) {
9             for (int i=0; i < arr.length; i++){
10                 System.out.print (a[i] + " ");
11             }
12             System.out.println();
13         }
14     }
}

```

```

Java(TM) SE Runtime Environment (build 1.8.0_31-b13)
Java HotSpot(TM) 64-Bit Server VM (build 25.31-b07, mixed mode)
> javac -classpath ./run_dir/junit-4.12.jar:/run_dir/hamcrest-core-1.3.jar:/run_dir/json-simple-1.1.1.jar -d . Main.java
> java -classpath ./run_dir/junit-4.12.jar:/run_dir/hamcrest-core-1.3.jar:/run_dir/json-simple-1.1.1.jar Main
1 2
1 3

```

QUESTION 140

Given:

MainTest.java:

```
public class MainTest {  
    public static void main(String[] args) {  
        System.out.println("String main " + args[0]);  
    }  
}
```

and commands:

```
javac MainTest.java  
java MainTest "1 2 3"
```

What is the result?

- A. String main 1
- B. An exception is thrown at runtime
- C. String main 1 2 3
- D. String main 123

Correct Answer: A

=> C Section:

(none)

Explanation

Explanation/Reference:

QUESTION 141

Which two statements are true about Java byte code? (Choose two.)

- A. It can be serialized across network.
- B. It can run on any platform that has a Java compiler.
- C. It can run on any platform.
- D. It has “.java” extension.
- E. It can run on any platform that has the Java Runtime Environment.

Correct Answer: AE

Section: (none)

Explanation

Explanation/Reference:

QUESTION 142

Which is true about the `switch` statement?

- A. Its expression can evaluate to a collection of values.
- B. The `break` statement, at the end of each case block, is optional.
- C. Its `case` label literals can be changed at runtime.
- D. It must contain the `default` section.

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:Reference: <https://www.geeksforgeeks.org/switch-statement-in-java/>**QUESTION 143**

Given the code fragment:

```
int n[][] = {{1, 3}, {2, 4}};
for (int i = n.length - 1; i >= 0; i--) {
    for (int j = n[i].length - 1; j >= 0; j--) {
        System.out.print(n[i][j]);
    }
}
```

What is the result?

- A. 3142
- B. 2413
- C. 1324
- D. 4231

Correct Answer: D**Section: (none)****Explanation****Explanation/Reference:**

Explanation:

The screenshot shows a Java IDE interface with two panes. The left pane contains the code for Main.java:

```
Main.java  saved
1
2  class C {
3      public C() {
4          System.out.print("C ");
5      }
6  }
7
8  class B extends C{
9      public B() {
10         System.out.print("B ");
11     }
12 }
13 public class A extends B{
14
15     public A(){
16         System.out.print("A ");
17     }
18     public static void main(String[] args) {
19         A a = new A();
20     }
21 }
```

The right pane shows a terminal window with the following output:

```
java version "1.8.0_31"
Java(TM) SE Runtime Environment (build 1.8.0_31-b13)
Java HotSpot(TM) 64-Bit Server VM (build 25.31-b07, mixed mode)
javac -classpath ./run_dir/junit-4.12.jar:/run_dir/hamcrest-core-1.3.jar:/run_dir/json-simple-1.1.1.jar -d . Main.java
Main.java:13: error: class A is public, should be declared in a file named A.java
public class A extends B{
^
1 error
compiler exit status 1
```

QUESTION 144

Given:

```

public class Test {
    int x, y;

    public Test(int x, int y) {
        initialize(x, y);
    }

    public void initialize(int x, int y) {
        this.x = x * x;
        this.y = y * y;
    }

    public static void main(String[] args) {
        int x = 9, y = 5;
        Test obj = new Test(x, y);
        System.out.println(x + " " + y);
    }
}

```

What is the result?

- A. 9 5
- B. 81 25
- C. Compilation fails.
- D. 0 0

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```

1  public class Main {
2
3      File IO Status
4      all io completed
5
6
7
8      public void initialize(int x, int y) {
9          this.x = x * x;
10         this.y = y * y;
11     }
12
13     public static void main(String[] args) {
14         int x = 9, y = 5;
15         Test obj = new Test(x, y);
16         System.out.println(x + " " + y);
17     }
18 }

```

```

Java(TM) SE Runtime Environment (build 1.8.0_31-b13)
Java HotSpot(TM) 64-Bit Server VM (build 25.31-b07, mixed mode)
> javac -classpath .:/run_dir/junit-4.12.jar:/run_dir/hamcrest-core-1.3.jar:/run_dir/json-simple-1.1.1.jar -d . Main.java
> java -classpath .:/run_dir/junit-4.12.jar:/run_dir/hamcrest-core-1.3.jar:/run_dir/json-simple-1.1.1.jar Main
9 5

```

QUESTION 145

Given this segment of code:

```

ArrayList<Cycle> myList = new ArrayList<>();
myList.add(new MotorCycle());

```

Which two statements, if either were true, would make the code compile? (Choose two.)

- A. MotorCycle is an interface that implements the Cycle class.
- B. Cycle is an interface that is implemented by the MotorCycle class.
- C. Cycle is an abstract superclass of MotorCycle.
- D. Cycle and MotorCycle both extend the Transportation superclass.
- E. Cycle and MotorCycle both implement the Transportation interface.
- F. MotorCycle is a superclass of Cycle.

Correct Answer: BC

Section: (none)

Explanation

Explanation/Reference:

QUESTION 146

Given the code fragments:

```
interface Exportable {  
    void export();  
}  
  
class Tool implements Exportable {  
    public void export() {  
        System.out.println("Tool::export");  
    }  
}  
  
class ReportTool extends Tool {  
  
    void export() {  
        System.out.println("RTool::export");  
    }  
  
    public static void main(String[] args) {  
        Tool aTool = new ReportTool();  
        Tool bTool = new Tool();  
        callExport(aTool);  
        callExport(bTool);  
    }  
  
    public static void callExport(Exportable ex) {  
        ex.export();  
    }  
}
```

What is the result?

- A. Compilation fails only at line n1.
- B. Compilation fails only at line n2.

- C. Tool::export
Tool::export
- D. Compilation fails at both line n1 and line2.
- E. RTool::export
Tool::export

Correct Answer: A

=> B Section:

(none)

Explanation

Explanation/Reference:

QUESTION 147

```
class Vehicle {  
    int x;  
    Vehicle(){  
        this(10); // line n1  
    }  
    Vehicle(int x) {  
        this.x = x;  
    }  
}  
  
class Car extends Vehicle {  
    int y;  
    Car() {  
        super(10); // line n2  
    }  
    Car(int y) {  
        super(y);  
        this.y = y;  
    }  
    public String toString() {  
        return super.x + ":" + this.y;  
    }  
}
```

And given the code fragment:

```
Vehicle y = new Car(20);  
System.out.println(y);
```

What is the result?

- A. Compilation fails at line n2.
- B. Compilation fails at line n1.
- C. 20:20
- D. 10:20

Correct Answer: A

=> C Section:

(none)

Explanation

Explanation/Reference:

QUESTION 148

Given the code fragment:

```
public static void main(String[] args) {  
    LocalDate date = LocalDate.of(2012, 1, 30);  
    date.plusDays(10);  
    System.out.println(date);  
}
```

What is the result?

- A. 2012-02-10 00:00
- B. 2012-01-30
- C. 2012-02-10
- D. A `DateTimeException` is thrown at runtime.


Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:



```
Main.java     saved  •  
1 import java.time.LocalDate;  
2 import java.time.Month;  
3  
4 public class Main {  
5     public static void main(String[] args) {  
6         LocalDate date = LocalDate.of(2012, 1, 30);  
7         date.plusDays(10);  
8         System.out.println(date);  
9     }  
10 }
```



```
java version "1.8.0_31"  
Java(TM) SE Runtime Environment (build 1.8.0_31-b13)  
Java HotSpot(TM) 64-Bit Server VM (build 25.31-b07, mixed mode)  
-> javac -classpath .:/run_dir/junit-4.12.jar:/run_dir/hamcrest-core-1.3.jar:/run_dir/json-simple-1.1.1.jar -d . Main.java  
-> java -classpath .:/run_dir/junit-4.12.jar:/run_dir/hamcrest-core-1.3.jar:/run_dir/json-simple-1.1.1.jar Main  
2012-01-30
```

QUESTION 149

Given:

```

public class Test {
    public static void main(String[] args) {
        int x = 1;
        int y = 1;
        if(x++ < ++y){
            System.out.print("Hello ");
        } else {
            System.out.print("Welcome ");
        }
        System.out.print("Log " + x + ":" + y);
    }
}

```

What is the result?

- A. Hello Log 2:2
- B. Welcome Log 1:2
- C. Welcome Log 2:1
- D. Hello Log 1:2

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```

1  public class Main {
2      public static void main(String[] args) {
3          int x = 1;
4          int y = 1;
5          if (x++ < ++y) {
6              System.out.print("Hello ");
7          } else {
8              System.out.print("Welcome ");
9          }
10         System.out.print("Log " + x + ":" + y);
11     }
12 }

```

```

Java(TM) SE Runtime Environment (build 1.8.0_31-b13)
Java HotSpot(TM) 64-Bit Server VM (build 25.31-b07, mixed mode)
> javac -classpath .:/run_dir/junit-4.12.jar:/run_dir/hamcrest-core-1.3.jar:/run_dir/json-simple-1.1.1.jar -d . Main.java
> java -classpath .:/run_dir/junit-4.12.jar:/run_dir/hamcrest-core-1.3.jar:/run_dir/json-simple-1.1.1.jar Main
Hello Log 2:2

```

QUESTION 150

Given the code snippet from a compiled Java source file:

```

public class MyFile
{
    public static void main (String[] args)
    {
        String arg1 = args[0];
        String arg2 = args[1];
        String arg3 = args[2];
        System.out.println("Arg is " + arg3);
    }
}

```

and this output:

Arg is 2

Which command should you run to obtain this output?

- A. java MyFile 2
- B. java MyFile 1 2 3 4
- C. java MyFile 1 2 2
- D. java MyFile 2 2

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 151

Given the code fragment:

```
public static void main(String[] args) {  
    String[] arr = {"A", "B", "C", "D"};  
    for (int i = 0; i < arr.length; i++) {  
        System.out.print(arr[i] + " ");  
        if (arr[i].equals("D")) {  
            System.out.println("Work done");  
            break;  
        }  
  
        continue;  
    }  
}
```

What is the result?

- A. A B C Work done
- B. A B C D Work done
- C. A Work done
- D. Compilation fails

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
1 public class Main {  
2     public static void main(String[] args) {  
3         String[] arr = {"A", "B", "C", "D"};  
4         for (int i = 0; i < arr.length; i++) {  
5             System.out.print (arr[i]+ " ");  
6             if (arr[i].equals("D")) {  
7                 System.out.println("work done");  
8                 break;  
9             }  
10            continue;  
11        }  
12    }  
13 }  
14 }
```

```
Java(TM) SE Runtime Environment (build 1.8.0_31-b13)  
Java HotSpot(TM) 64-Bit Server VM (build 25.31-b07, mixed mode)  
-> javac -classpath .:/run_dir/junit-4.12.jar:/run_dir/hamcrest-core-1.3.jar:/run_dir/json-simple-1.1.1.jar -d . Main.java  
-> java -classpath .:/run_dir/junit-4.12.jar:/run_dir/hamcrest-core-1.3.jar:/run_dir/json-simple-1.1.1.jar Main  
A B C D work done
```

QUESTION 152

Given the code fragment:

```
int wd = 0;
String days[] = {"sun", "mon", "wed", "sat"};
for (String s:days) {
    switch (s) {
        case "sat":
        case "sun":
            wd -= 1;
            break;
        case "mon":
            wd -= 1;
            break;
        case "wed":
            wd += 2;
    }
}
System.out.println(wd);
```

What is the result?

- A. 3
- B. 0
- C. Compilation fails.
- D. -1

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 153

Given the code fragment:

```
String[] arr = {"Hi", "How", "Are", "You"};
List<String> arrList = new ArrayList<>(Arrays.asList(arr));
if(arrList.removeIf(s -> { System.out.print(s); return s.length()<=2; }) {
    System.out.println(" removed");
}
```

What is the result?

- A. Compilation fails.
- B. The program compiles, but it prints nothing.
- C. HiHowAreYou removed
- D. An UnsupportedOperationException is thrown at runtime.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 154

Given the code fragment:

```
String[] strs = {"A", "B"};
int idx = 0;
for (String s : strs) {
    strs[idx].concat(" element " + idx);
    idx++;
}
for (idx = 0; idx < strs.length; idx++) {
    System.out.println(strs[idx]);
}
```

What is the result?

- A. A
 B
- B. A element0
 B element1
- C. A NullPointerException is thrown at runtime.
- D. A 0
 B 1

Correct Answer: C

=> A Section:

(none)

Explanation

Explanation/Reference:

QUESTION 155

Given:

```
class C {
    public C(){
        System.out.print("C ");
    }
}

class B extends C{
    public B() { //line n1
        System.out.print("B ");
    }
}

public class A extends B{

    public A(){ //line n2
        System.out.print("A ");
    }
    public static void main(String[] args) {
        A a = new A();
    }
}
```

What is the result?

- A. C B A
- B. C
- C. A B C
- D. Compilation fails at line n1 and line n2

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 156

Given this code for the classes MyException and Test:

```
public class MyException extends RuntimeException {}

public class Test {
    public static void main(String[] args) {
        try {
            method1();
        }
        catch (MyException ne) {
            System.out.print("A");
        }
    }
    public static void method1() { // line n1
        try {
            throw 3 > 10 ? new MyException() : new IOException();
        }
        catch(IOException ie) {
            System.out.println("I");
        }
        catch (Exception re) {
            System.out.print("B");
        }
    }
}
```

What is the result?

- A . A
- B . AB
- C . A compile time error occurs at line n1.
- D . B
- E . I

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Explanation:

QUESTION 157

Given the code fragment:

```

public static void main(String[] args) {
    String names[] = {"Thomas", "Peter", "Joseph"};
    String pwd[] = new String[3];
    int idx = 0;
    try {
        for (String n : names) {
            pwd[idx] = n.substring(2, 6);
            System.out.println(pwd[idx]);
            idx++;
        }
    } catch (Exception e) {
        System.out.println("Invalid Name");
    }
}

```

What is the result?

- A. omas
Invalid Name
null
- B. omas
ter
seph
- C. Invalid Name
- D. omas
Invalid Name

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Result
CPU Time: 0.15 sec(s), Memory: 29904 kilobyte(s)

omas
Invalid Name

QUESTION 158

Which three statements are true about the structure of a Java class? (Choose three.)

- A. A class cannot have the same name as its field.
- B. A public class must have a `main` method.
- C. A class can have final static methods.
- D. A class can have overloaded private constructors.
- E. Fields need to be initialized before use.

F. Methods and fields are optional components of a class.

Correct Answer: BDE

=> CDF Section:

(none) Explanation

Explanation/Reference:

QUESTION 159

Given the code fragment:

```
1. abstract class Planet {  
2.     protected void revolve() {  
3.     }  
4.     abstract void rotate();  
5. }  
6.  
7. class Earth extends Planet {  
8.     private void revolve() {  
9.     }  
10.    private void rotate() {  
11.    }  
12. }
```

Which two modifications enable the code to compile?

- A. Make the method at line 8 `protected`.
- B. Make the method at line 8 `public`.
- C. Make the method at line 10 `protected`.
- D. Make the method at line 4 `public`.
- E. Make the method at line 2 `public`.

Correct Answer: AC

=> BC Section:

(none) Explanation

Explanation/Reference:

QUESTION 160

Given these classes:

```

public class Employee {
    public int salary;
}

public class Manager extends Employee {
    public int budget;
}

public class Director extends Manager {
    public int stockOptions;
}

```

and this main method:

```

public static void main(String[] args) {
    Employee employee = new Employee();
    Employee manager = new Manager();
    Employee director = new Director();
    //line n1
}

```

Which two options compile when placed at line n1 of the main method? (Choose two.)

- A. director.stockOptions = 1_000;
- B. employee.salary = 50_000;
- C. manager.budget = 1_000_000;
- D. manager.stockOption = 500;
- E. employee.budget = 200_000;
- F. director.salary = 80_000;

Correct Answer: BF

Section: (none)

Explanation

Explanation/Reference:

QUESTION 161

Given:

```

public class App {
    int count;
    public static void displayMsg() {
        System.out.println("Welcome Visit Count: " + count++); // line n1
    }
    public static void main(String[] args) {
        App.displayMsg();
        displayMsg(); // line n2
    }
}

```

What is the result?

- A. Welcome Visit Count:0
Welcome Visit Count: 1
- B. Compilation fails at line n2.
- C. Compilation fails at line n1.
- D. Welcome Visit Count:0
Welcome Visit Count: 0

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
1
2 public class App {
3     int count;
4     public static void displayMsg() {
5         System.out.println("Welcome Visit Count: " + count++); //line n1
6     }
7     public static void main(String[] args) {
8         App.displayMsg();
9         displayMsg();
10    }
11 }
12 }
```

QUESTION 162

Given:

```
interface I {
    public void displayI();
}
abstract class C2 implements I {
    public void displayC2() {
        System.out.print("C2");
    }
}
class C1 extends C2 {
    public void displayI() {
        System.out.print("C1");
    }
}
```

And the code fragment:

```
C2 obj1 = new C1();
I obj2 = new C1();

C2 s = (C2) obj2;
I t = obj1;

t.displayI();
s.displayC2();
```

What is the result?

- A. C1C2
- B. C1C1
- C. Compilation fails.
- D. C2C2

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

The screenshot shows an IDE interface with two main panes. The left pane displays a file tree for a project named 'lund' with a single 'src' folder containing an 'App.java' file. The right pane contains the code for 'App.java'. The code defines an interface 'I' with a method 'displayI()', an abstract class 'C2' implementing 'I' and defining 'displayC2()', a class 'C1' extending 'C2' and overriding 'displayI()' to print 'C1', and a 'main' method in 'App' that creates instances of 'C1' and 'C2', casts them to 'I', and calls their respective methods. The bottom of the screen shows four consoles labeled 'Console 1' through 'Console 4'. Console 1 shows the output 'C1C2' and 'Completed with exit code: 0'.

```
1
2 interface I {
3     public void displayI();
4 }
5 abstract class C2 implements I {
6     public void displayC2() {
7         System.out.print("C2");
8     }
9 }
10 class C1 extends C2 {
11     public void displayI() {
12         System.out.print("C1");
13     }
14 }
15 }
16
17 public class App {
18     public static void main(String[] args) {
19         C2 obj1 = new C1();
20         I obj2 = new C1();
21
22         C2 s = (C2) obj2;
23         I t = obj1;
24
25         t.displayI();
26         s.displayC2();
27     }
28 }
29 }
```

Console 1 * Console 2 * Console 3 * Console 4 *

```
C1C2
Completed with exit code: 0
```

QUESTION 163

Given the code fragment:

```
public static void main(String[] args) {  
    int ii = 0;  
    int jj = 7;  
    for (ii = 0; ii < jj; ii = ii + 2) {  
        System.out.print(ii + " ");  
    }  
}
```

What is the result?

- A. 2 4
- B. 0 2 4 6
- C. 0 2 4
- D. Compilation fails.


Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:



```
Console 2  
0 2 4 6  
Completed with exit code: 0
```

QUESTION 164

Given:

```
class X {  
    int i;  
    static int j;  
    public static void main(String[] args) {  
        X x1 = new X();  
        X x2 = new X();  
        x1.i = 3;  
        x1.j = 4;  
        x2.i = 5;  
        x2.j = 6;  
        System.out.println(  
            x1.i + " " +  
            x1.j + " " +  
            x2.i + " " +  
            x2.j);  
    }  
}
```

What is the result?

- A. 3 4 5 6
- B. 3 4 3 6
- C. 5 4 5 6
- D. 3 6 5 6

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
3 6 5 6
Completed with exit code: 0
```

QUESTION 165

Given the code fragment:

```
int[] array = {1, 2, 3, 4, 5};
```

And given the requirements:

1. Process all the elements of the array in the reverse order of entry.
2. Process all the elements of the array in the order of entry.
3. Process alternating elements of the array in the order of entry.

Which two statements are true? (Choose two.)

- A. Requirements 1, 2, and 3 can be implemented by using the enhanced for loop.
- B. Requirements 1, 2, and 3 can be implemented by using the standard for loop.
- C. Requirements 2 and 3 CANNOT be implemented by using the standard for loop.
- D. Requirement 2 can be implemented by using the enhanced for loop.
- E. Requirement 3 CANNOT be implemented by using either the enhanced for loop or the standard for loop.

Correct Answer: BC

=> BD Section:

(none) Explanation

Explanation/Reference:

QUESTION 166

Given:

```
public class FieldInit {  
    Character c;  
    boolean b;  
    float f;  
    void printAll() {  
        System.out.println("c = " + c);  
        System.out.println("b = " + b);  
        System.out.println("f = " + f);  
    }  
  
    public static void main(String[] args) {  
        FieldInit f = new FieldInit();  
        f.printAll();  
    }  
}
```

What is the result?

- A. c =
b = false
f = 0.0
- B. c = null
b = true
f = 0.0
- C. c = 0
b = false
f = 0.0F
- D. c = null
b = false
f = 0.0

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
c = null  
b = false  
f = 0.0  
  
Completed with exit code: 0
```

QUESTION 167

Given:

```
public class Test {  
  
    public static void main(String[] args) {  
  
        String[][] chs = new String[5][2];  
        chs[0] = new String[2];  
        chs[1] = new String[5];  
        int i = 97;  
  
        for (int a = 0; a < chs.length; a++) {  
            for (int b = 0; b < chs.length; b++) {  
                chs[a][b] = "" + i;  
                i++;  
            }  
        }  
  
        for (String[] ca : chs) {  
            for (String c : ca) {  
                System.out.print(c + " ");  
            }  
            System.out.println();  
        }  
    }  
}
```

What is the result?

- A. 97 98
99 100 null null null
- B. 97 98
99 100 101 102 103
- C. Compilation fails.
- D. A NullPointerException is thrown at runtime.
- E. An ArrayIndexOutOfBoundsException is thrown at runtime.


Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Explanation:



```
Console 8 * | Console 9 *  
Exception in thread "main" java.lang.ArrayIndexOutOfBoundsException: Index 2 out of bounds for length 2  
at Test.main(Test.java:11)  
Completed with exit code: 1
```

QUESTION 168

Given the code fragment:

```
public class App {  
    public static void main(String[] args) {  
        String str1 = "Java";  
        String str2 = new String("java");  
        //line n1  
        {  
            System.out.println("Equal");  
        } else {  
            System.out.println("Not Equal");  
        }  
    }  
}
```

Which code fragment, when inserted at line n1, enables the App class to print Equal?

- A) str1.toLowerCase();
if (str1 == str2)
 - B) if (str2.equals(str1.toLowerCase()))
 - C) Str1.toLowerCase();
if (str1.equals(str2))
 - D) if (str1.toLowerCase() == str2.toLowerCase())
- A. OptionA
B. OptionB
C. OptionC
D. OptionD

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 169

Given the code fragment:

```
public static void main(String[] args) {  
    String[][] arr = {{ "A", "B", "C"}, {"D", "E"}};  
    for (int i = 0; i < arr.length; i++) {  
        for (int j = 0; j < arr[i].length; j++) {  
            System.out.print(arr[i][j] + " ");  
            if (arr[i][j].equals("B")) {  
                continue;  
            }  
        }  
        continue;  
    }  
}
```

What is the result?

- A. A B C
- B. A B C D E
- C. A B D E
- D. Compilation fails.

Correct Answer: D

=> B Section:

(none)

Explanation

Explanation/Reference:

QUESTION 170

Given the code fragment:

```
LocalDateTime dt = LocalDateTime.of(2014, 7, 31, 1, 1);  
dt.plusDays(30);  
dt.plusMonths(1);  
System.out.println(dt.format(DateTimeFormatter.ISO_DATE_TIME));
```

What is the result?

- A. An exception is thrown at runtime.
- B. 2014-07-31T01:01:00
- C. 2014-07-31
- D. 2014-09-30T00:00:00

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 171

Given the code fragment:

```
class Employee {  
    private String name;  
    private int age;  
    private int salary;  
  
    public Employee(String name, int age) {  
        setName(name);  
        setAge(age);  
        setSalary(2000);  
    }  
  
    public Employee(String name, int age, int salary) {  
        this(name, age);  
        setSalary(salary);  
    }  
  
    //getter and setter methods for attributes go here  
    public void printDetails() {  
        System.out.println(name + " : " + age + " : " + salary);  
    }  
}
```

Test.java:

```
class Test {  
    public static void main(String[] args) {  
        Employee e1 = new Employee();  
        Employee e2 = new Employee("Jack", 50);  
        Employee e3 = new Employee("Chloe", 40, 5000);  
  
        e1.printDetails();  
        e2.printDetails();  
        e3.printDetails();  
    }  
}
```

Which is the result?

A. Compilation fails in the Employee class.

B. null : 0 : 0

 Jack : 50 : 0

 Chloe : 40 : 5000

C. null : 0 : 0

 Jack : 50 : 2000

 Chloe : 40 : 5000

- D. Compilation fails in the Test class.
- E. Both the Employee class and the Test class fail to compile.

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 172

Given:

```
public class SumTest {  
  
    public static void doSum(Integer x, Integer y) {  
        System.out.println("Integer sum is " + (x + y));  
    }  
  
    public static void doSum(double x, double y) {  
        System.out.println("double sum is " + (x + y));  
    }  
  
    public static void doSum(float x, float y) {  
        System.out.println("float sum is " + (x + y));  
    }  
  
    public static void main(String[] args) {  
        doSum(10, 20);  
        doSum(10.0, 20.0);  
    }  
}
```

What is the result?

- A. float sum is 30.0
double sum is 30.0
- B. double sum is 30.0
float sum is 30.0
- C. Integer sum is 30
double sum is 30.0
- D. Integer sum is 30
float sum is 30.0

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 173

Given the code fragment:

```
3. public static void main(String[] args) {  
4.     int x = 6;  
5.     while (isAvailable(x)) {  
6.         System.out.print(x);  
7.     }  
8. }  
10.  
11. public static boolean isAvailable(int x) {  
12.     return --x > 0 ? true : false;  
13. }
```

Which modification enables the code to print 54321?

- A. Replace line 6 with `System.out.print (--x);`
- B. At line 7, insert `x --;`
- C. Replace line 5 with `while (is Available(--x)) {`
- D. Replace line 12 with `return (x > 0) ? false : true;`

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 174

Given:

```

class A {
    public void test() {
        System.out.println("A ");
    }
}

class B extends A {
    public void test() {
        System.out.println("B ");
    }
}

public class C extends A {
    public void test() {
        System.out.println("C ");
    }
}

public static void main(String[] args) {
    A b1 = new A();
    A b2 = new C();
    A b3 = (B) b2;           //line n1
    b1 = (A) b2;           //line n2
    b1.test();
    b3.test();
}
}

```

What is the result?

- A. A
B
- B. A
C
- C. C
C
- D. A ClassCastException is thrown only at line n1.
- E. A ClassCastException is thrown only at line n2.

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 175

Given the code fragment:

```
int num[][] = new int[3][1];
for (int i = 0; i < num.length; i++) {
    for (int j = 0; j < num[i].length; j++) {
        num[i][j] = 10;
    }
}
```

Which option represents the state of the num array after successful completion of the outer loop?

- A. num[0][0]=10
num[0][1]=10
num[0][2]=10
- B. num[0][0]=10
num[1][0]=10
num[2][0]=10
- C. num[0][0]=10
num[0][1]=0
num[0][2]=0
- D. num[0][0]=10
num[0][1]=10
num[0][2]=10
num[0][3]=10
num[1][0]=0
num[1][1]=0
num[1][2]=0
num[1][3]=0

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 176

Given the code fragment:

```

public static void main(String[] args) {
    int ans;
    try {
        int num = 10;
        int div = 0;
        ans = num / div;
    } catch (ArithmaticException ae) { // line n1
        ans = 0;
    } catch (Exception e) {
        System.out.println("Invalid calculation");
    }
    System.out.println("Answer = " + ans); // line n2
}

```

What is the result?

- A. Answer = 0
- B. Invalid calculation
- C. Compilation fails only at line n1.
- D. Compilation fails only at line n2.
- E. Compilation fails at line n1 and line2.

Correct Answer: C

=> D Section:

(none)

Explanation

Explanation/Reference:

Explanation:

```

1  public class Test {
2      public static void main(String[] args) {
3          int ans;
4          try {
5              int num = 10;
6              int div = 0;
7              ans = num / div;
8          } catch (ArithmaticException ae) {
9              ans = 0;
10         } catch (Exception e) {
11             System.out.println("Invalid calculation");
12             ✘variable ans might not have been initialized
13         }
14         System.out.println("Answer = " + ans); //line n2
15     }
16 }
17

```

QUESTION 177

Given:

Base.java:

```
class Base {  
    public void test(){  
        System.out.println("Base ");  
    }  
}
```

DerivedA.java:

```
class DerivedA extends Base {  
    public void test(){  
        System.out.println("DerivedA ");  
    }  
}
```

DerivedB.java:

```
class DerivedB  extends DerivedA {  
    public void test(){  
        System.out.println("DerivedB ");  
    }  
    public static void main(String[] args) {  
        Base b1 = new DerivedB();  
        Base b2 = new DerivedA();  
        Base b3 = new DerivedB();  
        Base b4 = b3;  
        b1 = (Base) b2;  
        b1.test();  
        b4.test();  
    }  
}
```

What is the result?

- A. Base
 DerivedA
- B. Base
 DerivedB
- C. DerivedB
 DerivedB
- D. DerivedB
 DerivedA
- E. A ClassCastException is thrown at runtime.

Correct Answer: D

=> DerivedA,B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 178

Given the definitions of the MyString class and the Test class:

```
package p1;
class MyString {
    String msg;
    MyString(String msg) {
        this.msg = msg;
    }
}
```

Test.java:

```
package p1;
public class Test {
    public static void main(String[] args) {
        System.out.println("Hello " + new StringBuilder("Java SE 8"));
        System.out.println("Hello " + new MyString("Java SE 8").msg);
    }
}
```

What is the result?

- A. Hello Java SE 8
Hello Java SE 8
- B. Hello java.lang.StringBuilder@<<hashcode1>>
Hello p1.MyString@<<hashcode2>>
- C. Hello Java SE 8
Hello p1.MyString@<<hashcode>>
- D. Compilation fails at the Test class

Correct Answer: D =>A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 179

Given:

```
public class Test {  
    public static void main(String[] args) {  
        Test ts = new Test();  
        System.out.print(isAvailable + " ");  
        isAvailable= ts.doStuff();  
        System.out.println(isAvailable);  
    }  
    public static boolean doStuff() {  
        return !isAvailable;  
    }  
    static boolean isAvailable = true;  
}
```

What is the result?

- A. Compilation fails.
- B. false true
- C. true false
- D. true true
- E. false false


Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:



Console 15 ✘ | Console 16 ✘

true false

Completed with exit code: 0

QUESTION 180

Given the code fragments:

```
class Student {  
    String name;  
    int age;  
}
```

And:

```
4. public class Test {  
5.     public static void main(String[] args) {  
6.         Student s1 = new Student();  
7.         Student s2 = new Student();  
8.         Student s3 = new Student();  
9.         s1 = s3;  
10.        s3 = s2;  
11.        s1 = s2;  
12.    }  
13.}
```

Which statement is true?

- A. After line 11, three objects are eligible for garbage collection.
- B. After line 11, two objects are eligible for garbage collection.
- C. After line 11, one object is eligible for garbage collection.
- D. After line 11, none of the objects are eligible for garbage collection.

Correct Answer: A

=>B Section:

(none)

Explanation

Explanation/Reference:

Explanation:

Result

CPU Time: sec(s), Memory: kilobyte(s)

```
/Test.java:3: error: cannot find symbol
    Student s1 = new Student();
          ^
symbol:   class Student
location: class Test
/Test.java:3: error: cannot find symbol
    Student s1 = new Student();
          ^
symbol:   class Student
location: class Test
/Test.java:4: error: cannot find symbol
    Student s2 = new Student();
          ^
symbol:   class Student
location: class Test
/Test.java:4: error: cannot find symbol
    Student s2 = new Student();
          ^
symbol:   class Student
location: class Test
/Test.java:5: error: cannot find symbol
    Student s3 = new Student();
          ^
symbol:   class Student
location: class Test
/Test.java:5: error: cannot find symbol
    Student s3 = new Student();
          ^
symbol:   class Student
location: class Test
6 errors
```

QUESTION 181

Given:

```
public static void main(String[] args) {  
    String ta = "A ";  
    ta = ta.concat("B ");  
    String tb = "C ";  
    ta = ta.concat(tb);  
    ta.replace("B", "C");  
    ta = ta.concat("D");  
    System.out.println(ta);  
}
```

What is the result?

- A. A B C D
- B. A C D
- C. A C D D
- D. A B C C
- E. A B D C

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
1 public class Alpha {  
2     public static void main (String[] args) {  
3         String ta = "A ";  
4         ta = ta.concat ("B ");  
5         String tb = "C ";  
6         ta = ta.concat (tb);  
7         ta.replace ("B", "C");  
8         ta = ta.concat ("D");  
9         System.out.println(ta);  
10    }  
11 }
```

▼ Execute Mode, Version, Inputs & Arguments

JDK 11.0.4 ▾

CommandLine Arguments

Result

CPU Time: 0.12 sec(s), Memory: 32196 kilobyte(s)

A B C D

QUESTION 182

Given the code fragment:

```
10. public static void main(String[] args {  
11.     List<String> lst = Arrays.asList("A", "B", "C", "D");  
12.     Iterator<String> itr = lst.iterator();  
13.     while(itr.hasNext()) {  
14.         String e = itr.next();  
15.         if (e == "C") {  
16.             break;  
17.         }  
18.         continue;  
19.         System.out.print(e);  
20.     }  
21. }  
22. }  
23. }
```

Which action enables it to print AB?

- A. Comment lines 18 to 21.
- B. Comment line 20.
- C. Comment line 19.
- D. Comment line 16.

Correct Answer: B

=>C Section:

(none)

Explanation

Explanation/Reference:

QUESTION 183

Given the definitions of the Bird class and the Peacock class:

```
public class Bird {  
    public void fly() {  
        System.out.print ("Fly.");  
    }  
}  
  
public class Peacock extends Bird {  
    public void dance() {  
        System.out.print("Dance.");  
    }  
}
```

and the code fragment:

```
/*insert code snippet here */  
p.fly();  
p.dance();
```

Which code snippet can be inserted to print Fly.Dance. ?

- A. Bird p = new Peacock();
- B. Bird b = new Bird();
Peacock p = (Peacock) b;
- C. Peacock b = new Peacock ();
Bird p = (Bird) b;
- D. Bird b = new Peacock ();
Peacock p = (Peacock) b;

Correct Answer: B

=>D Section:

(none)

Explanation

Explanation/Reference:

QUESTION 184

```
public class Test {  
    public static void main(String[] args) {  
        int x;  
        /* insert code here */  
    }  
}
```

Which two code fragments inserted at line 10 print ****?

- A. x = 3;
do {
 System.out.print("*");
 x--;
} while (x >= 0);
- B. x = 0;
do {
 System.out.print("*");
 x++;
} while (x >= 3);

- C.

```
x = 0;
do {
    System.out.print("*");
    ++x;
}while (x > 3);
```
- D.

```
x = 3;
do {
    System.out.print("*");
    x--;
}while (x != 1);
```
- E.

```
x = 0;
do {
    System.out.print("*");
} while (x++ < 3);
```

Correct Answer: E

=>A,E Section:

(none)

Explanation

Explanation/Reference:

Explanation:

```
1- public class Test {  
2-     public static void main (String[] args) {  
3-         int x;  
4-         x = 0;  
5-         do {  
6-             System.out.print("*");  
7-         } while (x++ < 3);  
8-     }  
9- }  
10 }
```

▼ Execute Mode, Version, Inputs & Arguments

JDK 11.0.4 ▾

CommandLine Arguments

Result

CPU Time: 0.13 sec(s), Memory: 31856 kilobyte(s)

QUESTION 185

Given the code fragment:

```
int x = 10;  
int y = ++x;  
int z = 0;  
if (y >= 10 || y <= ++x) {  
    z = x;  
} else {  
    z = x++;  
}  
System.out.println(z);
```

What is the result?

- B. 10
- C. 12
- D. A compile time error occurs.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Result

CPU Time: 0.14 sec(s), Memory: 32028 kilobyte(s)



12

QUESTION 186

Given the code fragment:

```
int a = 3;
int b = 2;
int c = 1;
int r1 = a * b / c + 1;
int r2 = a / b * c + 1;
int r3 = a * (b / (c + 1));
System.out.println(r1 + " : " + r2 + " : " + r3);
```

What is the result?

- A. 2 : 7 : 3
- B. 7 : 7 : 9
- C. 2 : 7 : 0
- D. 7 : 2 : 3

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Result

CPU Time: 0.32 sec(s), Memory: 35824 kilobyte(s)

7 : 2 : 3

QUESTION 187

Given:

```
class LogFileException extends Exception {}  
class AccessViolationException extends RuntimeException {}  
  
1. public class App {  
2.     public static void main (String[] args) throws LogFileException {  
3.         App obj = new App ();  
4.         try {  
5.             obj.open();  
6.             obj.process();  
7.             //insert code here  
8.         }  
9.         catch (Exception e) {  
10.             System.out.println("Completed.");  
11.         }  
12.     }  
13.     public void process() {  
14.         System.out.println("Processed");  
15.         throw new LogFileException();  
16.     }  
17.     public void open () {  
18.         System.out.println ("Opened.");  
19.         throw new AccessViolationException();  
20.     }  
21. }
```

Which action fixes the compiler error?

- A. At line 17, add throws AccessViolationException
- B. At line 13, add throws LogFileException
- C. At line 2, replace throws LogFileException with throws AccessViolationException
- D. At line 7, insert throw new LogFileException ();

Correct Answer: D

=>B Section:

(none)

Explanation

Explanation/Reference:

QUESTION 188

Given the code fragment:

```
int array1[] = {1, 2, 3};  
int array2[] = new int [5];  
array2 = array1;  
for (int i : array2) {  
    System.out.print(i + " ");  
}  
System.out.println();  
int array3[] = new int[3];  
array3 = array2;  
for (int i : array3) {  
    System.out.print(i + " ");  
}
```

What is the result?

- A. 1 2 3 0 0
 1 2 3 0 0
- B. An Exception is thrown at run time.
- C. 1 2 3 0 0
 1 2 3
- D. 1 2 3
 1 2 3


Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:



The screenshot shows a Java console window titled "Console 1". The output of the code is displayed, showing two lines of "123" followed by "Completed with exit code: 0".

```
Console 1  
123  
123  
Completed with exit code: 0
```

QUESTION 189

Examine:

```
class E1 extends Exception { }

class E2 extends RuntimeException { }

public class App {
    public void m1() {
        System.out.println("m1.Accessed.");
        throw new E1();
    }

    public void m2 () {
        System.out.println("m2.Accessed.");
        throw new E2();
    }
    public static void main (String[] args) {
        int level =1;
        App obj = new App();
        if (level <=5 && level >= 3) {
            obj.m1();
        } else {
            obj.m2();
        }
    }
}
```

Which statement is true?

- A. The program prints m1.Accessed.
- B. The program fails compile due to the unhandled E1 exception.
- C. The program prints m2.Accessed.
- D. The program fails to compile due to the unhandled E2 exception.

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
4 public class App {
5     public void m1() {
6         System.out.println("m1.Accessed.");
7         throw new E1();
8     }
9
10    public void m2 () {
11        System.out.println("m2.Accessed.");
12        throw new E2 ();
13    }
14
15    public static void main (String[] args) {
16        int level =1;
17        App obj = new App();
18        if (level <=5 && level >= 3) {
19            obj.m1();
20
21        } else {
22            obj.m2();
23        }
24    }
25}
26}
```

QUESTION 190

Given the code fragment:

```
6. char colorCode = 'y';
7. switch (colorCode) {
8.     case 'r':
9.         int color = 100;
10.    break;
11.    case 'b':
12.        color = 10;
13.        break;
14.    case 'y':
15.        color = 1;
16.        break;
17. }
18. System.out.println(color);
```

What is the result?

- A. It results in a compile time error at line 18.
- B. It results in a compile time error at line 9.
- C. It prints : 1
- D. It results in a compile time error at lines at lines 12 and 15.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```

1
2 class colorCode {
3     public static void main(String[] args) {
4
5         char colorCode = 'y';
6         switch (colorCode) {
7             case 'r':
8                 int color = 100;
9                 break;
10            case 'b':
11                color = 10;
12                break;
13            case 'y':
14                color = 1;
15                break;
16        }
17        System.out.println(color);
18    }
19 }
```

QUESTION 191

Given:

```

class Alpha {
    int ns;
    static int s;
    Alpha (int ns) {
        if (s <ns) {
            s = ns;
            this.ns = ns;
        }
    }
    void doPrint () {
        System.out.println("ns= " + ns + " s = " + s);
    }
}
```

And:

```

public class TestA {
    public static static void main(String[] args) {
        Alpha ref1 = new Alpha (100);
        Alpha ref2 = new Alpha (50);
        Alpha ref3 = new Alpha (125);
        ref1.doPrint();
        ref2.doPrint();
        ref3.doPrint();
    }
}
```

What is the result?

- A. ns = 100 s =125
ns = 0 s = 125
ns = 125 s = 125
- B. ns = 50 s = 50 ns
= 125 s = 125
ns = 0 s = 125
- C. ns = 50 s = 125
ns = 125 s =125
ns = 0 s = 125
- D. ns = 50 s = 50
ns = 125 s=125
ns = 100 s=100

Correct Answer: C

, => A Section:

(none)

Explanation

Explanation/Reference:

QUESTION 192

Which two array initialization statements are valid? (Choose two.)

- A. int array[] = new int[3] {1, 2, 3};
- B. int array[] = new int[3];
array[0] = 1;
array[1] = 2;
array[2] = 3;
- C. int array[3] = new int[] {1, 2, 3};
- D. int array[] = new int[3];
array = {1, 2, 3};
- E. int array[] = new int[] {1,2,3};

Correct Answer: BE

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://stackoverflow.com/questions/1200621/how-do-i-declare-and-initialize-an-array-in-java>

QUESTION 193

Given the class definitions:

```
class C1 {}  
class C2 extends C1 {}  
class C3 extends C2 {}
```

and the code fragment:

- 16. C1 obj1 = (C1) new C2();
- 17. C2 obj2 = (C2) new C3();
- 18. C2 obj3 = (C2) new C1();
- 19. C3 obj4 = (C3) obj2;

Which line throws ClassCastException?

- A. line 18

- B. line 17
- C. line 19
- D. line 16

Correct Answer: D

=> A Section:

(none)

[Explanation](#)

Explanation/Reference:

Explanation:

```
Exception in thread "main" java.lang.ClassCastException: class CC$IC1 cannot be cast to class CC$IC2 (CC$IC1 and CC$IC2 are in unnamed module of loader 'app'
at CC.main(CC.java:9)
```

QUESTION 194

Which two features can be implemented in a Java application by encapsulating the entity classes used?
(Choose two.)

- A. data validation
- B. compile time polymorphism
- C. data hiding
- D. data abstraction
- E. data memory optimization

Correct Answer: CD

Section: (none)

[Explanation](#)

Explanation/Reference:

Reference: <https://www.geeksforgeeks.org/encapsulation-in-java/>

QUESTION 195

Given the code fragment:

```
public static void main(String[] args) {
    int sum = 0;
    for(int xVal = 1; xVal <= 5; xVal++) {
        sum = sum + xVal;
    }
    System.out.print("The sum of " + xVal + " numbers is: " + sum);
}
```

What is the result?

- A. The sum of 4 numbers is: 10
- B. A compile time error occurs.
- C. The sum of 5 numbers is: 10
- D. The sum of 5 numbers is: 15

Correct Answer: B

Section: (none)

[Explanation](#)

Explanation/Reference:

Explanation:

```
/Main.java:29: error: cannot find symbol
    System.out.print("The sum of " + xVal + "numbers is:" + sum);
                           ^
  symbol:  variable xVal
  location: class Main
1 error
```

QUESTION 196

Given the code fragment:

```
List<String> arrayList = new ArrayList<>();
arrayList.add("Tech");
arrayList.add("Expert");
arrayList.set(0, "Java");
arrayList.forEach (a -> a.concat("Forum"));
arrayList.replaceAll (s -> s.concat("Group"));
System.out.println(arrayList);
```

What is the result?

- A. [JavaForum, ExpertForum]
- B. [JavaGroup, ExpertGroup]
- C. [JavaForumGroup, ExpertForumGroup]
- D. [JavaGroup, TechGroup ExpertGroup]

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
21 public class Main {  
22     public static void main(String[] args) {  
23         List<String> arrayList = new ArrayList<>();  
24         arrayList.add("Tech");  
25         arrayList.add("Expert");  
26         arrayList.set(0, "Java");  
27         arrayList.forEach (a -> a.concat ("Forum"));  
28         arrayList.replaceAll (s -> s.concat("Group"));  
29         System.out.println(arrayList);  
30     }  
31  
32  
33  
34  
35 }
```

CPU Time: 0.18 sec(s), Memory: 32824 kilobyte(s)

[JavaGroup, ExpertGroup]

QUESTION 197

Given the code fragment:

```
public class Game {  
    public static void menu() {  
        system.out.println("1. Left 2. Right 0. Stop");  
    }  
    public static void main(String[] args) {  
        int option;  
        /* insert code here */  
    }  
}
```

and the requirements of the application:

1. It must display the menu.
2. It must print the option selected.
3. It must continue its execution till it reads '0'.

Which code fragment can be used to meet the requirements?

- A. `for (option = 0; option != 0; option = //code that reads the option goes here) {
 /* code that print the option go here */
}`

- B. `while (option != 0) {
 menu();
 option = // code that reads the option goes here
 /* code that print the option go here */
}`
- C. `do {
 menu();
 option = // code that reads the option goes here
 /* code that print the option go here */
} while (option != 0);`
- D. `while (option >= 0) {
 menu ();
 option = // code that reads the option goes here
 /* code that print the option go here */
}`

Correct Answer: A

=> C Section:

(none)

Explanation

Explanation/Reference:

QUESTION 198

Which two initialization statements are valid? (Choose two.)

- A. Boolean available = "TRUE":
- B. String tmpAuthor = author, author ="Mc Donald";
- C. Double price = 200D;
- D. Integer pages = 20;

Correct Answer: CD

Section: (none)

Explanation

Explanation/Reference:

Reference: <http://www.functionx.com/java/Lesson06.htm>

QUESTION 199

Examine the given definitions:

```

class Player {}

interface Playable {
    public void play();
    public void setPlayers(List<Player> players);
}

class Game implements Playable {
    private List<Player> players;
    public List<Player> getPlayers() { return players; }
    public void setPlayers(List<Player> players) { this.players
= players; }
    public void play() { System.out.println("Played."); }
}

```

and the code fragment:

```

Playable p = new Game();
List<Player> players = new ArrayList<>();
p.setPlayers (players);
p.play();

```

Which statement is true about the implementation of Object-Oriented Programming concepts in the given code?

- A. Polymorphism, abstraction, and encapsulation are implemented.
- B. Only polymorphism and inheritance are implemented.
- C. Polymorphism, inheritance, and abstraction are implemented.
- D. Only inheritance and encapsulation are implemented.

Correct Answer: C

=> A Section:

(none)

Explanation

Explanation/Reference:

QUESTION 200

Given:

```
class Product {  
    int id;  
    String name;  
    Product (int id, String name) {  
        this.id = id;  
        this.name = name;  
    }  
}  
public class Shop {  
    public static void main(String[] args) {  
        List<Product> lst = new ArrayList<>();  
        lst.add(new Product(10, "IceCream"));  
        lst.add(new Product(11, "Chocolate"));  
        Product p1 = new Product(10, "IceCream");  
        System.out.println(lst.indexOf(p1));  
    }  
}
```

What is the result?

- A. true
- B. false
- C. -1
- D. 0

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
17 > class Product {  
18     int id;  
19     String name;  
20 >     Product(int id, String name) {  
21         this.id = id;  
22         this.name = name;  
23     }  
24 }  
25  
26 > public class Shop {  
27     public static void main(String[] args) {  
28         List<Product> lst = new ArrayList<>();  
29         lst.add(new Product(10, "IceCream"));  
30         lst.add(new Product(11, "Chocolate"));  
31         Product p1 = new Product(10, "IceCream");  
32  
33         System.out.println(lst.indexOf(p1));  
34     }  
35 }  
36 }
```

Result

CPU Time: 0.15 sec(s), Memory: 33216 kilobyte(s)

```
-1
```

QUESTION 201

Given the code fragment:

```
public class StockRoom {  
    private int stock = 10;  
    public void purchase(int qty) {stock += qty;}  
    public void sell(int qty) {stock -= qty}  
    public void printStock(String action) {  
        System.out.println(action + ":" + qty + " items. Stock  
in Hand: " + stock);  
    }  
    public static void main(String[] args) {  
        StockRoom k1 = new StockRoom();  
        k1.sell(5);  
        k1.printStock("Sold");  
        StockRoom k2 = new StockRoom();  
        k2.purchase(5);  
        k2.printStock("Purchased");  
    }  
}
```

You want the code to print:

```
Sold: 5 items. Stock in Hand: 5  
Purchased: 5 items. Stock in Hand: 10?
```

Which action enables the code to print this?

- A. Declare the stock variable and the purchase(), sell(), and printStock() methods static.
- B. Declare the stock variable and the printStock() method static.
- C. Declare the stock and qty variables and the printStock() method static.
- D. Declare the stock variable static.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 202

Given:

```
class S1 {  
    protected void display(int x) {  
        System.out.print("Parent" + x);  
    }  
}  
class S2 extends S1 {  
    public void display(int x, int y) {  
        this.display(x);  
        display(y);  
        super.display(y);  
    }  
    public void display(int x) {  
        System.out.println("Child " + x);  
    }  
}
```

and the code fragment:

```
S2 sobj = new S2();  
sobj.display(10, 100);
```

What is the result?

- A. Child 10
Child 100
Parent 100
- B. Parent 10
Child 10

- Parent 1000
 - C. Child 10
 - Parent 100
 - Parent 100
- D. A compile time error occurs.

Correct Answer: D

=> A Section:

(none)

Explanation

Explanation/Reference:

Explanation:

```
Error: Main method not found in class S1, please define the main method as:  
public static void main(String[] args)  
or a JavaFX application class must extend javafx.application.Application
```

QUESTION 203

Given the code fragment:

```
List<String> lst = Arrays.asList("EN", "FR", "CH", "JP");  
Iterator<String> itr = lst.iterator();  
while(itr.hasNext()) {  
    String e = itr.next();  
    if (e == "CH") {  
        break;  
    }  
    System.out.print(e + " ");  
}
```

What is the result?

- A. EN FR JP
- B. EN FR
- C. CH
- D. EN FR CH

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
16+ public class Main {  
17+     public static void main(String[] args) {  
18+         List<String> lst = Arrays.asList("EN", "FR", "CH", "JP");  
19+         Iterator<String> itr = lst.iterator();  
20+         while(itr.hasNext()) {  
21+             String e = itr.next();  
22+             if(e == "CH") {  
23+                 break;  
24+             }  
25+             System.out.print(e+ " ");  
26+         }  
27+     }  
28 }
```

Result

CPU Time: 0.28 sec(s), Memory: 35336 kilobyte(s)



```
EN FR
```

QUESTION 204

Given:

```
class Vehicle {  
    Vehicle() {  
        System.out.println("Vehicle");  
    }  
}  
class Bus extends Vehicle {  
    Bus() {  
        System.out.println("Bus");  
    }  
}  
public class Transport {  
    public static void main (String[] args) {  
        Vehicle v = new Bus();  
    }  
}
```

What is the result?

- A. Vehicle
 Bus
- B. Bus
 Vehicle

- C. Bus
- D. The program doesn't print anything

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
-- 16 * class Vehicle {  
17 *     Vehicle() {  
18 *         System.out.println("Vehicle");  
19 *     }  
21 * }  
22 * class Bus extends Vehicle {  
23 *     Bus() {  
24 *         System.out.println("Bus");  
25 *     }  
26 * }  
27 * public class Transport {  
28 *     public static void main (String[] args) {  
29 *         Vehicle v = new Bus();  
30 *     }  
31 * }
```

Result

CPU Time: 0.14 sec(s), Memory: 32160 kilobyte(s)

```
Vehicle  
Bus
```

QUESTION 205

Given:

```
class P1 {}  
class P2 extends P1 implements I1 {}  
interface I1 {}
```

and the code fragment:

```
P1 obj = new P1();
P2 obj2 = new P2();
I1 obj3 = new P2();
boolean r1 = obj instanceof P2;
boolean r2 = obj2 instanceof P1;
boolean r3 = obj3 instanceof I1;
System.out.println(r1 + ":" + r2 + ":"+r3);
```

What is the result?

- A. true:false:true
- B. false:true:true
- C. false:true:false
- D. true:true:false

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
-- 16 class P1 {}
17 class P2 extends P1 implements I1 {}
18 interface I1 {}

19
20 public class Main {
21
22 public static void main(String[] args) {
23     P1 obj = new P1();
24     P2 obj2 = new P2();
25     I1 obj3 = new P2();
26     boolean r1 = obj instanceof P2;
27     boolean r2 = obj2 instanceof P1;
28     boolean r3 = obj3 instanceof I1;
29     System.out.println(r1 + ":" + r2 + ":" + r3);
30 }
31 }
```

Result

CPU Time: 0.25 sec(s), Memory: 36044 kilobyte(s)

```
false:true:true
```

QUESTION 206

Given:

```
public class App {  
    String greet = "Welcome!";  
    public App() {  
        String greet = "Hello!";  
    }  
    public void setGreet() {  
        String greet = "Good Day!";  
    }  
  
    public static void main (String[] args) {  
        App t = new App();  
        String greet = "Good Luck!";  
        System.out.println(t.greet);  
    }  
}
```

What is the result?

- A. Good Luck!
- B. Good Day!
- C. Welcome!
- D. Hello!

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
16 * public class App {  
17     String greet = "Welcome!";  
18 *     public App() {  
19         String greet = "Hello!";  
20     }  
21 *     public void setGreet() {  
22         String greet = "Good Day!";  
23     }  
24  
25 *     public static void main(String[] args) {  
26         App t = new App();  
27         String greet = "Good Luck!";  
28         System.out.println(t.greet);  
29     }  
30 }
```

Result

CPU Time: 0.24 sec(s), Memory: 32280 kilobyte(s)

A black terminal window containing the text "Welcome!" in white.

QUESTION 207

Given:

```
public class OraString {  
    String s;  
    public boolean equals(OraString str) {  
        return this.s.equalsIgnoreCase(str.toString());  
    }  
    OraString(String s) {  
        this.s = s;  
    }  
}
```

and the code fragment:

```
String s1 = "Moon";
OraString s2 = new OraString("Moon");

if ((s1 == "Moon") && (s2.equals("Moon"))) {
    System.out.print("A");
} else {
    System.out.print("B");
}
if (s1.equalsIgnoreCase(s2.s)) {
    System.out.print("C");
} else {
    System.out.print("D");
}
```

What is the result?

- A. AC
- B. BD
- C. BC
- D. AD

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
16+ public class OraString {  
17     String s;  
18+     public boolean equals(OraString str) {  
19         return this.s.equalsIgnoreCase(str.toString());  
20     }  
22+     OraString(String s) {  
23         this.s = s;  
24     }  
25  
26+     public static void main(String[] args) {  
27         String s1 = "Moon";  
28         OraString s2 = new OraString("Moon");  
29  
30+         if ((s1 == "Moon") && (s2.equals("Moon"))) {  
31             System.out.println("A");  
32         } else {  
33             System.out.println("B");  
34         }  
35+         if (s1.equalsIgnoreCase(s2.s)) {  
36             System.out.println("C");  
37         } else {  
38             System.out.println("D");  
39         }  
40     }  
41 }
```

Result

CPU Time: 0.16 sec(s), Memory: 32160 kilobyte(s)

```
B  
C
```

QUESTION 208

Given:

```
public class App {  
    int foo;  
    static int bar;  
  
    static void process() {  
        foo += 10;  
        bar += 10;  
    }  
    public static void main(String[] args) {  
        App firstObj = new App();  
        App.process();  
        System.out.println(firstObj.bar);  
  
        App secondObj = new App();  
        App.process();  
        System.out.println(secondObj.bar);  
    }  
}
```

What is the result?

- A. 10
20
- B. A compile time error occurs
- C. 20
20
- D. 10
10

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Result

CPU Time: sec(s), Memory: kilobyte(s)

```
/App.java:21: error: non-static variable foo cannot be referenced from a static context  
    foo +=10;  
    ^  
1 error
```

QUESTION 209

Given:

```
4. public class Shop{  
5.     public static void main(String[] args) {  
6.         int price = 1000;  
7.         int qty = 2;  
8.         String grade = "2";  
9.         double discount = 0.0;  
10.        switch(grade) {  
11.            case "1":  
12.                discount = price * 0.1;  
13.                break;  
14.            case "2":  
15.                discount = price * 0.5;  
16.                continue;  
17.            default:  
18.                System.out.println("Thank You!");  
19.        }  
20.        System.out.println(discount);  
21.    }  
22. }
```

Which statement is true?

- A. The program executes and prints:
500.0
- B. Commenting line 16 enables the program to print:
Thank You!
500.0
- C. Commenting line 13 enables the program to print:
Thank You!
500.0
- D. The program executes and prints:
Thank You!
500.0

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
16- public class Shop {  
17-     public static void main(String[] args) {  
18-         int price = 1000;  
19-         int qty = 2;  
20-         String grade = "Z";  
21-         double discount = 0.0;  
22-         switch(grade) {  
23-             case "1":  
24-                 discount = price * 0.1;  
25-                 break;  
26-             case "2":  
27-                 discount = price * 0.5;  
28-                 //continue:  
29-             default:  
30-                 System.out.println("Thank You!");  
31-             }  
32-             System.out.println(discount);  
33-         }  
34-     }
```

Result

CPU Time: 0.16 sec(s), Memory: 32260 kilobyte(s)

```
Thank You!  
500.0
```

QUESTION 210

Which statement is true about the `main()` method?

- A. It is invoked by JRE
- B. It is a `final` method
- C. It returns `true` if it is executed successfully at run time
- D. It must be defined within a `public class`

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://www.quora.com/How-does-a-main-method-get-invoked-automatically-explain-it-in-brief>

QUESTION 211

Given the code fragment:

```
String str = "Sweet Sweat";  
String str2 = str.trim().charAt(6) + "" +str.indexOf("Sw",1);  
System.out.println(str2);
```

What is the result?

- A. S 6
- B. S 5

- C. s-1
- D. w 7

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
16 public class Shop {  
17     public static void main(String[] args) {  
18         String str = "Sweet sweat";  
19         String str2 = str.trim().charAt(6) + "" +str.indexOf("Sw",1);  
20         System.out.println(str2);  
21     }  
22 }
```

Result

CPU Time: 0.27 sec(s), Memory: 35780 kilobyte(s)

s-1

QUESTION 212

Given the code fragment:

```
8. public static void main(String[] args) {  
9.     int x;  
10.    /* insert code here */  
11. }
```

Which code fragment at line 10 prints Welcome 100?

- A.

```
for (x = 0; x < 100; ++x) {  
    System.out.println("Welcome " + x);  
}
```
- B.

```
for (x = 100; x <= 100; x++) {  
    System.out.println("Welcome " + x);  
}
```
- C.

```
x = 100;  
while (x <= 100) {  
    x++;  
    System.out.println("Welcome " + x);  
}
```

```

D. x = 100;
do {
    ++x;
    System.out.println("Welcome " + x);
} while (x < 100);

```

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```

16- public class Shop {
17-     public static void main(String[] args) {
18-         int x;
19-         for (x = 100; x <= 100; x++) {
20-             System.out.println("Welcome " + x);
21-         }
22-     }
23- }

```

Result

CPU Time: 0.23 sec(s), Memory: 33552 kilobyte(s)



Welcome 100

QUESTION 213

Given these requirements:

- Bus and Boat are Vehicle type classes.
- The `start()` and `stop()` methods perform common operations across the Vehicle class type.
- The `ride()` method performs a unique operations for each type of Vehicle.

Which set of actions meets the requirements with optimized code?

- A. 1. Create an abstract class Vehicle by defining `start()` and `stop()` methods, and declaring the `ride()` abstract method.
2. Create Bus and Boat classes by inheriting the Vehicle class and overriding the `ride()` method.
- B. 1. Create an interface Vehicle by defining `start()` and `stop()` methods, and declaring the `ride()` abstract method.
2. Create Bus and Boat classes by implementing the Vehicle class.
- C. 1. Create an abstract class Vehicle by declaring `stop()`, `start()`, and `ride()` abstract methods.
2. Create Bus and Boat classes by inheriting the Vehicle class and overriding all the methods.
- D. 1. Create an interface Vehicle by defining default `stop()`, `start()`, and `ride()` methods.
2. Create Bus and Boat classes by implementing the Vehicle interface and overriding the `ride()` method.

Correct Answer: B

= A Section:

(none)

Explanation

Explanation/Reference:

QUESTION 214

Given:

```
class Cart {  
    Product p;  
    double totalAmount;  
}  
  
class Product {  
    String name;  
    Double price;  
}  
  
public class Shop {  
    public static void main(String[] args) {  
        Cart c = new Cart();  
        System.out.println(c.p + ":" + c.totalAmount);  
    }  
}
```

What is the result?

- A. null:null:0.0
- B. null:null
- C. <>:0.0
- D. null:0.0

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
15  
16  class Cart {  
17      Product p;  
18      double totalAmount;  
19  }  
20  class Product {  
21      String name;  
22      Double price;  
23  }  
24  public class Shop {  
25      public static void main(String[] args) {  
26          Cart c = new Cart();  
27          System.out.println(c.p + ":" + c.totalAmount);  
28      }  
29  }
```

Result

CPU Time: 0.23 sec(s), Memory: 36060 kilobyte(s)

null:0.0

QUESTION 215

Given:

```
class Book {int pages;}  
  
public class App{  
    int count;  
  
    public void method(Book x, int k) {  
        x.pages = 100;  
        k = 200;  
    }  
  
    public static void main(String[] args) {  
        App obj = new App();  
        Book objBook = new Book();  
        System.out.println(objBook.pages + ":" + obj.count);  
        obj.method(objBook, obj.count);  
        System.out.println(objBook.pages + ":" + obj.count);  
    }  
}
```

What is the result?

- A. 0:0
 100:0
- B. null:0

- 100:0
C. 0:0
100:200
D. null:null
100:null

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
15
16 class Book {int pages;}
17 public class App{
18     int count;
19
20     public void method(Book x, int k) {
21         x.pages = 100;
22         k = 200;
23     }
24
25     public static void main(String[] args) {
26         App obj = new App();
27         Book objBook = new Book();
28         System.out.println(objBook.pages + ":" + obj.count);
29         obj.method(objBook, obj.count);
30         System.out.println(objBook.pages + ":" + obj.count);
31     }
32 }
```

Result

CPU Time: 0.24 sec(s), Memory: 35920 kilobyte(s)

```
0:0
100:0
```

QUESTION 216

Given:

```
public class Test {
    // line n1
}
```

Which two code fragments can be inserted at line n1?

- A. String str = "Java";
- B. for(int iVal = 0; iVal <=5; iVal++){};
- C. Test() {}
- D. package p1;
- E. import java.io.*;

Correct Answer: AD = AC

Section: (none)**Explanation****Explanation/Reference:****QUESTION 217**

Examine the content of App.java:

```
package p1;
public class App {
    public static void main(String[] args) {
        System.out.println("Java");
    }
}
```

and of Test.java:

```
package p1.p2;
public class Test {}
```

Which is true?

- A. The App.class file is stored within the p1 folder. The Test.class file is stored within the p2 sub-folder of p1.
- B. The App class is accessible within the Test class without an import statement.
- C. import p1.App; is used to access the App class within the Test class.
- D. It is optional to have the package statement as the first line of class definitions.

Correct Answer: C**Section: (none)****Explanation****Explanation/Reference:****QUESTION 218**

Given the code fragment:

```
7. public static void main(String[] args) {
8.     Predicate<Integer> p = (n) -> n % 2 == 0;
9.     // insert code here
10. }
```

Which code snippet at line 9 prints true?

- A. Boolean s = p.apply(101);
 System.out.println(s);

- B. Boolean s = p.test(100);
System.out.println(s);
- C. Integer s = p.test(100);
if (s == 1) {
 System.out.println("false");
}
else {
 System.out.println("true");
}
- D. System.out.println(p.apply(100));

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
18 public class App {  
19     public static void main(String[] args) {  
20         Predicate<Integer> p = (n) -> n % 2 == 0;  
21         Boolean s = p.test(100);  
22         System.out.println(s);  
23     }  
24 }
```

Result

CPU Time: 0.26 sec(s), Memory: 32908 kilobyte(s)

```
true
```

QUESTION 219

Given:

```
public class SumTest {  
    public static void doSum(Integer x, Integer y) {  
        System.out.println("Integer sum is " + (x + y));  
    }  
  
    public static void doSum(double x, double y) {  
        System.out.println("double sum is " + (x + y));  
    }  
  
    public static void doSum(float x, float y) {  
        System.out.println("float sum is " + (x + y));  
    }  
  
    public static void main(String[] args) {  
        doSum(10, 20);  
        doSum(10.0, 20.0);  
    }  
}
```

What is the result?

- A. double sum is 30.0
float sum is 30.0
- B. float sum is 30.0
double sum is 30.0
- C. Integer sum is 30
double sum is 30.0
- D. Integer sum is 30
float sum is 30.0

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Result

CPU Time: 0.34 sec(s), Memory: 35708 kilobyte(s)

```
float sum is 30.0  
double sum is 30.0
```

QUESTION 220

Given:

```

public class FieldInit {
    Character c;
    boolean b;
    float f;
    void printAll() {
        System.out.println("c = " + c);
        System.out.println("b = " + b);
        System.out.println("f = " + f);
    }
}

public static void main(String[] args) {
    FieldInit f = new FieldInit();
    f.printAll();
}
}

```

What is the result?

- A. c=null
b=true
f=0.0
- B. c=
b=false
f=0.0
- C. c=null
b=false
f=0.0
- D. c=0
b=false
f=0.0F

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Result

CPU Time: 0.27 sec(s), Memory: 35768 kilobyte(s)

```
c =null
b =false
f =0.0
```

QUESTION 221

Which two code fragments cause compilation errors? (Choose two.)

- A. double y1 = 203.22;
float fit = y1;
- B. float fit = (float) 1_11.00;
- C. Float fit = 100.00;
- D. int y2 = 100;
float fit = (float) y2;

E. float fit = 100.00F;

Correct Answer: BD

Section: (none)

Explanation

Explanation/Reference:

QUESTION 222

Given the code fragment:

```
abstract class Robot implements Speakable {
    public void process();
}

class Humanoid extends Robot {
    public void speak(String s) { System.out.println(s); }
    public void process() { System.out.println("Helping... "); }
}

interface Speakable {
    public void speak(String s);
}

public class RobotApp{
    public static void main(String[] args) {
        Robot r = new Humanoid();
        r.process();
        r.speak("Done");
    }
}
```

Which action enables the code to print `Helping... Done`?

- A. replace `class Humanoid extends Robot {`
with `abstract class Humanoid extends Robot {`
- B. replace `interface Speakable {`
with `abstract class Speakable`
- C. replace `public void process();`
with `public abstract void process();`
- D. replace `abstract class Robot implements Speakable {`
with `class Robot extends Speakable {`

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

```
18+ abstract class Robot implements Speakable {
19     public abstract void process();
20 }
21+ class Humanoid extends Robot {
22     public void speak(String s) { System.out.println(s); }
23     public void process() { System.out.println("Helping..."); }
24 }
25 }
26+ interface Speakable {
27     public void speak(String s);
28 }
29+ public class RobotApp{
30     public static void main(String[] args) {
31         Robot r = new Humanoid();
32         r.process();
33         r.speak("Done");
34     }
35 }
```

Result

CPU Time: 0.19 sec(s), Memory: 32108 kilobyte(s)

```
Helping...
Done
```

QUESTION 223

Given:

```
public class App {

    String myStr = "9009";

    public void doStuff(String str) {
        int myNum = 0;
        try {
            String myStr = str;
            myNum = Integer.parseInt(myStr);
        } catch (NumberFormatException ne) {
            System.err.println("Error");
        }
        System.out.println(
            "myStr: " + myStr + ", myNum: " + myNum);
    }

    public static void main(String[] args) {
        App obj = new App();
        obj.doStuff("7007");
    }
}
```

What is the result?

- A. myStr: 7007, myNum: 7007
- B. Error
- C. myStr: 9009, myNum: 7007
- D. myStr: 7007, myNum: 9009

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation:

Result

CPU Time: 0.30 sec(s), Memory: 35792 kilobyte(s)

```
myStr: 9009, myNum: 7007
```