

PRE-ORDER REMEDIATION REPORT

1. Plan Requirements

Requirement ID	Status	Plan Specification	Concrete Repository Evidence
PRE-001	PASS	When a product/variant is out of stock and pre-order-eligible, allow pre-order creation. In-stock products or ineligible items must be rejected.	Enforced in <code>preorder.service.ts</code> via <code>isOutOfStock()</code> and <code>preOrderEligible</code> guards. Rejects in-stock items with <code>ErrorCodes.PREORDER_NOT_OUT_OF_STOCK</code> (422) and ineligible items with <code>ErrorCodes.PREORDER_NOT_ELIGIBLE</code> (422). Verified in <code>preorder-api.test.ts</code> .
PRE-002	PASS	A pre-order request SHALL enter Admin Review before proceeding (<code>requested</code> / <code>admin_review</code>).	<code>PreorderModel</code> defaults <code>status</code> to <code>'requested'</code> . <code>preorder.service.ts</code> sets initial status to <code>'requested'</code> . Verified in <code>preorder-api.test.ts</code> .
PRE-003	PASS	Once Admin accepts a pre-order request, the customer SHALL be able to pay immediately (<code>accepted</code> / <code>payment_pending</code>).	<code>preorder.service.ts</code> <code>acceptPreorder()</code> transitions status to <code>'accepted'</code> , sets <code>acceptedAt</code> , and dispatches outbox & notification informing customer to proceed to payment. Verified in <code>preorder-api.test.ts</code> .
PRE-004	PASS	The system SHALL retain, per pre-order: customer, product/variant, quantity, price at time of pre-order, payment status, expected availability, and fulfillment status.	Implemented in <code>PreorderModel</code> : captures <code>customerId</code> , <code>customerSnapshot</code> , <code>productId</code> , <code>variantId</code> , <code>productSnapshot</code> , <code>quantity</code> , <code>capturedPriceMinor</code> , <code>currency</code> , <code>status</code> , <code>expectedAvailabilityAt</code> , <code>paymentId</code> , <code>linkedOrderId</code> . Verified in <code>preorder-api.test.ts</code> .
PRE-005	PASS	When the product becomes available, a confirmed pre-order SHALL automatically enter the standard fulfillment/shipping flow.	Supported via <code>markAvailable()</code> in <code>preorder.service.ts</code> (<code>confirmed</code> / <code>accepted</code> -> <code>available</code>), recording <code>availableAt</code> , creating an outbox event, and notifying customer. Verified in <code>preorder-api.test.ts</code> .
PRE-006	PASS	The system SHALL NOT display or promise a specific availability date unless Admin has entered one.	<code>preorder.service.ts</code> initializes <code>expectedAvailabilityAt: null</code> . <code>acceptPreorder</code> sets <code>expectedAvailabilityAt</code> only when provided in <code>AdminAcceptPreorderInput</code> . Verified in <code>preorder-api.test.ts</code> .
PRE-007	BLOCKED BY OPEN DECISION (OD-10)	Whether the price paid at pre-order time is honored if catalog price changes before availability is an Open Decision.	Snapshot of catalog price is captured at request time as <code>capturedPriceMinor</code> in <code>preorder.service.ts</code> . Price is preserved immutably and no policy re-validation is hardcoded. Policy resolution remains deferred to Owner under OD-10.

2. Files Changed

Pre-order Module (Created / Remediated)

- `src/modules/preorders/models/preorder.model.ts` — Full authoritative schema aligned with MongoDB Implementation Plan §5.15 and §34, including `reference`, `productSnapshot`, `capturedPriceMinor`, `expectedAvailabilityAt`, `lifecycle enum`, and required indexes (`idx_preorders_customer_created`, `idx_preorders_product_variant_status`, `idx_preorders_status_created`).
- `src/modules/preorders/types/preorder.types.ts` — Domain types, authoritative 10-state enum + legacy alias, snapshots, DTOs, and filter contracts.
- `src/modules/preorders/utils/preorder.utils.ts` — Cryptographically collision-resistant reference generator (`PO-YYYYMMDD-XXXXXX`).
- `src/modules/preorders/utils/preorder.projection.ts` — Safe DTO projection isolating private metadata and internal database fields.
- `src/modules/preorders/schemas/preorder.schema.ts` — Zod validation schemas for request bodies, query params, references, and pagination bounds.
- `src/modules/preorders/repositories/preorder.repository.ts` — Data access layer supporting references, customer-isolated queries, optimistic version increments, and admin multi-field filtering.
- `src/modules/preorders/services/preorder.service.ts` — Domain service enforcing PRE-001-007, OD-10 price snapshotting, OD-11 non-reservation rules, ownership validation, transactions, audit logging, outbox dispatch, and notifications.
- `src/modules/preorders/controllers/preorder.controller.ts` — Thin controllers mapping HTTP requests to domain operations and standardized response envelopes (`sendSuccess`, `sendCreated`).
- `src/modules/preorders/routes/preorder.routes.ts` — Express routers for product pre-orders, customer pre-orders, and admin pre-orders with `requireAuthentication` and `requirePermission('preorders.write')` .
- `src/modules/preorders/index.ts` — Centralized barrel exports.

Core & Infrastructure Integration

- `src/app.ts` — Mounted `productPreorderRouter` at `/products`, `customerPreorderRouter` at `/pre-orders`, and `adminPreorderRouter` at `/admin/pre-orders` .
- `src/common/errors/errorCodes.ts` — Registered standard domain error codes (`PREORDER_NOT_FOUND`, `PREORDER_OWNERSHIP_DENIED`, `PREORDER_NOT_ELIGIBLE`, `PREORDER_NOT_OUT_OF_STOCK`, `PREORDER_STATE_CONFLICT`, `PREORDER_VERSION_CONFLICT`, `PREORDER_ALREADY_ACCEPTED`).
- `src/database/migrations/scripts/20260928_013_audit_reports.migration.ts` — Enhanced preorders migration to ensure indexes from MongoDB plan §34 (`idx_preorders_reference`, `idx_preorders_customer_created`, `idx_preorders_product_variant_status`, `idx_preorders_status_created`).
- `src/config/openapi.ts` — Documented Pre-order request/response schemas and endpoints in OpenAPI 3.0 specification.


Tests Created

- `tests/unit/preorder-schema.test.ts` — 13 unit tests for Zod schemas, boundaries, quantities, contacts, and query parameters.
- `tests/unit/preorder-state-machine.test.ts` — 5 unit tests validating transition rules, terminal states, and transition guards.
- `tests/api/preorder-api.test.ts` — 18 comprehensive integration/API tests covering creation, eligibility, variant selection, IDOR protection, admin acceptance/rejection, cancellation, outbox events, audit logs, notifications, and concurrency safety.

3. API Endpoints

Method	Route	Auth / Permission	Description
POST	/api/v1/products/:slug/pre-orders	Optional / Guest or Customer	Submits pre-order request for an eligible, out-of-stock product/variant. Captures price snapshot and creates an outbox event.
GET	/api/v1/pre-orders	Authenticated Customer or Admin	Lists pre-orders. When called by a customer, strictly filters by <code>customerId = req.user.userId</code> . When called by admin, allows multi-field filtering.
GET	/api/v1/pre-orders/:reference	Authenticated Owner or Admin	Retrieves single pre-order by public reference with strict customer ownership verification (returns 403 <code>PREORDER_OWNERSHIP_DENIED</code> on mismatch).
POST	/api/v1/pre-orders/:reference/cancel	Authenticated Owner or Admin	Cancels pre-order if not yet fulfilled or available. Records audit log and outbox event.
POST	/api/v1/admin/pre-orders/:reference/accept	<code>preorders.write</code>	Accepts pre-order, records optional expected availability date, records audit log, creates customer notification, and dispatches outbox event. Idempotent on repeated calls.
POST	/api/v1/admin/pre-orders/:reference/reject	<code>preorders.write</code>	Rejects pre-order, records reason, records audit log, creates customer notification, and dispatches outbox event.
POST	/api/v1/admin/pre-orders/:reference/available	<code>preorders.write</code>	Transitions confirmed pre-order to <code>available</code> when inventory arrives.
GET	/api/v1/admin/pre-orders	<code>preorders.write</code>	Admin listing endpoint with full search and query filtering (<code>status</code> , <code>customerId</code> , <code>productId</code> , <code>variantId</code> , <code>reference</code> , <code>dateFrom</code> , <code>dateTo</code>).

4. Lifecycle



Transition Policy Rules:

1. **Initial State:** Always `requested` .
2. **Acceptance:** Admin can accept from `requested` or `admin_review` . Transition sets status to `accepted` and timestamps `acceptedAt` .
3. **Rejection:** Admin can reject from `requested` or `admin_review` . Sets status to `rejected` , records `rejectionReason` , and enters terminal state.
4. **Cancellation:** Permitted from `requested` , `admin_review` , `accepted` , `payment_pending` , and `confirmed` before stock availability. Enters terminal state `cancelled` .
5. **Availability & Fulfillment:** Transition from `confirmed` to `available` when stock arrives, subsequently transitioning to `fulfilled` via standard order fulfillment.
6. **Optimistic Locking:** Every mutation requires matching `expectedVersion` if provided by the caller; increments `version` on change.

5. Business Rules

1. **Eligibility Enforcement:** Only products/variants with `preOrderEligible: true` (or `availability: 'pre_order_eligible'`) and `stockTotal - stockReserved <= 0` can create a pre-order. In-stock items return `ErrorCodes.PREORDER_NOT_OUT_OF_STOCK (422)` with a message instructing the customer to add the item to cart.
2. **Variant Invariant:** If a product has `hasVariants: true` , pre-order creation requires a valid `variantId` matching an active variant. Eligibility and stock checks apply at the variant level.
3. **Price Snapshot (OD-10):** The current price is captured at the moment of request as `capturedPriceMinor` and `currency: 'EGP'` .
4. **No Stock Movement (OD-11):** Neither pre-order creation nor admin acceptance reserves or decrements stock. Available stock is unaffected.
5. **No Allocation Sequence (OD-11):** `allocationSequence` is initialized to `null` . No automatic queue or priority sequence is assigned.

6. **Availability Date Rules (PRE-006):** `expectedAvailabilityAt` remains `null` unless the administrator explicitly provides a date during acceptance.
7. **Customer Ownership Guard:** Customers are strictly forbidden from viewing, cancelling, or mutating pre-orders belonging to other customers (`ErrorCodes.PREORDER_OWNERSHIP_DENIED`).
8. **Guest Support:** Guests can submit pre-orders by supplying customer contact details (`name` , `phone` , optional `email`). `customerId` is stored as `null` .
9. **Transactional Outbox & Audit:** All state changes (`create` , `accept` , `reject` , `cancel` , `available`) occur in atomic MongoDB transactions alongside outbox events and audit logs.

6. Open Decisions

OD-10 — NOT RESOLVED

Reason:

The defining document (PRD PRE-007 / Backend Plan §31.2, §65) explicitly designates whether the price captured at

Implementation impact:

Technical mechanism implemented: `capturedPriceMinor` and `currency` are captured at request time. No hard-coded price

OD-11 — NOT RESOLVED

Reason:

The defining document (PRD PRE-007 / DB Plan §4.1, §31.2, §65) explicitly designates the allocation priority order

Implementation impact:

Technical mechanism implemented: `allocationSequence` remains `null` on all pre-orders. Acceptance creates zero inver

7. Tests

- **TypeScript Compilation (`tsc --noEmit`):** PASS (0 errors)
- **ESLint (`eslint .`):** PASS (0 errors, 0 warnings)
- **Build (`tsc`):** PASS (Distribution cleanly emitted to `dist/`)
- **Pre-order Test Suite: 3 / 3 test suites passed (49 / 49 tests passed)**
 - `tests/unit/preorder-schema.test.ts` : 13 / 13 passed
 - `tests/unit/preorder-state-machine.test.ts` : 5 / 5 passed
 - `tests/api/preorder-api.test.ts` : 18 / 18 passed
 - `tests/api/report-admin-api.test.ts` (Preorder demand aggregations): 16 / 16 passed
- **Full Test Suite (`npm test`):** PASS (140 passed, 140 total; 987 passed, 987 total)

8. Existing Regression Status

- **Previously Passing Tests:** All 137 pre-existing test suites (938 tests) continue to pass with zero regressions.
- **Reports Module:** `tests/api/report-admin-api.test.ts` verified — `getPreorderDemandReport` continues to aggregate preorders correctly.
- **Migrations:** `tests/unit/audit-reports-migration.test.ts` and `tests/unit/migrations-regression.test.ts` pass cleanly with 13 registered migrations and required indexes.

9. Out-of-Scope Findings

1. **Transaction Retry Flake in Heavy Parallel Test Runs:** In `tests/integration/return-concurrency.test.ts`, under full parallel execution of 140 suites across multiple workers, MongoDB in-memory replica set occasionally throws a raw `112 (WriteConflict)` error instead of returning domain `RETURN_STATE_CONFLICT`. The suite passes 100% when run independently or with `--maxWorkers=4`. Per Rule 24, this existing Phase 12 return test was left untouched.

10. Final Work Package Status

PRE-ORDERS — COMPLIANT WITH OPEN DECISION DEPENDENCIES