Linux Scripting

David Clinton

LINUX SYSTEM ADMINISTRATOR

bootstrap-it.com/linux-cli | @davidbclinton | linkedin.com/in/dbclinton

Overview

Overview

Scripting basics

Overview

Scripting basics

User inputs

Overview

Scripting basics

User inputs

Variables

Overview

Scripting basics

User inputs

Variables

Flow control

Overview

Scripting basics

User inputs

Variables

Flow control

- for

Overview

Scripting basics

User inputs

Variables

Flow control

- **for**

- **if**

Overview

Scripting basics

User inputs

Variables

Flow control

- **for**

- **if**

- **while**

Overview

Scripting basics

User inputs

Variables

Flow control
- for
- if
- while
- case

Overview

Scripting basics

User inputs

Variables

Flow control

    – for

    – if

    – while

    – case

Builtins

Working with Loops and Flow Controls

Module and Course Review

Module Review

Module Review

#!/bin/bash

Module Review

`#!/bin/bash`

`chmod +x myscript.sh`

Module Review

```bash
#!/bin/bash

chmod +x myscript.sh

read number1
```

Module Review

```bash
#!/bin/bash

chmod +x myscript.sh

read number1

total=$number1*$number2
```

Module Review

```bash
#!/bin/bash

chmod +x myscript.sh

read number1

total=$number1*$number2

for filename in file1 file2 file3
```

Module Review

```bash
#!/bin/bash

chmod +x myscript.sh

read number1

total=$number1*$number2

for filename in file1 file2 file3

if test $text1 != $text2; then
```

Module Review

```bash
#!/bin/bash

chmod +x myscript.sh

read number1

total=$number1*$number2

for filename in file1 file2 file3

if test $text1 != $text2; then

while [ $counter -gt 2 ]; do
```

Module Review

```bash
#!/bin/bash

chmod +x myscript.sh

read number1

total=$number1*$number2

for filename in file1 file2 file3

if test $text1 != $text2; then

while [ $counter -gt 2 ]; do

case $weather in
```