

GOOD PROGRAMMING STYLE

3RD WEEK LECTURE

엄현상(Eom, Hyeonsang)
School of Computer Science and Engineering
Seoul National University

Outline

- Good Programming Style C++
- Q&A

Guidelines for Writing C/C++ Code

- Point of a Style Guide
 - Greater Uniformity in Appearance of Source Code
- Benefit
 - Enhanced Readability and Hence Maintainability for the Code

File Contents

- Files as Modules to Group Functionality
 - Avoiding Duplicating Functionality in Separate Files
- Header Files
 - To Declare Public Interfaces
- Code Files
 - To Define Implementations
 - If a module calls a function defined externally. it is desirable to include that function's associated .h file in the implementation of the module

Header (Interface) File Contents

- Copyright Statement Comment
- Module Abstraction Comment
- Revision-String Comment; e.g., \$Id\$
- Multiple Inclusion `#ifndef`(a.k.a. “include guard”)
- Other Preprocessor Directives, `#include` and `#define`
- C/C++ `#ifndef`

Header (Interface) File Contents Cont'd

- Data Type Definitions (Classes and Structures)
- typedefs
- C/C++ #endif
- Multiple Inclusion #endif

```
#ifndef __cplusplus // predefined (double underscore)
extern 'C' { // Linkage directive informs the compiler not to encode f/n
#endif
...
#ifdef __cplusplus
}
#endif
```

gcc/g++ Basic Options

- -D
 - Set the Value of a Symbol
- -I (Capital i)
 - Include Files in a Non-Standard Directory

#define INFO_FILE "infofile"

martini:~\$gcc -c -DINFO_FILE= \ "infofile \ "backup

martini:~\$gcc -c -DUSE_ODIR backup2.c

martini:~\$ gcc -c -I./include backup3.c

indicate where to find the header files

#define USE_ODIR

#ifdef USE_ODIR

...

#else

...

#endif

Code File Contents

- Copyright Statement Comment
- Module Abstraction Comment
- Preprocessor Directives, `#include` and `#define`
- Revision-String Variable
 - Implementation-File Revision String Should Be Stored as a Program Variable

Code File Contents Cont'd

```
static const char rcs_id[] = "$Id$";
```

- Other Module-Specific Variable Definitions
- Local Function Interface Prototypes
- Class/Function Definitions

File Format

- Spatial Structure Illustrating the Logical Structure
 - Blank Lines to Help Separate Different Ideas
 - Indentation to Show Logical Relationships
 - Spaces to Separate Functionality
 - Each Block to Do Exact One Thing

File Format Cont'd

- All Function Definitions and Declarations Starting in Column Zero
 - Return Value Type, Function Interface Signature (Name and Argument List), and Function Body Open and End Brackets Put Each on a Separate Line
- Single Space to Separate All Operators from Their Operands
 - Exceptions: ->, .., () and [] Operators

File Format Cont'd

- Four Spaces for Each Level of Indentation
- Lines with No Longer Than 80 Characters
 - Breaking After a Comma
 - Breaking Before an Operator
 - Breaking Lines to Illustrate Logical Relation
 - Aligning the Newline with the Beginning of the Expression at the Same Level on the Previous Line

File Format Cont'd

- Pure-Block, Fully Bracketed Style for Blocks of Code
 - Opening Bracket Put at the End of the Line
 - Exception: conditions that are broken across multiple lines

```
new_shape = affine_transform(coords, translation,
                             rotation);


if ( ( (new_shape.x > left_border) &&
      (new_shape.x < right_border) ) &&
    ( (new_shape.y > bottom_border) &&
      (new_shape.y < top_border) ) )
{
    draw(new_shape);
}
```

Unique to C++

- Starting public, protected, private and friend Labels in Column Zero of Class Declarations
- Declaring the Members in a Consistent Order
- Putting Simple Inline Function Definitions on the Same Line as Their Definitions
 - Using a Pure-Block Style with Four-Space Indentation for Complex Inline Functions
- Avoiding Putting Complex Function Implementations into .h Files

Class Declaration Format

```
class Type : public Parent {  
private:  
    int x_;  
    int y_;  
public:  
    Type();  
    Type(int x) : x_(x) { }  
    ~Type();  
  
    int get_x() const { return x_; }  
    void set_x(const int new_x) { x_ = new_x; }  
    ...  
    void display() {  
        ...  
    }  
}
```



Choosing Meaningful Names

- Variable Names
 - Lower Case for All Variable Names with an Underscore as a Separator in C/C++
 - E.g., `boiling_point`
 - Variable Names Using Mixed Case Letters Starting with a Lower Case Letter And Starting Each Subsequent Word with an Upper Case Letter in Java
 - E.g., `boilingPoint`

Choosing Meaningful Names Cont'd

- Variable Names Cont'd
 - Careful Choice
 - Consistent names
 - Similar names for similar data types
 - No names that are homophones
 - Names that say what the variable represents; i.e., nouns
 - No generic names such as tmp, buf, and reg
 - No intentionally misspelled words such as lo or lite
 - No abbreviations
 - No overly long names

Choosing Meaningful Names Cont'd

- Function Names
 - Lower Case Letters for Public Function Names with an Underscore as a Separator
 - Consistent and Informative Names
 - Strong verb that indicates the purpose for a function that returns no value
 - Name that indicates the meaning of the value returned for a function that returns a value
- Method Names
 - Method Names Using Mixed Case Letters Starting with a Lower Case Letter And Starting Each Subsequent Word with an Upper Case Letter

Choosing Meaningful Names Cont'd

- Classes, Structures, and Type Definitions
 - Capitalizing the First Letter of the Name of Each Type That Is Defined
- Constants
 - Using ALL_UPPER_CASE for Your Named Constants, Separating Words with the Underscore Character

Comments

: Describing *Why* Code Does What It Does

- End-Line Comments
 - Variable Declarations
 - Marking **#if/#endif** Statements
- Short (Single-Line) Comments
- Block Comments
 - Function Descriptions
- Bold Comments
 - Delimiting Major Sections of Code

Illustrations : Comments

```
^L
/*
 * *****
 * Bold comment.
 * *****
 */

/*
 * Block comment.
 */

/* Short (single-line) comment. */
```

```
int i; /* end-line comment */
```

Syntax and Language Issues

- Each Line to Do Exact One Thing
- No Use of Side-Effects
- Clear Structure
- Trivial Branch
- **while() { ... }** Rather Than **do { ... } while ();**
- Short Control Structure
- No Deeply Nested Code
- No Use of Global Variable

Syntax and Language Issues Cont'd

- No Preprocessor Constants (#defines)
 - Declaring Vars of Proper Types as consts
 - Defining enums for Related Sets of Integer Constants
- Function Declarations/Prototypes for All Functions
- Explicit Assumptions about the Condition of Input Data to Routines
- Checking the Return Values of All Library Function Calls
- Informative Error Messages

Formatting

- Formatting Refers to the Indentation, Alignment, And Use of White Space to Lay Out Your Program to Increase Its **Readability** by Others
- **Consistency** Is the Key to Producing Readable Code
 - While Many Can Argue to Merits of 3 Versus 4 Spaces of Indentation, Placement of Curly Braces, Etc.

Real Key Is to Adopt a Formatting Style
And Keep to It!