
```
# This script runs at the login of a bash shell

# the default darwin "xterm-color" $TERM var doesn't
# play well with the solaris machines, use vt100 instead -kk
export TERM='vt100'

##### Make terminals aware of X server ##### -kk
# NOTE: X should be set to run at login
# export DISPLAY=':0.0'

#
# Your previous .profile (if any) is saved as .profile.mpsaved
# Setting the path for MacPorts.
export PATH=/opt/local/bin:/opt/local/sbin:$PATH

export MANPATH=/opt/local/man:$MANPATH

##### set user path to include ~/bin and source .aliases ##### -kk
if [ -f $HOME/.aliases ]; then
    source $HOME/.aliases
fi

PATH=$PATH:$HOME/bin:/usr/local/bin:/usr/texbin

pdflatex=${iTMInput}

##### IDL setup ##### -lbw
source /Applications/itt/idl/bin/idl_setup.bash
## Example: Add new path to ITT's default IDL path
IDL_PATH=$IDL_PATH:+./Applications/itt/idl/lib:~/Desktop/idllibs

#####
# Set up Wind/3DP
function uidl {
    # We have to unset the IDL_PATH to avoid TPLLOT conflicts... kludgy.
    # If you have personal IDL routines that you normally include (as long as
    # they don't include any TPLLOT routines!), you may add them to the IDL_PATH
    # after we clobber it below.
    unset IDL_PATH
    source $HOME/.bash_profile
    source $HOME/full/path_to/wind_3dp_pros/umn3dp_start
    source $HOME/.bash_profile
}

#####
# Set up Wind/3DP
function uidl64 {
    # We have to unset the IDL_PATH to avoid TPLLOT conflicts... kludgy.
    # If you have personal IDL routines that you normally include (as long as
    # they don't include any TPLLOT routines!), you may add them to the IDL_PATH
    # after we clobber it below.
    unset IDL_PATH
    source $HOME/.bash_profile
    source $HOME/full/path_to/wind_3dp_pros/umn3dp_start_64
    source $HOME/.bash_profile
}
```

