

NCM API DOCUMENTATION

NCM API COLLECTION

What is NCM API?

NCM API service gives you the capability to integrate your online system with NCM's portal. Our API service currently provides you the capability to

- [✓] Fetch Particular Order Details
- [✓] Fetch Order Comments
- [✓] Fetch last 25 comments of orders
- [✓] Fetch Order Status
- [✓] Create a new Order right from your own system

API Limits

Order Creation : 1,000 per day

Order View (Detail, Comments, Status): 20,000 per day

Every vendor is provided with an API Token Key. Use this api token key to make an api request into the server.

If you forgot the token or want to request new token, contact our IT Admin.

GET Branch Lists with details

This endpoint allows to fetch the list of all branches of NCM with their details like phone number, covered areas, district, regions etc.

Link: <https://demo.nepalcanmove.com/api/v2/branches>

GET Delivery Charges between branches

This endpoint allows to calculate the delivery charge for the branches.

Link: <https://demo.nepalcanmove.com/api/v1/shipping-rate?creation=TINKUNE&destination=POKHARA&type=Pickup/Collect>
Params:
creation : pickup branch

```
destination : destination branch to where order needs to be send  
type : delivery type
```

Available Delivery Types for 'type' parameter:

Type Value	Description	Charge Calculation
Pickup/Collect	Door2Door (NCM pickup & delivery)	Full base charge
Send	Branch2Door (Sender drops at branch, NCM delivers at door)	Full base charge
D2B	Door2Branch (NCM pick, Customer collect at branch)	Base charge - 50
B2B	Branch2Branch (Sender Drop at branch & customer collect at branch)	Base charge - 50

Headers

```
Authorization      Token <your token keys>
```

GET Order Details

This endpoint allows to fetch the details of a particular order in your system. These details are the same as the details you see on the NCM portal when you view a particular order.

```
Link: https://demo.nepalcanmove.com/api/v1/order?id=ORDERID
```

Headers

```
Authorization      Token <your token keys>
```

Params

```
id                ORDERID                your order id in ncm system
```

Example:

```
curl --location --request GET https://demo.nepalcanmove.com/api/v1/order?id=134 \
```

```
--header "Authorization: Token a3dede0dcfb45e2af76ced9f7a74909aac9d0a45" \
```

Result:

```
Response Status 200
{
  "orderid": 134,
  "cod_charge": "1710.00",
  "delivery_charge": "99.00",
  "last_delivery_status": "Delivered",
  "payment_status": "Completed"
}
```

GET Order Comments

This endpoint allows to fetch the comments of a particular order in your system. The api will provide all the comments done in a particular order. Comments will be in descending order of created date.

Link: <https://demo.nepalcanmove.com/api/v1/order/comment?id=ORDERID>

Headers

Authorization	Token <your access token keys>
---------------	--------------------------------

Params

id	ORDERID	your order id in ncm system
----	---------	-----------------------------

Example:

```
curl --location --request GET https://demo.nepalcanmove.com/api/v1/order/comment?id=134 \
--header "Authorization: Token a3dede0dcfb45e2af76ced9f7a74909aac9d0a45" \
```

Result:

```
Response Status 200
[
```

```
{
  "orderid": 134,
  "comments": "Please provide us with the correct phone number?",
  "addedBy": "NCM Staff",
  "added_time": "2019-11-02T16:43:15.687200+05:45"
},
{
  "orderid": 134,
  "comments": "Test comments",
  "addedBy": "Vendor",
  "added_time": "2019-10-15T12:22:15.989560+05:45"
},
{
  "orderid": 134,
  "comments": "Test Comment",
  "addedBy": "NCM Staff",
  "added_time": "2019-10-15T11:33:16.472031+05:45"
}
]
```

GET LAST 25 Order Comments

This endpoint allows to fetch the last 25 comments done to your orders. Latest comments will be fetched at the top.

Link: <https://demo.nepalcanmove.com/api/v1/order/getbulkcomments>

Headers

Authorization	Token <your access token keys>
---------------	--------------------------------

Example:

```
curl --location --request GET
https://demo.nepalcanmove.com/api/v1/order/getbulkcomments \
--header "Authorization: Token a3dede0dcfb45e2af76ced9f7a74909aac9d0a45"
```

Result:

```
Response Status 200
[
  {
```

```
[
  {
    "orderid": 123,
    "comments": "Test Comments",
    "addedBy": "NCM Staff",
    "added_time": "2020-01-28T18:20:29.349013+05:45"
  },
  {
    "orderid": 123,
    "comments": "Phone Not Received Multiple Times",
    "addedBy": "NCM Staff",
    "added_time": "2020-01-29T11:04:51.510397+05:45"
  },
  {
    "orderid": 123,
    "comments": "Phone Not Received Multiple Times",
    "addedBy": "NCM Staff",
    "added_time": "2020-01-28T16:02:54.335899+05:45"
  },
  {
    "orderid": 123,
    "comments": "Area not covered by NCM",
    "addedBy": "NCM Staff",
    "added_time": "2020-01-28T15:59:55.371198+05:45"
  }
  ...
]
```

GET Order Status

This endpoint allows to fetch the status of a particular order in your system. The api will provide all the status of a particular order. Statuses will be in descending order of created date.

Link: <https://demo.nepalcanmove.com/api/v1/order/status?id=ORDERID>

Headers

Authorization	Token <your access token keys>
---------------	--------------------------------

Params

id	ORDERID	your order id in ncm system
----	---------	-----------------------------

Example:

```
curl --location --request GET https://demo.nepalcanmove.com/api/v1/order/status?id=134 \
--header "Authorization: Token a3dede0dcfb45e2af76ced9f7a74909aac9d0a45"
```

Result:

Response Status 200

```
[
  {
    "orderid": 134,
    "status": "Delivered",
    "added_time": "2019-10-18T13:24:30.960365+05:45"
  },
  {
    "orderid": 134,
    "status": "Sent for Delivery",
    "added_time": "2019-10-18T13:22:21.033595+05:45"
  },
  {
    "orderid": 134,
    "status": "Pickup Complete",
    "added_time": "2019-10-18T13:17:25.326792+05:45"
  },
  {
    "orderid": 134,
    "status": "Sent for Pickup",
    "added_time": "2019-10-18T13:15:24.313074+05:45"
  },
  {
    "orderid": 134,
    "status": "Pickup Order Created",
    "added_time": "2019-10-15T11:32:18.149352+05:45"
  }
]
```

Possible Errors in GET requests:

*If token is not provided

Response Status 401:

```
{
  "detail": "Authentication credentials were not provided."
}
```

*If Order ID is missing/empty

Response Status 400:

```
{
  "detail": "ID parameter missing"
}
```

```
}

*If invalid or unknown order id provided

Response Status 404:
{
  "detail": "Not found."
}
Response Status 500:
{
  "detail": "Server Error"
}
```

POST Create an order

This endpoint allows you to create an order from your system. Vendor must provide necessary details from their end to create an order through this endpoint.

Link: <https://demo.nepalcanmove.com/api/v1/order/create>

Headers

Authorization Token <your access token keys>

Params

Params	Requirement	Description
name	required	customer name
phone	required	customer phone number
phone2	optional	customer secondary phone
cod_charge	required	cod amount including delivery
address	required	general address of customer
fbranch	required	From branch name
branch	required	Destination branch name
package	optional	Package name or type
vref_id	optional	Vendor reference id
instruction	optional	Delivery Instruction

Params	Requirement	Description
delivery_type	optional	Delivery Type: Door2Door, Branch2Door, Branch2Branch, Door2Branch (default: Door2Door if not provided)
weight	optional	Weight in kg (default: 1 kg if not provided)

Example:

```
curl --location --request POST 'https://demo.nepalcanmove.com/api/v1/order/create' \
--header 'Authorization: Token a3dede0dcfb45e2af76ced9f7a74909aac9d0a45' \
--header 'Content-Type: application/json' \
--data-raw '{
  "name": "John Doe",
  "phone": "9847023226",
  "phone2": "",
  "cod_charge": "2200",
  "address": "Byas Pokhari",
  "fbranch": "TINKUNE",
  "branch": "BIRATNAGAR",
  "package": "Jeans Pant",
  "vref_id": "VREF234",
  "instruction": "Test Instruction",
  "delivery_type": "Branch2Door",
  "weight": "2"
}'
```

Result:

```
Status 200
{
  "Message": "Order Successfully Created",
  "orderid": 747
}
```

Error if fields are missing

```
Status 400
{
  "Error": {
    "cod_charge": "Invalid COD Amount",
    "phone": "Invalid Phone Number",
    "branch": "Invalid Branch",
    "name": "Invalid Name",
    "address": "Invalid Address"
  }
}
```

```
}  
}
```

POST Create an order comment

This endpoint allows you to create a comment from your system. Vendor must provide necessary details from their end to create a comment through this endpoint.

Link: <https://demo.nepalcanmove.com/api/v1/comment>

Headers

Authorization Token <your access token keys>

Params

Params	Requirement	Description
orderid	required	order id in ncm portal
comments	required	text comment to put in order

Example:

```
curl --location --request POST 'https://demo.nepalcanmove.com/api/v1/comment' \  
--header 'Authorization: Token a3dede0dcfb45e2af76ced9f7a74909aac9d0a45' \  
--header 'Content-Type: application/json' \  
--data-raw '{  
  "orderid": "1234567",  
  "comments": "Test comment from api"  
}'
```

Result:

```
Status 200  
{  
  "message": "Comment successfully created"  
}
```

Error if fields are missing

```
Status 400
{
  "Error": {
    "Order Id": "Invalid / Empty orderid",
    "Comments": "Invalid / Empty comment",
  }
}
```

POST Retrieve Order statuses

This endpoint allows you to get status for the order ids provided through this endpoint.

Link: <https://demo.nepalcanmove.com/api/v1/orders/statuses>

Headers

Authorization Token <your access token keys>

Params

Params	Requirement	Description
orders	required	order id in ncm portal

Example:

```
curl --location --request POST
'https://demo.nepalcanmove.com/api/v1/orders/statuses' \
--header 'Authorization: Token a3dede0dcfb45e2af76ced9f7a74909aac9d0a45' \
--header 'Content-Type: application/json' \
--data-raw '{ "orders": [4041,3855,4032,3841,3842,4042] }'
```

Result:

```
Status 200
{
  "result": {
    "4041": "Pickup Order Created",
    "3855": "Arrived",
    "4032": "Drop off Order Created",
  }
}
```

```
    "3841": "Delivered",
    "3842": "Delivered"
  },
  "errors": [
    4042
  ]
}
```

POST Create Generic Vendor Ticket

This endpoint allows vendors to create a general support ticket.

```
Link: https://demo.nepalcanmove.com/api/v2/vendor/ticket/create/new
Method: POST
Authorization: Token <your_token>
Content-Type: application/json
```

Params

Params	Requirement	Description
ticket_type	required	Type of ticket (see available types below)
message	required	Message/description (max 500 chars)
branch	conditional	Required only when ticket_type is Pickup

Available Ticket Types:

- **General** - General inquiries or issues
- **Order Processing** - Order processing related issues
- **Return** - Return/refund related requests
- **Pickup** - Pickup scheduling or issues

Example:

```
{
  "ticket_type": "Pickup",
  "message": "98XXXXXXX, No. of Packets: 5, Address: Baneshwor",
  "branch": "Tinkune"
}
```

Result:

```
Status 201
{
  "message": "Ticket created",
  "ticket": 123
}
```

Note:

- **branch** is mandatory for Pickup ticket creation.
- **branch** must be one of the vendor's assigned pickup branches.

POST Create COD Transfer Ticket

This endpoint allows vendors to create a COD transfer request ticket.

```
Link: https://demo.nepalcanmove.com/api/v2/vendor/ticket/cod/create
Method: POST
Authorization: Token <your_token>
Content-Type: application/json
```

Params

Params	Requirement	Description
bankName	required	Name of the bank
bankAccountName	required	Account holder name
bankAccountNumber	required	Bank account number

Example:

```
{
  "bankName": "Nepal Bank Limited",
  "bankAccountName": "John Doe",
  "bankAccountNumber": "1234567890"
}
```

Result:

```
Status 201
{
  "message": "COD ticket created",
}
```

```
"ticket": 124
}
```

POST Close Vendor Ticket

This endpoint allows vendors to close their own tickets.

```
Link: https://demo.nepalcanmove.com/api/v2/vendor/ticket/close/<ticket_id>
Method: POST
Authorization: Token <your_token>
Content-Type: application/json
```

Params

Params	Requirement	Description
pk	required	Ticket ID (in URL path)

Example:

```
curl --location --request POST
'https://demo.nepalcanmove.com/api/v2/vendor/ticket/close/123' \
--header 'Authorization: Token a3dede0dcfb45e2af76ced9f7a74909aac9d0a45' \
--header 'Content-Type: application/json'
```

Result:

```
Status 200
{
  "message": "Ticket closed",
  "ticket": 123
}
```

GET Staff List

This endpoint retrieves a paginated list of active staff members.

```
Link: https://demo.nepalcanmove.com/api/v2/vendor/staffs?
q=search_term&page=1&page_size=20
Method: GET
Authorization: Token <your_token>
```

Query Params

Params	Requirement	Description
q	optional	Search staff by name (contains)
page	optional	Page number (default: 1)
page_size	optional	Results per page (default: 20, alias: limit)
limit	optional	Alias for page_size

Example:

```
curl --location --request GET 'https://demo.nepalcanmove.com/api/v2/vendor/staffs?
q=ram&page=1&limit=10' \
--header 'Authorization: Token a3dede0dcfb45e2af76ced9f7a74909aac9d0a45'
```

Result:

```
Status 200
{
  "count": 45,
  "next": "https://demo.nepalcanmove.com/api/v2/vendor/staffs?page=2",
  "previous": null,
  "results": [
    {
      "id": 12,
      "name": "Ram Sharma",
      "email": "ram@example.com",
      "phone": "9841234567"
    }
  ]
}
```

GET Vendor Assigned Branches

This endpoint returns all pickup branches assigned to the authenticated vendor.

```
Link: https://demo.nepalcanmove.com/api/v2/vendor/assigned-branches
Method: GET
Authorization: Token <your_token>
```

Query Params

No query params are required.

Example:

```
curl --location --request GET
'https://demo.nepalcanmove.com/api/v2/vendor/assigned-branches' \
--header 'Authorization: Token a3dede0dcfb45e2af76ced9f7a74909aac9d0a45'
```

Result:

```
Status 200
[
  "KATHMANDU",
  "POKHARA",
  "BIRATNAGAR"
]
```

Note:

- Response is a simple array of branch names.
- If no branches are assigned, the API returns an empty array [].

POST Return Order

This endpoint allows vendors to mark an order for return process.

```
Link: https://demo.nepalcanmove.com/api/v2/vendor/order/return
Method: POST
Authorization: Token <your_token>
Content-Type: application/json
```

Params

Params	Requirement	Description
pk	required	Order ID

Params	Requirement	Description
comment	optional	Comment/reason for the return

Example:

```
curl --location --request POST
'https://demo.nepalcanmove.com/api/v2/vendor/order/return' \
--header 'Authorization: Token a3dede0dcfb45e2af76ced9f7a74909aac9d0a45' \
--header 'Content-Type: application/json' \
--data-raw '{
  "pk": 4041,
  "comment": "Customer refused the delivery"
}'
```

Result:

```
Status 200
{
  "message": "Order marked for return successfully",
  "order": 4041,
  "vendor_return": true
}
```

Error Responses:

```
Status 400
{
  "message": "Order ID is required"
}
```

```
Status 404
{
  "message": "Order not found"
}
```

Note:

- This sets the order's `vendor_return` flag to `true`
- If a comment is provided, it creates an external comment with "Pending" status
- Only the vendor who owns the order can mark it for return

POST Create Exchange Order

This endpoint creates exchange orders for returning items and sending replacements.

```
Link: https://demo.nepalcanmove.com/api/v2/vendor/order/exchange-create
Method: POST
Authorization: Token <your_token>
Content-Type: application/json
```

Params

Params	Requirement	Description
pk	required	Original order ID

Example:

```
{
  "pk": 4041
}
```

Result:

```
Status 200
{
  "message": "Exchange orders created",
  "cust_order": 4567,
  "ven_order": 4568
}
```

Note: This creates two orders:

- Customer order (cust_order): New delivery to customer
- Vendor order (ven_order): Return of old item to vendor

POST Redirect Order

This endpoint allows vendors to redirect an order to a different address/customer.

```
Link: https://demo.nepalcanmove.com/api/v2/vendor/order/redirect
Method: POST
Authorization: Token <your_token>
Content-Type: application/json
```

Params

Params	Requirement	Description
pk	required	Order ID
name	required	New customer name
phone	required	New customer phone
address	required	New customer address
vendorOrderid	optional	Vendor's reference order ID
destination	optional	New destination branch ID (if changing)
cod_charge	optional	New COD amount (decimal value)

Example:

```
{
  "pk": 4041,
  "name": "New Customer Name",
  "phone": "9841234567",
  "address": "New delivery address, Kathmandu",
  "vendorOrderid": "VORD-12345",
  "destination": 5,
  "cod_charge": 750.5
}
```

Result:

```
Status 200
{
  "message": "Order redirected successfully",
  "order": 4041,
  "cod_charge": "500.00",
  "delivery_charge": "175.00",
  "changelogs": "-destination_branch was changed from TINKUNE to POKHARA\n-  
delivery_charge was changed from 150 to 175\nBranch Changed.\n"
}
```

Note:

- If destination branch is changed, RDRT-DiFF-BRNCH charge is added
- If destination remains same, REDIRECT charge is added
- Creates new customer record if phone doesn't exist
- COD charge can be updated by providing cod_charge parameter (optional)
- All changes are logged in order changelogs

POST Create/Update Webhook URLs

This endpoint allows vendors to create, update or remove their webhook URLs used by NCM to push order status and comment events.

```
Link: https://demo.nepalcanmove.com/api/v2/vendor/webhook
Method: POST
Authorization: Token <your_token>
Content-Type: application/json
```

Params

Params	Requirement	Description
webhook_url	required	Order status webhook URL (must start with http/https)

Notes:

- If `webhook_url` is an empty string, the stored order status webhook URL will be removed.
- URLs when provided, must start with `http://` or `https://`.

Example: Set webhooks

```
{
  "webhook_url": "https://example.com/webhooks/order-status"
}
```

Example: Remove order status webhook

```
{
  "webhook_url": ""
}
```

Result:

```
Status 200
{
  "success": true,
  "message": "Webhook URLs updated successfully!"
}
```

or, on first-time creation:

```
Status 201
{
  "success": true,
  "message": "Webhook URLs created successfully!"
}
```

Error Responses:

```
Status 400
{
  "success": false,
  "message": "Please enter a valid URL for Order Status Webhook (must start with http:// or https://)"
}
```

POST Test Webhook URL

This endpoint sends a test payload to a given webhook URL so vendors can verify that their endpoint is reachable and correctly processes status updates.

```
Link: https://demo.nepalcanmove.com/api/v2/vendor/webhook/test
Method: POST
Authorization: Token <your_token>
Content-Type: application/json
```

Params

Params	Requirement	Description
webhook_url	required	Your webhook endpoint URL (http/https)

Test Payload

The API will send a JSON body similar to:

```
{
  "event": "order.status.changed",
  "order_id": "TEST-123456",
  "status": "In Transit",
  "timestamp": "2024-01-01T12:00:00+05:45",
  "test": true
}
```

Example:

```
{  
  "webhook_url": "https://example.com/webhooks/order-status"  
}
```

Result (success):

```
Status 200  
{  
  "success": true,  
  "status_code": 200,  
  "response": "OK"  
}
```

Result (HTTP error from your server):

```
Status 200  
{  
  "success": true,  
  "status_code": 400,  
  "response": "Bad Request",  
  "headers": {  
    "Content-Type": "text/plain"  
  }  
}
```

Result (connection/timeout error):

```
Status 200  
{  
  "success": false,  
  "error": "Request timed out. The webhook URL did not respond within 10 seconds."  
}
```

```
Status 200  
{  
  "success": false,  
  "error": "Connection error. Could not connect to the webhook URL. Details: ..."  
}
```

GET Ticket Detail API

```
Link: https://demo.nepalcanmove.com/api/v1/tickets/<ticket_id>/detail
Method: GET
Authorization: Token <your_token>
```

Access Rules

- Vendor can view only own ticket.
- Logistics can view only assigned ticket.
- Other roles are forbidden.

Example

```
curl --location --request GET
'https://demo.nepalcanmove.com/api/v1/tickets/2639/detail' \
--header 'Authorization: Token <your_token>'
```

Sample Response

```
Status 200
{
  "success": true,
  "ticket": {
    "id": 2639,
    "ticket_type": "Pickup",
    "message": "dfsdf<br>No. of Packets: 33<br>Address: Pariatur Corporis e <br>Actual Pickup count : 52",
    "added_on": "2026-04-09T11:28:00+05:45",
    "status": false,
    "comment": "",
    "attachment": null,
    "branch": "BUTWAL",
    "closed_on": null,
    "vendor": {
      "id": 629,
      "name": "Vendor NCM",
      "location": "27.700769,85.300140"
    },
    "assigned_to": {
      "id": 43,
      "name": "Ram Logistics"
    },
    "closed_by": {
      "id": null,
      "name": null
    }
  }
}
```

```
    },
    "responses": [
      {
        "id": 901,
        "message": "Please pickup tomorrow morning.",
        "added_on": "2026-04-09T12:10:00+05:45",
        "vendor_display": true,
        "added_by": {
          "id": 629,
          "name": "Vendor NCM"
        }
      }
    ]
  }
}
```

POST Vendor Ticket Response Create API

Endpoint

Link: https://demo.nepalcanmove.com/api/v1/vendor/tickets/<ticket_id>/response
Method: POST
Authorization: Token <your_token>
Content-Type: application/json

Request Body

```
{
  "message": "Response text from vendor"
}
```

Behavior

- Creates a ticket response with `vendorDisplay=true`.
- If ticket is closed, it is reopened automatically.

Example

```
curl --location --request POST
'https://demo.nepalcanmove.com/api/v1/vendor/tickets/2639/response' \
--header 'Authorization: Token <your_token>' \
--header 'Content-Type: application/json' \
--data-raw '{
  "message": "Please check this update from vendor side."
}'
```

Sample Response

```
Status 201
{
  "success": true,
  "ticket_id": 2639,
  "response": {
    "id": 902,
    "message": "Please check this update from vendor side.",
    "added_on": "2026-04-09T12:35:10+05:45",
    "vendor_display": true,
    "added_by": {
      "id": 629,
      "name": "Vendor NCM"
    }
  }
}
```

GET Vendor Customer List

Returns a paginated list of customers associated with your vendor account — either created by you or who have received at least one of your orders.

```
Link: https://demo.nepalcanmove.com/api/v2/vendor/customers
Method: GET
Authorization: Token <your_token>
```

Query Params

Params	Requirement	Description
page	optional	Page number (default: 1)
page_size	optional	Results per page (default: 25, maximum: 100)
name	optional	Filter customers by name (contains)

Params	Requirement	Description
phone	optional	Filter customers by phone (starts with)

Example:

```
curl --location --request GET
'https://demo.nepalcanmove.com/api/v2/vendor/customers?page=1' \
--header 'Authorization: Token a3dede0dcfb45e2af76ced9f7a74909aac9d0a45'
```

Result:

```
Status 200
{
  "count": 320,
  "next": "https://demo.nepalcanmove.com/api/v2/vendor/customers?page=2",
  "previous": null,
  "results": [
    {
      "id": 109523,
      "name": "John Doe",
      "phone": "9841234567",
      "address": "Baneshwor, Kathmandu"
    },
    {
      "id": 109524,
      "name": "Jane Smith",
      "phone": "9807654321",
      "address": ""
    }
  ]
}
```

GET Vendor Customer Detail

Returns full profile and complete order history for a specific customer of your vendor account.

```
Link: https://demo.nepalcanmove.com/api/v2/vendor/customers/<customer_id>/detail
Method: GET
Authorization: Token <your_token>
```

URL Params

Params	Requirement	Description
customer_id	required	Customer ID (in URL path)

Example:

```
curl --location --request GET
'https://demo.nepalcanmove.com/api/v2/vendor/customers/109523/detail' \
--header 'Authorization: Token a3dede0dcfb45e2af76ced9f7a74909aac9d0a45'
```

Result:

```
Status 200
{
  "id": 109523,
  "name": "John Doe",
  "phone": "9841234567",
  "email": "john@example.com",
  "orders": [
    {
      "orderid": 74821,
      "created_date": "2026-04-15T10:30:00+05:45",
      "cod_charge": "1500.00",
      "delivery_charge": "150.00",
      "last_delivery_status": "Delivered"
    },
    {
      "orderid": 74100,
      "created_date": "2026-03-10T09:15:00+05:45",
      "cod_charge": "2200.00",
      "delivery_charge": "150.00",
      "last_delivery_status": "Sent to Vendor"
    }
  ]
}
```

Error Responses:

```
Status 404
{
  "detail": "Customer not found"
}
```

```
Status 404
{
```

```
"detail": "Not found"
}
```

GET Customer Rating Stats

Returns delivery performance stats for a customer by phone number — total orders placed, successful deliveries, and returns across the entire NCM system.

```
Link: https://demo.nepalcanmove.com/api/v2/vendor/ratings?phone=<phone>
Method: GET
Authorization: Token <your_token>
```

Query Params

Params	Requirement	Description
phone	required	Customer's phone number

Example:

```
curl --location --request GET
'https://demo.nepalcanmove.com/api/v2/vendor/ratings?phone=9841234567' \
--header 'Authorization: Token a3dede0dcfb45e2af76ced9f7a74909aac9d0a45'
```

Result:

```
Status 200
{
  "phone": "9841234567",
  "total_orders": 18,
  "total_delivered": 15,
  "total_returned": 3
}
```

Error Responses:

```
Status 400
{
  "detail": "phone parameter is required"
}
```

```
Status 404
{
  "detail": "No customer found with this phone number"
}
```

GET Order Label Data (Single Order)

Returns all information needed to render a delivery label for a specific order. Only the authenticated vendor's own orders are accessible.

```
Link: https://demo.nepalcanmove.com/api/v2/vendor/order/label/<order_id>
Method: GET
Authorization: Token <your_token>
```

URL Params

Params	Requirement	Description
order_id	required	Order ID (in URL path)

Example:

```
curl --location --request GET
'https://demo.nepalcanmove.com/api/v2/vendor/order/label/346844' \
--header 'Authorization: Token a3dede0dcfb45e2af76ced9f7a74909aac9d0a45'
```

Result:

```
Status 200
{
  "orderid": 346844,
  "delivery_type": "Home",
  "cod_charge": "1500.00",
  "from_branch": {
    "name": "TINKUNE",
    "code": "TINK1",
    "district": "Kathmandu"
  },
  "to_branch": {
    "name": "BIRATNAGAR",
    "code": "BIRA1",
    "district": "Morang"
  },
}
```

```
{
  "from": {
    "name": "Vendor Name",
    "phone": "9841000000",
    "phone2": ""
  },
  "receiver": {
    "name": "John Doe",
    "phone": "9847000000",
    "phone2": "",
    "address": "Baneshwor, Kathmandu"
  },
  "description": {
    "description": "Blue jeans",
    "delivery_instruction": "Handle carefully",
    "handling": "Non-Fragile",
    "vendor_orderid": "VREF-123"
  }
}
```

Error Responses:

```
Status 404
{
  "detail": "Order not found"
}
```

POST Order Label Data (Multiple Orders)

Returns label data for multiple orders in a single request. Pass an array of order IDs in the request body. Only orders belonging to the authenticated vendor are returned.

```
Link: https://demo.nepalcanmove.com/api/v2/vendor/order/label/
Method: POST
Authorization: Token <your_token>
Content-Type: application/json
```

Body Params

Params	Requirement	Description
ids	required	Array of integer order IDs (must be non-empty)

Example:

```
curl --location --request POST
'https://demo.nepalcanmove.com/api/v2/vendor/order/label/' \
--header 'Authorization: Token a3dede0dcfb45e2af76ced9f7a74909aac9d0a45' \
--header 'Content-Type: application/json' \
--data-raw '{
  "ids": [346844, 346845, 99999]
}'
```

Result:

```
Status 200
{
  "labels": [
    {
      "orderid": 346844,
      "delivery_type": "Home",
      "cod_charge": "1500.00",
      "from_branch": {
        "name": "TINKUNE",
        "code": "TINK1",
        "district": "Kathmandu"
      },
      "to_branch": {
        "name": "BIRATNAGAR",
        "code": "BIRA1",
        "district": "Morang"
      },
      "from": {
        "name": "Vendor Name",
        "phone": "9841000000",
        "phone2": ""
      },
      "receiver": {
        "name": "John Doe",
        "phone": "9847000000",
        "phone2": "",
        "address": "Baneshwor, Kathmandu"
      },
      "description": {
        "description": "Blue jeans",
        "delivery_instruction": "Handle carefully",
        "handling": "Non-Fragile",
        "vendor_orderid": "VREF-123"
      }
    },
    {
      "orderid": 346845,
      "delivery_type": "Office",
      "cod_charge": "2200.00",
      ...
    }
  ]
}
```

```
    }  
  ],  
  "not_found": [99999]  
}
```

Response Fields

Field	Type	Description
labels	array of objects	Label data for every ID that was found and belongs to this vendor. Same structure as GET.
not_found	array of integers	IDs from the request that were not found or belong to a different vendor. Empty [] if all were found.

Error Responses:

```
Status 400  
{  
  "detail": "\"ids\" must be a non-empty array"  
}
```

```
Status 401  
{  
  "detail": "Authentication credentials were not provided."  
}
```

Notes:

- **delivery_type** returns "Office" for D2B/B2B orders and "Home" for all others.
- **from** contains vendor details for Vendor-type orders, or sender customer details otherwise.
- **description** fields are null if no description was added to the order.
- **handling** will be "Fragile", "Fragile and Valuable", "Valuable", or "Non-Fragile".
- IDs belonging to a different vendor are silently returned in **not_found** — same as a wrong ID.
- Order of items in **labels** may not match the order of **ids** in the request. Match by **orderid** on the client side if order matters.
- Keep batch sizes reasonable (recommended ≤ 100 IDs per request).

Please use this api endpoints very carefully.

Avoid duplication of order creation from both bulk file upload and api system.

No Spamming or running scripts to overload the server.



Tel: 015199684

Tinkune, Kathmandu

[Nepal Can Move](#)