




**NANYANG
TECHNOLOGICAL
UNIVERSITY**

CE1007/ CZ1007 DATA STRUCTURES

Lesson 9.6 Typedef Construct

Assoc Prof Hui Siu Cheung

College of Engineering
School of Computer Science and Engineering



OVERVIEW

The following are the coverage for Structures:

- Structure Declaration, Initialisation and Operations
- Arrays of Structures
- Nested Structures
- Pointers to Structures
- Functions and Structures
- The typedef Construct

Content Copyright Nanyang Technological University 2

The following are the coverage for Structures: this video focusses on Pointers to Structures.

LEARNING OBJECTIVES

At this lesson, you should be able to:

Content Copyright Nanyang Technological University 3

The slide features a red header with the title 'LEARNING OBJECTIVES'. Below the header is a large, light gray rectangular box with rounded corners, intended for the learning objectives. The text 'At this lesson, you should be able to:' is positioned at the top left of this box. At the bottom of the slide, there is a footer containing the text 'Content Copyright Nanyang Technological University' and the page number '3'.

LEARNING OBJECTIVES: At this lesson, you should be able to:

LEARNING OBJECTIVES

At this lesson, you should be able to:

- Explain the advantages of using the typedef construct.

Content Copyright Nanyang Technological University 4

- Explain the advantages of using typedef construct.


LEARNING OBJECTIVES

At this lesson, you should be able to:

- Explain the advantages of using the typedef construct.
- Write program using the typedef construct.

Content Copyright Nanyang Technological University 5

Write program using typedef construct.



THE TYPEDEF CONSTRUCT

- **typedef** provides an elegant way in structure declaration.

Content Copyright Nanyang Technological University 6

typedef provides an elegant way in structure declaration

THE TYPEDEF CONSTRUCT

- **typedef** provides an elegant way in structure declaration.
- The general syntax for the **typedef** statement is

```
typedef datatype UserProvidedName;
```

Content Copyright Nanyang Technological University 7

The general syntax for the **typedef** statement is shown here: The **typedef** keyword is followed by the data type and the user provided name for the data type. It is very useful for creating simple names for complex structures

THE TYPEDEF CONSTRUCT

- **typedef** provides an elegant way in structure declaration.
- The general syntax for the **typedef** statement is

```
typedef datatype UserProvidedName;
```
- For example, if we have defined the structure:

```
struct date {
    int day, month, year;
};
```

Content Copyright Nanyang Technological University

For example, if we have defined the structure like shown here,
 we can define a new data type **Date** as

```
typedef struct date    Date;
```

Variables can then be declared either as

```
struct date    today, yesterday;
```

or **Date today, yesterday;**

We can also use the type **Date** in function prototypes and function definitions. When **typedef** is used, tag name is redundant. Therefore, we can declare

```
typedef struct {
    int    day, month, year;
} Date;
Date today, yesterday;
```

There are a number of advantages of using **typedef**. It enhances program documentation by using meaningful names for data types in the programs. It makes the program easier to read and understand. Another advantage is to define simpler data types for complex declarations such as structures.

In addition, **typedef** is similar to the **#define** preprocessor directive. However, there are a number of differences. **typedef** is limited to giving names to data types only and is processed by the compiler, while **#define** is not limited to data types and is processed by the preprocessor.

THE TYPEDEF CONSTRUCT

- **typedef** provides an elegant way in structure declaration.
- The general syntax for the **typedef** statement is
`typedef datatype UserProvidedName;`
- For example, if we have defined the structure:

```
struct date {  
    int day, month, year;  
};
```
- One can define a **new data type** **Date** as

`typedef struct date Date;`

Content Copyright Nanyang Technological University 9

For example, if we have defined the structure as shown here, we can define a new data type **Date** as shown.

THE TYPEDEF CONSTRUCT

- Variables can be defined either as
`struct date today, yesterday;`
or
`Date today, yesterday;`

Content Copyright Nanyang Technological University 10

Variables can then be declared as shown in 2 ways:

THE TYPEDEF CONSTRUCT

- Variables can be defined either as


```
struct date    today, yesterday;
```

 or


```
Date    today, yesterday;
```
- When **typedef** is used, tag name is **redundant**, thus:


```
typedef struct {
    int day, month, year;
} Date;
Date today, yesterday;
```

No tag name – **date**

Define variables

Note: It is similar to define a new data type with record members

Content Copyright Nanyang Technological University 11

We can also use the type **Date** in function prototypes and function definitions. When **typedef** is used, tag name is redundant. Therefore, we can declare as shown.

There are a number of advantages of using **typedef**. It enhances program documentation by using meaningful names for data types in the programs. It makes the program easier to read and understand. Another advantage is to define simpler data types for complex declarations such as structures.


In addition, **typedef** is similar to the **#define** preprocessor directive. However, there are a number of differences. **typedef** is limited to giving names to data types only and is processed by the compiler, while **#define** is not limited to data types and is processed by the preprocessor.

ADVANTAGES OF TYPEDEF CONSTRUCT

- There are a number of advantages of using typedef.

Content Copyright Nanyang Technological University 12

There are a number of advantages of using **typedef**




ADVANTAGES OF TYPEDEF CONSTRUCT

- There are a number of advantages of using typedef.
- It enhances program documentation by using meaningful names for data types in the programs.

Content Copyright Nanyang Technological University 13

It enhances program documentation by using meaningful names for data types in the programs




ADVANTAGES OF TYPEDEF CONSTRUCT

- There are a number of advantages of using typedef.
- It enhances program documentation by using meaningful names for data types in the programs.
- It makes the program easier to read and understand.

Content Copyright Nanyang Technological University 14

It makes the program easier to read and understand.




ADVANTAGES OF TYPEDEF CONSTRUCT

- There are a number of advantages of using typedef.
- It enhances program documentation by using meaningful names for data types in the programs.
- It makes the program easier to read and understand.
- Another advantage is to define simpler data types for complex declarations such as structures.

Content Copyright Nanyang Technological University 15

Another advantage is to define simpler data types for complex declarations such as structures.




ADVANTAGES OF TYPEDEF CONSTRUCT

- There are a number of advantages of using typedef.
- It enhances program documentation by using meaningful names for data types in the programs.
- It makes the program easier to read and understand.
- Another advantage is to define simpler data types for complex declarations such as structures.
- In addition, typedef is similar to the `#define` preprocessor directive.

Content Copyright Nanyang Technological University 16

In addition, **typedef** is similar to the **#define** preprocessor directive.



ADVANTAGES OF TYPEDEF CONSTRUCT

- There are a number of advantages of using typedef.
- It enhances program documentation by using meaningful names for data types in the programs.
- It makes the program easier to read and understand.
- Another advantage is to define simpler data types for complex declarations such as structures.
- In addition, typedef is similar to the #define preprocessor directive.
- However, there are a number of differences.

Content Copyright Nanyang Technological University 17

However, there are a number of differences. **typedef** is limited to giving names to data types only and is processed by the compiler, while **#define** is not limited to data types and is processed by the preprocessor.

ADVANTAGES OF TYPEDEF CONSTRUCT

- There are a number of advantages of using typedef.
- It enhances program documentation by using meaningful names for data types in the programs.
- It makes the program easier to read and understand.
- Another advantage is to define simpler data types for complex declarations such as structures.
- In addition, typedef is similar to the #define preprocessor directive.
- However, there are a number of differences.
- typedef is limited to giving names to data types only and is processed by the compiler, while #define is not limited to data types and is processed by the preprocessor.

Content Copyright Nanyang Technological University

18

typedef is limited to giving names to data types only and is processed by the compiler, while **#define** is not limited to data types and is processed by the preprocessor.

THE TYPEDEF CONSTRUCT: EXAMPLE

```
#define CARRIER 1
#define SUBMARINE 2
typedef struct {
    int shipClass;
    char *name;
    int speed, crew;
} warShip;
void printShipReport(warShip);
int main() {
    warShip ship[10]; int i;
    ship[0].shipClass = CARRIER;
    ship[0].name = "Washington";
    ship[0].speed = 40;
    ship[0].crew = 800;
    ship[1].shipClass = SUBMARINE;
    ship[1].name = "Rogers";
    ship[1].speed = 100;
    ship[1].crew = 800;
    for (i=0; i<2; i++)
        printShipReport(ship[i]);
    return 0;
}
```

Content Copyright Nanyang Technological University

19

The typedef Construct: Example

In this program, we use **typedef** to define a new structure type **warShip**:

THE TYPEDEF CONSTRUCT: EXAMPLE

```
#define CARRIER 1
#define SUBMARINE 2
typedef struct {
    int shipClass;
    char *name;
    int speed, crew;
} warShip;
void printShipReport(warShip);
int main() {
    warShip ship[10]; int i;
    ship[0].shipClass = CARRIER;
    ship[0].name = "Washington";
    ship[0].speed = 40;
    ship[0].crew = 800;
    ship[1].shipClass = SUBMARINE;
    ship[1].name = "Rogers";
    ship[1].speed = 100;
    ship[1].crew = 800;
    for (i=0; i<2; i++)
        printShipReport(ship[i]);
    return 0;
}
```

Content Copyright Nanyang Technological University

20

In the **main()** function, we declare an array of **warShip** structures variable called **ship**.

THE TYPEDEF CONSTRUCT: EXAMPLE

```

#define CARRIER 1
#define SUBMARINE 2
typedef struct {
    int shipClass;
    char *name;
    int speed, crew;
} warShip;
void printShipReport(warShip);
int main() {
    warShip ship[10]; int i;
    ship[0].shipClass = CARRIER;
    ship[0].name = "Washington";
    ship[0].speed = 40;
    ship[0].crew = 800;
    ship[1].shipClass = SUBMARINE;
    ship[1].name = "Rogers";
    ship[1].speed = 100;
    ship[1].crew = 800;
    for (i=0; i<2; i++)
        printShipReport(ship[i]);
    return 0;
}
    
```

/* Printing each record */

```

void printShipReport(warShip ship)
{
    if (ship.shipClass == CARRIER)
        printf("Carrier:\n");
    else
        printf("Submarine:\n");
    printf("\tname = %s\n", ship.name);
    printf("\tspeed = %d\n", ship.speed);
    printf("\tcrew = %d\n", ship.crew);
}
    
```

Content Copyright Nanyang Technological University 21

The function **printShipReport()** is used for printing the member information of the **warShip** structure.

THE TYPEDEF CONSTRUCT: EXAMPLE

```

#define CARRIER 1
#define SUBMARINE 2
typedef struct {
    int shipClass;
    char *name;
    int speed, crew;
} warShip;
void printShipReport(warShip);
int main() {
    warShip ship[10]; int i;
    ship[0].shipClass = CARRIER;
    ship[0].name = "Washington";
    ship[0].speed = 40;
    ship[0].crew = 800;
    ship[1].shipClass = SUBMARINE;
    ship[1].name = "Rogers";
    ship[1].speed = 100;
    ship[1].crew = 800;
    for (i=0; i<2; i++)
        printShipReport(ship[i]);
    return 0;
}

```

/* Printing each record */

```

void printShipReport(warShip ship)
{
    if (ship.shipClass == CARRIER)
        printf("Carrier:\n");
    else
        printf("Submarine:\n");
    printf("\tname = %s\n", ship.name);
    printf("\tspeed = %d\n", ship.speed);
    printf("\tcrew = %d\n", ship.crew);
}

```

Output

```

Carrier:
  name: Washington
  speed = 40
  crew = 800
Submarine:
  name = Rogers
  speed = 100
  crew = 800

```

Content Copyright Nanyang Technological University 22

In the **main()** function, a **for** loop is used to print the member information of the **ship** variable using the **printShipReport()** function.

SUMMARY

At this lesson, you should be able to:

- Explain the advantages of using the typedef construct.
- Write program using the typedef construct.

Content Copyright Nanyang Technological University 23

After viewing this video lecture, you will be able to do the listed.