

[Problems](#)[Submit](#)[Runs Status](#)[Rank List](#)[Statistics](#)[Clarifications](#)

A. DNA Sorting

Time Limit: 1.0 Seconds Memory Limit: 65536K Multiple test files

One measure of "unsortedness" in a sequence is the number of pairs of entries that are out of order with respect to each other. For instance, in the letter sequence "DAABEC", this measure is 5, since D is greater than four letters to its right and E is greater than one letter to its right. This measure is called the number of inversions in the sequence. The sequence "AACEDGG" has only one inversion (E and D)--it is nearly sorted--while the sequence "ZWQM" has 6 inversions (it is as unsorted as can be--exactly the reverse of sorted).

You are responsible for cataloguing a sequence of DNA strings (sequences containing only the four letters A, C, G, and T). However, you want to catalog them, not in alphabetical order, but rather in order of "sortedness", from "most sorted" to "least sorted". All the strings are of the same length.

Input

The first line contains two integers: a positive integer n ($0 < n \leq 50$) giving the length of the strings; and a positive integer m ($1 < m \leq 100$) giving the number of strings. These are followed by m lines, each containing a string of length n .

Output

Output the list of input strings, arranged from "most sorted" to "least sorted". If two or more strings are equally sorted, list them in the same order they are in the input.

Sample Input

```
10 6
AACATGAAGG
TTTGGCCAA
TTTGGCCAAA
GATCAGATT
CCCGGGGGA
ATCGATGCAT
```

Sample Output

```
CCCGGGGGA
AACATGAAGG
GATCAGATT
ATCGATGCAT
TTTGGCCAA
TTTGGCCAAA
```

Source: East Central North America 1998

[Problem ID in problemset: 1127](#)

[Submit](#) [Back](#) [Runs](#) [Statistics](#) [Clarifications](#)

