



Red Hat AMQ Broker 7.14

Getting Started with AMQ Broker

For Use with AMQ Broker 7.14

Red Hat AMQ Broker 7.14 Getting Started with AMQ Broker

For Use with AMQ Broker 7.14

Legal Notice

Copyright © Red Hat.

Except as otherwise noted below, the text of and illustrations in this documentation are licensed by Red Hat under the Creative Commons Attribution–Share Alike 3.0 Unported license . If you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, the Red Hat logo, JBoss, Hibernate, and RHCE are trademarks or registered trademarks of Red Hat, LLC. or its subsidiaries in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

XFS is a trademark or registered trademark of Hewlett Packard Enterprise Development LP or its subsidiaries in the United States and other countries.

The OpenStack[®] Word Mark and OpenStack logo are trademarks or registered trademarks of the Linux Foundation, used under license.

All other trademarks are the property of their respective owners.

Abstract

This guide describes how to get started using AMQ Broker.

Table of Contents

PREFACE	3
MAKING OPEN SOURCE MORE INCLUSIVE	4
CHAPTER 1. OVERVIEW	5
1.1. KEY FEATURES	5
1.2. SUPPORTED STANDARDS AND PROTOCOLS	5
1.3. SUPPORTED CONFIGURATIONS	5
1.4. DOCUMENT CONVENTIONS	6
1.4.1. The sudo command	6
1.4.2. About the use of file paths in this document	6
1.4.3. Replaceable values	6
CHAPTER 2. UNDERSTANDING AMQ BROKER	7
2.1. BROKER INSTANCES	7
2.2. MESSAGE PERSISTENCE	7
2.2.1. Journal-based persistence	7
2.2.2. Database persistence	7
2.3. RESOURCE CONSUMPTION	8
2.4. MONITORING AND MANAGEMENT	8
CHAPTER 3. INSTALLING AMQ BROKER	10
3.1. DOWNLOADING THE AMQ BROKER ARCHIVE	10
3.2. EXTRACTING THE AMQ BROKER ARCHIVE ON LINUX	10
3.3. EXTRACTING THE AMQ BROKER ARCHIVE ON WINDOWS SYSTEMS	11
3.4. UNDERSTANDING THE AMQ BROKER INSTALLATION ARCHIVE CONTENTS	11
CHAPTER 4. CREATING A STANDALONE BROKER	13
4.1. CREATING A BROKER INSTANCE	13
4.2. STARTING THE BROKER INSTANCE	15
4.3. PRODUCING AND CONSUMING TEST MESSAGES	15
4.4. STOPPING THE BROKER INSTANCE	17
CHAPTER 5. RUNNING THE AMQ BROKER EXAMPLES	19
5.1. SETTING UP YOUR MACHINE TO RUN THE AMQ BROKER EXAMPLES	19
5.1.1. Downloading and installing Maven	19
5.1.2. Downloading and installing the AMQ Maven repository	19
5.1.3. Configuring the Maven settings file	20
5.2. AMQ BROKER EXAMPLE PROGRAMS	21
5.3. RUNNING AN AMQ BROKER EXAMPLE PROGRAM	22
CHAPTER 6. NEXT STEPS	24
APPENDIX A. USING YOUR SUBSCRIPTION	25
APPENDIX B. USING RED HAT MAVEN REPOSITORIES	26
B.1. USING THE ONLINE REPOSITORY	26
B.2. USING A LOCAL REPOSITORY	27

PREFACE

Use this guide to get started with AMQ Broker by installing the software, creating a broker instance, and running example programs.

MAKING OPEN SOURCE MORE INCLUSIVE

Red Hat is committed to replacing problematic language in our code, documentation, and web properties. We are beginning with these four terms: master, slave, blacklist, and whitelist. Because of the enormity of this endeavor, these changes will be implemented gradually over several upcoming releases. For more details, see [our CTO Chris Wright's message](#).

CHAPTER 1. OVERVIEW

AMQ Broker is a high-performance messaging implementation based on Apache Artemis. It uses an asynchronous journal for fast message persistence, and supports multiple languages, protocols, and platforms.

1.1. KEY FEATURES

Review the key features of AMQ Broker, including clustering, high availability, native-IO persistence, and support for XA transactions.

AMQ Broker provides the following features:

- Clustering and high availability options
- Fast, native-IO persistence
- Supports local transactions
- Supports XA transactions when using AMQ Core Protocol JMS and AMQ OpenWire JMS clients
- Written in Java for broad platform support
- Multiple management interfaces: AMQ Management Console, Management APIs, and JMX

1.2. SUPPORTED STANDARDS AND PROTOCOLS

AMQ Broker supports multiple standards and protocols.

AMQ Broker supports the following standards and protocols:

- Wire protocols:
 - Core Protocol
 - AMQP 1.0
 - MQTT
 - OpenWire (Used by A-MQ 6 clients)
 - STOMP
- JMS 2.0



NOTE

The details of distributed transactions (XA) within AMQP are not provided in the 1.0 version of the specification. If your environment requires support for distributed transactions, it is recommended that you use the AMQ Core Protocol JMS.

1.3. SUPPORTED CONFIGURATIONS

Refer to the article "[Red Hat AMQ 7 Supported Configurations](#)" on the Red Hat Customer Portal to view the latest supported configurations for AMQ Broker.

1.4. DOCUMENT CONVENTIONS

This document uses the following conventions for the **sudo** command, file paths, and replaceable values.

1.4.1. The **sudo** command

In this document, **sudo** is used for any command that requires root privileges. You should always exercise caution when using **sudo**, as any changes can affect the entire system.

For more information about using **sudo**, see [Managing sudo access](#).

1.4.2. About the use of file paths in this document

In this document, all file paths are valid for Linux, UNIX, and similar operating systems (for example, **/home/...**). If you are using Microsoft Windows, you should use the equivalent Microsoft Windows paths (for example, **C:\Users\...**).

1.4.3. Replaceable values

This document sometimes uses replaceable values that you must replace with values specific to your environment. Replaceable values are lowercase, enclosed by angle brackets (< >), and are styled using italics and **monospace** font. Multiple words are separated by underscores (_).

For example, in the following command, replace **<install_dir>** with your own directory name.

```
$ <install_dir>/bin/artemis create mybroker
```

CHAPTER 2. UNDERSTANDING AMQ BROKER

AMQ Broker enables you to loosely couple heterogeneous systems together, while providing reliability, transactions, and many other features.

Before you use AMQ Broker, you should understand the capabilities it offers.

2.1. BROKER INSTANCES

A single AMQ Broker installation acts as a home for multiple broker instances. Each instance runs as a unique process with its own configuration and data.

In AMQ Broker, the installed AMQ Broker software serves as a "home" for one or more *broker instances*. This architecture provides several benefits, such as:

- You can create as many broker instances as you require from a single AMQ Broker installation. The AMQ Broker installation contains the necessary binaries and resources that each broker instance needs to run. These resources are then shared between the broker instances.
- When upgrading to a new version of AMQ Broker, you only need to update the software once, even if you are running multiple broker instances on that host.

You can think of a broker instance as a message broker. Each broker instance has its own directory containing its unique configuration and runtime data. This runtime data consists of logs and data files, and is associated with a unique broker process on the host.

2.2. MESSAGE PERSISTENCE

AMQ Broker persists message data to ensure that messages are not lost if the broker fails or shuts down unexpectedly.

AMQ Broker provides two options for message persistence: journal-based persistence and database persistence.

2.2.1. Journal-based persistence

The default method, this option writes message data to message journal files stored on the file system. Initially, each of these journal files is created automatically with a fixed size and filled with empty data. As clients perform various broker operations, records are appended to the journal. When one of the journal files is full, the broker moves to the next journal file.

Journal-based persistence supports transactional operations, including both local and XA transactions.

Journal-based persistence requires an IO interface to the file system. AMQ Broker supports the following:

Linux Asynchronous IO (AIO)

AIO typically provides the best performance. Make sure that your network file system is listed as supported in [Red Hat AMQ 7 Supported Configurations](#).

Java NIO

Java NIO provides good performance, and it can run on any platform with a Java 6 or later runtime.

2.2.2. Database persistence

This option stores message and bindings data in a database by using Java Database Connectivity (JDBC). This option is a good choice if you already have a reliable and high performing database platform in your environment, or if using a database is mandated by company policy.

The broker JDBC persistence store uses a standard JDBC driver to create a JDBC connection that stores message and bindings data in database tables. The data in the database tables is encoded using the same encoding as journal-based persistence. This means that messages stored in the database are not human-readable if accessed directly using SQL.

To use database persistence, you must use a supported database platform. To see the currently supported database platforms, see [Red Hat AMQ 7 Supported Configurations](#).

2.3. RESOURCE CONSUMPTION

You can configure options like resource limits, message paging, and large message support to manage memory and resource consumption on the broker.

Resource limits

You can set connection and queue limits for each user. This prevents users from consuming too many of the broker's resources and causing degraded performance for other users.

Message paging

Message paging enables AMQ Broker to support large queues containing millions of messages while also running with a limited amount of memory. When the broker receives a surge of messages that exceeds its memory capacity, it begins paging messages to disk. This paging process is transparent; the broker pages messages into and out of memory as needed.

Message paging is address-based. When the size of all messages in memory for an address exceeds the maximum size, each additional message for the address will be paged to the address's page file.

Large messages

With AMQ Broker, you can send and receive huge messages, even when running with limited memory resources. To avoid the overhead of storing large messages in memory, you can configure AMQ Broker to store these large messages in the file system or in a database table.

2.4. MONITORING AND MANAGEMENT

You can monitor and manage your brokers using the AMQ Management Console, the CLI, or the Management API via JMX or JMS.

AMQ Management Console

AMQ Management Console is a web interface accessible through a web browser. You can use to monitor network health, view broker topology, and create and delete broker resources.

CLI

AMQ Broker provides the **artemis** CLI, which you can use to administer your brokers. Using the CLI, you can create, start, and stop broker instances. The CLI also provides several commands for managing the message journal.

Management API

AMQ Broker provides an extensive management API. You can use it to modify a broker's configuration, create new resources, inspect these resources, and interact with them. Clients can also use the management API to manage the broker and subscribe to management notifications.

AMQ Broker provides the following methods for using the management API:

- Java Management Extensions (JMX) – JMX is a standard technology for managing Java applications. The broker’s management operations are exposed through AMQ MBeans interfaces.
- JMS API – Management operations are sent using standard JMS messages to a special management JMS queue.

Logs

Each broker instance logs error messages, warnings, and other broker-related information and activities. You can configure the logging levels, the location of the log files, and log format. You can then use the resulting log files to monitor the broker and diagnose error conditions.

CHAPTER 3. INSTALLING AMQ BROKER

Install AMQ Broker by downloading the platform-independent archive and extracting its contents.

3.1. DOWNLOADING THE AMQ BROKER ARCHIVE

AMQ Broker is distributed as a platform-independent archive file. You can download it from the Red Hat Customer Portal.

Prerequisites

- You must have a Red Hat subscription.
For more information, see [Using your Subscription](#).

Procedure

1. In a web browser, navigate to <https://access.redhat.com/downloads/> and log in.
The **Product Downloads** page is displayed.
2. In the **Integration and Automation** section, click the **Red Hat AMQ Broker** link.
The **Software Downloads** page is displayed.
3. Select the AMQ Broker version from the **Version** drop-down menu.
4. On the **Releases** tab, click the **Download** link for the specific AMQ Broker file you want to download.

3.2. EXTRACTING THE AMQ BROKER ARCHIVE ON LINUX

If you are installing AMQ Broker on Red Hat Enterprise Linux, create a new user account for AMQ Broker, and then extract the contents from the installation archive.

Procedure

1. Create a new user named **amq-broker** and provide it a password.

```
$ sudo useradd amq-broker
$ sudo passwd amq-broker
```

2. Create the directory **/opt/redhat/amq-broker** and make the new **amq-broker** user and group the owners of it.

```
$ sudo mkdir /opt/redhat
$ sudo mkdir /opt/redhat/amq-broker
$ sudo chown -R amq-broker:amq-broker /opt/redhat/amq-broker
```

3. Change the owner of the archive to the new user.

```
$ sudo chown amq-broker:amq-broker amq-broker-7.x.x-bin.zip
```


4. Move the installation archive to the directory you just created.

```
$ sudo mv amq-broker-7.x.x-bin.zip /opt/redhat/amq-broker
```

5. As the new **amq-broker** user, extract the contents by using the **unzip** command.

```
$ su - amq-broker
$ cd /opt/redhat/amq-broker
$ unzip <archive_name>.zip
$ exit
```

A directory named something similar to **apache-artemis-2.53.0.redhat-00003** is created. In the documentation, this location is referred to as **<install_dir>**.



NOTE

If you want to rename the default directory that was created when you extracted the broker installation archive, ensure that the new directory name does not contain unicode characters. If the directory name contains unicode characters, the AMQ Management Console is unable to start when you start the broker.

3.3. EXTRACTING THE AMQ BROKER ARCHIVE ON WINDOWS SYSTEMS

If you are installing AMQ Broker on a Windows system, create a new directory folder for AMQ Broker, and then extract the contents to that location on your Windows system.

Procedure

1. Use Windows Explorer to create the directory folder **\redhat\amq-broker** on the desired drive letter.
For example: **C:\redhat\amq-broker**
2. Use Windows Explorer to move the installation archive to the directory you just created.
3. In the **\redhat\amq-broker** directory, right-click the installation archive zip file and select **Extract All**.

A directory named something similar to **apache-artemis-2.53.0.redhat-00003** is created. In the documentation, this location is referred to as **<install_dir>**.



NOTE

If you want to rename the default directory that was created when you extracted the broker installation archive, ensure that the new directory name does not contain unicode characters. If the directory name contains unicode characters, the AMQ Management Console is unable to start when you start the broker.

3.4. UNDERSTANDING THE AMQ BROKER INSTALLATION ARCHIVE CONTENTS

Review the contents of the AMQ Broker installation directory, which includes binaries, configuration files, libraries, and schemas.

The directory created by extracting the archive is the top-level directory for the AMQ Broker installation. This directory is referred to as **<install_dir>**, and includes the following contents:

Table 3.1. Contents of AMQ Broker installation directory

This directory...	Contains...
<code><install_dir>/web/api</code>	API documentation.
<code><install_dir>/bin</code>	Binaries and scripts needed to run AMQ Broker.
<code><install_dir>/etc</code>	Configuration files.
<code><install_dir>/lib</code>	JARs and libraries needed to run AMQ Broker.
<code><install_dir>/schema</code>	XML schemas used to validate AMQ Broker configuration.
<code><install_dir>/web</code>	The web context loaded when AMQ Broker runs.

CHAPTER 4. CREATING A STANDALONE BROKER

You can get started quickly with AMQ Broker by creating a standalone broker instance on your local machine, starting it, and producing and consuming some test messages.

4.1. CREATING A BROKER INSTANCE

A broker instance is a directory that contains the configuration and runtime data for a broker. To create a new broker instance, you first create a directory for the broker instance, and then use the **artemis create** command to create the broker instance.

This procedure demonstrates how to create a simple, standalone broker on your local machine. The broker uses a basic, default configuration, and accepts connections from clients using any of the supported messaging protocols.

Prerequisites

- AMQ Broker must be installed.
For more information, see [Chapter 3, Installing AMQ Broker](#).

Procedure

1. Create a directory for the broker instance.

If you are using...	Do this...
Red Hat Enterprise Linux	1. Create a new directory to serve as the location for the broker instance. <pre>\$ sudo mkdir /var/opt/amq-broker</pre> 2. Assign the user that you created during installation. <pre>\$ sudo chown -R amq-broker:amq-broker /var/opt/amq-broker</pre>
Windows	Use Windows Explorer to create a new folder to serve as the location for the broker instance.

2. Use the **artemis create** command to create the broker.

If you are using...	Do this...
---------------------	------------

If you are using...	Do this...
Red Hat Enterprise Linux	1. Switch to the user account you created during installation. <pre>\$ su - amq-broker</pre> 2. Change to the directory you just created for the broker instance. <pre>\$ cd /var/opt/amq-broker</pre> 3. From the broker instance's directory, create the broker instance. <pre>\$ <install_dir>/bin/artemis create mybroker</pre>
Windows	1. Open a command prompt from the directory you just created for the broker instance. 2. From the broker instance's directory, create the broker instance. <pre>> <install_dir>\bin\artemis.cmd create mybroker</pre>

3. Follow the **artemis create** prompts to configure the broker instance. For example:

```
$ /opt/redhat/amq-broker/bin/artemis create mybroker

Creating Apache Artemis instance at: /var/opt/amq-broker/mybroker

--user: is mandatory with this configuration:
Please provide the default username:
admin

--password: is mandatory with this configuration:
Please provide the default password:

--role: is mandatory with this configuration:
Please provide the default role:
amq

--allow-anonymous | --require-login: is mandatory with this configuration:
Allow anonymous access? (Y/N):
Y

Auto tuning journal ...
done! Your system can make 19.23 writes per millisecond, your journal-buffer-timeout will be
52000
```

4. Start the broker by running the following command:

```
"/var/opt/amq-broker/mybroker/bin/artemis" run
```

Or, you can run the broker in the background using:

```
"/var/opt/amq-broker/mybroker/bin/artemis-service" start
```

4.2. STARTING THE BROKER INSTANCE

After the broker instance is created, you use the **artemis run** command to start it.

Procedure

1. Switch to the user account you created during installation.

```
$ su - amq-broker
```

2. Use the **artemis run** command to start the broker instance.

```
$ /var/opt/amq-broker/mybroker/bin/artemis run
```

[illegible]

Red Hat JBoss AMQ 7.2.1.GA

```
10:53:43,959 INFO [org.apache.activemq.artemis.integration.bootstrap] AMQ101000:
Starting Apache Artemis Server
10:53:44,076 INFO [org.apache.activemq.artemis.core.server] AMQ221000: live Message
Broker is starting with configuration Broker Configuration
(clustered=false,journalDirectory=./data/journal,bindingsDirectory=./data/bindings,largeMessage
sDirectory=./data/large-messages,pagingDirectory=./data/paging)
10:53:44,099 INFO [org.apache.activemq.artemis.core.server] AMQ221012: Using AIO
Journal
...
```

The broker starts and displays log output with the following information:

- The location of the transaction logs and cluster configuration.
- The type of journal being used for message persistence (AIO in this case).
- The URI(s) that can accept client connections.
By default, port 61616 can accept connections from any of the supported protocols (CORE, MQTT, AMQP, STOMP, HORNETQ, and OPENWIRE). There are separate, individual ports for each protocol as well.
- The web console is available at <http://localhost:8161>.
- The Jolokia service (JMX over REST) is available at <http://localhost:8161/jolokia>.

4.3. PRODUCING AND CONSUMING TEST MESSAGES

After you start the broker, verify that the broker is running properly by producing test messages to an address and then consuming them.

Procedure


1. Use the **artemis producer** command to produce a few test messages and send them to the broker.
This command sends 100 messages to the **helloworld** address, which is created automatically on the broker. The producer connects to the broker by using the default port 61616, which accepts all supported messaging protocols.

```
$ /opt/redhat/amq-broker/amq-broker-7.2.0/bin/artemis producer --destination helloworld --
message-count 100 --url tcp://localhost:61616
Producer ActiveMQQueue[helloworld], thread=0 Started to calculate elapsed time ...
```

```
Producer ActiveMQQueue[helloworld], thread=0 Produced: 100 messages
Producer ActiveMQQueue[helloworld], thread=0 Elapsed time in second : 1 s
Producer ActiveMQQueue[helloworld], thread=0 Elapsed time in milli second : 1289 milli
seconds
```

2. Use the web console to see the messages stored in the broker.
 - a. In a web browser, navigate to <http://localhost:8161>.
 - b. Log into the console using the default username and default password that you created when you created the broker instance.
The **Attributes** tab is displayed.
 - c. On the **Attributes** tab, navigate to menu:addresses[helloworld > queues > "anycast" > helloworld].
In the previous step, you sent messages to the **helloworld** address. This created a new anycast **helloworld** address with a queue (also named **helloworld**). The **Message count** attribute shows that all 100 messages that were sent to **helloworld** are currently stored in this queue.

Figure 4.1. Message count



3. Use the **artemis consumer** command to consume 50 of the messages stored on the broker.
This command consumes 50 of the messages that you sent to the broker previously.

```
$ /opt/redhat/amq-broker/amq-broker-7.2.0/bin/artemis consumer --destination helloworld --
message-count 50 --url tcp://localhost:61616
```

```
Consumer:: filter = null
```

```
Consumer ActiveMQQueue[helloworld], thread=0 wait until 50 messages are consumed
```

```
Consumer ActiveMQQueue[helloworld], thread=0 Consumed: 50 messages
```

```
Consumer ActiveMQQueue[helloworld], thread=0 Consumer thread finished
```

4. In the web console, verify that the **Message count** is now 50.
50 of the messages were consumed, which leaves 50 messages stored in the **helloworld** queue.
5. Stop the broker and verify that the 50 remaining messages are still stored in the **helloworld** queue.
 - a. In the terminal in which the broker is running, press kbd:[Ctrl+C] to stop the broker.
 - b. Restart the broker.

```
$ /var/opt/amq-broker/mybroker/bin/artemis run
```

- c. In the web console, navigate back to the **helloworld** queue and verify that there are still 50 messages stored in the queue.
6. Consume the remaining 50 messages.

```
$ /opt/redhat/amq-broker/amq-broker-7.2.0/bin/artemis consumer --destination helloworld --
message-count 50 --url tcp://localhost:61616
```

```
Consumer:: filter = null
```

```
Consumer ActiveMQQueue[helloworld], thread=0 wait until 50 messages are consumed
```

```
Consumer ActiveMQQueue[helloworld], thread=0 Consumed: 50 messages
```

```
Consumer ActiveMQQueue[helloworld], thread=0 Consumer thread finished
```

7. In the web console, verify that the **Message count** is 0.
All of the messages stored in the **helloworld** queue were consumed, and the queue is now empty.

4.4. STOPPING THE BROKER INSTANCE

You can stop the broker instance manually using the **artemis stop** command. This action forcefully closes all client connections.

In a production environment, you should configure the broker to stop gracefully so that client connections can be closed properly.

Procedure

- Use the **artemis stop** command to stop the broker instance:

```
$ /var/opt/amq-broker/mybroker/bin/artemis stop
```

```
2018-12-03 14:37:30,630 INFO [org.apache.activemq.artemis.core.server] AMQ221002:
```

```
Apache Artemis Message Broker version 2.6.1.amq-720004-redhat-1 [b6c244ef-f1cb-11e8-
a2d7-0800271b03bd] stopped, uptime 35 minutes
```

```
Server stopped!
```

■

CHAPTER 5. RUNNING THE AMQ BROKER EXAMPLES

AMQ Broker includes many example programs that demonstrate basic and advanced features of the product. You can run these examples to become familiar with the capabilities of AMQ Broker.

To run the AMQ Broker examples, you must first set up your machine by installing and configuring Apache Maven and the AMQ Maven repository. Then, you use Maven to run the AMQ Broker example programs.

5.1. SETTING UP YOUR MACHINE TO RUN THE AMQ BROKER EXAMPLES

Before you can run the included AMQ Broker example programs, you must first download and install Maven and the AMQ Maven repository, and configure the Maven settings file.

5.1.1. Downloading and installing Maven

Download and install the latest Apache Maven distribution for your operating system to run the AMQ Broker examples.

Procedure

1. Go to the [Apache Maven Download page](#) and download the latest distribution for your operating system.
2. Install Maven for your operating system.
For more information, see [Installing Apache Maven](#).

Additional resources

- [Introduction to Apache Maven](#)

5.1.2. Downloading and installing the AMQ Maven repository

After Maven is installed on your machine, you download and install the AMQ Maven repository. This repository is available on the Red Hat Customer Portal.

Procedure

1. In a web browser, navigate to <https://access.redhat.com/downloads/> and log in.
The **Product Downloads** page is displayed.
2. In the **Integration and Automation** section, click the **Red Hat AMQ Broker** link.
The **Software Downloads** page is displayed.
3. Select the desired AMQ Broker version from the **Version** drop-down menu.
4. On the **Releases** tab, click the **Download** link for the AMQ Broker Maven Repository.
The AMQ Maven repository file is downloaded as a zip file.
5. On your machine, unzip the AMQ repository file into a directory of your choosing.
A new directory is created on your machine, which contains the Maven repository in a subdirectory named **maven-repository/**.

5.1.3. Configuring the Maven settings file

After downloading and installing the AMQ Maven repository, you must add the repository to the Maven settings file.

Procedure

1. Open the Maven **settings.xml** file.
The **settings.xml** file is typically located in the **\${user.home}/.m2/** directory.

- For Linux, this is **~/.m2/**
- For Windows, this is **\Documents and Settings\.m2** or **\Users\.m2**

If you do not find a **settings.xml** file in **\${user.home}/.m2/**, there is a default version located in the **conf/** directory of your Maven installation. Copy the default **settings.xml** file into the **\${user.home}/.m2/** directory.

2. In the **<profiles>** element, add a profile for the AMQ Maven repository.

```
<!-- Configure the JBoss AMQ Maven repository -->
<profile>
  <id>jboss-amq-maven-repository</id>
  <repositories>
    <repository>
      <id>jboss-amq-maven-repository</id>
      <url>file://<JBoss-AMQ-repository-path></url> //
      <releases>
        <enabled>true</enabled>
      </releases>
      <snapshots>
        <enabled>>false</enabled>
      </snapshots>
    </repository>
  </repositories>
  <pluginRepositories>
    <pluginRepository>
      <id>jboss-amq-maven-repository</id>
      <url>file://<JBoss-AMQ-repository-path></url> //
      <releases>
        <enabled>true</enabled>
      </releases>
      <snapshots>
        <enabled>>false</enabled>
      </snapshots>
    </pluginRepository>
  </pluginRepositories>
</profile>
```

Replace **<JBoss-AMQ-repository-path>** with the location of the Maven repository that you installed. Typically, this location ends with **/maven-repository**. For example:

```
<url>file:///path/to/repo/amq-broker-7.2.0-maven-repository/maven-repository</url>
```

3. In the **<activeProfiles>** element, set the AMQ Maven repository to be active:


```

<activeProfiles>
  <activeProfile>jboss-amq-maven-repository</activeProfile>
  ...
</activeProfiles>

```

4. If you copied the default **settings.xml** from your Maven installation, uncomment the **<active-profiles>** section if it was commented out by default.
5. Save and close **settings.xml**.
6. Remove the cached **\${user.home}/.m2/repository/** directory.
If your Maven repository contains outdated artifacts, you may encounter one of the following Maven error messages when you build or deploy your project:

- **Missing artifact <artifact-name>**
- **[ERROR] Failed to execute goal on project <project-name>; Could not resolve dependencies for <project-name>**

5.2. AMQ BROKER EXAMPLE PROGRAMS

Explore the provided example programs to learn about broker-specific features like clustering and HA, as well as supported messaging protocols.

To find the example programs, see [AMQ Broker example programs](#). The examples include the following:

- **Features**
Broker-specific features such as:
 - Clustered - examples showing load balancing and distribution capabilities
 - HA - examples showing failover and reconnection capabilities
 - Perf - examples allowing you to run a few performance tests on the server
 - Standard - examples demonstrating various broker features
 - Sub-modules - examples of integrated external modules
- **Protocols**
Examples for each of the supported messaging protocols:
 - AMQP
 - MQTT
 - OpenWire
 - STOMP

Additional resources

- [Examples](#)

5.3. RUNNING AN AMQ BROKER EXAMPLE PROGRAM

Example programs for AMQ Broker demonstrate basic and advanced features of the product. You use Maven to run these programs.

Prerequisites

- Your machine is set up to run the AMQ Broker examples.
For more information, see [Section 5.1, "Setting up your machine to run the AMQ Broker examples"](#).
- You downloaded the [AMQ Broker example programs](#).

Procedure

1. Navigate to the directory of the example that you want to run. The following example assumed that you downloaded the examples to a directory called **amq-broker-examples**.

```
$ cd amq-broker-examples/examples/features/standard/queue
```

2. Use the **mvn clean verify** command to run the example program.
Maven starts the broker and runs the example program. The first time you run the example program, Maven downloads any missing dependencies, which may take a while to run.

In this case, the **queue** example program is run, which creates a producer, sends a test message, and then creates a consumer that receives the message:

```
$ mvn clean verify
[INFO] Scanning for projects...
[INFO]
[INFO] -----< org.apache.activemq.examples.broker:queue >-----
[INFO] Building Apache Artemis JMS Queue Example 2.6.1.amq-720004-redhat-1
[INFO] -----[ jar ]-----
...
server-out:2018-12-05 16:37:57,023 INFO [org.apache.activemq.artemis.core.server]
AMQ221001: Apache Artemis Message Broker version 2.6.1.amq-720004-redhat-1 [0.0.0.0,
nodeID=06f529d3-f8d6-11e8-9bea-0800271b03bd]
[INFO] Server started
[INFO]
[INFO] --- artemis-maven-plugin:2.6.1.amq-720004-redhat-1:runClient (runClient) @ queue --
-
Sent message: This is a text message
Received message: This is a text message
[INFO]
[INFO] --- artemis-maven-plugin:2.6.1.amq-720004-redhat-1:cli (stop) @ queue ---
server-out:2018-12-05 16:37:59,519 INFO [org.apache.activemq.artemis.core.server]
AMQ221002: Apache Artemis Message Broker version 2.6.1.amq-720004-redhat-1
[06f529d3-f8d6-11e8-9bea-0800271b03bd] stopped, uptime 3.734 seconds
server-out:Server stopped!
[INFO] -----
[INFO] BUILD SUCCESS
[INFO] -----
[INFO] Total time: 48.681 s
[INFO] Finished at: 2018-12-05T16:37:59-05:00
[INFO] -----
```



NOTE

Some of the example programs use UDP clustering, and may not work in your environment by default. To run these examples successfully, redirect traffic directed to 224.0.0.0 to the loopback interface:

```
$ sudo route add -net 224.0.0.0 netmask 240.0.0.0 dev lo
```

CHAPTER 6. NEXT STEPS

After you install AMQ Broker and create a standalone broker with the default configuration settings, you can configure it to meet your messaging requirements, connect messaging client applications to it, and monitor and manage it.

Configuring the broker

Use [Configuring AMQ Broker](#) to configure the broker to meet your requirements. You can configure:

- The broker to accept client connections
- The address space (including point-to-point and publish-subscribe messaging)
- Message persistence
- Broker resource consumption (including resource limits, message paging, and large message support)
- Duplicate message detection
- Logging

Securing the broker

Use [Configuring AMQ Broker](#) to implement any of the following methods to secure the broker:

- Guest/anonymous access control
- Basic user and password access control
- Certificate-based access control
- LDAP integration
- Kerberos integration

Setting up clustering and high availability

Use [Configuring AMQ Broker](#) to add additional brokers to form a broker cluster and increase messaging throughput. You can also configure high availability to increase messaging reliability.

Creating messaging client applications

Use [AMQ Clients Overview](#) to learn about AMQ Clients and how it can help you to create messaging client applications that connect to the broker and produce and consume messages.

Monitoring and managing the broker

Use [Managing AMQ Broker](#) to monitor and manage your broker (or brokers) once they are running.

APPENDIX A. USING YOUR SUBSCRIPTION

AMQ is provided through a software subscription. To manage your subscriptions, access your account at the Red Hat Customer Portal.

Procedure

1. To access your account, complete the following steps:
 - a. Go to access.redhat.com.
 - b. If you do not already have an account, create one.
 - c. Log in to your account.
2. To activate a subscription, complete the following steps:
 - a. Go to access.redhat.com.
 - b. Navigate to **My Subscriptions**.
 - c. Navigate to **Activate a subscription** and enter your 16-digit activation number.
3. To access .zip, .tar.gz, and other release files, use the Customer Portal to find the relevant files for download. If you are using RPM packages or the Red Hat Maven repository, this step is not required.
 - a. Open a browser and log in to the Red Hat Customer Portal **Product Downloads** page at access.redhat.com/downloads.
 - b. Locate the **Red Hat AMQ** entries in the **INTEGRATION AND AUTOMATION** category.
 - c. Select the required AMQ product. The **Software Downloads** page opens.
 - d. Click the **Download** link for your component.
4. To install RPM packages for this product on Red Hat Enterprise Linux, complete the following steps to register your system. If you are using downloaded release files, this step is not required.
 - a. Go to access.redhat.com.
 - b. Navigate to **Registration Assistant**.
 - c. Select your OS version and continue to the next page.
 - d. Use the listed command in your system terminal to complete the registration.

Additional resources

- [Red Hat Enterprise Linux 8 - Registering the system and managing subscriptions](#)
- [Red Hat Enterprise Linux 9 - Registering the system and managing subscriptions](#)

APPENDIX B. USING RED HAT MAVEN REPOSITORIES

You can configure your software to use either the online Red Hat Maven repository or a locally extracted file-based repository.

B.1. USING THE ONLINE REPOSITORY

Add the Red Hat online Maven repository to your Maven settings to use it with your projects.

If you add the repository to your Maven settings, that configuration applies to all Maven projects owned by your user, as long as POM file does not override the repository configuration and the included profile is enabled.

Procedure

1. Locate the Maven **settings.xml** file. It is usually inside the **.m2** directory in the user home directory. If the file does not exist, use a text editor to create it.
On Linux or UNIX:

```
/home/<username>/.m2/settings.xml
```

On Windows:

```
C:\Users\<username>\.m2\settings.xml
```

2. Add a new profile containing the Red Hat repository to the **profiles** element of the **settings.xml** file, as shown in the following example:

```
<settings>
  <profiles>
    <profile>
      <id>red-hat</id>
      <repositories>
        <repository>
          <id>red-hat-ga</id>
          <url>https://maven.repository.redhat.com/ga</url>
          <releases>
            <enabled>true</enabled>
          </releases>
          <snapshots>
            <enabled>false</enabled>
          </snapshots>
        </repository>
      </repositories>
      <pluginRepositories>
        <pluginRepository>
          <id>red-hat-ga</id>
          <url>https://maven.repository.redhat.com/ga</url>
          <releases>
            <enabled>true</enabled>
          </releases>
          <snapshots>
            <enabled>false</enabled>
          </snapshots>
        </pluginRepository>
      </pluginRepositories>
    </profile>
  </profiles>
</settings>
```

```

    </pluginRepository>
  </pluginRepositories>
</profile>
</profiles>
<activeProfiles>
  <activeProfile>red-hat</activeProfile>
</activeProfiles>
</settings>

```

For more information about Maven configuration, see the [Maven settings reference](#).

B.2. USING A LOCAL REPOSITORY

Configure Maven to use a locally extracted repository by defining the file URL in your Maven settings or POM file.

Procedure

1. To configure Maven to use a locally extracted repository, apply the following XML in your Maven settings or POM file:

```

<repository>
  <id>red-hat-local</id>
  <url>${repository-url}</url>
  <releases>
    <enabled>true</enabled>
  </releases>
  <snapshots>
    <enabled>false</enabled>
  </snapshots>
</repository>
<pluginRepository>
  <id>red-hat-local</id>
  <url>${repository-url}</url>
  <releases>
    <enabled>true</enabled>
  </releases>
  <snapshots>
    <enabled>false</enabled>
  </snapshots>
</pluginRepository>

```

`${repository-url}` must be a file URL containing the local filesystem path of the extracted repository.

Table B.1. Example URLs for local Maven repositories

Operating system	Filesystem path	URL
Linux or UNIX	<code>/home/alice/maven-repository</code>	<code>file:/home/alice/maven-repository</code>

Operating system	Filesystem path	URL
Windows	C:\repos\red-hat	file:C:\repos\red-hat

Revised on 2026-04-16 16:31:06 UTC