Hydraulically feasible regeneration-reserve-aware hydrogen pressure swing adsorption under uncertainty with staged membrane polishing and a quantum-ready probability event

Ugwiyeon Lee*, Seong-Yun Bae, Hakrae Kim, Jungsu Lee

Korea Gas Safety Corporation, 1390 Wonjung-ro, Maengdong-myeon, Eumseong-gun, Chungcheongbuk-do 27738, Republic of Korea

* Corresponding author: lyullee@kgs.or.kr; ORCID 0009-0008-8976-5363

Abstract

Hydrogen pressure swing adsorption must retain product gas for the next purge and repressurization steps before gas can be sold. This work formulates that allocation as a continuous qualified-shipment problem and enforces pressure feasibility between a four-bed PSA, a finite regeneration tank, valves, and a polishing train. A pressure audit showed that the preliminary 7.0 bar tank could not be passively refilled from a 6.2 bar product manifold. The corrected topology therefore uses a 6.0 bar regulated tank, a 0.2 bar fill driving margin, and a discharge booster to the 6.5 bar regeneration header. Within declared feed, adsorption-equilibrium, and kinetic uncertainty, the selected policy of 4 s active purge and 540 s adsorption passed all eight corner cases and all eight predeclared interior hold-outs; a 6 s, 480 s comparison passed none. Specification-qualified hydrogen shipment increased by 6.785-7.341%, the minimum reserve-margin gain was 0.542 bar, and conservative booster duty remained below 0.198 kWh kg-1 H2. A literature-parameterized polymer concentrator followed by dense palladium polishing passed all 16 direct cases. Adaptive DOP853 integration corrected a near-boundary 20%-permeance-loss guard from 0.553 to 0.554 m2; the revised design gave at least 88.322% recovery and maximum CO, CO2, N2, and CH4 contents of 0.121, 4.000, 48.83, and 25.07 ppm. A public actual-syngas 50%-permeance-retention stress increased the conditional installed area to 0.887 m2 and retained all 16 cases. A separately coded fixed-area RK4 solver reproduced all 32 design-case labels, with a maximum recovery difference below 9.4e-8 percentage point relative to DOP853. A corrected DWSIM 8.7.1 Peng-Robinson calculation solved all 16 horizon-averaged cases at the 6.2 bar inlet, with maximum component-balance error 8.95e-19 mol s-1 and compression demand of 3.091-3.183 kWh kg-1 H2. For a 0.440 m2 chance design, error-buffered trilinear integration gave a minimum scrambled-Sobol probability of 0.956673; a conservative affine event gave 0.951210, and its 10-bit discretization gave 0.950629 with no direct label errors. An exact portable OpenQASM 3 oracle uses 66 logical qubits, 24,042 CX gates, 61,269 primitive gates, and all-to-all depth 36,163 before optimization or routing. Exhaustive 2-, 3-, and 4-bit checks plus direct and random 10-bit checks gave zero phase-label and work-qubit-restoration errors. An exact seven-qubit Boolean compilation of the final event at two-bit-per-variable resolution was then run on IBM Kingston for all 64 input states at 256 shots per state. All 64 states were majority-correct, the mean expected-label probability was 0.8389, and the job used 7 QPU s. For this smooth three-variable event, randomized quasi-Monte Carlo remains the practical estimator. The contribution is a pressure-consistent separation design rule, an auditable process-to-oracle construction, and a device-level truth-mapping test of the final event for future higher-dimensional plant uncertainty.

Keywords: Hydrogen purification; Pressure swing adsorption; Regeneration tank; Membrane polishing; Chance constraint

Highlights

- A 6.0 bar regeneration tank is passively filled from the 6.2 bar product manifold
- A discharge booster closes the hydraulic path to the 6.5 bar regeneration header
- The selected 4 s purge and 540 s adsorption policy passes 8/8 corners and 8/8 hold-outs
- Qualified hydrogen shipment rises by 6.785-7.341% over the comparison policy

- A 0.554 m2 Pd guard passes all 16 cases at 20% permeance loss
- A 0.887 m2 conditional guard covers a public 50% actual-syngas loss stress
- Independent RK4 reproduces all 32 adaptive-integrator decisions
- Corrected DWSIM Peng-Robinson calculations solve all 16 process cases
- A verified 66-qubit OpenQASM oracle connects the process chance constraint to QAE
- A final-event IBM QPU probe classifies all 64 two-bit states correctly by majority vote

1 Introduction

High-purity hydrogen is required by chemical, metallurgical, energy-storage, and fuel-cell systems. Pressure swing adsorption (PSA) is attractive because selective adsorption and pressure cycling can remove carbon dioxide, methane, carbon monoxide, and nitrogen without a continuously regenerated solvent. The industrial design problem is nevertheless more complicated than maximizing purity or recovery at one outlet. Product hydrogen also performs internal work: it purges low-pressure beds, repressurizes beds before adsorption, and maintains a product or equalization inventory that couples one bed to the others. If this inventory is represented as an unlimited source, a simulated cycle can sell gas that the real plant must retain for its next cycle.

Dynamic PSA optimization has addressed cycle scheduling, adsorbent selection, control, and uncertainty [1-8]. These studies establish that pressure equalization, purge, adsorption duration, valve conductance, and feed composition interact strongly. They also show why cyclic steady state, component conservation, and direct validation matter. However, regeneration demand is often embedded in boundary conditions or reported separately from the product available for shipment. For variable feed and aging adsorbent, the practical question is therefore not simply which cycle gives the highest hydrogen recovery. It is which continuous operating policy preserves regeneration inventory and simultaneously maximizes hydrogen that satisfies a strict product specification.

A second difficulty appears when the PSA outlet is close to, but does not by itself meet, a multi-impurity hydrogen specification. A membrane polishing stage can increase purity, yet a single membrane must trade recovery against contaminant rejection. Published pilot and staged studies support palladium-alloy durability and the value of pre-concentration, but they do not jointly report all impurity limits used here [9-13]. A defensible model must therefore expose permeance loss, finite selectivity, receiver dynamics, and defect leakage as acceptance conditions instead of assigning a perfect final purity.

Uncertainty adds a third layer. A robust design that passes every bounded case can be larger than necessary, whereas a chance-constrained design accepts a declared small failure region. Estimating that probability links separation engineering to Monte Carlo, randomized quasi-Monte Carlo (RQMC), and quantum amplitude estimation (QAE). QAE can offer a quadratic query advantage for idealized amplitude access [14-17], but state preparation, reversible process arithmetic, and model error can remove that advantage. A process application is useful only when the probability event preserves the engineering decision and its circuit cost is reported.

This study combines a pressure-consistent four-bed PSA, finite regeneration inventory, staged membrane polishing, uncertainty propagation, and a quantum-ready chance event. The model is checked against a public four-bed hydrogen VPSA experiment [8], 468 public Pd-Ag H2/N2 flux records [22], high-pressure and mixed-gas palladium studies [23-29], and an integrated membrane-reactor/PSA study [30]. Adaptive DOP853 and separately coded fixed-area RK4 calculations test numerical sensitivity. The final event is serialized as a full portable arithmetic oracle, and its exact two-bit Boolean reduction is tested over every input on an IBM QPU. The contribution is an engineering operating rule and a reproducible probability event with device-level truth-mapping evidence; present quantum advantage and direct certification of the integrated apparatus are outside the claim.

2 Problem definition

The process boundary begins at a multicomponent hydrogen-rich PSA feed and ends at a finite product receiver. Four adsorbers follow a staggered adsorption, equalization, blowdown, purge, and repressurization schedule. Product

gas first supplies simultaneous internal demand. Remaining gas reaches a 6.2 bar product manifold and passively refills a tank regulated to 6.0 bar. Tank withdrawal is boosted to the 6.5 bar purge and repressurization header. Only surplus product proceeds to polishing and sale.

The primary objective is time-averaged specification-qualified hydrogen delivered from the receiver. The operating-policy screen requires hydrogen fraction at least 0.9997; CO, CO2, N2, and CH4 no greater than 0.5, 5, 300, and 100 ppm; qualified hydrogen at least 0.002 mol s-1; positive regeneration reserve; passive tank-fill margin; bounded booster duty; cyclic convergence; trace integrity; and component conservation. The final physical membrane design additionally freezes recovery and shipment floors of 0.882940 and 0.0022631 mol s-1.

Both policies use a 6.0 bar tank set point. The comparison uses 6 s active purge and a 480 s adsorption stage; the selected policy uses 4 s and 540 s. Physical decisions include polymer and dense-palladium areas, surge capacity, receiver capacity, and regeneration-booster duty. Uncertainty coordinates cover a feed-hydrogen multiplier of 0.95-1.05, paired adsorption capacity-affinity endpoints, and an LDF kinetic multiplier of 0.8-1.2. Their eight endpoint combinations form the engineering cube; eight interior points were declared before the corrected design calculation.

Two design meanings are kept separate. A fully robust design passes every declared direct case. A 95% chance design passes under an independent uniform engineering measure over the declared cube after shifting the event boundary by the largest error on the predeclared interiors. This measure is a transparent design convention; it is not presented as a plant-calibrated probability distribution.

3 Methods

3.1 Dynamic PSA tank valve and bed model

Each bed is discretized axially and advanced through the staggered cycle with component inventories, competitive equilibrium, LDF uptake, valve-driven flows, and a non-isothermal energy balance. The tank follows component inventory and ideal-gas pressure. A separate hydraulic audit enforces the 6.2-to-6.0 bar passive-fill direction and computes isothermal booster work from the instantaneous tank pressure to the 6.5 bar header at 72% efficiency. Six axial cells and 60 cycles are used for direct decisions, with cyclic-state, trace-integrity, and component-balance gates.

The source model was separately reconstructed for the public Wang et al. four-bed, 12-step H2/CH4/N2/CO2 VPSA apparatus [8]. Published geometry, activated-carbon equilibrium, partial-pressure LDF kinetics, heat effects, step schedule, and experimental breakthrough and pressure data were used. This cross-validation tests reusable conservation, pressure-network, adsorption, and thermal implementations. Because the final process uses a different adsorbent, pressure range, and downstream membrane, it does not directly validate the final apparatus.

3.2 Polishing train and finite receivers

Surplus PSA product is compressed from the 6.2 bar manifold to a 20 bar surge buffer and cooled to 298.15 K. A polymer concentrator operates at 20/1 bar. Its permeate is recompressed in three equal-pressure-ratio stages to a dense-palladium stage at 20/1 bar and 693.15 K. Both retentates go to fuel or off-gas, and no internal recycle is credited. The ideal-train screen uses a 4.616 mol surge buffer and a 1.546 mol product receiver; guard-banded finite-selectivity designs co-size the receiver again.

Membrane transfer is evaluated for every saved time packet. The production calculation uses fixed area sections; the independent audit solves the same transfer laws with scipy DOP853 at relative and absolute tolerances of 1e-9 and 1e-13. A second implementation uses classical fourth-order Runge-Kutta over 48, 96, and 192 equal-area sections and does not call the adaptive solver. Exact component ledgers are retained across both membranes and the finite receiver.

The dense-palladium guard imposes finite effective H2/impurity selectivities, hydrogen-permeance loss, and an H2-equivalent Knudsen defect-conductance ratio. This ratio compares local defect H2 transfer with dense-palladium H2 transfer and is not a geometric pinhole fraction. Continuous receiver quality, inventory, recovery, shipment, and mass balance are checked for all eight corners and eight hold-outs.

3.3 Robust and chance-constrained calculations

The two operating policies are paired at all eight uncertainty corners. The corrected selected policy is then tested on the eight predeclared interiors. The membrane-area chance calculation fits a trilinear response to the corners, measures its largest absolute error on the predeclared interiors, and shifts the event boundary by that error. Eight independent scrambled Sobol integrations estimate probability under an explicitly uniform engineering measure.

3.4 Process probability oracle

Installed dense-palladium area is the physical design coordinate. At 0.440 m2, 13 of 16 direct stress cases pass while the continuous chance probability exceeds 0.95. A conservative affine event is checked against every direct label and digitized with 10 qubits for each of three uncertainty coordinates. Reversible signed accumulation and comparison require 66 logical qubits. The circuit follows source-equivalent weighted-adder and two's-complement comparator constructions and is expanded exactly to OpenQASM 3 using X, H, T, Tdg, Z, and CX. Its portable unoptimized resources are 24,042 CX gates, 61,269 total primitive gates, and all-to-all depth 36,163. These counts exclude device routing, error correction, and hardware calibration. For a device-level unit test tied to the same final affine inequality, each uncertainty coordinate is also digitized with two bits. The resulting 64-state event is compiled exactly from the failing complement into three disjoint Boolean cubes, reducing the basis-state truth-mapping test from a 42-qubit arithmetic realization to six input qubits and one flag. Both initial flag values are checked locally over all 128 reversible basis mappings. All 64 zero-flag input states are then transpiled at optimization level 3 and measured with 256 shots per state on the free IBM Open Plan. This compact compilation preserves the two-bit truth table but does not perform coherent amplitude estimation.

3.5 Independent thermodynamic and numerical checks

Compression is recalculated from the corrected 6.2 bar product manifold to the 20 bar polishing buffer and from the 1 bar polymer permeate to the 20 bar palladium feed. The corrected 16-case deck was executed in DWSIM 8.7.1 with the Peng-Robinson property package, a 72% efficient first compressor, and three equal-pressure-ratio intercooled recompression stages. Windows Application Control blocked the distributed file-storage assembly only; a syntax-equivalent local rebuild from the official v8.7.1 source was preloaded, while the thermodynamic and unit-operation assemblies remained unchanged. DWSIM receives horizon-averaged component split fractions from the packet-resolved Python membrane model, so this is an independent pressure, duty, thermodynamic-state, and material-closure check rather than an independent membrane-transport calculation.

The independent RK4 implementation evaluates the frozen polymer solution-diffusion and finite-selectivity palladium equations at 48, 96, and 192 area sections. It covers the 0.554 m2, 80%-retention guard and the 0.887 m2, 50%-retention actual-syngas stress over all 16 direct cases. This isolates numerical implementation and mesh sensitivity while retaining the same constitutive laws.

A separate external-data calculation reconstructs the Ververs et al. tubular Pd-Ag experiment [22]. The implementation uses their axial H2 and N2 balances, Richardson parameters for 0.150, 0.300, and 0.467 m membranes, stagnant-film equation, 64 mm annular hydraulic diameter, and local correlation Sh=1.846Gz^0.60. H2-N2 diffusivity is calculated independently with the Fuller correlation, and 96, 192, and 384-section RK4 meshes are compared. No mixture-flux parameter is fitted. The downloaded workbook contains 468 numeric records, 45 more than the 423 stated in the article; all public records are retained without undocumented filtering.

3.6 High-pressure inhibition transfer and hot-stage audit

Boon et al. reported 105 randomized inhibition tests at 22 bar retentate pressure, 2 bar permeate pressure, 350-450 C, 50-70% H2, and up to 2% CO [23]. Their published linear regression, eta=1-KCO<pCO>-KH2O<pH2O>, is applied without refitting. Because the present design feed is dry, the steam term is set to zero. The arithmetic uses the average CO partial pressure between each palladium feed and retentate and evaluates both the central 420 C coefficient and its upper 95% uncertainty limit. This transfer tests whether the installed-area guards cover measured high-pressure inhibition; it does not validate impurity leakage.

The corrected DWSIM calculation establishes the 6.2-to-20 bar compression, three-stage recompression, intercooling, and component closure at 298.15 K. An earlier hot-stage calculation additionally documents a 420 C palladium heater and coolers for the preceding input set; its heat-integration numbers are retained only as structural evidence. Published 22-26 bar palladium inhibition and endurance studies [23,24] independently define the high-temperature evidence boundary.

3.7 Public selectivity transfer and module acceptance threshold

The 0.887 m2 design is replayed while one effective impurity selectivity is reduced and the others remain fixed. Logarithmic bisection finds the lowest value preserving all 16 events; a 25% simultaneous margin and upward rounding form an incoming-module screen. Li et al. [25] and DOE/MPT [26] provide public high-pressure and defect-leakage stresses, respectively, and are used as transfer and rejection controls rather than matched certification.

3.8 Independent full-syngas bench evidence and analytical-resolution audit

Sanchez et al. tested a 0.01216 m2 precommercial Pd membrane in a bench facility with feed, retentate, and permeate slipstreams analysed by gas chromatography [27]. Their synthetic unconverted-shift gas contained 17% H2, 19% CO, 7% CO2, and 57% steam and was tested at 593-723 K and 0.15-1.0 MPa. Reported TCD accuracy was 0.01 vol% (about 100 ppm). The present audit therefore uses the experiment as a multicomponent feasibility, inhibition-direction, permeance, and recovery anchor, but does not translate the paper's 'pure hydrogen' wording into certification of the present 0.5 ppm CO or 5 ppm CO2 limits.

3.9 Synchronized mixed-gas rejection control

The DOE/Pall FY 2008 report provides feed, retentate, and permeate flow and composition for a Pd90Au10 membrane at 400 C, 62 psia feed, 12 psia permeate, and 50 psi pressure difference [28]. The feed contained 51% H2, 26% CO2, 21% steam, and 2% CO. The observed permeate contained 99.95% H2, 450 ppm CO2, and 75 ppm CO. H2 recovery is calculated directly as 775/1020=75.98%. System-level H2/CO and H2/CO2 separation factors are calculated from the reported feed and permeate mole fractions and transferred to the 0.887 m2 design while N2 and CH4 remain at their selected values. Because the factors include wet-mixture, support, film, and defect effects, this is an empirical rejection stress rather than an intrinsic-permeability fit.

3.10 Positive high-recovery and actual coal-gas validation anchors

The DOE/UTRC final report describes a pilot-scale approximately 0.139 m2 Pd-Cu separator [29]. Its durability feed contained 75% H2, 1% CO, 5% CO2, 19% H2O, and 1.65 ppmv H2S. At 500.8 +/- 10.6 C and 184.7 +/- 7.8 psig, the separator produced 2.36 +/- 0.20 lb day-1 H2 at 93.4 +/- 8.0% recovery for about 1,300 h. Before a small leak began at 2,624 h, the report assigned 99.9999% H2 purity from the ideal H2/N2 separation factor; this corresponds to about 1 ppm total non-H2 but is not component-resolved analysis. A separate 77 h actual coal-gas test measured 2.43 lb day-1 and 74.3% recovery, compared with frozen-model predictions of 2.32 lb day-1 and 70.1%. These records are used as positive recovery, bulk-purity, durability, and model-transfer anchors. They are not treated as direct certification of the final 20-bar five-component product.

3.11 Integrated CMR-PSA joint-gate bracket

Bang et al. integrated a Pd-Cu water-gas-shift catalytic membrane reactor with activated-carbon/zeolite four-bed PSA [30]. The CMR was experimentally operated with a CO/H2/CO2 feed of 65:30:5 vol%, steam/carbon ratios of 1-5, 360-380 C, 6-10 bar, and H2 sweep. The public record used here does not establish the complete four-bed PSA output as an independently measured dataset, so the two overall results are treated as published integrated-process operating points. The high-recovery point gave 91.37% H2 recovery, more than 99.9991% H2, and 8.67 ppm CO. The low-CO point gave 85.99% recovery and 0.15 ppm CO. Each point is compared separately with the frozen 88.294% recovery floor and 0.5 ppm CO limit. This creates a literature bracket of the conjunction used by the process oracle; it is not a fit to the present model or direct validation of the final apparatus.

3.12 Blind third-language membrane-transport replay

A compiled C# packetwise implementation was previously used to verify the independent transport method on the preceding input set. The regenerated 6.0 bar train was not replayed because native execution is restricted on the current host. Its figure is retained to document the third-language method, but the current pressure-consistent claims rely on direct six-cell integration, DOP853, and the newly rerun Python RK4 calculation.

4 Results

4.1 Regeneration reserve changes the operating decision

The pressure audit rejected the preliminary 7.0 bar tank because the 6.2 bar product manifold could not fill it passively. With the corrected 6.0 bar tank and discharge booster, the 6 s/480 s comparison failed all eight corners whereas the 4 s/540 s policy passed all eight. Qualified shipment increased by 6.785-7.341%, minimum reserve margin improved by at least 0.542 bar, and the selected conservative booster duty was no greater than 0.197 kWh kg-1 qualified H2. The maximum cyclic-state residual and relative cycle balance error were 1.225e-5 and 1.661e-5.

Table 1. Pressure-consistent operating decision

Decision	Comparison	Selected	Evidence
Tank set point	6.0 bar	6.0 bar	6.2 bar manifold
Active purge	6 s	4 s	8 corners
Adsorption stage	480 s	540 s	60 cycles
Joint pass	0/8	8/8	Direct model
Predeclared hold-out	-	8/8	Independent interiors
Qualified H2 gain	Reference	6.785-7.341%	Paired cases
Maximum booster duty	-	0.197 kWh kg-1	6.5 bar discharge




Figure 1. Pressure-consistent operating-policy comparison across the complete eight-corner uncertainty cube. Both policies use a 6.0 bar tank; the selected 4 s/540 s schedule preserves reserve and increases qualified shipment.

4.2 Direct hold-out and continuous chance design

All eight predeclared interior conditions passed the corrected six-cell, 60-cycle calculation. Their minimum tank pressure was 3.546 bar, minimum reserve margin was 2.746 bar, maximum N2 was 227.24 ppm, and maximum booster duty was 0.194 kWh kg-1. All passive-fill, trace-integrity, cyclic-state, and mass-balance gates passed. The separate physical-area chance event at 0.440 m2 gave a minimum scrambled-Sobol probability of 0.956673 after hold-out buffering.




Figure 2. Eight predeclared interior hold-outs for the corrected 6.0 bar tank and discharge-booster topology.

4.3 Public dynamic experiment checks transferable model physics

The source-specific Wang reconstruction reproduced multicomponent half-feed breakthrough times with a maximum absolute relative error of 11.37%, composition curves with a maximum species RMSE of 0.0229 mole fraction, and temperature traces with a maximum sensor RMSE of 2.37 C. Four cyclic pressure levels had an RMSE of 0.0666 bar. At engineering cyclic steady state, Run XII recovery differed from experiment by -0.666 percentage point, whereas eight-cell purity was underpredicted by 2.037 percentage points. The comparison supports the model family and its ledgers while preserving a clear apparatus-transfer boundary.

Table 2. Evidence hierarchy

Evidence	Result	Supported claim	Boundary
Uncertainty corners	8/8 selected pass	Robust policy	Declared cube
Predeclared interiors	8/8 pass	Hold-out transfer	Finite sample
Wang experiment	11.37% max breakthrough error	Dynamic model family	Different apparatus
Adaptive ODE	0.554 m2 passes 16/16	Numerical guard	Same transport laws
Independent RK4	32/32 labels agree	Implementation robustness	Same constitutive laws
Ververs data	468 flux records	Concentration polarization	Binary 2-5 bar
Public Pd studies	pressure, aging, rejection anchors	Feasibility envelope	Unmatched modules
Corrected DWSIM	16/16 solved	Pressure/duty/closure	Supplied membrane splits
Portable QASM	0 phase/restoration errors	Executable event	Pre-routing resources
IBM final-event probe	64/64 majority correct	Two-bit truth mapping	No coherent QAE




Figure 3. Public dynamic H2-VPSA validation using the Wang et al. apparatus.

4.4 Staging is required to meet the joint separation target

Direct membrane evidence shows why a single ideal polisher is not an adequate engineering representation. A 1,050 cm2 multicomponent Pd/Au/Pd pilot achieved 98-99.87% purity and 64% recovery over 840 h [9]. A two-stage Pd-alloy experiment used a 99.99% purity and 80% recovery benchmark [10]. A binary repaired-Pd membrane reached 99.986% purity and 91% recovery [11], but the simple binary feed does not test the present contaminants. Published PSA-plus-membrane and staged concentration-plus-palladium simulations enter the present purity-recovery region [12,13]. More directly, the present polymer area normalizes to 0.513-0.530 m2 per Nm3 h-1 across all 16 cases, only 1.025-1.059 times the Zito 20-bar value of 0.5 m2 per Nm3 h-1 for 90% recovery [13]. The same public table supplies the exact polymer and Pd transport coefficients used here. This quantitative agreement supports parameter traceability and scale plausibility, while the differing feeds and pressures prevent it from serving as final validation.




Figure 4. Public membrane purity-recovery evidence and flow-normalized area traceability. Different feeds and pressures make this a scaling audit rather than a matched validation.

The ideal literature-bounded train uses a 0.1892 m2 polymer stage and 0.4799 m2 dense-palladium stage. It passes all eight corners and eight hold-outs, with minimum recovery 93.450%, minimum qualified hydrogen 0.0024562 mol s-1, 4.616 mol surge capacity, and 1.546 mol receiver capacity. The conservative design-screen compression requirement is 2.573 kWh kg-1 H2 for the corrected 6.2-to-20 bar boundary and interstage recompression.




Figure 5. Corrected pressure-consistent polymer plus dense-palladium train over eight corners and eight hold-outs.

4.5 Adaptive integration corrects the final guard band

The fixed-section calculation suggested that 0.553 m2 would cover 20% permeance loss. Adaptive DOP853 integration found one failure, so bisection and upward rounding increased the guard to 0.554 m2. This revised area is a numerical and performance guard, not a membrane-manufacturing tolerance.

The 0.554 m2 design passed all 16 direct cases. Minimum recovery was 0.883221 and minimum qualified hydrogen was 0.00236055 mol s-1. Maximum CO, CO2, N2, and CH4 were 0.1204, 3.9998, 48.83, and 25.07 ppm. The receiver capacity was 1.2320 mol (30.541 L at 1 bar and 298.15 K), and module and receiver balance errors remained below 4.2e-17 and 1.3e-11 mol.

Table 3. Membrane and receiver design tiers

Quantity	Value	Gate
Polymer area	0.1892 m2	Literature bounded
Ideal dense-Pd area	0.4799 m2	16/16 direct
20% loss guard	0.554 m2	16/16
50% loss guard	0.887 m2	16/16
Guard receiver	1.232009 mol	30.541 L
Minimum recovery	88.3221%	88.2940% floor
Minimum qualified H2	0.0023605 mol s-1	0.0022631 floor
Maximum CO2	3.9998 ppm	5 ppm




Figure 6. Independent continuous-area DOP853 audit that changes the 20%-permeance-loss palladium guard from 0.553 to 0.554 m2.




Figure 7. Finite selectivity, defect leakage, and permeance-retention sensitivity for the corrected train.

4.6 Corrected DWSIM compression and process-simulator cross-check

Changing the polishing inlet from the obsolete 8 bar assumption to the physically available 6.2 bar manifold increased the ideal-gas isothermal design-screen requirement to 2.573 kWh kg-1 H2, without changing area, recovery, purity, or pass labels. The corrected DWSIM deck solved all 16 cases with zero calculation errors. Maximum component-balance error was 8.95e-19 mol s-1 and maximum product-stream difference from the supplied split fractions was 1.30e-18 mol s-1. DWSIM adiabatic compression required 3.091-3.183 kWh kg-1 H2, 16.94-16.98% above the matched isothermal lower bound. Maximum first-compressor and recompression-stage discharge temperatures were 460.03 and 433.64 K, respectively.




Figure 8. Corrected DWSIM 8.7.1 Peng-Robinson cross-check for all 16 horizon-averaged cases at the 6.2 bar polishing inlet. The calculation independently checks pressure states, compression and cooling duties, temperatures, and material closure while using membrane split fractions supplied by the packet model.

4.7 The compact QAE event preserves the process decision

At 0.440 m2 installed dense-palladium area, 13 of 16 direct points passed. The error-buffered trilinear probability had a minimum-scramble value of 0.956673; the conservative affine probability was 0.951210. Ten-bit digitization gave 0.950629, an absolute probability error of 0.000581, with zero false-positive and zero false-negative direct labels. The included OpenQASM 3 oracle uses 66 logical qubits, 24,042 CX gates, 61,269 primitive gates, and all-to-all depth 36,163 before optimization or routing. It produced zero phase-label and restoration errors in exhaustive 2-, 3-, and 4-bit tests, all 16 direct 10-bit engineering states, and 4,096 seeded random 10-bit states. The exact two-bit final-event compilation used seven logical qubits and was routed to 80-179 CZ gates with depth 244-456 on IBM Kingston. Job db6emt04qg6s73c4lja0 tested all 64 inputs at 256 shots per state. Every state was majority-correct; expected-label probability averaged 0.8389 and ranged from 0.6523 to 0.9297. The job consumed 7 QPU s, and a separate read-only retrieval exactly reproduced all 64 archived count dictionaries. Figure 9 separates this hardware truth-mapping result from the full-oracle resource boundary.

Table 4. Corrected energy and quantum-event summary

Calculation	Metric	Value
Regeneration booster	Maximum duty	0.197 kWh kg-1 H2
Polishing compression	Conservative screen	2.573 kWh kg-1 H2
Polishing compression	Pressure basis	6.2->20 bar; 1->20 bar
DWSIM compression	Adiabatic range	3.091-3.183 kWh kg-1 H2
DWSIM compression	Premium over isothermal	16.94-16.98%

Calculation	Metric	Value
DWSIM temperatures	Maximum discharges	460.03 / 433.64 K
QAE event	Chance Pd area	0.440 m2
QAE event	Continuous affine probability	0.951210
QAE event	10-bit probability	0.950629
QAE event	Discretization error	0.000581
QAE event	Logical qubits	66
OpenQASM 3	Portable CX	24,042
OpenQASM 3	Primitive size / depth	61,269 / 36,163
IBM Kingston	Two-bit states / shots	64 / 256 each
IBM Kingston	Expected-label probability	mean 0.8389; min 0.6523
IBM Kingston	QPU usage	7 s; 64/64 majority correct




Figure 9. Process chance event, portable OpenQASM resource boundary, and IBM QPU truth-mapping result. The full-oracle CX and depth values are exact all-to-all counts before device optimization and routing. The hardware panel reports all 64 states of the exact two-bit reduction of the final event at 256 shots per state; it is not a coherent QAE execution.

RQMC is still the practical estimator for this smooth three-variable event. The quantum construction supplies a reproducible Boolean event, integer coefficients, register layout, discretization error, and a hardware-tested low-resolution truth mapping. The IBM result closes the software-to-device chain for the final event definition, but it does not test coherent superposition, amplitude amplification, or the 66-qubit arithmetic circuit. QAE becomes computationally interesting when future plant-calibrated uncertainty is higher-dimensional, process evaluation is expensive, and repeated risk queries can reuse the same oracle.

4.8 Public actual-syngas aging defines a larger conditional guard

A public coal-syngas membrane study reported a 40-50% loss of hydrogen permeance while Pd-Au selectivity remained stable for more than 473 h [21]. Under the conservative 50% retention stress, bisection required 0.8860 m2 and the installed guard was rounded to 0.887 m2. All 16 cases passed with minimum recovery 0.883679 and minimum qualified hydrogen 0.00236153 mol s-1.




Figure 10. Corrected installed-area requirement under the 40-50% actual-syngas permeance-loss stress.

4.9 A separately coded RK4 solver preserves both design decisions

At 192 sections per membrane, fixed-grid RK4 passed all 16 cases for both the 0.554 m2, 80%-retention guard and the 0.887 m2, 50%-retention guard. All 32 labels matched DOP853. The maximum recovery difference was 9.33e-8 percentage point, the maximum relative qualified-flow difference was 1.01e-9, and maximum component-balance error was 4.25e-17 mol.




Figure 11. Corrected fixed-area RK4 mesh refinement and agreement with adaptive DOP853 for both guard designs.

4.10 Public flux data validate the concentration-polarization model form

The independently implemented Ververs model reproduced all 468 numeric H2/N2 records in the public workbook without fitting mixture-flux data. Including the published local Sherwood correlation gave 4.405% mean absolute relative error, 3.144% median absolute relative error, R2=0.9966, and 92.52% of predictions within 10% of experiment. The 192-section result differed from the 384-section result by at most 0.00577%. When concentration polarization was omitted while axial depletion and the same Richardson parameters were retained, mean absolute relative error increased to 29.016%, R2 decreased to 0.8481, and only 9.62% of predictions remained within 10%. The local film model predicted a median 19.94% flux penalty. This public raw-data reproduction independently verifies the need for concentration-polarization physics; its binary 2-5 bar, 350-450 C apparatus does not certify the present five-component 20-bar polisher.




Figure 12. Independent reproduction of 468 public H2/N2 Pd-Ag membrane flux records using the published local Sherwood correlation. Including concentration polarization sharply reduces error relative to an otherwise identical depletion-only calculation.

4.11 High-pressure palladium evidence and legacy hot-stage cross-check

The corrected DWSIM run resolves the current 6.2 bar pressure basis, compressor duties, temperatures, and Peng-Robinson closure, as shown in Figure 8. Figure 13 retains the earlier 420 C heater and heat-integration structure for the preceding input set and is not used for current energy numbers. Published 22 bar inhibition and 26 bar, 400 C endurance studies [23,24] independently support the high-temperature feasibility envelope but do not certify the final impurity vector.




Figure 13. Earlier hot-stage DWSIM equipment and heat-integration audit retained as structural evidence for the 420 C palladium stage; current corrected compression results are reported in Figure 8.

The literature inhibition and endurance records support retaining an explicit permeance-loss guard. The 0.554 and 0.887 m2 designs are therefore interpreted as conditional engineering sizes tied to 80% and 50% permeance retention, respectively. A matched wet multicomponent module test remains necessary before converting either size into a procurement specification.

4.12 Public selectivity data define an incoming-module acceptance rule

Pressure-consistent bisection converts each impurity leakage channel into an incoming-module selectivity threshold. The rounded, simultaneous guard and all 16 direct confirmations are reported in Table 5 and Figure 14. Public defect-leaking selectivity vectors are retained as rejection stresses, which separates required area from required membrane integrity.

Table 5. Dense-Pd incoming-module selectivity acceptance

Component/test	Minimum or measured	Acceptance guard	Direct result
H2/CO	4,522.5	>= 5,660	16/16 at guard
H2/CO2	134,920.9	>= 168,660	16/16 at guard
H2/N2	427.3	>= 540	16/16 at guard

Component/test	Minimum or measured	Acceptance guard	Direct result
H2/CH4	26.44	>= 40	16/16 at guard
Li 2011 end test	H2/N2=307.7	N2 transfer only	0/16
DOE/MPT 60 psig	H2/i=92-116	defect stress	0/16




Figure 14. Pressure-consistent component selectivity thresholds and simultaneous incoming-module acceptance guard.

4.13 Full-syngas bench evidence has an analytical boundary

The Sanchez membrane produced a hydrogen-only permeate by the reported GC analysis under the full unconverted-shift-gas mixture, and maximum hydrogen recovery was about 47% at 723 K and 1 MPa [27]. The same study reported a pure-H2 permeance of 2.8 m3 m-2 h-1 kPa-0.5, pure-N2 or pure-CO2 permeate below 8 mL min-1 at 1 MPa, and no measured CO or steam in the permeate during binary and ternary tests. This is independent evidence that hot multicomponent Pd separation, reversible co-component inhibition, and nonzero recovery are physically credible. Its 100 ppm TCD accuracy is 200 times the project CO limit and 20 times the CO2 limit; the source therefore cannot validate the final component-selectivity vector or product gate. It closes a model-trend gap while leaving the matched analytical-validation gate explicit.




Figure 15. Analytical-resolution boundary of the public Sanchez bench test. The reported 0.01 vol% TCD accuracy is equivalent to about 100 ppm and therefore cannot directly certify the 0.5 ppm CO or 5 ppm CO2 gates used here.

4.14 A synchronized public experiment fails the strict gate

The DOE/Pall flow ledger gives 75.98% H2 recovery, 75 ppm CO, and 450 ppm CO2 [28]. These values are 13.15 percentage points below the project recovery floor and 150 and 90 times the respective impurity limits. The corresponding system-level H2/CO and H2/CO2 separation factors are also far below the corrected incoming-module guards of 5,660 and 168,660. The experiment therefore supplies a synchronized empirical rejection control: measured impurity leakage, rather than membrane area alone, prevents entry into the joint pass region.




Figure 16. Synchronized DOE/Pall mixed-gas experiment used as an empirical rejection control. The observed impurity concentrations, effective separation factors, and hydrogen recovery all remain below the corresponding project acceptance requirements.

4.15 DOE/UTRC supplies a positive high-recovery validation anchor

The DOE/UTRC simulated-syngas durability mean of 93.4% recovery is 5.11 percentage points above the present 88.294% recovery floor [29]. The one-standard-deviation lower value is 85.4%, so the record supports target feasibility without proving a deterministic pass at every reported fluctuation. The pre-leak calculated purity of 99.9999% corresponds to approximately 1 ppm total non-H2, compared with the present 300 ppm bulk ceiling implied by 99.97%

H2. After a small leak developed, the reported purity fell to about 99.98%, or 200 ppm total impurity, demonstrating how bulk purity can remain apparently acceptable while component-specific limits remain unknown. In the independent actual coal-gas run, the frozen model underpredicted product rate by 4.53% and recovery by 4.2 percentage points. Together these results add the positive side of the validation hierarchy: high recovery and bulk purity are physically achievable in a durable multicomponent Pd-Cu separator, and a physics model predicts actual-gas performance to engineering accuracy. Because the report does not resolve CO, CO2, N2, and CH4 in the permeate at the present limits, the component-specific acceptance gate remains open.




Figure 17. DOE/UTRC pilot-scale Pd-Cu validation anchors. The simulated-syngas durability test provides a positive high-recovery and calculated bulk-purity case; the actual coal-gas run tests the frozen physics model. Purity was inferred from H2/N2 separation and is not component-resolved certification.

4.16 Published integrated operating points bracket the joint CO-recovery gate

Neither of the two reported Bang operating points satisfies the present joint event [30]. The 91.37% recovery point exceeds the project recovery floor by 3.076 percentage points but its 8.67 ppm CO is 17.34 times the 0.5 ppm limit. The 0.15 ppm CO point uses only 30% of the CO allowance but its 85.99% recovery is 2.304 percentage points below the floor. By comparison, the present conservative 0.887 m2 model has a worst-case pair of 88.3676% recovery and 0.1207 ppm CO, giving margins of only 0.0736 percentage point and 0.3793 ppm. The published pair therefore demonstrates the engineering conflict that motivates a joint event rather than separate purity and recovery summaries. It also makes the present claim falsifiable: a matched experiment must enter the upper-left pass region instead of reproducing either side of the observed tradeoff. Because the source used a reacting CMR, H2 sweep, and no N2 or CH4 in the reported feed, it does not certify the final five-component product.




Figure 18. Published Pd-Cu catalytic-membrane-reactor/four-bed-PSA operating points relative to the frozen joint gate. The two points pass opposite single criteria and bracket the upper-left joint pass region; the present worst-case point is a model prediction, not a matched experiment.

4.17 Third-language packetwise transport preserves every decision

The compiled C# replay previously demonstrated that the transport implementation could be reproduced without membrane split inputs. It belongs to the superseded input set and is not counted as current pressure-consistent confirmation. The corrected claim is instead supported by direct packetwise DOP853 and the independently coded RK4 result in Section 4.9.




Figure 19. Third-language packetwise method evidence from the superseded input set. It is not counted as current pressure-consistent confirmation.

5 Discussion

5.1 Engineering meaning of the selected policy

The principal result is a physically closed material-allocation rule. Product hydrogen first secures the next cycle, the 6.2 bar manifold passively restores the 6.0 bar tank, and a booster supplies the 6.5 bar regeneration header when tank pressure falls below it. Shortening active purge and extending adsorption increased qualified saleable hydrogen without relaxing product quality or reserve gates.

The robust and chance designs answer different questions. The 0.4799 m2 ideal palladium stage passes all direct cases under the ideal dense-Pd assumption. The 0.440 m2 chance design accepts a small low-performance region under the declared uniform measure. The 0.554 and 0.887 m2 guards then address finite selectivity and permeance loss. These areas must be reported with their assumptions because they are not interchangeable.

5.2 Why the independent numerical failure strengthens the design

The 0.553-to-0.554 m2 correction is small in area but important in logic because the event lies near its recovery boundary. Adaptive integration exposed the missed failure, and the independent RK4 mesh reproduced the corrected 32 labels to much tighter tolerance than the engineering margin. This adverse result supports the final guard rather than being hidden as solver noise.

5.3 Separation journal relevance and experimental boundary

The work contributes a separation-process operating rule: pressure-consistent regeneration inventory, strict product quality, and uncertain feed and adsorption performance are optimized together. Public experiments validate transferable dynamic, mass-transfer, inhibition, recovery, and rejection behavior, while their measurement limits are

carried into the claim boundary. The missing experiment is a synchronized test of the final integrated apparatus at the declared ppm limits.

5.4 Quantum role and computational boundary

QAE is subordinate to the separation result. Current RQMC is cheaper for this three-dimensional response. The quantum contribution is the auditable reduction from a physical membrane-area chance constraint to a verified discrete reversible event with known probability error, a portable OpenQASM implementation, explicit pre-routing resources, and an IBM QPU test of every state in the exact two-bit final-event reduction. The 64/64 majority result shows that the engineering inequality can survive compilation, device routing, and measurement at low resolution. The 24,042-CX full-oracle count remains a reproducible resource baseline rather than an optimized device cost, and no hardware-advantage claim is made.

5.5 Limitations

The main limitations are the uniform engineering uncertainty measure, transfer of adsorption and membrane parameters across apparatuses, common constitutive laws in DOP853 and RK4, use of supplied horizon-averaged membrane split fractions in DWSIM, and the lack of a matched component-resolved integrated experiment. Device-specific execution is limited to a seven-qubit truth-table test at two-bit resolution; coherent QAE and the 42- and 66-logical-qubit arithmetic realizations were not run. The coarse two-bit uniform-grid fraction is therefore not used as the reported process probability. Public membrane studies establish feasibility, recovery scale, degradation stresses, and rejection cases, but their feeds, pressures, modules, and analytical resolutions differ. These boundaries define the next validation work and do not change the pressure-consistent numerical design decision reported here.

6 Conclusions

A finite regeneration inventory makes hydrogen PSA an allocation problem between the next cycle and sale. The physically feasible design uses a 6.0 bar tank passively filled from the 6.2 bar product manifold and a booster to the 6.5 bar regeneration header. The selected 4 s purge and 540 s adsorption policy passed 8/8 uncertainty corners and 8/8 predeclared hold-outs, increased qualified shipment by 6.785-7.341%, and kept conservative booster duty below 0.198 kWh kg-1 H2.

The staged polishing train combines a 0.1892 m2 polymer concentrator with dense-palladium polishing. Adaptive integration set the 20%-loss guard at 0.554 m2; it passed 16/16 cases with minimum recovery 88.322% and every impurity below its limit. A public 50%-retention actual-syngas stress increased the conditional guard to 0.887 m2 and again passed 16/16. Independent RK4 preserved all 32 final labels, confirming that the design decision is insensitive to the numerical integrator and refined area mesh.

The corrected DWSIM calculation solved all 16 horizon-averaged cases and quantified the adiabatic compression penalty above the isothermal screen. The physical chance event at 0.440 m2 has conservative continuous probability 0.951210 and 10-bit discrete probability 0.950629 with no direct label errors. The verified portable oracle requires 66 logical qubits and has an exact pre-routing count of 24,042 CX gates. An exact seven-qubit reduction of the same final event classified all 64 two-bit inputs correctly by majority vote on IBM Kingston, with mean expected-label probability 0.8389 and 7 QPU s usage. This establishes a reproducible process-to-device path while leaving coherent QAE and full arithmetic-oracle execution as future work. RQMC remains preferred for the present model; QAE becomes relevant when validated plant uncertainty and repeated probability queries make classical event evaluation expensive. A synchronized integrated separation experiment remains the principal external validation step.

CRediT authorship contribution statement

Ugwiyeon Lee: Conceptualization, Methodology, Software, Formal analysis, Investigation, Data curation, Visualization, Writing - original draft, Writing - review and editing, Project administration. Seong-Yun Bae: Writing - review and editing. Hakrae Kim: Writing - review and editing. Jungsu Lee: Writing - review and editing.

Declaration of competing interest

The authors declare no competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Data and code availability

The complete calculation records, direct states, portable OpenQASM circuit, corrected DWSIM input and results, figures, tables, and SHA-256 manifests are archived under the version-independent repository DOI https://doi.org/10.5281/zenodo.23271866 and mirrored at https://github.com/lyullee/psa-qae-resource-audit.

Declaration of generative AI and AI-assisted technologies

During manuscript preparation, the authors used OpenAI Codex for code drafting and refactoring, local workflow orchestration, figure and table generation, manuscript organization, and language editing. The authors reviewed and edited the outputs, reran the documented analyses, verified numerical claims and sources, and take full responsibility for the publication.

References

[1] J. Yang, C.-H. Lee, J.-W. Chang, Separation of hydrogen mixtures by a two-bed pressure swing adsorption process using zeolite 5A, Ind. Eng. Chem. Res. 36 (1997) 2789-2798. https://doi.org/10.1021/ie960728h.

[2] A.M. Ribeiro, C.A. Grande, F.V.S. Lopes, J.M. Loureiro, A.E. Rodrigues, Four beds pressure swing adsorption for hydrogen purification: case of humid feed and activated carbon beds, AIChE J. 55 (2009) 2292-2302. https://doi.org/10.1002/aic.11886.

[3] H. Khajuria, E.N. Pistikopoulos, Optimization and control of pressure swing adsorption processes under uncertainty, AIChE J. 59 (2013) 120-131. https://doi.org/10.1002/aic.13783.

[4] Y. Park, J.-H. Kang, D.-K. Moon, Y.S. Jo, C.-H. Lee, Parallel and series multi-bed pressure swing adsorption processes for H2 recovery from a lean hydrogen mixture, Chem. Eng. J. 408 (2021) 127299. https://doi.org/10.1016/j.cej.2020.127299.

[5] T. Kim, J.K. Scott, Dynamic modeling and simulation of pressure swing adsorption processes using toPSAil, Comput. Chem. Eng. 176 (2023) 108309. https://doi.org/10.1016/j.compchemeng.2023.108309.

[6] S. Ga, N. An, C. Joo, J. Kim, pyAPEP: an all-in-one software package for the automated preparation of adsorption process simulations, Comput. Phys. Commun. 291 (2023) 108830. https://doi.org/10.1016/j.cpc.2023.108830.

[7] A. Golmakani, S.A. Nabavi, V. Manovic, Data for the paper Effect of impurities on ultra-pure hydrogen production by pressure vacuum swing adsorption, Cranfield Online Research Data (2019). https://doi.org/10.17862/cranfield.rd.10123346.

[8] J. Wang, X. Chen, T. Du, L. Liu, P.A. Webley, G.K. Li, Hydrogen production from low pressure coke oven gas by vacuum pressure swing adsorption, Chem. Eng. J. 472 (2023) 144920. https://doi.org/10.1016/j.cej.2023.144920.

[9] B. Castro-Dominguez, I.P. Mardilovich, R. Ma, N.K. Kazantzis, A.G. Dixon, Y.H. Ma, Performance of a pilot-scale multitube membrane module under coal-derived syngas for hydrogen production and separation, J. Membr. Sci. 523 (2017) 515-523. https://doi.org/10.1016/j.memsci.2016.10.024.

[10] A. Iulianelli, A. Brunetti, L. Pino, C. Italiano, G.D. Ferrante, M. Gensini, A. Vita, An integrated two stages inorganic membrane-based system to generate and recover decarbonized H2: An experimental study and performance indexes analysis, Renew. Energy 210 (2023) 472-485. https://doi.org/10.1016/j.renene.2023.04.095.

[11] J. Yu, J. Zhang, C. Bao, H. Li, H. Xu, J. Sun, Confined and in-situ zeolite synthesis: A novel strategy for defect reparation over dense Pd membranes for hydrogen separation, Sep. Purif. Technol. 184 (2017) 43-53. https://doi.org/10.1016/j.seppur.2017.04.035.

[12] B. Li, G. He, X. Jiang, Y. Dai, X. Ruan, Pressure swing adsorption/membrane hybrid processes for hydrogen purification with a high recovery, Front. Chem. Sci. Eng. 10 (2016) 255-264. https://doi.org/10.1007/s11705-016-1567-1.

[13] P.F. Zito, A. Brunetti, G. Barbieri, Hydrogen concentration and purification by membrane process: A multistage analysis, Renew. Energy 218 (2023) 119243. https://doi.org/10.1016/j.renene.2023.119243.

[14] S. Woerner, D.J. Egger, Quantum risk analysis, npj Quantum Inf. 5 (2019) 15. https://doi.org/10.1038/s41534-019-0130-6.

[15] G. Brassard, P. Hoyer, M. Mosca, A. Tapp, Quantum amplitude amplification and estimation, Contemp. Math. 305 (2002) 53-74.

[16] A. Callison, D.E. Browne, Improved maximum-likelihood quantum amplitude estimation, arXiv:2209.03321 (2022). https://arxiv.org/abs/2209.03321.

[17] J. He et al., An efficient quantum computing based structural reliability analysis method using quantum amplitude estimation, Struct. Saf. 114 (2025) 102555. https://doi.org/10.1016/j.strusafe.2024.102555.

[18] P. Virtanen et al., SciPy 1.0: fundamental algorithms for scientific computing in Python, Nat. Methods 17 (2020) 261-272. https://doi.org/10.1038/s41592-019-0686-2.

[19] A.B. Owen, Scrambled net variance for integrals of smooth functions, Ann. Stat. 25 (1997) 1541-1562. https://doi.org/10.1214/aos/1031594731.

[20] D. Medeiros, DWSIM open-source chemical process simulator, https://dwsim.org (accessed 12 October 2026).

[21] F. Guazzone, J. Catalano, I.P. Mardilovich, T. Wu, R.C. Lambrecht, S. Datta, J. Kniep, S. Pande, N.K. Kazantzis, Y.H. Ma, Enhancement of the long-term permeance, selectivity stability, and recoverability of Pd-Au membranes in coal derived syngas atmospheres, Energy Fuels 27 (2013) 4150-4160. https://doi.org/10.1021/ef302130s.

[22] W.J.R. Ververs, M. Ongis, A. Arratibel, L. Di Felice, F. Gallucci, On the modeling of external mass transfer phenomena in Pd-based membrane separations, Int. J. Hydrogen Energy 71 (2024) 1121-1133. https://doi.org/10.1016/j.ijhydene.2024.04.337. Dataset: https://doi.org/10.5281/zenodo.7961792.

[23] J. Boon, J.A.Z. Pieterse, F.P.F. van Berkel, Y.C. van Delft, M. van Sint Annaland, Hydrogen permeation through palladium membranes and inhibition by carbon monoxide, carbon dioxide, and steam, J. Membr. Sci. 496 (2015) 344-358. https://doi.org/10.1016/j.memsci.2015.08.061.

[24] T.A. Peters, M. Stange, H. Klette, R. Bredesen, High pressure performance of thin Pd-23%Ag/stainless steel composite membranes in water gas shift gas mixtures; influence of dilution, mass transfer and surface effects on the hydrogen flux, J. Membr. Sci. 316 (2008) 119-127. https://doi.org/10.1016/j.memsci.2007.08.056.

[25] H. Li, A. Goldbach, W. Li, H. Xu, WGS-mixture separation and WGS reaction test in a bench-scale multi-tubular membrane reactor, Energy Procedia 4 (2011) 666-673. https://doi.org/10.1016/j.egypro.2011.01.103.

[26] Media and Process Technology Inc., Development of a Novel Membrane Reactor for Direct Hydrogen Production from Coal, final technical report DE-FG36-04GO14330, U.S. Department of Energy (2005). https://www.osti.gov/servlets/purl/883041.

[27] J.M. Sanchez, M.M. Barreiro, M. Marono, Bench-scale study of separation of hydrogen from gasification gases using a palladium-based membrane reactor, Fuel 116 (2014) 894-903. https://doi.org/10.1016/j.fuel.2013.02.051.

[28] J. Acquaviva, High Performance Palladium-Based Membrane for Hydrogen Separation and Purification, DOE Hydrogen Program FY 2008 Annual Progress Report, contract DE-FG36-05GO15093, pp. 57-62 (2008). https://www.hydrogen.energy.gov/docs/hydrogenprogramlibraries/pdfs/progress08/ii_a_9_acquaviva.pdf.

[29] S. Emerson, N. Magdefrau, Y. She, C. Thibaud-Erkey, Advanced Palladium Membrane Scale-up for Hydrogen Separation, final technical report DE-FE0004967, U.S. Department of Energy (2012). https://doi.org/10.2172/1063878.

[30] G. Bang, D.K. Moon, J.H. Kang, Y.J. Han, K.M. Kim, C.H. Lee, High-purity hydrogen production via a water-gas-shift reaction in a palladium-copper catalytic membrane reactor integrated with pressure swing adsorption, Chem. Eng. J. 411 (2021) 128473. https://doi.org/10.1016/j.cej.2021.128473.