Site engineering requirements

Lampwick Instruments | Frozen profile set | controlled 30 October 2025

Great Britain

Profile status: FROZEN Effective profile date: 2025-10-30 Units: seconds and millimetres

Profile ID	Metric	Direction	Limit	Unit	Engineering meaning	Clause
GB-01	Index time	MAX	1.25	s	Cell index period shall not exceed 1.25 s.	GB-CELL-04
GB-02	Fixture clearance	MIN	6.00	mm	Minimum free space normal to the fixture envelope.	GB-SAFE-11
GB-03	Dimensional deviation (absolute)	MAX	0.30	mm	Absolute dimensional deviation limit.	GB-QA-07

Interpretation

- The direction field identifies whether the value is an upper limit (MAX) or a lower limit (MIN).
- Index time is compared in seconds; clearance and dimensional deviation are compared in millimetres.
- The profiles apply to installations within the named jurisdiction and remain separate in the engineering package.
- Source references: GB-01 through GB-03.

Profile distinction

The Great Britain profile sets the fixture-clearance minimum at 6.00 mm.

This profile is retained separately from the Republic of Ireland profile for jurisdiction-specific checks.

Republic of Ireland

Profile status: FROZEN Effective profile date: 2025-10-30 Units: seconds and millimetres

Profile ID	Metric	Direction	Limit	Unit	Engineering meaning	Clause
ROI-01	Index time	MAX	1.25	s	Cell index period shall not exceed 1.25 s.	ROI-CELL-04
ROI-02	Fixture clearance	MIN	7.80	mm	Minimum free space normal to the fixture envelope.	ROI-SAFE-11
ROI-03	Dimensional deviation (absolute)	MAX	0.30	mm	Absolute dimensional deviation limit.	ROI-QA-07

Interpretation

- The direction field identifies whether the value is an upper limit (MAX) or a lower limit (MIN).
- Index time is compared in seconds; clearance and dimensional deviation are compared in millimetres.
- The profiles apply to installations within the named jurisdiction and remain separate in the engineering package.
- Source references: ROI-01 through ROI-03.

Profile distinction

The Republic of Ireland profile sets the fixture-clearance minimum at 7.80 mm.

This profile is retained separately from the Great Britain profile for jurisdiction-specific checks.