Pump Shaft Dimensional Inspection Records

Tanneryside Cooperative | Batch PS-25-1015 | Oversight packet | Retained inspection evidence

Part	Pump shaft blank
Inspection lot	PS-25-1015 / 24 pieces
Measurement basis	Controlled drawing and recorded observed values
Record source	Dimensional inspection bench log

Record Set A - Drawing PS-104 Rev A, effective 2025-10-01

Recorded during the first inspection pass. The source reference identifies the retained line in this packet.

Record ID	Characteristic	Nominal	Lower	Upper	Observed	Unit	Source ref
PSA-01	Journal diameter	30.000	29.985	30.015	30.011	mm	p.1 / A01
PSA-02	Keyway width	8.000	7.980	8.020	8.025	mm	p.1 / A02
PSA-03	Journal runout	0.000	0.000	10.000	7.000	µm	p.1 / A03
PSA-04	Coupling bore diameter	18.000	17.990	18.010	18.008	mm	p.1 / A04
PSA-05	Keyway angle	90.000	89.800	90.200	90.100	deg	p.1 / A05
PSA-06	Retention torque	55.000	50.000	60.000	56.000	N·m	p.1 / A06

Bench note: Keyway width record PSA-02 was retained with the measured value and process hold note.

Pump Shaft Dimensional Inspection Records

Tanneryside Cooperative | Batch PS-25-1015 | Continued record set

Record Set B - Drawing PS-104 Rev B, effective 2025-10-15

Second dated record set. The coupling-bore drawing requirement differs from Record Set A; preserve the date and governing revision with each observation.

Record ID	Characteristic	Nominal	Lower	Upper	Observed	Unit	Source ref
PSB-01	Journal diameter	30.000	29.985	30.015	30.009	mm	p.2 / B01
PSB-02	Keyway width	8.000	7.980	8.020	8.019	mm	p.2 / B02
PSB-03	Journal runout	0.000	0.000	10.000	8.000	µm	p.2 / B03
PSB-04	Coupling bore diameter	18.020	18.010	18.030	18.021	mm	p.2 / B04
PSB-05	Keyway angle	90.000	89.800	90.200	90.000	deg	p.2 / B05
PSB-06	Retention torque	55.000	50.000	60.000	55.000	N·m	p.2 / B06

Record continuity: retain both dated record sets with their stated drawing revision, observed value, unit, and source reference.