



DEALER BEST PRACTICE SERIES

Ensuring Proper Lube Service With Quick Disconnect Fittings

Application Maintenance Component Rebuild Component Life MARC Management

Ensuring Proper Lube Service With Quick Disconnect Fittings 0

1.0 Introduction 1

2.0 Best Practice Description..... 1

3.0 Implementation Steps 1

4.0 Benefits..... 2

5.0 Resources Required 2

6.0 Supporting Attachments / References 2

7.0 Related Best Practices 2

8.0 Acknowledgements..... 2

DISCLAIMER: The information and potential benefits included in this document are based upon information provided by one or more Cat® dealers, and such dealer(s) opinion of “Best Practices”. Caterpillar makes no representation or warranty about the information contained in this document or the products referenced herein. Caterpillar welcomes additional “Best Practice” recommendations from our dealer network.

1.0 Introduction

During daily lube service and preventative maintenance services it is critical to refill fluid compartments with the correct type of fluid. Further, it is also recommended to refill in a manner that minimizes open compartments and fluid contamination.

Daily lube services are performed either at the fuel island or by the mobile lube truck. It is very easy for a serviceman to put the wrong type of oil into a given reservoir. The same is true for PM services in the workshop. This practice was put into place to minimize the probability of this happening.

This practice can be easily replicated at any mine site and involves minimal effort and cost to proactively prevent incorrect fluid handling.

2.0 Best Practice Description

Simply, quick connections are installed on all oil fill ports. Each type of oil has a different size connector. Each connection is labeled to ensure proper filling.

When the technician recognizes a need to fill an oil reservoir he/she identifies the proper oil type and connects the dispensing port in the workshop/fuel bay/lube truck to the fill port on the machine. Only the correct connections will fit together to guarantee proper filling of the reservoir.



Connection ports on a 16H motor grader



Close up of connection ports. Notice that each port is a different size and labeled.

3.0 Implementation Steps

1. Identify all fittings needed for all machines on site
2. Purchase fittings for machines, service lube truck, fuel bay, and work shop
3. Install all fittings
4. Train service personnel to use the proper fittings

THE INFORMATION HEREIN MAY NOT BE COPIED OR TRANSMITTED TO OTHERS WITHOUT THE WRITTEN PERMISSION OF CATERPILLAR

Ensuring Proper Lube Service With Quick Disconnect Fittings	DATE 2/17/2015	CHG NO 02	NUMBER 1006-2.10-1034
---	-------------------	-----------------	--------------------------

4.0 Benefits

- Improvement of service accuracy - avoidance of compartments being filled with the wrong fluid, resulting in extended life and/or performance of a part or component.
- Increased service quality and consistency.
- Time savings during maintenance operations.
- Oil spills are more easily avoided, increasing operator/technician safety.

5.0 Resources Required

List of fittings for machines in fleet (see attached worksheet). A local supplier can supply standard fittings.

Costs include the cost of parts and cost of installation. Total is approximately \$930 to \$1300 per machine.

6.0 Supporting Attachments / References

[Service truck fittings.xls](#)

The parts list from a purchase order for fittings on certain mining trucks, loaders, dozers, and service equipment.

7.0 Related Best Practices

None

8.0 Acknowledgements

This *Maintenance Best Practice* was written by:

Jeff Wolffe
EAME Global Mining Service Rep
Wolffe_Jeffrey_S@cat.com
+41-22-849-4423

Andrew Broadbent
Unatrac Technical Manager
abroadbent@unatrac.com

Rian Gouws
Unatrac Site Project Manager
RIGouws@tractorequip.com

THE INFORMATION HEREIN MAY NOT BE COPIED OR TRANSMITTED TO OTHERS WITHOUT THE WRITTEN PERMISSION OF CATERPILLAR

Ensuring Proper Lube Service With Quick Disconnect Fittings	DATE 2/17/2015	CHG NO 02	NUMBER 1006-2.10-1034
---	-------------------	-----------------	--------------------------