



MINING DEALER BEST PRACTICE

Improved Painting Process of 777D/F Final Drives

Maintenance and
Repair

Application

Component Life
Management

Component
Renewal (CRC)

MARC
Management

Improved Painting Process of 777D/F Final Drives....	0
1.0 Introduction.....	1
2.0 Best Practice Description.....	1
3.0 Implementation Steps.....	2
4.0 Benefits.....	2
5.0 Resources Required.....	2
6.0 Supporting Attachments / References.....	2
7.0 Related Best Practices.....	2
8.0 Acknowledgements.....	3

DISCLAIMER: The information and potential benefits included in this document are based upon information provided by one or more Cat® dealers, and such dealer(s) opinion of “Best Practices.” Caterpillar makes no representation or warranty about the information contained in this document or the products referenced herein. Caterpillar welcomes additional “Best Practice” recommendations from our dealer network.

June 2016
1604-4.03-1424

1.0 Introduction

The preparation of one final drive for painting takes 45 minutes, and one roll of the packing tape is used for it. Borusan Makina Kazakhstan has fabricated multi-use covers to protect the places on the final drive that should not be painted.

For example, 40 covers were made for 2 x 777D/F Final Drives. The use of those covers has considerably reduced the component paint preparation time (from 45 minutes to 1 minute per 1 x Final Drive).

2.0 Best Practice Description

The multi-use cover is made from the pipe welded to the tin-plate pattern. The pipe is selected as per the diameter of the final drive bolt (see attached drawings for 777D/F pipe and plate specifications).



The cover (front view)



The cover (bottom view)

The pictures below show the ease of paint preparation due to the use of the covers.

BEFORE



The old way of preparing the final drive for painting. It took **45 minutes** per one final drive.

AFTER



The new way of preparing the final drive for painting. Now it takes **1 min.** per one final drive.

THE INFORMATION HEREIN MAY NOT BE COPIED OR TRANSMITTED TO OTHERS WITHOUT THE WRITTEN PERMISSION OF CATERPILLAR

Improved Painting Process of 777D/F Final Drives

DATE
6/17/2016

CHG
NO
00

NUMBER
1604-4.03-1424

3.0 Implementation Steps

- Obtain necessary material and fabricate the covers
- Install covers and your final drive is ready to be painted!



Improved painting process with the use of the multi-use covers.

4.0 Benefits

- The use of multi-use covers considerably saves time when the component is prepared for painting (from 45 minutes to 1 minute per 1 x Final Drive), and that expedites the painting process accordingly.

5.0 Resources Required

- Machine shop (lathe & milling machine).
- Time and material to fabricate

6.0 Supporting Attachments / References

The drawing of 777D/F Final Drive Cover is attached.

7.0 Related Best Practices

N/A

THE INFORMATION HEREIN MAY NOT BE COPIED OR TRANSMITTED TO OTHERS WITHOUT THE WRITTEN PERMISSION OF CATERPILLAR			
Improved Painting Process of 777D/F Final Drives	DATE 6/17/2016	CHG NO 00	NUMBER 1604-4.03-1424

8.0 Acknowledgements

The idea of creating & implementing this Best Practice belongs to:

Sergey INYUTIN
Painter
Equipment Rebuild Shop (ERS)
Borusan Makina Kazakhstan LLP

Daniil PONAMOREV
Technician
Component Rebuild Shop (CRS)
Borusan Makina Kazakhstan LLP

Vyacheslav KLYKOV
Turner
Machine Shop
Borusan Makina Kazakhstan LLP

Yernar NARGELOV
Design Engineer
Mining Product Support Department
Borusan Makina Kazakhstan LLP
ynargelov@borusan.com

This Best Practice was written by:

Gulnaz MANSUROVA
CRC Process Engineer
Borusan Makina Kazakhstan LLP
gmansurova@borusan.com
+7 (701) 951 98 14

THE INFORMATION HEREIN MAY NOT BE COPIED OR TRANSMITTED TO OTHERS WITHOUT THE WRITTEN PERMISSION OF CATERPILLAR

Improved Painting Process of 777D/F Final Drives

DATE
6/17/2016

CHG
NO
00

NUMBER
1604-4.03-1424