



DEALER BEST PRACTICE SERIES

Tool for Installing Transmission Bolt Dampers

Maintenance and Repair Application Component Life Management Component Renewal (CRC) MARC Management

Efficient Tool for Installing Transmission Bolt
Dampers**Error! Bookmark not defined.**

1.0 Introduction 1

2.0 Best Practice Description 1

3.0 Benefit 3

4.0 Resources Required..... 3

5.0 Supporting Attachments / References 3

6.0 Related Best Practices 3

7.0 Acknowledgements 3

DISCLAIMER: The information and potential benefits included in this document are based upon information provided by one or more Cat® dealers, and such dealer(s) opinion of “Best Practices”. Caterpillar makes no representation or warranty about the information contained in this document or the products referenced herein. Caterpillar welcomes additional “Best Practice” recommendations from our dealer network.

1.0 Introduction


It is a difficult task to install the 6l-9790 bolt dampers into the clutch housings of transmissions, such as in the 793C.



The bolt damper must be compressed with a vise grip in order to install in the bore of the housing. It is difficult to grip the bolt damper with the vise grip.

2.0 Best Practice Description

Ferreyros has developed a very simple tool (collet) to compress the damper bolt. The collet is sized for the damper bolt that has a tapered bore.



The collet holds and compresses the bolt damper while it is being installed.

THE INFORMATION HEREIN MAY NOT BE COPIED OR TRANSMITTED TO OTHERS WITHOUT THE WRITTEN PERMISSION OF CATERPILLAR

Efficient Tool for Installing Transmission Damper
Bolts

DATE
6/9/2017

CHG
NO
00

NUMBER
1107-4.03-1251



The upper diameter of the collet is slightly larger than the bolt damper diameter. The taper of the collet compresses the bolt damper. The bottom diameter is 0.3mm smaller than the clutch housing bore.

Process:

Lightly tap the bolt damper into the collet with a rubber mallet.

Place the collet and compressed bolt damper over the clutch housing bore. Tap in the bolt damper with a mallet.

Remove the collet. Finish installation by tapping the bolt damper in position with the rubber mallet.

THE INFORMATION HEREIN MAY NOT BE COPIED OR TRANSMITTED TO OTHERS WITHOUT THE WRITTEN PERMISSION OF CATERPILLAR

Efficient Tool for Installing Transmission Damper Bolts

DATE
6/9/2017

CHG
NO
00

NUMBER
1107-4.03-1251

3.0 Benefit

- Allows quicker and easier installation of bolt dampers. More efficient.
- Less chance of damaging the bolt damper.
- Decreases risk of injury while inserting the bolt damper.

4.0 Resources Required

- Fabrication of collet.
- Minimal expense to fabricate the tool.

5.0 Supporting Attachments / References

None.

6.0 Related Best Practices

None.

7.0 Acknowledgements

This Best Practice was written by:

Dale Brehm
Caterpillar Global Mining

The idea for this Best Practice, belongs to:

Alexander Lazaro Enciso
Ferreyros SAA

This Best Practice was revised by:

Aninu Mitacc Vizcardo
Ferreyros SAA
amitacc@ferreyros.com.pe

THE INFORMATION HEREIN MAY NOT BE COPIED OR TRANSMITTED TO OTHERS WITHOUT THE WRITTEN PERMISSION OF CATERPILLAR

Efficient Tool for Installing Transmission Damper
Bolts

DATE
6/9/2017

CHG
NO
00

NUMBER
1107-4.03-1251