



DEALER BEST PRACTICE SERIES

Remote Control Cameras
in Dyno Room Improve
Safety

Application Maintenance Site Management Component Rebuild Component Life Management Safety MARC Management

Remote Control Cameras in Dyno Room Improve
Safety 1
1.0 Introduction 2
2.0 Best Practice Description 2
3.0 Implementation Steps..... 2
4.0 Benefits 4
5.0 Resources Required..... 4
6.0 Supporting Attachments / References 4
7.0 Related Best Practices 4
8.0 Acknowledgements 4

DISCLAIMER: The information and potential benefits included in this document are based upon information provided by one or more Cat® dealers, and such dealer(s) opinion of “Best Practices.” Caterpillar makes no representation or warranty about the information contained in this document or the products referenced herein. Caterpillar welcomes additional “Best Practice” recommendations from our dealer network.

1.0 Introduction

A few dealers have installed remote control cameras in the dyno test cell. The test cell operator can conduct the dyno test, monitor changes, and visually monitor the engine, all without leaving the control room.

2.0 Best Practice Description

This Best Practice has been implemented by Ferreyros. Three wall mount remote control cameras are located in the dyno test cell. The cameras can operate by a toggle switch and pan from side to side and zoom in as required. Ferreyros has installed one camera on each side of the engine, and another in front of the engine. A video monitor in the control room displays images.

3.0 Implementation Steps

Acquire cameras, monitors, and remote control hardware. Approximate cost \$1500 per camera.



THE INFORMATION HEREIN MAY NOT BE COPIED OR TRANSMITTED TO OTHERS WITHOUT THE WRITTEN PERMISSION OF CATERPILLAR

Remote Control Cameras in Dyno Room Improve
Safety

DATE
4/12/2017

CHG
NO
01

NUMBER
0408-5.1-1118



THE INFORMATION HEREIN MAY NOT BE COPIED OR TRANSMITTED TO OTHERS WITHOUT THE WRITTEN PERMISSION OF CATERPILLAR			
Remote Control Cameras in Dyno Room Improve Safety	DATE 4/12/2017	CHG NO 01	NUMBER 0408-5.1-1118

4.0 Benefits

- Technician can monitor both instruments and visual condition at the same time.
- Technician does not have to enter the dyno test cell at any point during the test.
- Technician not expose to trip or fall hazards.

5.0 Resources Required

- Purchase and install cameras

6.0 Supporting Attachments / References

None.

7.0 Related Best Practices

None at this time.

8.0 Acknowledgements

Special thanks to:

Aninu Mitacc
Ferreiros
CRC Quality, Safety, and Continuous Improvement Manager

Written by

Dale Brehm
6 Sigma Black Belt
Cat Global Mining Product Support

THE INFORMATION HEREIN MAY NOT BE COPIED OR TRANSMITTED TO OTHERS WITHOUT THE WRITTEN PERMISSION OF CATERPILLAR

Remote Control Cameras in Dyno Room Improve
Safety

DATE
4/12/2017

CHG
NO
01

NUMBER
0408-5.1-1118