```
# collection = single "variable" used to store multiple values
#   List  = [] ordered and changeable. Duplicates OK
#   Set   = {} unordered and immutable, but Add/Remove OK. NO duplicates
#   Tuple = () ordered and unchangeable. Duplicates OK. FASTER
```

main.py

```python
# collection = single "variable" used to store multiple values
#   List  = [] ordered and changeable. Duplicates OK
#   Set   = {} unordered and immutable, but Add/Remove OK. NO duplicates
#   Tuple = () ordered and unchangeable. Duplicates OK. FASTER

fruits = ["apple", "orange", "banana", "coconut"]

print(fruits[1])
```

```python
# collection = single "variable" used to store multiple values
#   List  = [] ordered and changeable. Duplicates OK
#   Set   = {} unordered and immutable, but Add/Remove OK. NO duplicates
#   Tuple = () ordered and unchangeable. Duplicates OK. FASTER

fruits = ["apple", "orange", "banana", "coconut"]

print(fruits[::-1])
```

```
['coconut', 'banana', 'orange', 'apple']
```

main.py

```python
# collection = single "variable" used to store multiple values
#   List  = [] ordered and changeable. Duplicates OK
#   Set   = {} unordered and immutable, but Add/Remove OK. NO duplicates
#   Tuple = () ordered and unchangeable. Duplicates OK. FASTER

fruits = ["apple", "orange", "banana", "coconut"]

print(fruits[::2])
```

ain.py

```python
# collection = single "variable" used to store multiple values
#   List  = [] ordered and changeable. Duplicates OK
#   Set   = {} unordered and immutable, but Add/Remove OK. NO duplicates
#   Tuple = () ordered and unchangeable. Duplicates OK. FASTER

fruits = ["apple", "orange", "banana", "coconut"]

# print(fruits[0])

for fruit in fruits:
    print(x)
```

```python
# collection = single "variable" used to store multiple values
#   List  = [] ordered and changeable. Duplicates OK
#   Set   = {} unordered and immutable, but Add/Remove OK. NO duplicates
#   Tuple = () ordered and unchangeable. Duplicates OK. FASTER

fruits = ["apple", "orange", "banana", "coconut"]
print(dir(fruits))

# print(fruits[0])
# for fruit in fruits:
    # print(fruit)
```

```
['__add__', '__class__', '__class_getitem__', '__contains__', '__delattr__', '__delitem__', '__dir__', '__doc__
```

main.py

```python
# collection = single "variable" used to store multiple values
#   List  = [] ordered and changeable. Duplicates OK
#   Set   = {} unordered and immutable, but Add/Remove OK. NO duplicates
#   Tuple = () ordered and unchangeable. Duplicates OK. FASTER

fruits = ["apple", "orange", "banana", "coconut"]
# print(dir(fruits))
# print(help(fruits))
# print(len(fruits))
print("pineapple" in fruits)

# print(fruits[0])
```

View Navigate Code Refactor Run Tools VCS Window Help practice - main.py

main.py

```
# print("pineapple" in fruits)

# fruits[0] = "pineapple"
# fruits.append("pineapple")
# fruits.remove("apple")
# fruits.insert(0, "pineapple")
# fruits.sort()
# fruits.reverse()
# fruits.clear()
# print(fruits.index("apple"))
print(fruits.count("pine"))

print(fruits)
```

```python
# collection = single "variable" used to store multiple values
#   List  = [] ordered and changeable. Duplicates OK
#   Set   = {} unordered and immutable, but Add/Remove OK. NO duplicates
#   Tuple = () ordered and unchangeable. Duplicates OK. FASTER

fruits = ["apple", "orange", "banana", "coconut"]
# print(dir(fruits))
# print(help(fruits))
# print(len(fruits))
# print("pineapple" in fruits)

# fruits[0] = "pineapple"
# fruits.append("pineapple")
```

main.py

```python
# collection = single "variable" used to store multiple values
#   List  = [] ordered and changeable. Duplicates OK
#   Set   = {} unordered and immutable, but Add/Remove OK. NO duplicates
#   Tuple = () ordered and unchangeable. Duplicates OK. FASTER

fruits = {"apple", "orange", "banana", "coconut"}
# print(dir(fruits))
# print(help(fruits))
# print(len(fruits))
# print("pineapple" in fruits)

# fruits[0] = "pineapple"
# fruits.append("pineapple")
```

practice / main.py

main.py

```python
# collection = single "variable" used to store multiple values
#   List  = [] ordered and changeable. Duplicates OK
#   Set   = {} unordered and immutable, but Add/Remove OK. NO duplicates
#   Tuple = () ordered and unchangeable. Duplicates OK. FASTER

fruits = {"apple", "orange", "banana", "coconut"}
# print(dir(fruits))
# print(help(fruits))
# print(len(fruits))
# print("pineapple" in fruits)

print(fruits)
#for fruit in fruits:
```

Run: main

```
{'orange', 'apple', 'banana', 'coconut'}
```

```python
# collection = single "variable" used to store multiple values
#   List  = [] ordered and changeable. Duplicates OK
#   Set   = {} unordered and immutable, but Add/Remove OK. NO duplicates
#   Tuple = () ordered and unchangeable. Duplicates OK. FASTER

fruits = {"apple", "orange", "banana", "coconut"}
# print(dir(fruits))
# print(help(fruits))
# print(len(fruits))
# print("pineapple" in fruits)

print(fruits[0])
```

```
    print(fruits[0])
TypeError: 'set' object is not subscriptable
```

You cannot use indexing on a set because it is unordered.

Edit View Navigate Code Refactor Run Tools VCS Window Help practice - main.py

main.py

main

main.py

ctice C:\Users\HP\Pych

venv

main.py

ernal Libraries

atches and Consoles

```
fruits = {"apple", "orange", "banana", "coconut"}
# print(dir(fruits))
# print(help(fruits))
# print(len(fruits))
# print("pineapple" in fruits)

# fruits.add("pineapple")
# fruits.remove("apple")
# fruits.pop()
fruits.clear()
```

main.py

```python
# collection = single "variable" used to store multiple values
#   List  = [] ordered and changeable. Duplicates OK
#   Set   = {} unordered and immutable, but Add/Remove OK. NO duplicates
#   Tuple = () ordered and unchangeable. Duplicates OK. FASTER

fruits = ("apple", "orange", "banana", "coconut", "coconut")
# print(dir(fruits))
# print(help(fruits))
# print(len(fruits))
# print("pineapple" in fruits)

# fruits.add("pineapple")
# fruits.remove("apple")
```

main.py

```python
#   Tuple = () ordered and unchangeable. Duplicates OK. FASTER

fruits = ("apple", "orange", "banana", "coconut", "coconut")
# print(dir(fruits))
# print(help(fruits))
# print(len(fruits))
# print("pineapple" in fruits)

# print(fruits.index("apple"))
print(fruits.count("coconut"))

print(fruits)
#for fruit in fruits:
    #print(fruit)
```

https://youtu.be/gOMW_n2-2Mw