```
AvokTech API Documentation
V 0.1.7
6/23/2015
Schemas
Account:
  id: String,
                                 unique for each user
  firstName: String,
  lastName: String,
  email: String,
                                 functions as a username (unique)
  password: String,
                                 the value is hashed for security
  phone: String,
  photo: Object,
  paid: boolean,
  billingAddress: {
                                 Address class
     street: String,
     city: String,
     state: String,
     zipcode: String
  },
  creditCard: String,
                                 TBD
                                 maps a lot id to the corresponding role,
  lots: Map<String, String>,
                                    including:
                                    owner, manager, patrol, etc.
  roles: Set<String>
                                 set of systems admin roles, including:
                                    super, analytics, onboarding, etc.
Lot:
  id: String,
                                 unique for each lot
  name: String,
                                 `residential` vs. `parking lot`
  type: String,
                                 Address class
  address: {
     street: String,
     city: String,
     state: String,
     zipcode: String
  },
  location: double[],
                                (lng, lat) pair
  photo: Object,
  price: Map<String, double>, maps the price type (hourly, daily, etc.) to the
                                    value of the price
  priceRatio: double,
                                scale multiplier of price (default 1.0)
```

capacity: int,
occupied: int,

available: boolean, if the lot is available (does not include

reservable spaces)

reservable: boolean,

reserveMax: int, the maximum number of reservable spaces

calendar: Set<Long> a set of the weekly reservable times

Reservation:

id: String, unique for each reservation

accountId: String, the account associated with the reservation

firstName: String,

lastName: String,

lotId: String, the lot associated with the reservation

status: String the status of the reservation, including:

active, cancelled, deleted, etc.

LotHistory:

time: long,
occupied: int

}>,

SearchHistory:

Endpoints

Required fields are listed under the endpoint.

Optional fields are in italics.

All `date` fields are represented in milliseconds.

GET

Account:

/listAccounts return all accounts

/accountById returns account with corresponding id

accountId

/accountByEmail returns account with corresponding email

email

/getLots returns all of the lots of the user

accountId

Lot:

/listLots returns all lots

/lotById returns lot with corresponding id

lotId

/searchNear returns lots within 1 mile of the location

latitude longitude

/getMembers returns the account ids of members of the lot

lotId

Reservation:

/listReservations returns all reservations

/reservationById returns reservation with corresponding id

reservationId

/reservationsByAccountId returns reservations for corresponding account

accountId

/reservationsByLotId returns reservations for corresponding lot

lotId

 $/ {\tt active Reservations By Account Id} \textit{returns active reservations for corresponding}$

accountId account

/activeReservationsByLotId returns active reservations for corresponding lot

lotId

LotHistory:

/listLotHistory returns all lot history

/lotHistory returns lot history for corresponding lot

lotId

SearchHistory:

/listSearchHistory returns all search history

```
accountId
POST
Account:
                                  handles login (returns false if incorrect
  /login
     email
                                    password)
     password
  /signup
                                  handles signup and creates a new account
     firstName
     lastName
     email
     password
  /addRole
                                  adds a systems admin role to the account
     accountId
     role
  /addLot
                                  adds a lot and corresponding role to the account
     accountId
     lotId
     role
Lot:
                                  creates a new lot (returns updated account)
   /newLot
     accountId
     name
     type
     address
     latitude
     longitude
     capacity
     reserveMax
                                     a list of the times for the calendar
     calendar
  /entered
                                  increases the occupancy of the lot by 1
     lotId
  /exited
                                  decreases the occupancy of the lot by 1
     lotId
  /changeReserveMax
                                  changes the number of reservable spots
     lotId
     reserveMax
  /setCalendar
                                  adds a member to the lot
     lotId
     calendar
                                    a list of the times for the calendar
Reservation:
```

creates a new reservation

returns search history for corresponding account

/searchHistory

/reserve

accountId lotId

startTimes start times of reservations

durations durations of reservations (in hours)

SearchHistory:

/addSearchHistory adds a new search history point

accountId this field is optional

latitude longitude

DELETE

Account:

/deleteAccount deletes account with corresponding id

accountId

Lot:

/deleteLot deletes lot with corresponding id

lotId

LotHistory:

/deleteAllLotHistory deletes all lot history

/deleteLotHistory deletes lot history for corresponding lot

lotId

SearchHistory:

/deleteAllSearchHistory deletes all search history

/deleteSearchHistory deletes search history for corresponding account

accountId