

The OpenGL Mathematics (GLM) Library

Mike Bailey

mjb@cs.oregonstate.edu

Oregon State University



This work is licensed under a [Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License](https://creativecommons.org/licenses/by-nc-nd/4.0/)



Oregon State University
Computer Graphics

What is GLM?

2

GLM is a set of C++ classes and functions to fill in the programming gaps in writing the basic vector and matrix mathematics for OpenGL applications.

GLM isn't really a *library* – it is all specified in ***.hpp** header files so that it gets compiled in with your source code.

You can find it at:

<http://glm.g-truc.net/0.9.4/>

You invoke GLM like this:

#include <glm/glm.hpp>

Or, you can #include only the specific GLM .hpp files you need.

If GLM is not installed in a system place, put it somewhere you can get access to. Later on, these notes will show you how to use it from there.



Why are we even talking about this?

3

The OpenGL overlords have “deprecated” some of the OpenGL functions we have been using to perform transformations. In the desktop world, it means that the use of such functions is **discouraged**. In the mobile world of OpenGL-ES, it means those functions are **gone**. You might as well become familiar with how to live without them. So, instead of saying:

```
gluLookAt( 0., 0., 3., 0., 0., 0., 0., 1., 0. );  
glRotatef( (GLfloat)Yrot, 0., 1., 0. );  
glRotatef( (GLfloat)Xrot, 1., 0., 0. );  
glScalef( (GLfloat)Scale, (GLfloat)Scale, (GLfloat)Scale );
```

you would say:

```
glm::mat4 modelview;  
glm::vec3 eye(0.,0.,3.);  
glm::vec3 look(0.,0.,0.);  
glm::vec3 up(0.,1.,0.);  
modelview = glm::lookAt( eye, look, up );  
modelview = glm::rotate( modelview, D2R*Yrot, glm::vec3(0.,1.,0.) );  
modelview = glm::rotate( modelview, D2R*Xrot, glm::vec3(1.,0.,0.) );  
modelview = glm::scale( modelview, glm::vec3(Scale,Scale,Scale) );  
glMultMatrixf( glm::value_ptr( modelview ) );
```

Exactly the same concept, but a different expression of it. Read on for details ...



The Most Useful GLM Variables, Operations, and Functions⁴

// constructor:

```
glm::mat4( );  
glm::vec4( );           // identity matrix  
glm::vec3( );
```

GLM recommends that you use the “**glm::**” syntax and not use “**using namespace**” syntax

// multiplications:

```
glm::mat4 * glm::mat4  
glm::mat4 * glm::vec4  
glm::mat4 * glm::vec4( glm::vec3 )    // promote vec3 to a vec4
```

// emulating OpenGL transformations *with concatenation*:

```
glm::mat4 glm::rotate( glm::mat4 const & m, float angle, glm::vec3 const & axis);
```

```
glm::mat4 glm::scale( glm::mat4 const & m, glm::vec3 const & factors);
```

```
glm::mat4 glm::translate( glm::mat4 const & m, glm::vec3 const & translation);
```

The Most Useful GLM Variables, Operations, and Functions⁵

// viewing volume (assign, not concatenate):

```
glm::mat4 glm::ortho( float left, float right, float bottom, float top, float near, float far);
```

```
glm::mat4 glm::ortho( float left, float right, float bottom, float top );
```

```
glm::mat4 glm::frustum( float left, float right, float bottom, float top, float near, float far);
```

```
glm::mat4 glm::perspective( float fovy, float aspect, float near, float far);
```

// viewing (assign, not concatenate):

```
glm::mat4 glm::lookAt( glm::vec3 const & eye, glm::vec3 const & look, glm::vec3 const & up);
```

// loading matrices into opengl:


```
glLoadMatrix( glm::value_ptr( glm::mat4 ) );
```

```
glUniformMatrix4fv( Location, 1, GL_FALSE, glm::value_ptr( glm::mat4 ) );
```

Installing GLM into your own space


6

I like to just put the whole thing under my Visual Studio project folder so I can zip up a complete project and give it to someone else.



Here's what that GLM folder looks like


7



Telling Linux about where the GLM folder is

8

```
g++ ... -I. ...
```




“minus-capital-eye-period” means “also look for the < > includes in this same folder”

Instead of the period, you can list a full or relative pathname.

Telling Visual Studio about where the GLM folder is

9


1.



Telling Visual Studio about where the GLM folder is

10

A **period**, indicating that the **project folder** should also be searched when a **#include <xxx>** is encountered. If you put it somewhere else, enter that full or relative path instead.



Using Transformations OpenGL-style

11

```
glMatrixMode( GL_PROJECTION );
glLoadIdentity( );
if( WhichProjection == ORTHO )
    glOrtho( -3., 3., -3., 3., 0.1, 1000. );
else
    gluPerspective( 90., 1., 0.1, 1000. );

// place the objects into the scene:
glMatrixMode( GL_MODELVIEW );
glLoadIdentity( );

// set the eye position, look-at position, and up-vector:
gluLookAt( 0., 0., 3., 0., 0., 0., 0., 1., 0. );

// rotate the scene:
glRotatef( (GLfloat)Yrot, 0., 1., 0. );
glRotatef( (GLfloat)Xrot, 1., 0., 0. );

// uniformly scale the scene:
if( Scale < MINSCALE )
    Scale = MINSCALE;
glScalef( (GLfloat)Scale, (GLfloat)Scale, (GLfloat)Scale );
```



Using Transformations GLM-style, I

12

```
#include <glm/vec3.hpp>
#include <glm/mat4x4.hpp>
#include <glm/gtc/matrix_transform.hpp>
#include <glm/gtc/type_ptr.hpp>

...

// convert degrees to radians:
const float D2R = M_PI/180.f;           // 0.01745...

...

glMatrixMode( GL_PROJECTION );
glLoadIdentity( );
glm::mat4 projection;

if( WhichProjection == ORTHO )
    projection = glm::ortho( -3., 3.,   -3., 3.,   0.1, 1000. );
else
    projection = glm::perspective( 90., 1., 0.1, 1000. );

// apply the projection matrix:
glMultMatrixf( glm::value_ptr( projection ) );
```

// place the objects into the scene:

```
glMatrixMode( GL_MODELVIEW );  
glLoadIdentity( );  
glm::mat4 modelview;
```

// set the eye position, look-at position, and up-vector:

```
glm::vec3 eye(0.,0.,3.);  
glm::vec3 look(0.,0.,0.);  
glm::vec3 up(0.,1.,0.);  
modelview = glm::lookAt( eye, look, up );
```

**// rotate the scene (warning -- unlike OpenGL's glRotatef,
// GLM's rotate method takes angles in *radians*):**

```
modelview = glm::rotate( modelview, D2R*Yrot, glm::vec3(0.,1.,0.) );  
modelview = glm::rotate( modelview, D2R*Xrot, glm::vec3(1.,0.,0.) );
```

// uniformly scale the scene:

```
if( Scale < MINSCALE )  
    Scale = MINSCALE;  
modelview = glm::scale( modelview, glm::vec3(Scale,Scale,Scale) );
```

// apply the modelview matrix:

```
glMultMatrixf( glm::value_ptr( modelview ) );
```