

# lightsail

Here's a policy that grants necessary permissions for managing Lightsail instances:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "VisualEditor0",
      "Effect": "Allow",
      "Action": [
        "lightsail:CreateRelationalDatabaseSnapshot",
        "lightsail:GetRelationalDatabaseEvents",
        "lightsail:CreateContainerService",
        "lightsail:GetKeyPair",
        "lightsail:GetContactMethods",
        "lightsail:GetCloudFormationStackRecords",
        "lightsail:GetContainerServiceDeployments",
        "lightsail:GetBucketAccessKeys",
        "lightsail:CreateContainerServiceRegistryLogin",
        "lightsail:GetContainerImages",
        "lightsail:CreateRelationalDatabase",
        "lightsail:CreateContactMethod",
        "lightsail:CreateDistribution",
        "lightsail:GetDomain",
        "lightsail:GetBuckets",
        "lightsail:GetRelationalDatabaseParameters",
        "lightsail:GetInstanceState",
        "lightsail:GetOperationsForResource",
        "lightsail:AllocateStaticIp",
        "lightsail:GetInstances",
        "lightsail:GetRelationalDatabase",
        "lightsail:CreateLoadBalancer",
        "lightsail:GetDistributionLatestCacheReset",
        "lightsail:GetLoadBalancerTlsPolicies",
        "lightsail:GetLoadBalancers",
        "lightsail:GetExportSnapshotRecords",
        "lightsail:GetAutoSnapshots",
        "lightsail:GetStaticIp",
        "lightsail:GetRelationalDatabaseBundles",
```

"lightsail:GetRelationalDatabaseBlueprints",  
"lightsail:CreateInstances",  
"lightsail:GetRelationalDatabaseLogEvents",  
"lightsail:GetContainerServices",  
"lightsail:GetRelationalDatabaseSnapshot",  
"lightsail:GetInstancePortStates",  
"lightsail:DeleteContactMethod",  
"lightsail:GetContainerServicePowers",  
"lightsail:GetKeyPairs",  
"lightsail:GetLoadBalancer",  
"lightsail:DisableAddOn",  
"lightsail:CreateCloudFormationStack",  
"lightsail:GetRelationalDatabaseSnapshots",  
"lightsail:UnpeerVpc",  
"lightsail:GetLoadBalancerTlsCertificates",  
"lightsail:GetAlarms",  
"lightsail:GetInstance",  
"lightsail:CreateDomain",  
"lightsail:GetDiskSnapshots",  
"lightsail:GetRelationalDatabaseMetricData",  
"lightsail:PeerVpc",  
"lightsail:CreateCertificate",  
"lightsail:CreateKeyPair",  
"lightsail:SendContactMethodVerification",  
"lightsail:GetStaticIps",  
"lightsail:GetRegions",  
"lightsail:GetOperation",  
"lightsail:GetDistributions",  
"lightsail:GetDomains",  
"lightsail:GetDisks",  
"lightsail:CreateDisk",  
"lightsail:GetBundles",  
"lightsail:GetInstanceMetricData",  
"lightsail:GetBucketBundles",  
"lightsail:GetContainerServiceMetricData",  
"lightsail:GetActiveNames",  
"lightsail:GetInstanceSnapshot",  
"lightsail:GetOperations",  
"lightsail:EnableAddOn",  
"lightsail:GetDistributionBundles",

```

        "lightsail:GetBlueprints",
        "lightsail:GetContainerAPIMetadata",
        "lightsail:GetCertificates",
        "lightsail:GetLoadBalancerMetricData",
        "lightsail:GetDiskSnapshot",
        "lightsail:DeleteAutoSnapshot",
        "lightsail:CopySnapshot",
        "lightsail:GetDisk",
        "lightsail:GetDistributionMetricData",
        "lightsail:GetRelationalDatabases",
        "lightsail:GetContainerLog",
        "lightsail:GetBucketMetricData",
        "lightsail:ImportKeyPair",
        "lightsail:DownloadDefaultKeyPair",
        "lightsail:IsVpcPeered",
        "lightsail:GetInstanceSnapshots",
        "lightsail:CreateBucket",
        "lightsail:GetRelationalDatabaseLogStreams",
        "lightsail:DeleteInstance",
        "lightsail:DeleteInstanceSnapshot",
        "lightsail:OpenInstancePublicPorts"
    ],
    "Resource": "*"
},
{
    "Sid": "VisualEditor1",
    "Effect": "Allow",
    "Action": [
        "lightsail:*",
        "network-firewall:*"
    ],
    "Resource": "arn:aws:lightsail:*:464063468077:Bucket/*"
}
]
}

```

Key actions included in this policy are:

```

"lightsail:DeleteInstance",
"lightsail:DeleteInstanceSnapshot",
"lightsail:OpenInstancePublicPorts"

```

This policy can be attached to a user or role to grant the necessary permissions.

```
import subprocess
import random
import string
import argparse
import yaml
import os

KEY_PATH = os.path.expanduser("~/Downloads/LightsailDefaultKey-ap-northeast-1.pem")

def _get_lightsail_instances():
    print("Fetching Lightsail instances...")
    try:
        result = subprocess.run(["aws", "lightsail", "get-instances"], capture_output=True, text=True, check=True)
        print("Lightsail instances fetched successfully.")
        return yaml.safe_load(result.stdout)
    except subprocess.CalledProcessError as e:
        print(f"Error getting Lightsail instances: {e}")
        return None
    except yaml.YAMLError as e:
        print(f"Error decoding YAML response: {e}")
        return None
    except Exception as e:
        print(f"An unexpected error occurred: {e}")
        return None

def _get_lightsail_instance(instance_name):
    print(f"Fetching details for instance: {instance_name}")
    try:
        result = subprocess.run(["aws", "lightsail", "get-instance", "--instance-name", instance_name], capture_output=True, text=True, check=True)
        instance_data = yaml.safe_load(result.stdout)
        if not instance_data or 'instance' not in instance_data:
            print(f"Could not find instance with name: {instance_name}")
            return None
        return instance_data['instance']
    except subprocess.CalledProcessError as e:
        print(f"Error getting instance details: {e}")
        return None
    except yaml.YAMLError as e:
        print(f"Error decoding YAML response: {e}")
        return None
```

```

        print(f"Error decoding YAML response: {e}")
        return None
    except Exception as e:
        print(f"An unexpected error occurred: {e}")
        return None

def create_lightsail_instance(instance_name=None, availability_zone="ap-northeast-1a", bundle_id="nano_2_0", user_data=None):
    if not instance_name:
        random_chars = ''.join(random.choice(string.ascii_lowercase) for _ in range(4))
        instance_name = f"{random_chars}"

    if not user_data:
        user_data = """#!/bin/bash
        sudo apt update
        """

    print(f"Creating Lightsail instance with name: {instance_name}, zone: {availability_zone}, bundle: {bundle_id}")

    command = [
        "aws", "lightsail", "create-instances",
        "--instance-names", instance_name,
        "--availability-zone", availability_zone,
        "--bundle-id", bundle_id,
        "--blueprint-id", "ubuntu_24_04"
    ]

    if user_data:
        command.extend(["--user-data", user_data])

    try:
        subprocess.run(command, check=True)
        print(f"Lightsail instance '{instance_name}' created successfully.")
        return instance_name
    except subprocess.CalledProcessError as e:
        print(f"Error creating Lightsail instance: {e}")
        return None

def delete_all_lightsail_instances(instance_name=None):
    if instance_name:
        print(f"Deleting instance: {instance_name}")

```

```

print(f"Executing command: aws lightsail delete-instance --instance-name {instance_name}")
try:
    subprocess.run(["aws", "lightsail", "delete-instance", "--instance-name", instance_name], check=True)
    print(f"Lightsail instance '{instance_name}' deleted successfully.")
except subprocess.CalledProcessError as e:
    print(f"Error deleting Lightsail instance: {e}")
return

instances_yaml = _get_lightsail_instances()
if not instances_yaml or 'instances' not in instances_yaml:
    print("No Lightsail instances found to delete.")
    return

instance_list = instances_yaml['instances']
if not instance_list:
    print("No Lightsail instances found to delete.")
    return

for instance in instance_list:
    instance_name = instance['name']
    print(f"Deleting instance: {instance_name}")
    print(f"Executing command: aws lightsail delete-instance --instance-name {instance_name}")
    subprocess.run(["aws", "lightsail", "delete-instance", "--instance-name", instance_name], check=True)
print("All Lightsail instances deleted successfully.")

def install_outline_server(instance_name):
    instance = _get_lightsail_instance(instance_name)
    if not instance:
        return
    public_ip = instance['publicIpAddress']
    print(f"Installing outline server on instance: {instance_name} with IP: {public_ip}")
    user_data = """#!/bin/bash
sudo apt update
sudo bash -c "$(wget -qO- https://raw.githubusercontent.com/Jigsaw-Code/outline-server/master/src/server_m
"""

os.chmod(KEY_PATH, 0o600)
print(f"Executing command: chmod 600 {KEY_PATH}")

```

```

ssh_command = [
    "ssh",
    "-i",
    KEY_PATH,
    f"ubuntu@{public_ip}",
    user_data
]

print(f"Executing command: {' '.join(ssh_command)}")
try:
    subprocess.run(ssh_command, check=True)
    print(f"Outline server installed on {instance_name} successfully.")
except subprocess.CalledProcessError as e:
    print(f"Error installing outline server: {e}")


def open_firewall_ports(instance_name):
    print(f"Opening firewall ports for instance: {instance_name}")
    for protocol in ["tcp", "udp"]:
        command = [
            "aws", "lightsail", "open-instance-public-ports",
            "--port-info", f"protocol={protocol},fromPort=1000,toPort=65535",
            "--instance-name", instance_name
        ]
        print(f"Executing command: {' '.join(command)}")
        subprocess.run(command, check=True)
    print(f"Firewall ports opened for instance '{instance_name}' successfully.")


if __name__ == "__main__":
    parser = argparse.ArgumentParser(description="Create or delete Lightsail instances.")
    parser.add_argument("--job", type=str, choices=["create", "delete", "install"], required=True, help="Action to perform")
    args = parser.parse_args()

    print(f"Setting AWS region to ap-northeast-1")
    subprocess.run(["aws", "configure", "set", "region", "ap-northeast-1"], check=True)

    if args.job == "create":
        instance_name = create_lightsail_instance()

```

```
    if instance_name:
        open_firewall_ports(instance_name)
elif args.job == "delete":
    instance_name = input("Enter the instance name to delete: ")
    delete_all_lightsail_instances(instance_name)
elif args.job == "install":
    instance_name = input("Enter the instance name to install Outline server on: ")
    install_outline_server(instance_name)
```