

Virtual Private Database for a University Information System

Row-level, column-level and write-path access control with Oracle VPD

Group 5 · October 2026

Team member	Matric no.
[Member 1 name]	[A0000000X]
[Member 2 name]	[A0000000X]
[Member 3 name]	[A0000000X]
[Member 4 name]	[A0000000X]
[Member 5 name]	[A0000000X]
[Member 6 name]	[A0000000X]

Implemented and verified on Oracle AI Database 26ai Free (23.26.2),
pluggable database CS5322 of the group virtual machine.

1 Introduction

Table-level grants cannot express most rules of a university information system. Students, professors, administrators and officers all query the same tables, yet each must see different rows, sometimes different columns, and may change different rows. Oracle Virtual Private Database (VPD) lets the database enforce such rules itself: a trusted *application context* carries the caller's identity, *policy functions* turn that identity into a SQL predicate, and Oracle appends the predicate to every statement that touches a protected table. The rules therefore cannot be skipped by an application bug or by hand-written SQL.

We hypothesise a university information system with six user roles over fourteen tables (students, professors, courses and their *sections*, enrolments, grades, payments and student housing). Its security policy goes beyond “users see their own rows”: department scope is derived through *section* → *course*, professors see their class lists, grades are drafts until a department administrator publishes them, a *resident fellow* sees the residents of the residence he currently looks after, and finance sees students but not their e-mail addresses.

The implementation consists of **27 VPD policies on 13 tables** (13 read policies, 13 write policies and one column-level policy), a trusted context package, two triggers and an audit table. **190 automated checks** (49 with simulated identities, 141 with real database logins) all pass; switching a policy off makes the matching checks fail. Everything was deployed and verified on the group's Oracle VM (Oracle AI Database 26ai Free 23.26.2, pluggable database CS5322).

2 Application and users

The system serves six kinds of users (Table 1). Each person has an own database account; the account name is mapped to an application role


and department in the table APP_USER.

Role	Accounts	Business need
Student	alice (Computing), bob (Business), carol (Medicine)	own academic, payment and housing records
Professor	prof_lee (Computing), prof_wong (Business)	teach sections, grade students; both are also resident fellows
Department administrator	admin_comp, admin_bus	manage the records of one department, publish grades
Finance officer	finance1	process payments; no academic data
Housing officer	housing1	allocate rooms; no academic or payment data
University administrator	uni_admin	read-only oversight, including the audit trail

Table 1. Roles and demo accounts.

The dummy data is small but contains the edge cases the policies must handle: CS5322 is offered twice by different professors (S1 Lee, S2 Wong), so a professor must see only his own offering; Bob (Business) takes the Computing course CS5322 S2 taught by a Business professor; Carol lives in Lee's residence without being in his class; Alice's second grade is still a draft; Wong's former fellowship of Kent Ridge Hall and Bob's old room allocation have ended. In total: 3 departments, 3 students, 2 professors, 4 courses, 5 sections, 5 enrolments, 4 grades, 3 payments, 2 residences, 5 rooms, 6 allocations and 3 fellowship records.

3 Database design



† foreign key to DEPARTMENT or APP_USER (lookup tables, drawn dashed); these lines are omitted to keep the diagram readable.
APP_USER maps a database login to its role and department; only the context package reads it and no role has a grant on it.

Figure 1. Schema (14 tables). Lines run from the referencing table to the referenced table.

COURSE is the catalogue entry; SECTION is one *offering* (course, professor, term, room). Teaching assignments live in SECTION, so policies can tell two professors teaching the same course apart. ENROLLMENT references a section, not a course. GRADE references an enrolment and carries a RELEASED flag (draft or published). ROOM_ALLOCATION assigns a room to a student or to a professor acting as resident fellow (a check constraint demands exactly one occupant); RESIDENT_FELLOW records which residence a professor currently looks after (status ACTIVE/ENDED). GRADE_AUDIT is filled only by a trigger. Primary, foreign and unique keys and check constraints (for example the grade domain and the status values) are declared in the schema.

4 Security requirements and threat model

We defend against four kinds of adversary: (T1) an authorised user who runs arbitrary SQL with his own account, for example a curious student with SQL*Plus; (T2) a user who tries to act as somebody else or to escalate his role; (T3) a defect or SQL injection in an application that connects with these accounts; (T4) an administration mistake that grants a role too much. The DBA, the operating system and network eavesdropping are out of scope (Section 9). Table 2 lists the requirements, the policy objects that enforce each of them and the test suites that check it.

ID	Requirement	Enforced by	Tested in
SR1	A student reads only his own student, enrolment, payment and housing rows.	STUDENT_VPD, ENROLLMENT_VPD, PAYMENT_VPD, ROOM_ALLOCATION_VPD	06, 07
SR2	A student sees only the sections he is enrolled in, their courses and instructors.	SECTION_VPD, COURSE_VPD, PROFESSOR_VPD	06, 07

ID	Requirement	Enforced by	Tested in
SR3	A student sees a grade only after it has been released.	GRADE_VPD	06, 07
SR4	A professor sees his own sections (not other offerings of the same course), their enrolments, grades (drafts included) and class list.	SECTION_VPD, ENROLLMENT_VPD, GRADE_VPD, STUDENT_VPD	06, 07
SR5	A professor may create or edit only <i>draft</i> grades of his own sections; he cannot publish a grade, change a published one or delete one.	GRADE_WRITE_VPD; no DELETE grant	08
SR6	A department administrator manages courses, sections, enrolments, students and grades of his department only, cannot move a record out of it, publishes and corrects grades, and deletes only drafts.	*_WRITE_VPD, GRADE_DELETE_VPD	08
SR7	Finance reads all payments and student names (not e-mail), records payments and never sees grades.	PAYMENT_VPD, PAYMENT_WRITE_VPD, STUDENT_EMAIL_MASK_VPD; no grant on GRADE	06, 07, 08
SR8	Housing officers read and manage all housing data and nothing academic or financial.	RESIDENCE*_VPD, ROOM_ALLOCATION_*; grants	07, 08
SR9	A resident fellow sees the residence he <i>currently</i> looks after: rooms, active allocations and the residents' names. An ended assignment grants nothing.	RESIDENT_FELLOW, RESIDENCE*_VPD, ROOM_ALLOCATION_VPD, STUDENT_VPD	06, 07
SR10	A student sees only his current residence and room and his own allocation history.	RESIDENCE_VPD, RESIDENCE_ROOM_VPD, ROOM_ALLOCATION_VPD	06, 07
SR11	University administrators read everything, including the audit trail, and write nothing.	grants, GRADE_AUDIT_VPD	07, 08
SR12	A missing or invalid identity returns no rows and permits no write.	every policy function returns 1=0	06, 07, 08
SR13	A database user cannot act as another application user.	CS5322_SECURITY_CTX.SET_USER	07
SR14	Write rules hold even if a privilege is granted by mistake, and every new row is validated.	*_WRITE_VPD with update_check	08, 09
SR15	The recorded editor of a grade cannot be spoofed; every grade change is audited with the real actor.	GRADE_EDITOR_TRG, GRADE_AUDIT_TRG	06, 08
SR16	Contact data (e-mail) is hidden from roles without a need for it.	STUDENT_EMAIL_MASK_VPD (column level)	06, 07

Table 2. Security requirements, enforcement and tests (06 = matrix, 07 = real-user reads, 08 = real-user writes, 09 = defense in depth).

5 VPD design

5.1 Trusted identity

Authentication is delegated to the database: every person logs in with an own account. The application then calls CS5322_SECURITY_CTX.SET_USER. This package is the only code allowed to write the context namespace CS5322_APP_CTX (Oracle enforces this through CREATE CONTEXT ... USING). It looks the account up in APP_USER and stores USER_ID, ROLE and DEPARTMENT_ID. A normal account can activate only its own name (Listing 1); any other name

raises ORA-20002. The schema owner, SYS and SYSTEM may activate any name so that the test scripts can simulate users. **Without an identity the role is NULL and every policy returns 1=0**: the system fails closed for reads and writes. Figure 2 shows how a statement travels from the login to the rewritten query.

```
IF v_session_user NOT IN ('CS5322_P1','SYS','SYSTEM')
AND v_session_user <> UPPER(p_username) THEN
  RAISE_APPLICATION_ERROR(-20002,
    'Session user cannot impersonate another application user');
END IF;
```

Listing 1. Impersonation check in SET_USER.




Figure 2. From login to the rewritten statement (the predicate is the text returned by GRADE_VPD_FN for alice).

5.2 Policy construction

Each policy function is a short CASE over the role. The fragments it needs — “my student id”, “my professor id”, “the sections of my department”, “the residences I look after” — are built by the helper package CS5322_VPD_HELPER, so all policies are written the same way, and every value spliced into a predicate is a number read from the context, never user input. Scope is *derived from the schema*, not taken from submitted values: department scope runs through SECTION → COURSE.department_id, a professor’s scope through SECTION.professor_id, a student’s through ENROLLMENT. All policies are CONTEXT_SENSITIVE: the predicate depends only on the context, so Oracle re-runs a policy function only when the context changes. Listing 2 is the policy that governs grade writes.

```
CREATE OR REPLACE FUNCTION grade_write_fn(
  p_schema VARCHAR2, p_object VARCHAR2)
RETURN VARCHAR2 IS
BEGIN
  RETURN CASE cs5322_vpd_helper.ctx_role
    WHEN 'PROFESSOR' THEN
      'released = 'N' AND enrollment_id IN '
      || cs5322_vpd_helper.professor_enrollments
    WHEN 'DEPT_ADMIN' THEN
      'enrollment_id IN '
      || cs5322_vpd_helper.dept_enrollments
    ELSE '1=0' END;
END;
```

Listing 2. Write policy of GRADE (insert and update).

5.3 Policy matrices

Every table has a SELECT policy and a separate policy for INSERT/UPDATE/DELETE that denies by default and validates the *new* row (update_check). Tables 3 and 4 summarise the rows each role can read and write; Table 5 shows the coarser layer underneath, the object privileges. A - means no rows (1=0) or no privilege.

Table	Student	Professor	Dept admin	Finance	Housing	Univ. admin
STUDENT	own row	students of his sections + residents of his residence (fellow)	own department	all rows, e-mail masked	students with a room allocation	all
PROFESSOR	instructors of his sections	own row	own department	-	-	all
COURSE	courses of his sections	courses of his sections	own department	-	-	all
SECTION	his sections	his sections	sections of own department's courses	-	-	all
ENROLLMENT	own	his sections	own department's sections	-	-	all
GRADE	own, released only	his sections, drafts included	own department's	-	-	all
PAYMENT	own	-	-	all	-	all
RESIDENCE, RESIDENCE_ROOM	current residence / room	those he looks after	-	-	all	all
ROOM_ALLOCATION	own (history too)	active allocations of his residence	-	-	all	all
RESIDENT_FELLOW	-	own assignments	-	-	all	all
GRADE_AUDIT	-	-	-	-	-	all
DEPARTMENT	all	all	all	all	all	all

Table 3. Read policies (<TABLE>_VPD): rows visible to each role.

Table	Who may write	Row scope
STUDENT, COURSE	dept admin	own department; a row cannot be moved to another department
SECTION, ENROLLMENT	dept admin	course / section belongs to the own department
GRADE insert, update	professor	draft of his own section, which must stay a draft of his own section
GRADE insert, update	dept admin	any grade of his department (publishes, corrects)
GRADE delete	dept admin	drafts of his department only; a published grade is permanent
PAYMENT	finance (no delete)	all payments
ROOM_ALLOCATION	housing (no delete)	all allocations
DEPARTMENT, PROFESSOR, RESIDENCE, RESIDENCE_ROOM, RESIDENT_FELLOW	nobody	-
GRADE_AUDIT	nobody (trigger only)	-

Table 4. Write policies (<TABLE>_WRITE_VPD, GRADE_DELETE_VPD).

Table	Student	Professor	Dept admin	Finance	Housing	Univ. admin
DEPARTMENT	S	S	S	S	S	S
STUDENT, COURSE, SECTION, ENROLLMENT	S	S	S I U D	S (student only)	S (student only)	S
PROFESSOR	S	S	S	-	-	S
GRADE	S	S I U	S I U D	-	-	S
PAYMENT	S	-	-	S I U	-	S
RESIDENCE, RESIDENCE_ROOM	S	S	-	-	S	S
ROOM_ALLOCATION	S	S	-	-	S I U	S
RESIDENT_FELLOW	-	S	-	-	S	S
GRADE_AUDIT, APP_USER	-	-	-	-	-	S (audit only)

Table 5. Object privileges per role (S select, I insert, U update, D delete). Finance and housing hold SELECT on STUDENT only; nobody holds a privilege on APP_USER.

5.4 Four policies worth explaining

Class list and residents. A professor's predicate on STUDENT is an OR of two subqueries: students enrolled in his sections, and students with an active allocation in a room of a residence he currently looks after. Lee therefore sees Alice (his class) and Carol (his resident but not his student) but not Bob. Because VPD also rewrites the subqueries, the nested ENROLLMENT, SECTION and ROOM_ALLOCATION policies apply inside the predicate. Table 6 shows the predicates Oracle appends in a few cases; the last row is the fail-closed case.

Grade workflow. A grade is a draft (RELEASED = 'N') until the department administrator publishes it. The student policy adds released = 'Y'. The professor's write policy requires released = 'N' and, through update_check, applies to the new row as well: the predicate that lets Lee edit a draft also forbids setting released to 'Y'

(ORA-28115) and hides published grades from UPDATE (0 rows). Separation of duties follows without any extra code.

Column-level masking. STUDENT_EMAIL_MASK_VPD (Listing 3) is registered with sec_relevant_cols => 'EMAIL' and ALL_ROWS. Finance still sees every student row (it needs names to reconcile payments), but the e-mail column comes back NULL.

Resident fellow — a design lesson. Our first design derived a fellow's residence from his own row in ROOM_ALLOCATION. A policy on ROOM_ALLOCATION then queried ROOM_ALLOCATION, and Oracle rejects such self-referencing predicates with ORA-28113; running the verification script on the VM exposed it for every housing table. The fellowship is now a table of its own (RESIDENT_FELLOW, with a status), so no policy queries the table it protects, and an *ended* assignment is simply ignored by the predicates.

Identity	Policy	Predicate appended by Oracle (returned by the policy function)
alice	STUDENT_VPD	user_id = 1001
alice	GRADE_VPD	released = 'Y' AND enrollment_id IN (SELECT e.enrollment_id FROM enrollment e WHERE e.student_id = (SELECT student_id FROM student WHERE user_id = 1001))
prof_lee	GRADE_WRITE_VPD	released = 'N' AND enrollment_id IN (SELECT e.enrollment_id FROM enrollment e WHERE e.section_id IN (SELECT x.section_id FROM section x WHERE x.professor_id = (SELECT professor_id FROM professor WHERE user_id = 2001)))
prof_lee	ROOM_ALLOCATION_VPD	(allocation_status = 'ACTIVE' AND room_id IN (SELECT rr.room_id FROM residence_room rr WHERE rr.residence_id IN (SELECT rf.residence_id FROM resident_fellow rf WHERE rf.status = 'ACTIVE' AND rf.professor_id = (SELECT professor_id FROM professor WHERE user_id = 2001))))
admin_comp	SECTION_VPD	course_id IN (SELECT c.course_id FROM course c WHERE c.department_id = 10)
finance1	STUDENT_VPD / STUDENT_EMAIL_MASK_VPD	1=1 / 1=0 (all rows; e-mail masked)
(no identity)	any policy	1=0

Table 6. Predicates generated for selected identities (04b_show_predicates.sql on the VM).

5.5 Triggers and defense in depth

Privileges, VPD and triggers are independent layers. Roles hold only the object privileges they need (Table 5), and the write policies would still stop a role that was granted too much: script 09 grants INSERT, UPDATE, DELETE on GRADE to the student role and shows that Alice changes 0 rows and cannot insert. A BEFORE trigger (Listing 4) overwrites LAST_UPDATED_BY with the authenticated user, so a writer cannot spoof it, and an AFTER trigger records every grade change (old and new value, actor, database user, time) in GRADE_AUDIT, which only the university administrator can read.

Attacks on the mechanism itself. Two attempts against the identity and the predicates were turned into regression tests. A user cannot forge the context by calling DBMS_SESSION.SET_CONTEXT himself: the namespace is bound to the package, and Oracle answers ORA-01031. A user who is allowed to create tables cannot hijack the unqualified table names inside a predicate (enrollment, student, ...) by creating look-alike tables: Oracle resolves them in the schema of the protected table, so a fake ENROLLMENT table in Alice's schema, claiming that Bob's and Carol's enrolments are hers, changes nothing (script 09).

```
DBMS_RLS.ADD_POLICY(
  object_schema => USER,
  object_name   => 'STUDENT',
  policy_name   => 'STUDENT_EMAIL_MASK_VPD',
  function_schema => USER,
  policy_function => 'STUDENT_EMAIL_MASK_FN',
  statement_types => 'SELECT',
  policy_type    => DBMS_RLS.CONTEXT_SENSITIVE,
  sec_relevant_cols => 'EMAIL',
  sec_relevant_cols_opt => DBMS_RLS.ALL_ROWS);
```

Listing 3. Column-level policy registration.

```
CREATE OR REPLACE TRIGGER grade_editor_trg
BEFORE INSERT OR UPDATE ON grade
FOR EACH ROW
DECLARE
  v_uid VARCHAR2(30) :=
    SYS_CONTEXT('CS5322_APP_CTX', 'USER_ID');
BEGIN
  IF v_uid IS NOT NULL THEN
    :NEW.last_updated_by := TO_NUMBER(v_uid);
  END IF;
END;
```

Listing 4. The recorded editor is the authenticated user.

5.6 Why VPD

Views and stored procedures could express some of these rules, but every client would have to use them: a forgotten view or a direct table access bypasses them. VPD attaches the rule to the table, so it applies to

every access path, including ad-hoc SQL tools and application code, and to INSERT, UPDATE and DELETE as well. The price is that policies are invisible to the application and therefore need tests (Section 7), that a predicate cannot query the table it protects, and that privileged accounts are exempt. Oracle Label Security, the subject of Project II, covers classification-based rules; VPD fits the attribute- and relationship-based rules of this system.

6 Implementation

All objects live in the schema CS5322_P1 of the pluggable database CS5322: 14 tables, 23 policy functions, 3 packages, 2 triggers, 27 policies, 6 roles and 10 demo accounts. The scripts are separated by the privilege they need (Table 7). 00_run_all.sql resets, deploys, verifies and runs the demonstration in a few seconds and records one log per step.

Script	Run as	Purpose
00, 01	SYSDBA, owner	schema owner; tables, triggers, context package, data
02 (+ regrant)	SYSDBA	demo accounts, six roles, object privileges
03, 03b	owner (not SYS)	helper package, policy functions, DBMS_RLS policies; assertion helper
04, 04b, 06	owner	visibility matrix; generated predicates; automated verification
07, 08, 09	real users	read, write and defense-in-depth tests
10	real users	optional mutation check (policies off)
demo	real users	live demonstration (restores the data)

Table 7. Scripts and execution identities.

The policy script must run as the schema owner: the policy functions and the policies have to live in the same schema as the tables, and SYS is exempt from VPD. Object privileges are re-granted by a single script, because Oracle drops grants together with the tables, and the account scripts are re-runnable (they reset the demo passwords and unlock an account that failed logins locked).

7 Testing and evaluation

Method. Three layers of tests, all automated with PASS/FAIL output.

(1) *Visibility matrix* (script 06): for every identity (ten users and “no identity”) the row count of every table is compared with a matrix derived by hand from the data and the rules, independently of the policy code. (2) *Real logins* (scripts 07 and 08): each user connects with his own account, activates his identity and runs reads, impersonation attempts, writes and attempts that must be refused; statements run with the caller's privileges and the policies. (3) *Negative controls*: script 09 (a mistaken grant, a look-alike table) and a mutation check (script 10) that switches policies off.

Suite	Checks	Content
06 verification	49	27 policies enabled, all objects valid, SELECT and DML policy on every table, 11 × 13 visibility matrix, column masking, draft grades, spoof-proof editor, audit trail
07 real-user reads	84	ten logins: expected counts, impersonation (ORA-20002), forged context (ORA-01031), tables without grant (ORA-00942), fail-closed before and after <code>clear_user</code>
08 real-user writes	52	allowed writes, rows hidden from the write policy (0 rows), ORA-28115, privilege refusals
09 defense in depth	5	the write policy blocks a role that was granted INSERT/UPDATE/DELETE; a look-alike table cannot redirect a predicate
Total	190	all PASS on the group VM; the data is unchanged afterwards (06 repeated)

Table 8. Automated checks.

	department	student	professor	course	section	enrollment	grade	payment	residence	residence room	room allocation	resident fellow	grade audit
alice	3	1	1	2	2	2	1	1	1	1	1	0	0
bob	3	1	1	2	2	2	1	1	1	1	2	0	0
carol	3	1	1	1	1	1	1	1	1	1	1	0	0
prof_lee	3	2	1	2	2	2	2	0	1	3	3	1	0
prof_wong	3	2	1	3	3	3	2	0	1	2	2	2	0
admin_comp	3	1	1	2	3	3	2	0	0	0	0	0	0
admin_bus	3	1	1	1	1	1	1	0	0	0	0	0	0
finance1	3	3	0	0	0	0	0	3	0	0	0	0	0
housing1	3	3	0	0	0	0	0	0	2	5	6	3	0
uni_admin	3	3	2	4	5	5	4	3	2	5	6	3	0
(no identity)	0	0	0	0	0	0	0	0	0	0	0	0	0

Rows each identity sees (SELECT COUNT(*)); shading = share of the table; uni_admin sees the full table. Source: 04_tests.sql run on the group VM.

Figure 3. Rows visible to each identity in each table (output of 04_tests.sql on the VM).

Figure 3 shows the matrix. Each row is one policy decision: for example bob sees two enrolments and two allocations (his current room and a past one), prof_lee sees three allocations (the active ones of Kent Ridge Hall), prof_wong sees two (his residence) although he once looked after Kent Ridge Hall, finance1 sees all students and payments but no grade, and with no identity every count is 0. Table 9 lists representative negative tests.

Identity	Statement	Result
alice	set_user('bob')	ORA-20002
alice	UPDATE grade ...	ORA-41900 (no privilege)
alice	DBMS_SESSION.SET_CONTEXT('CS5322_APP_CTX', ...)	ORA-01031
alice, may create tables	create a look-alike ENROLLMENT table	no effect (still 1 grade)
prof_lee	update released grade 90001	0 rows
prof_lee	UPDATE grade SET released = 'Y'	ORA-28115
prof_lee	grade a student of prof_wong	ORA-28115
prof_lee	set last_updated_by = 2002	stored as 2001
admin_comp	insert a Business course	ORA-28115
admin_comp	move a student to Business	ORA-28115
admin_comp	delete a published grade	0 rows
finance1	SELECT COUNT(email) FROM student	0 (masked)
finance1	SELECT ... FROM grade	ORA-00942
no identity	INSERT INTO grade ...	ORA-28115

Table 9. Selected negative tests.

Do the tests detect errors? With GRADE_WRITE_VPD switched off, 11 of the 52 write checks fail; with GRADE_VPD switched off, 7 of the 84 read checks fail (Alice then sees all four grades). Restoring the policies brings the verification back to 49/49.

The logs of the final run are part of the repository:

project1_verification.log, project1_real_user_smoke.log, project1_write_tests.log, project1_defense_in_depth.log, project1_mutation_check.log, project1_visibility_matrix.log,

project1_predicates.log and the echoed transcript project1_demo.log.

What testing found. (i) ORA-28113 in the housing policies (see above). (ii) Oracle 23ai reports a missing DML privilege as ORA-41900 instead of ORA-01031; the first run of the write tests flagged this, and the helper now accepts both. (iii) The first smoke test printed no result for its second and third login, because in SQL*Plus SET SERVEROUTPUT ON does not survive repeated CONNECT commands (we reproduced this); the scripts now set it after every login so that a FAIL can never be silent.

8 Demonstration plan

demo.sql logs in as real users and echoes every statement. (1) *alice* — no rows before an identity is set, own rows afterwards, draft grade hidden, cannot become *bob*, cannot write. (2) *prof_lee* — class list plus resident, draft versus published grade, ORA-28115 when publishing or grading another professor's student, fellow view of Kent Ridge Hall. (3) *prof_wong* — another residence; the ended fellowship grants nothing. (4) *admin_comp* — own department, publishing a grade, ORA-28115 for a Business course. (5) *finance1* — masked e-mail, payments, no grades. (6) *housing1* — all allocations, nothing academic. (7) *uni_admin* — read-only oversight and the audit trail showing the real actor of a grade change. The script restores the data at its end;

04b_show_predicates.sql can be shown to explain how a policy turns an identity into a predicate. Listing 5 is an excerpt of the transcript recorded on the VM (schema prefix omitted).

```
SQL> SELECT grade_id, enrollment_id, grade_value, released FROM
grade;
GRADE_ID ENROLLMENT_ID GRADE RELEASED
90001      10001 A      Y
90004      10004 B      N
SQL> UPDATE grade SET grade_value = 'B+' WHERE grade_id = 90004;
1 row updated.
SQL> UPDATE grade SET grade_value = 'A+' WHERE grade_id = 90001;
0 rows updated.
SQL> UPDATE grade SET released = 'Y' WHERE grade_id = 90004;
ORA-28115: policy with check option violation
```

Listing 5. prof_lee edits a draft but can neither change nor publish.

9 Limitations and future work

- **Privileged accounts bypass VPD.** SYS and any account with EXEMPT ACCESS POLICY are exempt; we verified that SYS sees all rows without an identity. Protecting data from a DBA needs Database Vault and auditing.
- **Identity is trusted from the session.** The schema owner, SYS and SYSTEM can activate any application user (a test convenience). A real deployment would set the context from a logon trigger or a trusted login service.
- **Constraints leak existence.** Integrity checks ignore VPD: when admin_comp enrolls the Business student 2, whom he cannot see, the insert succeeds, while the non-existent student 99 fails with ORA-02291; he can probe which ids exist.
- **Scope.** Data at rest and in transit are not encrypted, passwords are demo values, and the data set is tiny; with large data the ENROLLMENT/SECTION subqueries rely on the indexes created in the

schema. Oracle unified auditing, Real Application Security and Data Redaction are natural extensions.

10 Conclusion

Oracle VPD expresses the rules of a university information system as small, testable SQL predicates enforced inside the database for reads, writes and individual columns. Deriving scope from the schema, validating every new row, failing closed without an identity and testing with real logins and negative controls gave a policy set whose behaviour we could verify end to end on the group VM, including the design error that only this verification exposed.

References

1. Oracle, *Database Security Guide*: “Using Oracle Virtual Private Database to Control Data Access”.
2. Oracle, *PL/SQL Packages and Types Reference*: DBMS_RLS and DBMS_SESSION.

Contribution Statement

Each member's contribution to the project. The shares add up to 100 %.

Member	Contribution	Share
[Member 1 name] [A0000000X]	[What this member actually did: scripts, tests, report sections, demo]	[]%
[Member 2 name] [A0000000X]	[What this member actually did]	[]%
[Member 3 name] [A0000000X]	[What this member actually did]	[]%
[Member 4 name] [A0000000X]	[What this member actually did]	[]%
[Member 5 name] [A0000000X]	[What this member actually did]	[]%
[Member 6 name] [A0000000X]	[What this member actually did]	[]%

Evidence of individual work: scripts and commits in the project repository, the logs `project1_*.log` produced on the VM, and the review of each other's work.