

Lesson 11

# REACT OBJECTS AND LISTS

# **WORKING WITH STATE OBJECTS**

# Routing with state

React App

localhost:3000

## Page 1

Name

React App

localhost:3000/paget...

Username: John Doe

## Page 2

Address

React App

localhost:3000/paget...

Username: John Doe  
Address: Mainstreet 1 Chicago

## Page 3

Creditcard number

React App

localhost:3000/pagef...

## Thank you for your order!

Username: John Doe  
Address: Mainstreet 1 Chicago  
Creditcard: 97865435321

# State values: pageone.js

```
import React, { useState } from 'react';

export const Pageone = (props) => {
  const [firstname, setFirstname] = useState("");
  const [lastname, setLastname] = useState("");

  const handleOnSubmit = () => {
    props.history.push("/pagetwo", {firstname:firstname, lastname : lastname});
  }
}
```

What if we have many form fields?

Pass all state values

React App

localhost:3000

## Page 1

Firstname

Lastname

React App

localhost:3000/pagetwo

First name: Frank  
Last name: Brown


## Page 2

Address

# State values: pageone.js

```
let page1 = (  
  <form>  
    <h3>Page 1</h3>  
    <div>  
      First name  
      <input  
        type="text"  
        placeholder="First name"  
        value={firstname}  
        onChange={e => setFirstname(e.target.value)} />  
    </div>  
    <div>  
      Last name  
      <input  
        type="text"  
        placeholder="Last name"  
        value={lastname}  
        onChange={e => setLastname(e.target.value)} />  
    </div>  
    <button onClick={handleOnSubmit}>Next</button>  
  </form>  
>);  
return page1;  
</>
```

value



React App

localhost:3000

### Page 1

Firstname

Lastname

Set the value

# State objects: pageone.js

```
import React, { useState } from 'react';
```

```
export const Pageone = (props) => {  
  const [user, setUser] = useState({  
    firstname: "",  
    lastname: "",  
    address: "",  
    creditcard: ""  
  })
```

user is an object

Pass the whole  
object to the  
next page

```
  const handleOnSubmit = () => {  
    props.history.push("/pagetwo", {user :user});  
  }  
}
```

React App

localhost:3000

## Page 1

Firstname

Lastname

React App

localhost:3000/pagetwo

First name: Frank  
Last name: Brown

## Page 2

Address

# State objects: pageone.js

```
let page1 = (  
  <form>  
    <h3>Page 1</h3>  
    <div>  
      Firstname  
      <input  
        type="text"  
        placeholder="First name"  
        name="firstname"  
        onChange={e => setUser({...user,[e.target.name]: e.target.value })} />  
    </div>  
    <div>  
      Lastname  
      <input  
        type="text"  
        placeholder="Last name"  
        name="lastname"  
        onChange={e => setUser({...user,[e.target.name]: e.target.value,})} />  
    </div>  
    <button onClick={handleOnSubmit}>Next</button>  
  </form>  
  
);  
return page1;  
}
```

name

Update user object, leave all fields as is but update the field firstname with the value "Frank"

React App

localhost:3000

### Page 1


Firstname

Lastname

# State objects: pageone.js

```
let page1 = (  
  <form>  
    <h3>Page 1</h3>  
    <div>  
      Firstname  
      <input  
        type="text"  
        placeholder="First name"  
        name="firstname"  
        onChange={e => setUser({...user,[e.target.name]: e.target.value })} />  
    </div>  
    <div>  
      Lastname  
      <input  
        type="text"  
        placeholder="Last name"  
        name="lastname"  
        onChange={e => setUser({...user,[e.target.name]: e.target.value,})} />  
    </div>  
    <button onClick={handleOnSubmit}>Next</button>  
  </form>  
  
);  
return page1;  
}
```

Same method




The screenshot shows a web browser window titled 'React App' at 'localhost:3000'. The page content is titled 'Page 1'. It contains a form with two text input fields: 'Firstname' with the value 'Frank' and 'Lastname' with the value 'Brown'. Below these fields is a button labeled 'Next'.



# State objects: pageone.js

```
let page1 = (  
  <form>  
    <h3>Page 1</h3>  
    <div>  
      Firstname  
      <input  
        type="text"  
        placeholder="First name"  
        name="firstname"  
        onChange={e => setUser({...user,[e.target.name]: e.target.value })} />  
    </div>  
    <div>  
      Lastname  
      <input  
        type="text"  
        placeholder="Last name"  
        name="lastname"  
        onChange={e => setUser({...user,[e.target.name]: e.target.value,})} />  
    </div>  
    <button onClick={handleOnSubmit}>Next</button>  
  </form>  
  
);  
return page1;  
}
```

Same method



The screenshot shows a web browser window titled 'React App' at 'localhost:3000'. The page content is titled 'Page 1'. It contains a form with two text input fields: 'Firstname' with the value 'Frank' and 'Lastname' with the value 'Brown'. Below these fields is a button labeled 'Next'.

# State objects: pageone.js

```
const [user, setUser] = useState({
  firstname: "",
  lastname: "",
  address: "",
  creditcard: ""
})
...
const handleFieldChange = (e) => {
  setUser({...user,[e.target.name]: e.target.value });
}
let page1 = (
  ...
  <div>
    Firstname
    <input
      ...
      name="firstname"
      onChange={handleFieldChange} />
    </div>
    <div>
      Lastname
      <input
        ...
        name="lastname"
        onChange={handleFieldChange} />
      </div>
  ...
)
```

Define function

Call function

Call function

# State objects: pagetwo.js

```
export const Pagetwo = (props) => {
  const [user, setUser] = useState(props.location.state.user);
  const handleOnSubmit = () => {
    props.history.push("/pagethree", {user :user});
  }
  const handleFieldChange = (e) => {
    setUser({...user,[e.target.name]: e.target.value });
  }
  let page2 = (
    <div>
      <div>First name: {user.firstname}</div>
      <div>Last name: {user.lastname}</div>
      <form>
        <h3>Page 2</h3>
        <div>
          Address
          <input
            type="text"
            placeholder="Address"
            name="address"
            onChange={handleFieldChange} />
        </div>
        <button onClick={handleOnSubmit}>Next</button>
      </form>
    </div>
  );
  return page2;
};
```

Create a local user object based on the state of the passed user object



The screenshot shows a web browser window titled 'React App' with the address 'localhost:3000/pagetwo'. The page content is as follows:

First name: John  
Last name: Doe

**Page 2**

Address

# **WORKING WITH LISTS**

# List of strings

```
import React, { useState } from 'react';


export const ToDoList = () => {

  const todoList = [
    'Learn JavaScript',
    'Learn React',
    'Learn Spring Boot',
  ];

  return (
    <div>
      <h1>Todo list</h1>
      <table>
        <tbody>
          {todoList.map(item => (
            <tr key={item}>
              <td>{item}</td>
            </tr>
          ))}
        </tbody>
      </table>
    </div>
  );
};
```

Map expects a  
unique key


item is the  
key



# List of users

```
export const UsersList = () => {
  const initialList = [
    { userid: "1", firstname: "Frank", lastname: "Jones", email: "Franky1@gmail.com" },
    { userid: "2", firstname: "John", lastname: "Doe", email: "jdoe@gmail.com" },
    { userid: "3", firstname: "Mary", lastname: "Brown", email: "marybrown@gmail.com" }
  ];
  const [userlist, setUserlist] = useState(initialList);
  return (
    <div>
      <h1>Users</h1>
      <table>
        <thead>
          <tr><th>Userid</th><th>First name</th><th>Last name</th><th>Email</th></tr>
        </thead>
        <tbody>
          {userlist.map(user => (
            <tr key={user.userid}>
              <td>{user.userid}</td>
              <td>{user.firstname}</td>
              <td>{user.lastname}</td>
              <td>{user.email}</td>
            </tr>
          ))}
        </tbody>
      </table>
    </div>
  );
}
```


userid is the key



Userid	First name	Last name	Email
1	Frank	Jones	Franky1@gmail.com
2	John	Doe	jdoe@gmail.com
3	Mary	Brown	marybrown@gmail.com

**MODIFY THE LIST IN THE SAME  
PAGE**

# Add to a list of objects



React App

localhost:3000

## Users

Userid	First name	Last name	Email
1	Frank	Jones	Franky1@gmail.com
2	John	Doe	jdoe@gmail.com

### Add a new user

Userid

Firstname

Lastname

Email



# UsersList.js(1/4)

```
import React, { useState } from 'react';
```

```
export const UsersList = () => {  
  const cleanuser = { userid: "", firstname: "", lastname: "", email: "" };  
  const [user, setUser] = useState(cleanuser);  
  const initialList = [  
    { userid: "1", firstname: "Frank", lastname: "Jones", email: "Franky1@gmail.com" },  
    { userid: "2", firstname: "John", lastname: "Doe", email: "jdoe@gmail.com" },  
  ];
```

One users

```
  const [userlist, setUserlist] = useState(initialList);
```

List of users

```
  const handleSubmit = (e) => {  
    if (user) {  
      setUserlist(userlist.concat(user)); //add user to the list  
    }
```

Called when you click the "Add user" button

```
    //clear user  
    setUser(cleanuser);  
    //prevent POST request  
    e.preventDefault();  
  }
```

Do not send a  
POST request

Called when you  
change one of the  
form fields

```
  const handleFieldChange = (e) => {  
    setUser({ ...user, [e.target.name]: e.target.value });  
  }
```

Userid	First name	Last name	Email
1	Frank	Jones	Franky1@gmail.com
2	John	Doe	jdoe@gmail.com

**Add a new user**

Userid

Firstname

Lastname

Email

# UsersList.js(2/4)

```
return (  
  <div>  
    <h1>Users</h1>  
  
    <table>  
      <tr><th>Userid</th><th>First name</th><th>Last name</th><th>Email</th></tr>  
      {userlist.map(user => (  
        <tr><td>{user.userid}</td>  
          <td>{user.firstname}</td>  
          <td>{user.lastname}</td>  
          <td>{user.email}</td></tr>  
      ) )}  
    </table>  
  </div>  
)
```

Show table of users

React App

localhost:3000

## Users

Userid	First name	Last name	Email
1	Frank	Jones	Franky1@gmail.com
2	John	Doe	jdoe@gmail.com

### Add a new user

Userid

Firstname


Lastname

Email

# UsersList.js(3/4)

```
<p><h2>Add a new user</h2></p>
<form onSubmit={handleSubmit}>
  <div>
    Userid
    <input
      type="text"
      placeholder="Userid"
      name="userid"
      value={user.userid}
      onChange={handleFieldChange} />
  </div>
  <div>
    Firstname
    <input
      type="text"
      placeholder="First name"
      name="firstname"
      value={user.firstname}
      onChange={handleFieldChange} />
  </div>
```

Call handleSubmit when you click the "Add user" button



Userid	First name	Last name	Email
1	Frank	Jones	Franky1@gmail.com
2	John	Doe	jdoe@gmail.com

### Add a new user

Userid

Firstname


Lastname

Email

# UsersList.js(4/4)

```
<div>
  Lastname
  <input
    type="text"
    placeholder="Last name"
    name="lastname"
    value={user.lastname}
    onChange={handleFieldChange} />
</div>
<div>
  Email
  <input
    type="text"
    placeholder="Email"
    name="email"
    value={user.email}
    onChange={handleFieldChange} />
</div>
<button type="submit">Add User</button>
</form>
</div>
);
};
```

Submit button



React App

localhost:3000

## Users

Userid	First name	Last name	Email
1	Frank	Jones	Franky1@gmail.com
2	John	Doe	jdoe@gmail.com

### Add a new user

Userid

Firstname

Lastname

Email

# Remove from a list of objects

React App

localhost:3000

## Users

Userid	First name	Last name	Email	
1	Frank	Jones	Franky1@gmail.com	Remove
2	John	Doe	jdoe@gmail.com	Remove

## Add a new user

Userid

Firstname

Lastname

Email

Add User

Userid

First name

Last name

Email

# UsersList.js

```
const removeUser = (e) => {  
  const newUserlist = userlist.filter((user) => user.userid !== e.target.value);  
  setUserlist(newUserlist);  
}
```

Create a new list and filter out the user to be removed

```
<table>  
  <tr><th>Userid</th><th>First name</th><th>Last name</th><th>Email</th></tr>  
  {userlist.map(user => (  
    <tr><td>{user.userid}</td>  
    <td>{user.firstname}</td>  
    <td>{user.lastname}</td>  
    <td>{user.email}</td>  
    <td><button onClick={removeUser} value={user.userid}>Remove</button></td>  
  </tr>  
  )</td>  
</table>
```

Add button to the table

Call  
removeUser  
function  
when clicked

Pass userid as  
value in event

Userid	First name	Last name	Email	
1	Frank	Jones	Franky1@gmail.com	Remove
2	John	Doe	jdoe@gmail.com	Remove

**MODIFY THE LIST IN SEPARATE  
PAGES**

# Add to a list of objects



React App

localhost:3000

## Users

Userid	First name	Last name	Email	
22	John	Johnson	jjohnson@gmail.com	Remove
44	Mary	Jones	mjones@hotmail.com	Remove

Add User

React App

localhost:3000/adduser

## Add a new user

Userid

Firstname

Lastname

Email

Add User





# App.js

```
function App() {  
  const [userlist, setUserlist] = useState([]);  
  
  return (  
    <div >  
      <Router>  
        <Route  
          exact path='/'  
          render={(props) => (  
            <UsersList {...props} userList={userlist} setUserlist={setUserlist} />  
          )}  
        />  
        <Route  
          path='/adduser'  
          render={(props) => (  
            <AddUser {...props} userList={userlist} setUserlist={setUserlist} />  
          )}  
        />  
      </Router>  
    </div>  
  );  
}  
  
export default App;
```

List of users is in the top component

Pass **userlist** and **setUserlist** function to the child components




# UsersList.js(1/2)

```
import React, { useState } from 'react';
```

```
export const UsersList = (props) => {  
  const cleanuser = { userid: "", firstname: "", lastname: "", email: "" };  
  const [user, setUser] = useState(cleanuser);
```


```
  const handleAddUser = () => {  
    props.history.push("/adduser"); //navigate to add user  
  }
```

```
  const removeUser = (e) => {  
    const newUserlist = props.userlist.filter((user) => user.userid !== e.target.value);  
    props.setUserlist(newUserlist);  
  }
```




# UsersList.js(1/2)

```
return (  
  <div>  
    <h1>Users</h1>  
    <table>  
      <thead><tr><th>Userid</th><th>First name</th><th>Last name</th><th>Email</th>  
      </tr></thead>  
      <tbody>  
        {props.userlist.map(user => (  
          <tr key={user.userid}>  
            <td>{user.userid}</td>  
            <td>{user.firstname}</td>  
            <td>{user.lastname}</td>  
            <td>{user.email}</td>  
            <td><button onClick={removeUser} value={user.userid}>Remove</button></td>  
          </tr>  
        ))}  
      </tbody>  
    </table>  
    <button onClick={handleAddUser}>Add User</button>  
  </div>  
)  
);
```



# AddUser.js(1/2)

```
export const AddUser = (props) => {  
  const cleanuser = { userid: "", firstname: "", lastname: "", email: "" };  
  const [user, setUser] = useState(cleanuser);  
  
  const handleSubmit = (e) => {  
    props.setUserlist(props.userlist.concat(user)); //add user to the list  
    props.history.push("/"); //navigate to userlist  
  }  
  
  const handleFieldChange = (e) => {  
    setUser({ ...user, [e.target.name]: e.target.value });  
  }  
}
```



React App

localhost:3000/adduser

### Add a new user

Userid


Firstname

Lastname

Email

# AddUser.js(2/2)

```
return (  
  <div>  
    <h2>Add a new user</h2>  
    <form onSubmit={handleSubmit}>  
      <div>  
        Userid  
        <input  
          type="text"  
          placeholder="Userid"  
          name="userid"  
          value={user.userid}  
          onChange={handleFieldChange} />  
      </div>  
      ...  
      <button type="submit">Add User</button>  
    </form>  
  </div>  
)  
);
```



The screenshot shows a web browser window titled 'React App' with the address bar displaying 'localhost:3000/adduser'. The page content includes a heading 'Add a new user' followed by a form with four input fields: 'Userid' (containing '22'), 'Firstname' (containing 'John'), 'Lastname' (containing 'Johnson'), and 'Email' (containing 'jjohnson@gmail.com'). Below the email field is an 'Add User' button.