

Combinatorial Optimization Games

Maria Serna

Fall 2019

- 1 Induced subgraph games
- 2 Minimum cost spanning tree games
- 3 References

- 1 Induced subgraph games
- 2 Minimum cost spanning tree games
- 3 References

Induced subgraph games

Induced subgraph games

- A game is described by an undirected, weighted graph $G = (N, E)$ with $|N| = n$ and $|E| = m$ and an integer edge weight function w .

Induced subgraph games

- A game is described by an undirected, weighted graph $G = (N, E)$ with $|N| = n$ and $|E| = m$ and an integer edge weight function w .
- The weight of edge $(i, j) \in E$ is denoted by w_{ij} .

Induced subgraph games

- A game is described by an undirected, weighted graph $G = (N, E)$ with $|N| = n$ and $|E| = m$ and an integer edge weight function w .
- The weight of edge $(i, j) \in E$ is denoted by $w_{i,j}$.
- In the game $\Gamma(G, w) = (N, v)$ the set of players is N , and the value v of a coalition $C \subseteq N$ is

$$v(C) = \sum_{e \in E(G[C])} w_e$$

Induced subgraph games

- A game is described by an undirected, weighted graph $G = (N, E)$ with $|N| = n$ and $|E| = m$ and an integer edge weight function w .
- The weight of edge $(i, j) \in E$ is denoted by $w_{i,j}$.
- In the game $\Gamma(G, w) = (N, v)$ the set of players is N , and the value v of a coalition $C \subseteq N$ is

$$v(C) = \sum_{e \in E(G[C])} w_e$$

- Usually **self-loops** are allowed when we want that the value of a singleton is different from 0.

Induced subgraph games

- A game is described by an undirected, weighted graph $G = (N, E)$ with $|N| = n$ and $|E| = m$ and an integer edge weight function w .
- The weight of edge $(i, j) \in E$ is denoted by $w_{i,j}$.
- In the game $\Gamma(G, w) = (N, v)$ the set of players is N , and the value v of a coalition $C \subseteq N$ is

$$v(C) = \sum_{e \in E(G[C])} w_e$$

- Usually **self-loops** are allowed when we want that the value of a singleton is different from 0.
- Observe that $v(\emptyset) = 0$ and $v(N) = w(E)$.

Induced subgraph games

Induced subgraph games

- Induced subgraph games model aspects of social networks.

Induced subgraph games

- Induced subgraph games model aspects of social networks.
- The value of each coalition (team, club) is determined by the relationships among its members: a player assigns a positive utility to being in a coalition with his friends and a negative utility to being in a coalition with his enemies.

Induced subgraph games

- Induced subgraph games model aspects of social networks.
- The value of each coalition (team, club) is determined by the relationships among its members: a player assigns a positive utility to being in a coalition with his friends and a negative utility to being in a coalition with his enemies.
- The representation is succinct as long as the number of bits required to encode edge weights is polynomial in $|N|$: using an adjacency matrix to represent the graph requires only n^2 entries.

Induced subgraph games

- Induced subgraph games model aspects of social networks.
- The value of each coalition (team, club) is determined by the relationships among its members: a player assigns a positive utility to being in a coalition with his friends and a negative utility to being in a coalition with his enemies.
- The representation is succinct as long as the number of bits required to encode edge weights is polynomial in $|N|$: using an adjacency matrix to represent the graph requires only n^2 entries.
- Weights can be exponential in n and still have polynomial size.

Completeness?

Completeness?

- Is this is a **complete** representation?

Completeness?

- Is this is a **complete** representation?
All simple games can be represented as induced subgraph games?

Completeness?

- Is this is a **complete** representation?
All simple games can be represented as induced subgraph games? **NO**

Completeness?

- Is this is a **complete** representation?

All simple games can be represented as induced subgraph games? **NO**

Consider the game $\Gamma = (N, v)$, where $n = \{1, 2, 3\}$ and

$$v(C) = \begin{cases} 0 & \text{if } |C| \leq 1 \\ 1 & \text{if } |C| = 2 \\ 6 & \text{if } |C| = 3 \end{cases}$$

Completeness?

- Is this a **complete** representation?

All simple games can be represented as induced subgraph games? **NO**

Consider the game $\Gamma = (N, v)$, where $n = \{1, 2, 3\}$ and

$$v(C) = \begin{cases} 0 & \text{if } |C| \leq 1 \\ 1 & \text{if } |C| = 2 \\ 6 & \text{if } |C| = 3 \end{cases}$$

- Assume that $\Gamma(G, w)$ realizes Γ .

Completeness?

- Is this a **complete** representation?

All simple games can be represented as induced subgraph games? **NO**

Consider the game $\Gamma = (N, v)$, where $n = \{1, 2, 3\}$ and

$$v(C) = \begin{cases} 0 & \text{if } |C| \leq 1 \\ 1 & \text{if } |C| = 2 \\ 6 & \text{if } |C| = 3 \end{cases}$$

- Assume that $\Gamma(G, w)$ realizes Γ .
 - By the first condition all self-loops must have weight 0.

Completeness?

- Is this a **complete** representation?

All simple games can be represented as induced subgraph games? **NO**

Consider the game $\Gamma = (N, v)$, where $n = \{1, 2, 3\}$ and

$$v(C) = \begin{cases} 0 & \text{if } |C| \leq 1 \\ 1 & \text{if } |C| = 2 \\ 6 & \text{if } |C| = 3 \end{cases}$$

- Assume that $\Gamma(G, w)$ realizes Γ .
 - By the first condition all self-loops must have weight 0.
 - By the second condition any pair of different vertices must be connected by an edge with weight 1. So **G must be a triangle.**

Completeness?

- Is this a **complete** representation?

All simple games can be represented as induced subgraph games? **NO**

Consider the game $\Gamma = (N, v)$, where $n = \{1, 2, 3\}$ and

$$v(C) = \begin{cases} 0 & \text{if } |C| \leq 1 \\ 1 & \text{if } |C| = 2 \\ 6 & \text{if } |C| = 3 \end{cases}$$

- Assume that $\Gamma(G, w)$ realizes Γ .
 - By the first condition all self-loops must have weight 0.
 - By the second condition any pair of different vertices must be connected by an edge with weight 1. So **G must be a triangle.**
 - But then $v(\{1, 2, 3\}) = 3 \neq 6$.

Properties of valuations

- **monotone** if $v(C) \leq v(D)$ for $C \subseteq D \subseteq N$.
- **superadditive** if $v(C \cup D) \geq v(C) + v(D)$, for every pair of disjoint coalitions $C, D \subseteq N$.
- **supermodular** $v(C \cup D) + v(C \cap D) \geq v(C) + v(D)$.

Properties of valuations

- **monotone** if $v(C) \leq v(D)$ for $C \subseteq D \subseteq N$.
- **superadditive** if $v(C \cup D) \geq v(C) + v(D)$, for every pair of disjoint coalitions $C, D \subseteq N$.
- **supermodular** $v(C \cup D) + v(C \cap D) \geq v(C) + v(D)$.
- A game (N, v) is **convex** iff v is supermodular.

Properties of valuations

- **monotone** if $v(C) \leq v(D)$ for $C \subseteq D \subseteq N$.
- **superadditive** if $v(C \cup D) \geq v(C) + v(D)$, for every pair of disjoint coalitions $C, D \subseteq N$.
- **supermodular** $v(C \cup D) + v(C \cap D) \geq v(C) + v(D)$.
- A game (N, v) is **convex** iff v is supermodular.
- Since we allow for negative edge weights, induced subgraph games are not necessarily monotone.

Properties of valuations

- **monotone** if $v(C) \leq v(D)$ for $C \subseteq D \subseteq N$.
- **superadditive** if $v(C \cup D) \geq v(C) + v(D)$, for every pair of disjoint coalitions $C, D \subseteq N$.
- **supermodular** $v(C \cup D) + v(C \cap D) \geq v(C) + v(D)$.
- A game (N, v) is **convex** iff v is supermodular.
- Since we allow for negative edge weights, induced subgraph games are not necessarily monotone.
- However, when all edge weights are non-negative, induced subgraph games are **convex**.

Can the core be empty?

Can the core be empty?

The **core** of $\Gamma(N, v)$ is the set of all imputations x such that $v(S) \leq x(S)$, for each coalition $S \subseteq N$.

Can the core be empty?

Can the core be empty?

Theorem

If $\Gamma = (N, v)$ is a convex game, then Γ has a non-empty core.

Can the core be empty?

Theorem

If $\Gamma = (N, v)$ is a convex game, then Γ has a non-empty core.

- Fix an arbitrary permutation π , and let x_i be the marginal contribution of i with respect to π .

Can the core be empty?

Theorem

If $\Gamma = (N, v)$ is a convex game, then Γ has a non-empty core.

- Fix an arbitrary permutation π , and let x_i be the marginal contribution of i with respect to π .
- Let us show that (x_1, \dots, x_n) is in the core of Γ .

Can the core be empty?

Theorem

If $\Gamma = (N, v)$ is a convex game, then Γ has a non-empty core.

- Fix an arbitrary permutation π , and let x_i be the marginal contribution of i with respect to π .
- Let us show that (x_1, \dots, x_n) is in the core of Γ .
 - For $C \subseteq N$, we can assume that $C = \{i_1, \dots, i_s\}$ where $\pi(i_1) < \dots < \pi(i_s)$.
 - So, $v(C) = v(\{i_1\}) - v(\emptyset) + v(\{i_1, i_2\}) - v(\{i_1\}) + \dots + v(C) - v(C \setminus \{i_s\})$.
 - By supermodularity we have, $v(\{i_1, \dots, i_{j-1}, i_j\}) - v(\{i_1, \dots, i_{j-1}\}) \leq v(\{1, \dots, i_j\}) - v(\{1, \dots, i_{j-1}\})$.
 - Therefore $v(C) \leq x(C)$ and $v(N) = x(N)$.

Can the core be empty?

Theorem

If $\Gamma = (N, v)$ is a convex game, then Γ has a non-empty core.

- Fix an arbitrary permutation π , and let x_i be the marginal contribution of i with respect to π .
- Let us show that (x_1, \dots, x_n) is in the core of Γ .
 - For $C \subseteq N$, we can assume that $C = \{i_1, \dots, i_s\}$ where $\pi(i_1) < \dots < \pi(i_s)$.
 - So, $v(C) = v(\{i_1\}) - v(\emptyset) + v(\{i_1, i_2\}) - v(\{i_1\}) + \dots + v(C) - v(C \setminus \{i_s\})$.
 - By supermodularity we have, $v(\{i_1, \dots, i_{j-1}, i_j\}) - v(\{i_1, \dots, i_{j-1}\}) \leq v(\{1, \dots, i_j\}) - v(\{1, \dots, i_{j-1}\})$.
 - Therefore $v(C) \leq x(C)$ and $v(N) = x(N)$.
- Observe that we have shown that the vector formed by the Shapley value is in the core of a convex game.

Shapley value

- A permutation of $\{1, \dots, n\}$ is a one-to-one mapping from $\{1, \dots, n\}$ to itself

Shapley value

- A permutation of $\{1, \dots, n\}$ is a one-to-one mapping from $\{1, \dots, n\}$ to itself
- $\Pi(N)$ denote the set of all permutations of N

Shapley value

- A permutation of $\{1, \dots, n\}$ is a one-to-one mapping from $\{1, \dots, n\}$ to itself
- $\Pi(N)$ denote the set of all permutations of N
- Let $S_\pi(i)$ denote the set of predecessors of i in $\pi \in \Pi(N)$

Shapley value

- A permutation of $\{1, \dots, n\}$ is a one-to-one mapping from $\{1, \dots, n\}$ to itself
- $\Pi(N)$ denote the set of all permutations of N
- Let $S_\pi(i)$ denote the set of predecessors of i in $\pi \in \Pi(N)$
- For $C \subseteq N$, let $\delta_i(C) = v(C \cup \{i\}) - v(C)$

Shapley value

- A permutation of $\{1, \dots, n\}$ is a one-to-one mapping from $\{1, \dots, n\}$ to itself
- $\Pi(N)$ denote the set of all permutations of N
- Let $S_\pi(i)$ denote the set of predecessors of i in $\pi \in \Pi(N)$
- For $C \subseteq N$, let $\delta_i(C) = v(C \cup \{i\}) - v(C)$
- The **Shapley value of player i** in a game $\Gamma = (N, v)$ with n players is

$$\Phi_i(\Gamma) = \frac{1}{n!} \sum_{\pi \in \Pi(N)} \delta_i(S_\pi(i))$$

Shapley value: Axiomatic Characterization

Properties of the Shapley value:

- Efficiency: $\Phi_1 + \dots + \Phi_n = v(N)$
- Dummy: if i is a dummy, $\Phi_i = 0$
- Symmetry: if i and j are symmetric, $\Phi_i = \Phi_j$
- Additivity: $\Phi_i(\Gamma_1 + \Gamma_2) = \Phi_i(\Gamma_1) + \Phi_i(\Gamma_2)$

Shapley value: Axiomatic Characterization

Properties of the Shapley value:

- Efficiency: $\Phi_1 + \dots + \Phi_n = v(N)$
- Dummy: if i is a dummy, $\Phi_i = 0$
- Symmetry: if i and j are symmetric, $\Phi_i = \Phi_j$
- Additivity: $\Phi_i(\Gamma_1 + \Gamma_2) = \Phi_i(\Gamma_1) + \Phi_i(\Gamma_2)$

Theorem

The Shapley value is the only payoff distribution scheme that has properties (1) - (4)

Shapley value

Shapley value

Theorem

The Shapley value of player i in $\Gamma(G, w)$ is

$$\Phi(i) = \frac{1}{2} \sum_{(i,j) \in E} w_{i,j}.$$

Shapley value: Computation

Shapley value: Computation

- Let $\{e_1, \dots, e_m\}$ be the set of edges in G .

Shapley value: Computation

- Let $\{e_1, \dots, e_m\}$ be the set of edges in G .
- We can decompose the graph G into m graphs G_1, \dots, G_m , where for $1 \leq j \leq m$ the graph $G_j = (V, \{e_j\})$.

Shapley value: Computation

- Let $\{e_1, \dots, e_m\}$ be the set of edges in G .
- We can decompose the graph G into m graphs G_1, \dots, G_m , where for $1 \leq j \leq m$ the graph $G_j = (V, \{e_j\})$.
- Considering the same weight as in the original graph, let $\Gamma_j = \Gamma(G_j, w)$.

Shapley value: Computation

- Let $\{e_1, \dots, e_m\}$ be the set of edges in G .
- We can decompose the graph G into m graphs G_1, \dots, G_m , where for $1 \leq j \leq m$ the graph $G_j = (V, \{e_j\})$.
- Considering the same weight as in the original graph, let $\Gamma_j = \Gamma(G_j, w)$.
- According to the definitions:

$$\Gamma = \Gamma(G, w) = \Gamma_1 + \dots + \Gamma_m.$$

Shapley value: Computation

- Let $\{e_1, \dots, e_m\}$ be the set of edges in G .
- We can decompose the graph G into m graphs G_1, \dots, G_m , where for $1 \leq j \leq m$ the graph $G_j = (V, \{e_j\})$.
- Considering the same weight as in the original graph, let $\Gamma_j = \Gamma(G_j, w)$.
- According to the definitions:

$$\Gamma = \Gamma(G, w) = \Gamma_1 + \dots + \Gamma_m.$$

- By the additivity axiom, for each player $i \in N$ we have

Shapley value: Computation

- Let $\{e_1, \dots, e_m\}$ be the set of edges in G .
- We can decompose the graph G into m graphs G_1, \dots, G_m , where for $1 \leq j \leq m$ the graph $G_j = (V, \{e_j\})$.
- Considering the same weight as in the original graph, let $\Gamma_j = \Gamma(G_j, w)$.
- According to the definitions:

$$\Gamma = \Gamma(G, w) = \Gamma_1 + \dots + \Gamma_m.$$

- By the additivity axiom, for each player $i \in N$ we have

$$\Phi_i(\Gamma) = \sum_{j=1}^m \Phi_i(\Gamma_j).$$

Shapley value: Computation

Shapley value: Computation

- We have to compute $\Phi_i(\Gamma_j)$.

Shapley value: Computation

- We have to compute $\Phi_i(\Gamma_j)$.
- When i is not incident to e_j , i is a dummy in Γ_j and $\Phi_i(\Gamma_j) = 0$.

Shapley value: Computation

- We have to compute $\Phi_i(\Gamma_j)$.
- When i is not incident to e_j , i is a dummy in Γ_j and $\Phi_i(\Gamma_j) = 0$.
- When $e_j = (i, \ell)$ for some $\ell \in N$, players i and ℓ are symmetric in Γ_j .

Shapley value: Computation

- We have to compute $\Phi_i(\Gamma_j)$.
- When i is not incident to e_j , i is a dummy in Γ_j and $\Phi_i(\Gamma_j) = 0$.
- When $e_j = (i, \ell)$ for some $\ell \in N$, players i and ℓ are symmetric in Γ_j .
- Since the value of the grand coalition in Γ_j equals $w(i, \ell)$, by efficiency and symmetry we get $\Phi_i(\Gamma_j) = w(i, \ell)/2$.

Shapley value

Shapley value

Theorem

The Shapley value of player i in $\Gamma(G, w)$ is

$$\Phi_i = \frac{1}{2} \sum_{(i,j) \in E} w_{i,j}.$$

Shapley value

Theorem

The Shapley value of player i in $\Gamma(G, w)$ is

$$\Phi_i = \frac{1}{2} \sum_{(i,j) \in E} w_{i,j}.$$

Corollary

The Shapley values of induced subgraph games can be computed in polynomial time.

Can the core be empty?

Theorem

Consider a game $\Gamma(G, w)$, the following are equivalent

- *The vector of Shapley values is in the core*
- *(G, w) has no negative cut*
- *The core is non-empty*

Can the core be empty?

Can the core be empty?

The Shapley value is in the core iff G has no negative cut.

Can the core be empty?

The Shapley value is in the core iff G has no negative cut.

- Let $e(S, x) = v(S) - x(S)$ be the excess of coalition S at the imputation x .

Can the core be empty?

The Shapley value is in the core iff G has no negative cut.

- Let $e(S, x) = v(S) - x(S)$ be the excess of coalition S at the imputation x .
- Thus, x is in the core iff $e(x, S) \leq 0 \forall S \subseteq N$.

Can the core be empty?

The Shapley value is in the core iff G has no negative cut.

- Let $e(S, x) = v(S) - x(S)$ be the excess of coalition S at the imputation x .
- Thus, x is in the core iff $e(x, S) \leq 0 \ \forall S \subseteq N$.
- For the Shapley values, $e(S, \Phi)$ is $-\frac{1}{2}$ times the weight of the edges going from S to $N \setminus S$.

Can the core be empty?

The Shapley value is in the core iff G has no negative cut.

- Let $e(S, x) = v(S) - x(S)$ be the excess of coalition S at the imputation x .
- Thus, x is in the core iff $e(x, S) \leq 0 \ \forall S \subseteq N$.
- For the Shapley values, $e(S, \Phi)$ is $-\frac{1}{2}$ times the weight of the edges going from S to $N \setminus S$.
- Hence the Shapley value is in the core if and only if there is no negative cut $(S, N \setminus S)$.

Can the core be empty?

Can the core be empty?

The core is nonempty iff G has no negative cut.

Can the core be empty?

The core is nonempty iff G has no negative cut.

- If G has no negative cut, the vector of Shapley values is in the core (by the previous proof).

Can the core be empty?

The core is nonempty iff G has no negative cut.

- If G has no negative cut, the vector of Shapley values is in the core (by the previous proof).
- We have seen that if the core is non-empty, then the vector of Shapley values is in the core.

Can the core be empty?

- **NEGATIVE-CUT:** Given a weighted graph (G, w) , determine whether there is a negative cut in G .

Can the core be empty?

- **NEGATIVE-CUT**: Given a weighted graph (G, w) , determine whether there is a negative cut in G .

NEGATIVE-CUT is NP-complete

- **W-MAX-CUT**: Given a weighted graph (G, w) with non-negative weights and an integer k , determine whether there is a cut of size at least k in G , is NP-complete.

Can the core be empty?

- **NEGATIVE-CUT:** Given a weighted graph (G, w) , determine whether there is a negative cut in G .

NEGATIVE-CUT is NP-complete

- **W-MAX-CUT:** Given a weighted graph (G, w) with non-negative weights and an integer k , determine whether there is a cut of size at least k in G , is NP-complete.
- Let (G, w) with non-negative weights and an integer k . G' is obtained as the disjoint union of G and the graph $(\{a, b\}, \{(a, b)\})$. Define w' as $w'(e) = w(e)$ for $e \in E(G)$ and $w'((a, b)) = -k$.

Can the core be empty?

- **NEGATIVE-CUT:** Given a weighted graph (G, w) , determine whether there is a negative cut in G .

NEGATIVE-CUT is NP-complete

- **W-MAX-CUT:** Given a weighted graph (G, w) with non-negative weights and an integer k , determine whether there is a cut of size at least k in G , is NP-complete.
- Let (G, w) with non-negative weights and an integer k . G' is obtained as the disjoint union of G and the graph $(\{a, b\}, \{(a, b)\})$. Define w' as $w'(e) = w(e)$ for $e \in E(G)$ and $w'((a, b)) = -k$.
- G has a cut of size at least k iff G' has a negative cut.

Complexity of core related problems

Theorem

The following problems are NP-complete:

- *Given (G, w) and an imputation x , is it not in the core of $\Gamma(G, w)$?*
- *Given (G, w) , is the vector of Shapley values of $\Gamma(G, w)$ not in the core of $\Gamma(G, w)$?*
- *Given (G, w) , is the core of $\Gamma(G, w)$ empty?*

Complexity of core related problems

Theorem

Given (G, w) , when all weights are non-negative, we can test in polynomial time

- *whether the core is non-empty.*
- *whether an imputation x is in the core of $\Gamma(G, w)$.*

Complexity of core related problems

Theorem

Given (G, w) , when all weights are non-negative, we can test in polynomial time

- *whether the core is non-empty.*
- *whether an imputation x is in the core of $\Gamma(G, w)$.*

The first question is trivial as the vector of Shapley values belong to the core. The second problem can be solved by a reduction to MAX-FLOW.

- 1 Induced subgraph games
- 2 Minimum cost spanning tree games**
- 3 References

MST Games

Minimum cost spanning tree games

MST Games

Minimum cost spanning tree games

- A game is described by a weighted complete graph (G, w) with $n + 1$ vertices.

MST Games

Minimum cost spanning tree games

- A game is described by a weighted complete graph (G, w) with $n + 1$ vertices.
- $V(G) = \{v_0, \dots, v_n\}$.

MST Games

Minimum cost spanning tree games

- A game is described by a weighted complete graph (G, w) with $n + 1$ vertices.
- $V(G) = \{v_0, \dots, v_n\}$.
- The weight of edge $(i, j) \in E$ is denoted by $w_{i,j}$.
We assume $w_{i,j} \geq 0$

MST Games

Minimum cost spanning tree games

- A game is described by a weighted complete graph (G, w) with $n + 1$ vertices.
- $V(G) = \{v_0, \dots, v_n\}$.
- The weight of edge $(i, j) \in E$ is denoted by $w_{i,j}$.
We assume $w_{i,j} \geq 0$
- In the game $\Gamma(G, w) = (N, c)$ the set of players is $N = \{v_1, \dots, v_n\}$, and the **cost** c of a coalition $C \subseteq N$ is $c(C) =$ the weight of a minimum spanning tree of $G[\cup\{v_0\}]$

MST Games

Minimum cost spanning tree games

- A game is described by a weighted complete graph (G, w) with $n + 1$ vertices.
- $V(G) = \{v_0, \dots, v_n\}$.
- The weight of edge $(i, j) \in E$ is denoted by $w_{i,j}$.
We assume $w_{i,j} \geq 0$
- In the game $\Gamma(G, w) = (N, c)$ the set of players is $N = \{v_1, \dots, v_n\}$, and the **cost** c of a coalition $C \subseteq N$ is
 $c(C) =$ the weight of a minimum spanning tree of $G[S \cup \{v_0\}]$
- Self-loops are not allowed.

MST Games

Minimum cost spanning tree games

- A game is described by a weighted complete graph (G, w) with $n + 1$ vertices.
- $V(G) = \{v_0, \dots, v_n\}$.
- The weight of edge $(i, j) \in E$ is denoted by $w_{i,j}$.
We assume $w_{i,j} \geq 0$
- In the game $\Gamma(G, w) = (N, c)$ the set of players is $N = \{v_1, \dots, v_n\}$, and the **cost** c of a coalition $C \subseteq N$ is
 $c(C) =$ the weight of a minimum spanning tree of $G[\cup\{v_0\}]$
- Self-loops are not allowed.
- The cost of a singleton coalition $\{i\}$ is $c(\{i\}) = w_{0,i}$.

MST Games

Minimum cost spanning tree games

- A game is described by a weighted complete graph (G, w) with $n + 1$ vertices.
- $V(G) = \{v_0, \dots, v_n\}$.
- The weight of edge $(i, j) \in E$ is denoted by $w_{i,j}$.
 We assume $w_{i,j} \geq 0$
- In the game $\Gamma(G, w) = (N, c)$ the set of players is $N = \{v_1, \dots, v_n\}$, and the **cost** c of a coalition $C \subseteq N$ is
 $c(C) =$ the weight of a minimum spanning tree of $G[S \cup \{v_0\}]$
- Self-loops are not allowed.
- The cost of a singleton coalition $\{i\}$ is $c(\{i\}) = w_{0,i}$.
- Observe that $v(\emptyset) = 0$ and $v(N) = w(T)$ where T is a MST of G .

MST Games

MST Games

- MST games model situations where a number of users must be connected to a common supplier, and the cost of such connection can be modeled as a minimum spanning tree problem.

MST Games

- MST games model situations where a number of users must be connected to a common supplier, and the cost of such connection can be modeled as a minimum spanning tree problem.
- The representation is succinct as long as the number of bits required to encode edge weights is polynomial in $|N|$: using an adjacency matrix to represent the graph requires only n^2 entries.

Completeness?

Completeness?

- Is this is a **complete** representation?

Completeness?

- Is this is a **complete** representation? All simple games can be represented as MST games?

Completeness?

- Is this is a **complete** representation? All simple games can be represented as MST games? **NO**

Completeness?

- Is this is a **complete** representation? All simple games can be represented as MST games? **NO**

Consider the game $\Gamma = (N, c)$, where $n = \{1, 2, 3\}$ and

$$c(C) = \begin{cases} 0 & \text{if } |C| \leq 1 \\ 1 & \text{if } |C| = 2 \\ 6 & \text{if } |C| = 3 \end{cases}$$

Completeness?

- Is this is a **complete** representation? All simple games can be represented as MST games? **NO**

Consider the game $\Gamma = (N, c)$, where $n = \{1, 2, 3\}$ and

$$c(C) = \begin{cases} 0 & \text{if } |C| \leq 1 \\ 1 & \text{if } |C| = 2 \\ 6 & \text{if } |C| = 3 \end{cases}$$

- Assume that $\Gamma(G, w)$ realizes Γ . $V(G) = \{0, 1, 2, 3\}$

Completeness?

- Is this a **complete** representation? All simple games can be represented as MST games? **NO**

Consider the game $\Gamma = (N, c)$, where $n = \{1, 2, 3\}$ and

$$c(C) = \begin{cases} 0 & \text{if } |C| \leq 1 \\ 1 & \text{if } |C| = 2 \\ 6 & \text{if } |C| = 3 \end{cases}$$

- Assume that $\Gamma(G, w)$ realizes Γ . $V(G) = \{0, 1, 2, 3\}$
 - By the first condition $w_{0,i} = 0$, for $i \in \{1, 2, 3\}$.

Completeness?

- Is this is a **complete** representation? All simple games can be represented as MST games? **NO**

Consider the game $\Gamma = (N, c)$, where $n = \{1, 2, 3\}$ and

$$c(C) = \begin{cases} 0 & \text{if } |C| \leq 1 \\ 1 & \text{if } |C| = 2 \\ 6 & \text{if } |C| = 3 \end{cases}$$

- Assume that $\Gamma(G, w)$ realizes Γ . $V(G) = \{0, 1, 2, 3\}$
 - By the first condition $w_{0,i} = 0$, for $i \in \{1, 2, 3\}$.
 - Thus, a coalition with $|C| = 2$ has a MST with zero cost and the second condition cannot be met.

Properties of valuations

- **monotone** if $v(C) \leq v(D)$ for $C \subseteq D \subseteq N$.
- **superadditive** if $v(C \cup D) \geq v(C) + v(D)$, for every pair of disjoint coalitions $C, D \subseteq N$.
- **subadditive** $v(C \cup D) \leq v(C) + v(D)$, for every pair of disjoint coalitions $C, D \subseteq N$.
- **supermodular** $v(C \cup D) + v(C \cap D) \geq v(C) + v(D)$.
- A game (N, v) is **convex** iff v is supermodular.

Properties of valuations

- **monotone** if $v(C) \leq v(D)$ for $C \subseteq D \subseteq N$.
- **superadditive** if $v(C \cup D) \geq v(C) + v(D)$, for every pair of disjoint coalitions $C, D \subseteq N$.
- **subadditive** $v(C \cup D) \leq v(C) + v(D)$, for every pair of disjoint coalitions $C, D \subseteq N$.
- **supermodular** $v(C \cup D) + v(C \cap D) \geq v(C) + v(D)$.
- A game (N, v) is **convex** iff v is supermodular.
- MST games are not necessarily monotone.

Properties of valuations

- **monotone** if $v(C) \leq v(D)$ for $C \subseteq D \subseteq N$.
- **superadditive** if $v(C \cup D) \geq v(C) + v(D)$, for every pair of disjoint coalitions $C, D \subseteq N$.
- **subadditive** $v(C \cup D) \leq v(C) + v(D)$, for every pair of disjoint coalitions $C, D \subseteq N$.
- **supermodular** $v(C \cup D) + v(C \cap D) \geq v(C) + v(D)$.
- A game (N, v) is **convex** iff v is supermodular.
- MST games are not necessarily monotone. Consider a triangle on $V = \{0, 1, 2\}$ and weights $w_{0,1} = 1$, $w_{0,2} = 10$ and $w_{1,2} = 1$
 $c(N) = 2$ and $c(\{1\}) = 1$ and $c(\{2\}) = 10$

Properties of valuations

- **monotone** if $v(C) \leq v(D)$ for $C \subseteq D \subseteq N$.
- **superadditive** if $v(C \cup D) \geq v(C) + v(D)$, for every pair of disjoint coalitions $C, D \subseteq N$.
- **subadditive** $v(C \cup D) \leq v(C) + v(D)$, for every pair of disjoint coalitions $C, D \subseteq N$.
- **supermodular** $v(C \cup D) + v(C \cap D) \geq v(C) + v(D)$.
- A game (N, v) is **convex** iff v is supermodular.
- MST games are not necessarily monotone. Consider a triangle on $V = \{0, 1, 2\}$ and weights $w_{0,1} = 1$, $w_{0,2} = 10$ and $w_{1,2} = 1$
 $c(N) = 2$ and $c(\{1\}) = 1$ and $c(\{2\}) = 10$
- c is **subadditive**.

Can the core be empty?

Theorem

Consider a MST game $\Gamma(G, w)$. Let T^ be a MST of (G, w) obtained using Prim's algorithm. The vector $x = (x_1, \dots, x_n)$ that allocates to player $i \in N$ the weight of the first edge i encounters on the (unique path) from v_i to v_0 in T^* belongs to the core of Γ .*

Such an allocation is called **standard core allocation**

Can the core be empty?

A standard allocation x belongs to the core

Can the core be empty?

A standard allocation x belongs to the core

- Clearly $\sum_{i=1}^n x_i = w(T^*) = c(N)$.

Can the core be empty?

A standard allocation x belongs to the core

- Clearly $\sum_{i=1}^n x_i = w(T^*) = c(N)$.
- We need to show that $\sum_{i=1}^n x_i \leq c(S)$.

Can the core be empty?

A standard allocation x belongs to the core

- Clearly $\sum_{i=1}^n x_i = w(T^*) = c(N)$.
- We need to show that $\sum_{i=1}^n x_i \leq c(S)$.
- Consider a coalition S and let T be a MST obtained using Prim's algorithm of $G[S \cup \{v_0\}]$.

Can the core be empty?

A standard allocation x belongs to the core

- Clearly $\sum_{i=1}^n x_i = w(T^*) = c(N)$.
- We need to show that $\sum_{i=1}^n x_i \leq c(S)$.
- Consider a coalition S and let T be a MST obtained using Prim's algorithm of $G[S \cup \{v_0\}]$.
- For j in S , let e_j be the first edge j encounters on the path from v_j to v_0 in T and let $y_j = w(e_j)$.

Can the core be empty?

A standard allocation x belongs to the core


- Clearly $\sum_{i=1}^n x_i = w(T^*) = c(N)$.
- We need to show that $\sum_{i=1}^n x_i \leq c(S)$.
- Consider a coalition S and let T be a MST obtained using Prim's algorithm of $G[S \cup \{v_0\}]$.
- For j in S , let e_j be the first edge j encounters on the path from v_j to v_0 in T and let $y_j = w(e_j)$.
- The selected edge corresponds to the point in which Prim's algorithm connects the vertex to the component including v_0 , i.e., it is a minimum weight edge in the allowed cut.

Can the core be empty?

A standard allocation x belongs to the core

- Clearly $\sum_{i=1}^n x_i = w(T^*) = c(N)$.
- We need to show that $\sum_{i=1}^n x_i \leq c(S)$.
- Consider a coalition S and let T be a MST obtained using Prim's algorithm of $G[S \cup \{v_0\}]$.
- For j in S , let e_j be the first edge j encounters on the path from v_j to v_0 in T and let $y_j = w(e_j)$.
- The selected edge corresponds to the point in which Prim's algorithm connects the vertex to the component including v_0 , i.e., it is a minimum weight edge in the allowed cut.
- Analyzing carefully both executions it can be shown that $x_j \leq y_j$ as the edges considered in one partition are a subset of the other.

How fair are standard core allocations?



- Most of the cost is charged to player 1.
- How to find more appropriate core allocations?

More appropriate core allocations?

- There are many proposals to try to get more appropriate core allocations.

More appropriate core allocations?

- There are many proposals to try to get more appropriate core allocations.
- Granot and Huberman [1984] propose the **weak demand allocation** and **strong demand allocation** procedures. Which rectify standard allocations by transferring cost (whenever possible) from one node to their children.

More appropriate core allocations?

- There are many proposals to try to get more appropriate core allocations.
- Granot and Huberman [1984] propose the **weak demand allocation** and **strong demand allocation** procedures. Which rectify standard allocations by transferring cost (whenever possible) from one node to their children.
- Norde, Moretti and Tijs [2001] show how to find a **population monotonic allocation scheme** (PMAS), which is an allocation scheme that provides a core element for the game and all its subgames and which, moreover, satisfies a monotonicity condition in the sense that players have to pay less in larger coalitions.

Complexity of core related problems

Complexity of core related problems

Theorem

The following problem is NP-complete:

- *Given (G, w) and an imputation x , is it not in the core of $\Gamma(G, w)$?*

Complexity of core related problems

Theorem

The following problem is NP-complete:

- *Given (G, w) and an imputation x , is it not in the core of $\Gamma(G, w)$?*

The proof follows by a reduction from EXACT COVER BY 3-SETS
[Faigle et al., Int. J. Game Theory 1997]

- 1 Induced subgraph games
- 2 Minimum cost spanning tree games
- 3 References**

References

- X. Deng and C. Papadimitriou. *On the complexity of cooperative solution concepts*. Mathematics of Operations Research, 19(2):257–266, 1994.
- C. G. Bird. *On cost allocation for a spanning tree: A game theory approach*. Networks, 6:335–350, 1976.
- U. Faigle, W. Kern, S. P. Fekete, and W. Hochstättler. *On the complexity of testing membership in the core of min-cost spanning tree games*. International Journal of Game Theory, 26:361–366, 1997.

References

- G. Chalkiadakis, E. Elkind, M. Wooldridge. [Computational Aspects of Cooperative Game Theory](#) Synthesis Lectures on Artificial Intelligence and Machine Learning, Morgan & Claypool, October 2011.