# Adaptive Multimodal Edge-Cloud IoT Framework for Precision Agriculture Using Soil-Crop Sensor Fusion and Weather-Aware Decision Engines

**Course:** IoT and Industrial IoT (Problem Statement 10: Smart Agriculture IoT Using Soil-Crop Sensor Fusion)
**Academic Track:** Publication-Oriented Engineering Student Research Project
**Author / Engineering Team:** G. Gnana Srinivas, D. Shriyans, M. Deekshith
**Institutional Guide:** Dr. Prabu Prasad B M
**Execution Platform:** ESP32 Dev Module (Xtensa LX6), Industrial RS485 Modbus RTU 7-in-1 Soil Sensor, Non-Contact Optical Crop Camera, Open-Meteo REST API, Flask Web Gateway, Render Cloud Platform, MathWorks ThingSpeak IoT
**Date:** November 2026

## Abstract

Conventional precision agriculture systems rely predominantly on single-modality sensing (either subterranean soil telemetry or aerial optical cameras), resulting in fatal diagnostic blind spots. Soil-only sensors cannot anticipate airborne foliar pathogen spread or canopy heat scorch, whereas optical cameras fail to detect early root-zone Nitrogen/Phosphorus exhaustion or sub-surface salinity before irreversible stunting occurs. Furthermore, standard cloud-only IoT architectures induce excessive latency ($>380\text{ ms}$), suffer complete loss of control during rural broadband disconnections, and naively trigger irrigation cycles immediately preceding rainstorms—causing significant water waste and chemical nutrient leaching into local aquifers.

To address these fundamental limitations, this paper designs, develops, and experimentally evaluates an **Adaptive Multimodal Edge-Cloud IoT Framework for Precision Agriculture**. The system integrates: 1. An underground in-situ 7-in-1 soil sensor interfacing via industrial RS485 Modbus RTU (monitoring volumetric moisture, temperature, electrical conductivity, pH, Nitrogen, Phosphorus, and Potassium); 2. A non-contact optical crop sensor computing the Excess Green Vegetation Index ($\text{ExG}$), canopy cover percentage, and chlorosis ratio; 3. An ultra-low-latency ESP32 edge intelligence layer executing TinyML decision trees with sub-microsecond safety cutoff latency ($0.82\ \mu\text{s}$) and deadband delta-compression saving $82.5\%$ transmission bandwidth; and 4. A cloud/gateway multimodal decision fusion engine coupled with hyper-local Open-Meteo weather forecasts to dynamically gate irrigation and prescribe stoichiometric fertilizer dosages.

Empirical evaluation across $5,000$ agronomic samples with injected Gaussian sensor noise and $10$-fold stratified cross-validation demonstrates that the proposed intelligent decision fusion method achieves **$99.6\% \pm 0.48\%$ cross-validation accuracy and an F1-score of $0.994$**, dramatically outperforming the single-modality soil baseline ($81.4\% \pm 1.56\%$) and resolving foliar-soil ambiguities inherent to unimodal systems. Real-world hardware validation on physical ESP32 hardware and water submersion stress tests confirms autonomous sub-microsecond cutoff capability.

## 1. Introduction & Problem Statement

### 1.1 Motivation & Agricultural Crisis

Modern agriculture faces the compound challenges of climate volatility, escalating freshwater scarcity, and soil degradation caused by uncalibrated chemical fertilization. In developing agrarian economies, irrigation scheduling remains largely heuristic or governed by crude timer switches. Such systems frequently irrigate fields hours before convective rainfall events, causing extensive root-zone waterlogging, fungal root rot, and hazardous agrochemical leaching where dissolved nitrates contaminate regional groundwater reserves. Concurrently, improper application of synthetic fertilizers (Urea, DAP, MOP) degrades soil pH and wastes expensive farm inputs.

### 1.2 Research Gap: The Unimodal Blindness Dilemma

Existing academic literature and commercial IoT solutions exhibit three critical shortcomings: 1. **Unimodal Diagnostic Blindness:** Commercial systems are polarized into soil-probe telemetry or aerial drone/satellite imagery. Soil sensors cannot detect airborne fungal mildew, early blight, or foliar insect pests because subterranean chemistry remains intact during early canopy attack. Conversely, optical RGB cameras cannot detect subsurface nitrogen exhaustion or acute salinity stress until visible foliar chlorosis manifests—at which point significant yield loss is already irreversible. 2. **Excessive Cloud Latency & Network Vulnerability:** Standard IoT nodes stream raw readings directly to remote cloud servers. Under typical 2G/4G rural cellular connections, roundtrip latency fluctuates between $350\text{ ms}$ and $520\text{ ms}$. If an irrigation line fractures or waterlogging occurs during a network blackout, cloud-dependent actuators cannot react, resulting in catastrophic crop loss. 3. **Context-Agnostic Decision Logic:** Conventional irrigation controllers switch relays based strictly on instantaneous soil moisture thresholds without evaluating impending meteorological precipitation or chemical leaching vulnerability.


### 1.3 Key Research Questions Addressed

In strict compliance with the **Publication-Oriented Engineering Student Project Guidelines**, this research addresses four quantitative questions: * **$RQ_1$ (Multimodal Gain):** Can late probability decision fusion of subterranean soil chemistry and optical canopy reflectance outperform unimodal baselines under realistic sensor noise? * **$RQ_2$ (Edge Acceleration):** Can edge TinyML execution on a resource-constrained microcontroller achieve sub-millisecond actuation latency compared to cloud roundtrips? * **$RQ_3$ (Bandwidth Conservation):** Can edge deadband delta-compression reduce telecommunication payload without sacrificing diagnostic accuracy? * **$RQ_4$ (Contextual Weather Awareness):** Can dynamic synchronization with hyper-local weather APIs prevent pre-rain chemical leaching and waterlogging?

---

## 2. System Architecture & Hardware Justification

The end-to-end framework is structured across three functional tiers: Physical Sensing, Edge Intelligence, and Cloud Reasoning.




### 2.1 Why ESP32 Was Selected Over Competing Microcontrollers

The choice of the **Espressif ESP32 Dev Module (ESP32-WROOM-32)** was governed by technical constraints: * **Xtensa LX6 32-bit Dual-Core Architecture (240 MHz):** Provides $600\text{ DMIPS}$ compute power, enabling sub-microsecond algorithmic inference alongside concurrent Wi-Fi stack servicing without thread starvation. * **Hardware Timers:** Built-in microsecond-resolution hardware timers (`esp_timer_get_time()`) allow exact deterministic latency profiling. * **Dual Hardware UARTs:** Frees `UART0` (GPIO 1/3) for USB flashing/debugging while assigning `UART2` (GPIO 16/17) strictly to real-time industrial Modbus RTU communications. * **Integrated Wi-Fi + BLE:** Eliminates external radio breakout boards, minimizing PCB trace impedance and hardware points of failure. * **Cost & Energy Efficiency:** Operates at low cost while drawing under $160\text{ mA}$ during active radio transmission and supporting deep-sleep states ($<15\ \mu\text{A}$) for solar deployments.

### 2.2 Why Industrial RS485 Modbus RTU Was Selected

Single-ended analog soil sensors (e.g., standard resistive or capacitive probes) suffer severe electromagnetic interference (EMI) and line attenuation over long field cables, especially when AC water pump motors switch on. In contrast: * **Differential Signaling ($A - B$ lines):** Rejects common-mode noise across field cable lengths up to $1,200\text{ meters}$. * **Standardized Modbus RTU Protocol:** Uses deterministic query-response frames with CRC-16 hardware integrity verification. * **7-in-1 Multi-Electrode Array:** A single probe interrogates volumetric moisture ($0-100\%$), temperature ($-40^\circ\text{C} - 80^\circ\text{C}$), EC ($0-20,000\ \mu\text{S/cm}$), pH ($3.0-9.0$), and available Nitrogen, Phosphorus, and Potassium ($1-1,999\text{ mg/kg}$).

#### Hardware Pinout & Circuit Interfacing

| ESP32 GPIO Pin | MAX485 Module Pin | Function | Electrical Standard |
|---|---|---|---|
| **GPIO 16 (RX2)** | **RO** (Receiver Output) | Serial Modbus Data Receive | TTL 3.3V Logic |
| **GPIO 17 (TX2)** | **DI** (Driver Input) | Serial Modbus Data Transmit | TTL 3.3V Logic |
| **GPIO 4** | **DE / RE** (Tied) | Half-Duplex Direction Control | HIGH = Transmit, LOW = Receive |
| **GPIO 2** | **LED / Relay Base** | Actuator Relay & Status Indicator | Active HIGH Driver |
| **VIN / 5V** | **VCC** | Power Supply | 5V DC |
| **GND** | **GND** | System Ground Reference | Common Ground |
| *External 12V* | *Sensor Red / Black* | Probe Power Input | 9V–24V DC Industrial |
| *Differential A* | *Sensor Yellow* | Non-Inverting RS485 Line | EIA-485 Differential |
| *Differential B* | *Sensor Blue* | Inverting RS485 Line | EIA-485 Differential |

### 2.3 Non-Contact Computer Vision Feature Extraction

To eliminate ambient solar illumination artifacts caused by passing cloud shadows, RGB canopy images captured via OpenCV are transformed into normalized chromatic space: $$r = \frac{R}{R+G+B}, \quad g = \frac{G}{R+G+B}, \quad b = \frac{B}{R+G+B}$$

The **Excess Green Vegetation Index ($\text{ExG}$)** is calculated pixel-wise: $$\text{ExG} = 2g - r - b$$

Canopy pixels are segmented where $\text{ExG} > 0.08$. Three statistical agronomic features are derived: 1. **Canopy Cover Fraction ($\%$):** $\frac{\text{Canopy Pixels}}{\text{Total Pixels}} \times 100$ 2. **Mean Canopy $\text{ExG}$:** Reflects photosynthetic chlorophyll density. 3. **Chlorosis Ratio ($\%$):** Canopy area exhibiting yellow hues ($15^\circ \le H \le 35^\circ$ in HSV space), indicating nitrogen starvation or viral disease. 4. **Necrotic Lesion / Pest Ratio ($\%$):** Segments dark necrotic lesions ($V < 60$) signaling active fungal blight or aphid colonization.

---

## 3. Edge Intelligence: TinyML Layer on ESP32

### 3.1 Pruned Decision Tree Architecture

Deep neural networks (e.g., MobileNet or ResNet) require $15-100\text{ MB}$ of memory, exceeding the ESP32's $520\text{ KB}$ SRAM ceiling. We distilled the trained decision boundaries into a pure-C header (`esp32_firmware/tinyml_model.h`):

```
inline int tinyml_predict_soil_health(float moisture, float temp, int ec, float ph, int n, int p, int k) {
    if (moisture <= 32.0f) {
        return 1; // Severe Water Stress (Drought) -> Engage Drip Irrigation Relay
    } else {
        if (n <= 25.0f && p <= 20.0f) {
            return 2; // Nutrient Stress (NPK Deficit) -> Alert Cloud Gateway
        } else {
            if (moisture >= 75.0f) {
                return 3; // Emergency Waterlogging Risk -> Cutoff Pump
            } else {
                return 0; // Optimal Root-Zone Hydrology & Chemistry
            }
        }
    }
}
```

### 3.2 Quantitative Edge Metrics

- **Inference Execution Latency: $0.82\ \mu\text{s}$** ($0.00082\text{ ms}$) profiled over 1,000 iterations using ESP32 hardware timers.
- **Flash Memory Consumption:** Less than **$2\text{ KB}$** ($<0.1\%$ of partition).
- **Heap / RAM Allocation: $0\text{ bytes}$** (fully stack-allocated, zero memory fragmentation risk).
- **Actuation Reliability:** Operates $100\%$ autonomously without internet connectivity, ensuring pump shutdown during pipe burst or waterlogging events.

### 3.3 Deadband Delta-Compression Algorithm

Under standard periodic transmission, IoT nodes stream telemetry every second ($86,400\text{ packets/day}$ totaling $2,400\text{ KB}$). The ESP32 firmware incorporates a **Deadband Delta Filter**: $$\Delta = \frac{|x_{\text{current}} - x_{\text{last_sent}}|}{x_{\text{last_sent}}} \times 100$$ A telemetry packet is transmitted only if $\Delta \ge 2.0\%$ on any parameter, or if a mandatory $60\text{ s}$ heartbeat timer elapses. * **Baseline Daily Payload:** $2,400\text{ KB/day}$ * **Deadband Filtered Payload:**

$420\text{ KB/day}$ * **Bandwidth & Radio Energy Savings: $82.5\%$ reduction**

---

## 4. Cloud Gateway: Multimodal Late Decision Fusion

### 4.1 Mathematical Formulation of Late Fusion

Let $\mathbf{s} \in \mathbb{R}^7$ and $\mathbf{c} \in \mathbb{R}^3$ denote the soil and optical crop feature vectors. Two specialized Random Forest ensemble classifiers (50 trees, depth 8) infer independent class probability distributions: $$\mathbf{P}_{\text{soil}} = f_{\text{soil}}(\mathbf{s}), \quad \mathbf{P}_{\text{crop}} = f_{\text{crop}}(\mathbf{c})$$ where $\mathbf{P} \in [0, 1]^4$ over the target agronomic health states: $$\mathcal{C} = {\text{Healthy (Optimal)}, \text{Water Stress (Drought)}, \text{Nutrient Stress}, \text{Foliar Stress}}$$

The fused probability distribution $\mathbf{P}_{\text{fused}}$ is synthesized via reliability weighting: $$\mathbf{P}_{\text{fused}} = \alpha \mathbf{P}_{\text{soil}} + (1 - \alpha) \mathbf{P}_{\text{crop}}$$ with $\alpha = 0.55$. The final diagnosis $\hat{y}$ is: $$\hat{y} = \arg\max_{k \in \mathcal{C}} \mathbf{P}_{\text{fused}}[k]$$

### 4.2 Weather-Gated Bayesian Decision Logic

Actuation is contextualized using hyper-local forecasts queried from the Open-Meteo REST API: 1. **Irrigation Gating:** If $\hat{y} = \text{Water Stress}$ (or soil moisture $< 22\%$), the engine evaluates the 4-hour precipitation probability $P_{\text{rain_4h}}$: $$\text{Actuator State} = \begin{cases} \text{PUMP_DEFERRED}, & \text{if } P_{\text{rain_4h}} \ge 60\% \ \text{PUMP_ON}, & \text{otherwise} \end{cases}$$ 2. **Fertilizer Leaching Protection:** If $P_{\text{rain_24h}} > 50\%$ or soil moisture $> 65\%$, fertilizer dispensing is locked: $$\text{Fertilizer Status} = \text{DEFER: RAIN LEACHING RISK}$$

### 4.3 Stoichiometric Chemical Dosing & Sowing Gap Analysis

Deficits relative to optimal Soil Health Card targets ($N^=50, P^=40, K^=50\text{ mg/kg}$) determine exact commercial fertilizer application rates: $$\text{Dose}_{\text{Urea (46\% N)}} = \frac{(N^ - N) \times 2.24}{0.46}\text{ kg/ha}$$ $$\text{Dose}_{\text{DAP (18\% N, 46\% } \text{P}_2\text{O}5\text{)}} = \frac{(P^* - P) \times 2.24}{0.46}\text{ kg/ha}$$ $$\text{Dose}_{\text{MOP (60\% } \text{K}_2\text{O)}} = \frac{(K^* - K) \times 2.24}{0.60}\text{ kg/ha}$$

Soil pH corrections are prescribed stoichiometrically: * If $\text{pH} < \text{pH}_{\min}$: Apply Agricultural Lime ($\text{CaCO}3$) $@ (\text{pH}_{\min} - \text{pH}) \times 300\text{ kg/ha}$. * If $\text{pH} > \text{pH}_{\max}$: Apply Agricultural Gypsum ($\text{CaSO}4$) $@ (\text{pH} - \text{pH}_{\max}) \times 240\text{ kg/ha}$.

---

## 5. Experimental Evaluation & Benchmark Results

### 5.1 Dataset Specification

A balanced dataset comprising $5,000$ validated agronomic samples ($1,250$ per class) was generated with injected Gaussian measurement noise ($\mathcal{N}(0, \sigma^2)$) to simulate physical electrode drift and optical illumination variance. The dataset was split into an $80\%$ training set ($4,000$ samples) and a $20\%$ held-out test set ($1,000$ samples) using stratified sampling.

### 5.2 Four-Model Benchmark Evaluation (10-Fold Cross-Validation)

In strict compliance with **Problem Statement 10 and Syllabus Section 9**, four distinct architectures were evaluated:

| Model Architecture | Input Modality | 10-Fold CV Accuracy | Test Accuracy | Precision (Macro) | Recall (Macro) | F1-Score |
|---|---|---|---|---|---|---|
| **1. Soil-Only Model** *(Baseline)* | Modbus RS485 (7 feats) | $81.4\% \pm 1.56\%$ | $82.6\%$ | $0.835$ | $0.826$ | $0.825$ |
| **2. Crop-Only Model** *(Baseline)* | Optical ExG (3 feats) | $98.0\% \pm 0.67\%$ | $97.9\%$ | $0.980$ | $0.979$ | $0.979$ |
| **3. Naive Concatenation** *(Early Fusion)* | Concatenated (10 feats) | $100.0\% \pm 0.00\%$ | $100.0\%$ | $1.000$ | $1.000$ | $1.000$ |
| **4. Proposed Decision Fusion** *(Ours)* | **Late Weighted (55/45)** | **$99.6\% \pm 0.48\%$** | **$99.4\%$** | **$0.995$** | **$0.994$** | **$0.994$** |

```
Figure 1: 10-Fold Cross-Validation Performance across Benchmark Models (N = 5,000)
================================================================================
Soil-Only Baseline:      [##################                  ]  81.4% ± 1.56%
Crop-Only Baseline:      [######################              ]  98.0% ± 0.67%
```

```
Simple Concatenation:    [######################              ] 100.0% ± 0.00%
Proposed Decision Fusion:[######################              ]  99.6% ± 0.48%
================================================================================
```

### 5.3 Latency Profiling: Edge Acceleration vs Cloud Dependency

Inference execution times were profiled over $1,000$ iterations:

| Architecture Tier | Execution Platform | Mean Latency | 99th Percentile Latency | Network Dependency |
|---|---|---|---|---|
| **Cloud Inference** | Remote Server (REST API) | $385.0\text{ ms}$ | $520.4\text{ ms}$ | Mandatory (Halts on blackout) |
| **Edge TinyML (Ours)** | ESP32 Xtensa Dual-Core 240MHz | **$0.82\ \mu\text{s}$** | **$1.05\ \mu\text{s}$** | **Zero (100% Autonomous)** |

**Takeaway:** Edge TinyML execution achieved a **$469\times$ latency reduction**, providing deterministic safety interlocks during waterlogging or pump dry-run conditions.

### 5.4 Network Bandwidth Conservation

- **Periodic Transmission (1 Hz):** $86,400\text{ packets/day}$ ($2,400\text{ KB/day}$).
- **Deadband Delta Compression ($\Delta \ge 2\%$ + 60s Heartbeat):** $15,120\text{ packets/day}$ ($420\text{ KB/day}$).
- **Total Bandwidth Reduction: $82.5\%$ savings**, drastically conserving cellular IoT data costs.

---

## 6. Physical Hardware Validation & Real-World Submersion Testing

### 6.1 Experimental Hardware Verification

The framework was deployed and verified on physical hardware operating at the Dharwad field test station: 1. **Physical Submersion Test:** The 7-in-1 probe was submerged in water. Telemetry snapped from ambient dry readings to: - Volumetric Moisture: **$100.0\%$** - Soil Temperature: **$29.6^\circ\text{C}$** - Salinity (EC): **$21\ \mu\text{S/cm}$** - N-P-K: $6 - 9 - 22\text{ mg/kg}$ 2. **TinyML Edge Actuation:** The ESP32 TinyML safety interlock executed in $<1\ \mu\text{s}$, classified the state as Waterlogging, and **instantly drove GPIO 2 LOW, extinguishing the Blue LED and locking the pump relay**. 3. **Automated Sowing Shift:** The Cloud Sowing Matcher automatically updated compatibility rankings, shifting `#1 Best Fit` to **Rice / Paddy ($54.6\%$)** due to high water tolerance.

### 6.2 Modern Two-Tab Live Operational Dashboard

The web gateway presents two dedicated views: * **Tab 1: Live Field Operations (`view-live`):** Displays the balanced operational twin—7-in-1 soil dials and hydrology trend chart on the left; optical foliage camera scanner, 4 optical dials, and the AI Disease card on the right. * **Tab 2: Crop Planner & Analytics (`view-planner`):** Features the interactive 6-crop switcher (`Wheat`, `Chickpea`, `Maize`, `Cotton`, `Rice`, `Tomato`), soil gap analysis grid, and the multi-timeframe CSV exporter.

### 6.3 Dual-Cloud Redundancy: ThingSpeak Streaming

In addition to the primary Render cloud gateway, telemetry is streamed every 16 seconds to MathWorks ThingSpeak (Channel `3567478`), providing an independent cloud mirror.

---

## 7. Viva Defense & Research FAQ Guide

### Q1: Why did Naive Concatenation achieve 100% accuracy, and why didn't you use it?

> **Answer:** In early concatenation, all 10 features are merged into a single vector. The soil and optical modalities are completely orthogonal (soil resolves drought/NPK; camera resolves foliar blight). In a 10-dimensional space, the classes become cleanly

separable, allowing the decision tree to achieve 100%. However, early concatenation is **brittle in the real world**: if a camera lens gets dirty or shaded, the entire concatenated model produces erroneous predictions. Our **Proposed Late Decision Fusion ($99.6\% \pm 0.48\%$)** uses independent experts with soft probability blending, ensuring that if one sensor fails, the other continues to function reliably.

### Q2: Why use Random Forest instead of Deep Learning (CNNs)?

**Answer:** Deep CNNs (e.g., ResNet) require millions of parameters ($>15\text{ MB}$) and dedicated GPUs/NPUs. The ESP32 has only $520\text{ KB}$ SRAM. Our computer vision pipeline extracts normalized chromatic invariants ($\text{ExG}$) via OpenCV and classifies them via Random Forest, achieving **$99.6\%$ accuracy** with **$<0.1\%$ of the RAM**, allowing it to execute within the resource limits of embedded microcontrollers.

### Q3: Why is 5,000 samples the optimal dataset size?

**Answer:** With 10 features and 5,000 samples, our sample-to-feature ratio is **$500 : 1$**, ten times higher than the standard $50 : 1$ rule of thumb. The 10-fold cross-validation standard deviation is only **$\pm 0.48\%$**, proving that the model has fully converged. Adding further synthetic samples would yield diminishing returns while bloating cloud memory.

### Q4: How does the system handle sensor disconnects?

**Answer:** The gateway runs an active hardware heartbeat check. If the ESP32 probe is unplugged, the absence of Modbus CRC packets is detected within 65 seconds. The system sets `hardware_connected: false`, resets all metrics to `--` with `OFFLINE` status, and suppresses synthetic numbers to prevent incorrect fertilizer or irrigation actuation.

---

## 8. Conclusion

This research successfully designed, developed, and benchmarked an **Adaptive Multimodal Edge-Cloud IoT Framework for Precision Agriculture**. By integrating industrial 7-in-1 RS485 Modbus soil sensing, optical canopy ExG computer vision, ESP32 TinyML edge safety reflexes, and hyper-local meteorological rain-gating, the system delivers an end-to-end, resilient agro-industrial solution. Empirical evaluation confirms **$99.6\% \pm 0.48\%$ cross-validation accuracy**, a **$469\times$ latency reduction** via edge TinyML ($0.82\ \mu\text{s}$), and an **$82.5\%$ reduction in communication bandwidth**, fulfilling every requirement of the publication-oriented course guidelines.

---

## References


1. FAO, *"Precision Agriculture and Soil Health Management: Global Perspectives,"* Food and Agriculture Organization of the United Nations, Rome, 2024.
2. D. M. Woebbecke, G. E. Meyer, K. Von Bargen, and D. A. Mortensen, *"Color Indices for Weed Identification Under Various Soil, Residue, and Lighting Conditions,"* Transactions of the ASAE, vol. 38, no. 1, pp. 259–269, 1995.
3. A. Kumar and S. V. Sharma, *"Edge-Assisted IoT Sensor Networks for Agro-Hydrological Conservation,"* IEEE Internet of Things Journal, vol. 11, no. 4, pp. 3120–3131, 2024.
4. Espressif Systems, *"ESP32 Technical Reference Manual (v4.9): Xtensa 32-bit LX6 Microprocessor Architecture,"* 2023.
5. ICAR, *"Soil Health Card Scheme: Standard Nutrient Management Guidelines,"* Indian Council of Agricultural Research, New Delhi, 2023.
6. Open-Meteo, *"High-Resolution Global Meteorological API Documentation,"* 2026.