

Changelog

All notable changes to this project will be documented in this file.

The format is based on [Keep a Changelog](#), and this project adheres to [Semantic Versioning](#).

[UNRELEASED]

Added

Client management

- `folio client new` — create a client interactively (same wizard previously only available inline during `folio new`).
- `folio client list` — table of all clients: slug, name, email, contact.
- `folio client show <slug>` — detailed view of a single client.

Template system

- Bundled document templates renamed from `invoice.html` → `document.html`. Custom templates using `invoice.html` continue to work as a legacy fallback.
 - Each bundled template now ships with `email.html` — a Tera HTML email template for the email body, styled to match the template's personality. Resolution order: custom `email.html` → bundled `email.html` → `[email.templates].body` in config → hardcoded default.
 - All six bundled `email.html` templates redesigned as full HTML emails (responsive layout, inline styles); emails are sent as `text/html` instead of plain text.
 - `folio templates export` now exports `document.html`, `email.html`, and `template.toml`.
 - `render_email_body` and `render_email_subject` now receive `document_type` in their Tera context so email templates can reference `{{ document_type }}` (“Invoice” or
-

“Quote”).

- Default email subject updated to `{{ document_type }} {{ invoice.id }}` from `{{ me.company }}`.
- `[email.templates].body` removed from the `folio init` generated config; body is now driven by the template's `email.html`.

First-class invoice and quote parity

- `folio invoice` subcommand group — mirrors `folio quote` exactly: `new`, `list`, `build`, `send`, `paid`, `void`, `preview`, `summary`. Invoices and quotes are now equal citizens at the CLI level.
 - `folio new --type invoice|quote` — global create command now prompts for document type when `--type` is not given.
 - `folio build <id>` — auto-detects invoice vs quote from the filesystem; no flag needed.
 - `folio send <id>` — auto-detects invoice vs quote from the filesystem.
 - `folio preview <id>` — auto-detects invoice vs quote from the filesystem.
 - `folio list` now shows both invoices and quotes by default with a `TYPE` column. Use `--type invoice` or `--type quote` to filter to one kind.
 - `folio summary` now includes a Quote Pipeline section (total quoted, accepted, pending, by-status breakdown) after the invoice financials.
 - `[invoice]` section in `folio.toml` — type-specific defaults for `template`, `id_format`, `due_days`; takes priority over shared `[defaults]`.
 - `[quote]` section in `folio.toml` — type-specific defaults for `template`, `id_format`, `expires_days`; takes priority over shared `[defaults]`.
 - `[defaults]` is now the truly shared fallback layer (currency, tax_rate, template, primary_color, notes); type-specific settings (`id_format`, `due_days`, `expires_days`) live in `[invoice]` / `[quote]` only.
 - `folio init` no longer creates empty directories — they are created on demand when the first document is saved.
 - `folio init` now writes a detailed `README.md` to the new repo with a full quick-start guide, client/document examples, and layout reference.
-

Quotations (first introduced this release)

- New `Quote` document type stored as `quotes/{year}/{id}.toml` — same line-item model as invoices but with an `expires` date and its own status lifecycle.
- `folio quote new` — interactive wizard to create a quote with auto-generated `QUO-{year}-{seq:03}` IDs.
- `folio quote list` — colour-coded table (expired=red, sent=yellow, accepted=green, draft/declined=dim) with PDF freshness indicator.
- `folio quote build` — render a quote to PDF using any bundled or custom template.
- `folio quote send` — email a quote as a PDF attachment and record the `[sent]` block.
- `folio quote accept` — mark a quote as accepted; `--convert` automatically creates an invoice from the quote's line items and records the resulting invoice ID in `[accepted].invoice_id`.
- `folio quote decline` — mark a quote as declined with an optional `--reason`.
- `folio quote preview` — open the rendered quote HTML in the default browser.
- Quote status lifecycle: `draft` → `sent` → `accepted` / `declined` / `expired` (auto, when `expires < today`).
- `folio init` now creates the `quotes/` directory as part of the standard scaffold.
- All six bundled templates updated to use `document_type` and `due_label` Tera variables; quotes render with `Quote` heading and `Expires` date label; existing invoices are unaffected.

Changed

- Invoice notes are now displayed in a side-by-side layout next to the totals block rather than below the line-items table.
 - All six bundled document templates: notes text rendered at a smaller font size and explicitly left-aligned to prevent renderer-dependent alignment issues.
 - SMTP credentials (`username` / `password`) are now optional when the password is empty, enabling unauthenticated connections to local mail catchers (e.g. Mailpit) without requiring dummy credentials.
-

Fixed

- All computed amounts (`subtotal` , `tax_amount` , `total` , `outstanding`) are now rounded to 2 decimal places.
- Invoice and quote notes are trimmed of surrounding whitespace via Tera's `| trim` filter before rendering, fixing lines appearing centred or offset when `white-space: pre-wrap` was in effect.

[0.1.1] - 2026-05-25

Added

- `[defaults].notes` in `folio.toml` — a global fallback note rendered on every invoice that does not define its own `notes` .
- `[defaults].notes` in `clients/{slug}.toml` — a per-client fallback (e.g. payment details) that takes priority over the global default but loses to a note written directly on the invoice.
- Resolution order: `invoice.notes` → `client [defaults].notes` → `folio.toml [defaults].notes` .

0.1.0 - 2026-05-25

Added

Core

- Plaintext invoice management stored entirely in TOML files, designed to live in a git repository.
 - `folio init` — initialise a new folio repository with `folio.toml` , directory scaffold, `.gitignore` , and `git init` .
 - `folio new` — interactive invoice creation with auto-generated sequential IDs; inline client creation if the client does not exist yet.
 - `folio build` — render invoices to PDF via headless Chrome/Chromium, with a
-

`--status` , `--force` , and `--open` flags.

- `folio send` — email an invoice via SMTP, SendGrid, or Resend and append a `[sent]` block to the invoice file. Pass `--manual` to skip the email and record `method = "manual"` instead (for invoices delivered outside of folio).
- `folio paid` — mark an invoice as paid with optional `--amount` , `--method` , `--ref` , and `--date` flags.
- `folio void` — void an invoice with an optional `--reason` .
- `folio list` — colour-coded table of invoices showing ID, client, dates, total, status, and PDF freshness indicator.
- `folio summary` — aggregate financial report: total billed, paid, outstanding, per-client breakdown, and per-currency breakdown when multiple currencies are in use.
- `folio preview` — open the rendered invoice HTML in the default browser without producing a PDF; useful for iterating on template design.
- `folio templates` — list all available templates (bundled and custom), or export a bundled template to a local directory for customisation.
- `folio update` — self-update the binary to the latest GitHub release via axoupdater. `--check` flag reports availability without installing.

Invoice model

- Invoice status derived at runtime from file state: `draft` , `sent` , `overdue` , `paid` , `partially_paid` , `voided` .
- Per-invoice and per-client overrides for `currency` , `template` , `due_days` , `tax_rate` , and `primary_color` .
- `[sent]` , `[paid]` , and `[voided]` blocks appended in place by CLI commands, preserving all existing file content.
- Computed fields: `subtotal` , `tax_amount` , `total` , `outstanding` .

Templates

- Five bundled Tera/HTML invoice templates, all rendered with Tailwind CSS via CDN (no build step):
-

- `basic` — clean, minimal, black and white.
 - `classic` — traditional ruled header and footer, serif typeface.
 - `modern` — bold accent colour, sans-serif, left-aligned logo block.
 - `floral` — decorative botanical header and footer, warm terracotta palette.
 - `slate` — dark header band, light body, sky-blue accent.
 - `signature` — editorial serif design; cream paper (`#fcfaf8`), forest-green ink, EB Garamond italic accents.
- Configurable primary/accent colour (`primary_color`) supported by all six templates. A single hex value is expanded into a full tonal palette (`primary` , `primary_mid` , `primary_light` , `primary_dark` , `primary_alpha_low` , `primary_alpha_very_low`) and injected as a `theme` context variable.
 - Custom template support: any directory under `templates/` containing `invoice.html` is automatically discovered and takes priority over a bundled template of the same name.
 - Template context includes `me` , `client` , `invoice` (with computed fields), and `theme` (when `primary_color` is set).

Configuration

- `folio.toml` — global config with `[me]` , `[defaults]` , `[email]` , `[build]` , and `[paths]` sections.
 - Configurable directory layout via `[paths]` : `clients` , `invoices` , `templates` , `output` can each be redirected.
 - Email provider config for SMTP (with `FOLIO_SMTP_PASSWORD` env var, optional for local testing), SendGrid (`FOLIO_SENDGRID_API_KEY`), and Resend (`FOLIO_RESEND_API_KEY`).
 - `Smtplib` supports a `tls` field (`true` by default); set to `false` for plain/unencrypted SMTP connections such as local mail catchers.
 - Customisable email subject and body templates (Tera syntax).
 - `FOLIO_CONFIG` env var to override the path to `folio.toml` .
 - `FOLIO_CHROME_PATH` env var to specify the Chrome/Chromium binary.
-

Testing

- Email integration tests against **Mailpit** via `docker compose up -d` ; covers plain send, CC recipients, PDF attachments, and missing-config error path.
- `docker-compose.yml` included in the repository root to spin up Mailpit on SMTP `:1025` and HTTP API `:8025` .
- Integration tests are `#[ignore]` d and opt-in: `cargo test --test email_integration -- --ignored` .

Distribution

- cargo-dist artifact renamed from `folio-cli-*` to `folio-*` via `[package.metadata.dist] name = "folio" in folio-cli/Cargo.toml` .
-