OSHA COMPLIANT

29 CFR 1910 · GENERAL INDUSTRY

WORKPLACE SAFETY PLAN

All personnel must read, understand, and follow this Safety Plan at all times. This facility operates robotic arm systems, conveyor belts, and pneumatic actuators. Although hazard severity is moderate, OSHA regulations still apply fully. Failure to comply may result in serious injury or disciplinary action.

1 MACHINE GUARDING & ROBOTIC SAFETY

29 CFR 1910.212 / 1910.217

🚫

NO BYPASSING GUARDS
Never remove, disable, or reach past machine guards or safety interlocks on conveyor belts or robot work cells.

🦾

ROBOTIC CELL CLEARANCE
Stay outside the marked robot work envelope at all times during operation. Enter only after full power-down.

🔒

LOCKOUT / TAGOUT (LOTO)
Before any maintenance or jam clearance, follow LOTO procedures: isolate energy, lock, tag, verify zero energy state.

⛔

CONVEYOR BELT SAFETY
Do not reach into moving conveyors. Use proper tools to clear jams. Keep loose clothing, hair, and jewelry secured.

2 PNEUMATIC SYSTEM SAFETY

29 CFR 1910.147 / 1910.169

💨

DEPRESSURIZE BEFORE SERVICE
Always bleed pneumatic lines to zero pressure before disconnecting fittings or performing maintenance.

🧯

NO HORSEPLAY WITH AIR
Never point air nozzles at people. Compressed air above 30 psi can penetrate skin and cause fatal embolisms.

🔍

INSPECT HOSES DAILY
Check all pneumatic hoses and fittings for cracks, wear, or leaks before startup. Report damage immediately.

3 PERSONAL PROTECTIVE EQUIPMENT (PPE)

29 CFR 1910.132-138

🥽

SAFETY GLASSES
Required at all times on the factory floor. Protect against pneumatic debris and packaging fragments.

👟

CLOSED-TOE FOOTWEAR
Steel-toed or sturdy closed-toe shoes required. No sandals, heels, or open-toe footwear on factory floor.

🧤

GLOVES (TASK-SPECIFIC)
Wear cut-resistant gloves when handling packaging edges. Remove gloves near rotating machinery.

🦺

SECURE ALL CLOTHING
Tie back long hair. No loose sleeves, dangling lanyards, or jewelry near conveyor or robot systems.

4 ELECTRICAL SAFETY & HOUSEKEEPING

29 CFR 1910.303 / 1910.22

🚪

EMERGENCY EXITS CLEAR
Aisles, exits, and fire extinguisher access must remain unobstructed at all times (minimum 28" aisle width).

📢

REPORT HAZARDS IMMEDIATELY
Report any unsafe condition, near-miss, or injury to the supervisor immediately — no matter how minor.

🚨

EMERGENCY CONTACTS

In case of injury, fire, or any life-threatening event — act immediately.

For non-emergency safety concerns, contact your supervisor or safety officer directly.

EMERGENCY SERVICES
911

POISON CONTROL
1-800-222-1222

OSHA HOTLINE
1-800-321-OSHA