
WEB TECHNOLOGY

LAB8

Name : Krishanu Mishra
Roll no.: 22IT3020

T1. Develop a currency converter application that allows users to input an amount in one currency and convert it to another. For the sake of this challenge, you can use a hard-coded exchange rate. Take advantage of React state and event handlers to manage the input and conversion calculations.

```
import React, { useState } from 'react';
import './App.css';

function App() {
  const [amount, setAmount] = useState('');
  const [fromCurrency, setFromCurrency] = useState('USD');
  const [toCurrency, setToCurrency] = useState('INR');
  const [convertedAmount, setConvertedAmount] = useState(null);

  const handleAmountChange = (event) => {
    setAmount(event.target.value);
  };

  const handleFromCurrencyChange = (event) => {
    setFromCurrency(event.target.value);
  };

  const handleToCurrencyChange = (event)
    => {
    setToCurrency(event.target.value);
  };

  const handleConvert = () => {
    let exchangeRate
    if fromCurrency === 'USD' && toCurrency === 'INR'
```

```

    exchangeRate = 82.91;
  } else if (fromCurrency === 'INR' && toCurrency === 'USD') {
    exchangeRate = 1 / 82.91;
  } else {
    exchangeRate = 1;
  }

  const converted = parseFloat(amount) * exchangeRate;
  setConvertedAmount(converted.toFixed(2));
};

return (
  <div className="App">
    <h1>Currency Converter</h1>
    <div>
      <label>
        Amount
        :
        <input type="number" value={amount}
onChange={handleAmountChange} />
      </label>
    </div>
    <div>
      <label>
        From:
        <select value={fromCurrency}
onChange={handleFromCurrencyChange}>
          <option value="USD">USD</option>
          <option value="INR">INR</option>
        </select>
      </label>
    </div>
    <div>
      <label>
        >
        To:
        <select value={toCurrency} onChange={handleToCurrencyChange}>
          <option value="USD">USD</option>
          <option value="INR">INR</option>
        </select>
      </label>
    </div>
    <button onClick={handleConvert}>
      </button>

```

```

    {convertedAmount && (
      <p>{amount} {fromCurrency} equals {convertedAmount}
    {toCurrency}</p>
    )}
  )}
</div>
);
}

export default App

```

Currency Converter

Amount:

From: USD ▾

To: INR ▾

1 USD equals 82.91 INR

T2. Create a stopwatch application through which users can start, pause and reset the timer. Use React state, event handlers and the `setTimeout` or `setInterval` functions to manage the timer's state and actions.

```

// App.js
import React, { useState, useRef } from 'react';
import './App.css';

function App() {
  const [time, setTime] = useState(0);
  const [isRunning, setIsRunning] =
    useState(false); const intervalRef =
    useRef null

```

```

const handleStart = () => {
  setIsRunning(true);
  intervalRef.current = setInterval(() => {
    setTime((prevTime) => prevTime + 1);
  }, 1000);
};


const handlePause = () => {
  clearInterval(intervalRef.current);
  setIsRunning(false);
};

const handleReset = () => {
  clearInterval(intervalRef.current);
  setTime(0);
  setIsRunning(false);
};

const formatTime = (timeInSeconds) => {
  const minutes = Math.floor(timeInSeconds / 60);
  const seconds = timeInSeconds % 60;
  return (
    String(minutes).padStart(2, '0') + ':' +
    String(seconds).padStart(2, '0')
  );
};

return (
  <div className="App">
    <h1>Stopwatch</h1>
    <div className="timer">{formatTime(time)}</div>
    <div className="controls">
      {!isRunning ? (
        <button onClick={handleStart}>Start</button>
      ) : (
        <button onClick={handlePause}>Pause</button>
      )}
      <button onClick={handleReset}>Reset</button>
    </div>
  </div>

```



T3. Develop a messaging application that allows users to send and receive messages in real time. The application should display a list of conversations and allow the user to select a specific conversation to view its messages. The messages should be displayed in a chat interface with the most recent message at the top. Users should be able to send new messages and receive push notifications.

```
import React, { useState, useEffect } from
'react'; import './App.css';

function App() {
  const [conversations, setConversations] = useState([]);
  const [selectedConversation, setSelectedConversation] =
  useState(null); const [newMessage, setNewMessage] = useState('');
  const [messages, setMessages] = useState([]);

  useEffect(() => {
    fetchConversations();
  }, []);
```

```

useEffect(() => {
  if (selectedConversation) {
    fetchMessages(selectedConversation.id);
  }
}, [selectedConversation]);

const fetchConversations = () => {
  const mockConversations = [
    { id: 1, name: 'Friend 1' },
    { id: 2, name: 'Friend 2' },
  ];
  setConversations(mockConversations);
};

const fetchMessages = (conversationId) => {
  const mockMessages = [
    { id: 1, text: 'Hello!', sender: 'Friend 1', timestamp: new Date() },
    { id: 2, text: 'Hi there!', sender: 'You', timestamp: new Date() },
  ];
  setMessages(mockMessages);
};

const handleConversationClick = (conversation) => {
  setSelectedConversation(conversation);
};

const handleMessageSend = () => {
  const message = { id: messages.length + 1, text: newMessage, sender:
'You', timestamp: new Date() };
  setMessages([message, ...messages]);
  setNewMessage('');
};

return (
  <div className="App">
    <div className="sidebar">
      <h2>Conversations</h2>
      <ul>

```

```

        {conversations.map((conversation) => (
            <li key={conversation.id} onClick={() =>
handleConversationClick(conversation)}>
                {conversation.name}
            </li>
        ))}
    </ul>
</div>
<div className="chat">
    <h2>Chat</h2>
    {selectedConversation && (
        <div>
            <h3>{selectedConversation.name}</h3>
            <div className="messages">
                {messages.map((message) => (
                    <div key={message.id} className={message.sender === 'You'
? 'sent' : 'received'}>
                        <p>{message.text}</p>
                        <span>{message.sender} -
{message.timestamp.toLocaleString()}</span>
                    </div>
                ))}
            </div>
            <div className="message-input">
                <input type="text" value={newMessage} onChange={(e) =>
setNewMessage(e.target.value)} />
                <button onClick={handleMessageSend}>Send</button>
            </div>
        </div>
    )}
</div>
</div>
);
}

export default App;

```

