



Hardware Build System User Manual

Revision 0.0

20 December 2025

Abstract

This document serves as the official user manual for Hardware Build System (HBS). HBS is a Tcl-based, minimal common abstraction approach for build system for hardware designs. The main goals of the system include simplicity, readability, a minimal number of dependencies, and ease of integration with the existing Electronic Design Automation (EDA) tools.

keywords: automation, hardware build system, hardware design, hardware synthesis, project maintenance, testbench runner, simulation, FPGA, ASIC, productivity

Contents

1 Overview	6
2 Installation	6
2.1 Dependencies	6
3 Internal architecture	6
3.1 General structure	7
3.2 Cores and cores detection	7
3.2.1 Excluding hbs files from being sourced	9
3.3 Targets and targets detection	9
3.4 Testbench targets	9
3.5 Running targets	10
3.6 Targets parameters	10
3.7 Target context	10
3.8 Target dependencies	10
3.9 EDA tool flow and stages	10
3.10 EDA tool commands custom arguments	10
3.11 HBS API extra symbols	10
3.12 Code generation	11
4 Command line interface commands	11
4.1 doc - viewing HBS API documentation	11
4.2 dump-cores - dumping cores information	11
4.3 graph - generating dependency graph	11
4.4 help - displaying help message for commands	11
4.5 list-cores - listing cores found in hbs files	11
4.6 list-targets - listing targets for discovered cores	12
4.7 list-tb - listing testbench targets	12
4.8 run - running targets	12
4.9 test - running testbench targets	12
4.10 version - displaying HBS version	13
4.11 whereis - locating cores definition	13
5 Tcl tips	13
5.1 Support for arrow keys in tclsh	13
5.2 Passing variadic arguments to proc	13

Participants

Michał Kruszewski, *Chair, Technical Editor*, mkru@protonmail.com

Glossary

Not all terms defined in the glossary list are used in the user manual. Some of them are formally defined because they are helpful when discussing, for example, core definition.

core

Tcl namespace in which `hbs::Register` proc is called.

core name

Name of the Tcl namespace in which `hbs::Register` is called. For example, if `hbs::Register` is called in namespace `lib::pkg::my-core`, then `my-core` is the core name.

core path

Tcl namespace for the core. For example, if `hbs::Register` is called in namespace `lib::pkg::my-core`, then `lib::pkg::my-core` is the core path.

dependency

A target on which at least one other target depends. The dependency is an argument for at least one `hbs::AddDep` proc call.

depender

A target depending on at least one another target. Within a depender body the `hbs::AddDep` proc is called at least once.

flow

An ordered set of actions taken by a tool to produce a result specified by a user.

hbs file

A file with `.hbs` extension containing valid Tcl code.

proc

A Tcl procedure.

stage

A piece of a tool flow with a clearly defined task and output. The number and types of stages depend on a tool. For example, the GHDL has analysis, elaboration and simulation stages.

target

A proc, which name does not start with the floor character (`_`), defined in core.

target name

The name of the target in the target path. For example, if the target path is `lib::pkg::my-core::my-target`, then the target name is `my-target`.

target path

The Tcl path for the target. For example, if proc `my-target` is defined in the core with the core path `lib::pkg::my-core`, then the target path is `lib::pkg::my-core::my-target`.

tool

A software capable of processing hardware description sources or output from another tool. Example tools are: GHDL, Verilator, yosys, Vivado, nvc, etc.

to run a target

To execute commands defined in the target.

1 Overview

Hardware Build System (HBS) is a build system for hardware design projects. A build system for hardware design collects and processes files required for FPGA programming, ASIC production, running functional simulation, or carrying out formal verification. The files required to obtain desired output usually include much more than just classic hardware description files such as VHDL or SystemVerilog sources. For example, any synthesis or place and route tool requires also design constraints, at least for pin location and timing closure analysis. Moreover, most of real projects are not implemented from scratch and utilize third-party IP cores. Those IP cores might be provided in different formats. Sometimes, they might even be encrypted. HBS tries to support all files that might potentially be required to generate final result. HBS does not limit to managing only pure hardware description files.

HBS was created out of frustration with all existing build systems for hardware designs.

2 Installation

All installation methods require that `hbs` and `hbs.tcl` files are placed in the same directory. There are four preferred installation methods.

1. Copy `hbs` and `hbs.tcl` files to your project. This is preferred if you want to modify HBS source files change its default behavior. It is not advised to change the default behavior, but if you need, feel free to adjust the build system to your project needs.
2. Copy `hbs` and `hbs.tcl` files to one of the directories in the `$PATH` environment variable.
3. Clone the repository and add its path to the `$PATH` environment variable.
4. Clone the repository and add an alias to the `hbs` file in `.bashrc` file (or equivalent).

2.1 Dependencies

HBS has three dependencies, one mandatory and two optional.

1. `tclsh` (version `>= 8.5`).
2. `python3` - required for testbench target detection, automatic testbench running and dependency graph generation. If mentioned functionalities are not required, you can directly use `hbs.tcl` script instead of the `hbs` Python wrapper.
3. `graphviz` - required only if user wants to generate a dependency graph.

3 Internal architecture

It was decided that HBS will be implemented using Tcl language because of the following reasons:

1. Implementing a hardware build system in Tcl allows the execution of build system code during the EDA tool flow. This, in turn, gives direct access to all EDA tool custom commands. Moreover, these custom commands can be evaluated in arbitrary places.
2. If the EDA tool provides the Tcl interface, then the Tcl shell is provided by the EDA tool vendor. The shell is installed during the installation of vendor tools. This implies that, in some cases, the build system user does not even have to install additional programs.
3. Executing arbitrary programs in arbitrary places in Tcl is very simple. There is a dedicated `exec` command for invoking subprocesses. If executing a subprocess requires prior dynamic arguments evaluation, the `exec` command call must be prepended with the `eval` command. Even in Python, invoking a subprocess is not so straightforward.

One of the most important things while designing the HBS was the separation of common build process operations that would constitute a common abstraction layer over EDA tools. At the end, it was decided that the following actions should constitute the common abstraction layer:

1. Target device setting - some EDA tools use the term “part” instead of “device,” for example, Vivado. Simulation EDA tools do not require a device setting. However, all synthesis EDA tools require

information on the target device. This is why setting the device became part of the common abstraction layer.

2. File addition - this includes support for adding files of all formats supported by a given EDA tool.
3. Library setting - setting HDL file library.
4. HDL standard setting - setting HDL file standard revision. The build system has to manage this because some tools can not handle analyzing different design units using different standard revisions, for example, nvc. In such a case, the build system must decide what the common standard revision shall be used for analyzing all HDL files.
5. Dependency specification - this is the core feature of any build system.
6. Generics/parameters setting - configuring parametric designs must be an inherent feature of any hardware build system.
7. Design top module setting - all EDA tools carrying out simulation or synthesis requires information on the top module.
8. Code generation - a hardware build system must provide a simple way for automatic arbitrary code generation. This is further explained in [Section 3.12](#).

3.1 General structure

The HBS is implemented in two files `hbs.tcl` and `hbs`. The first is implemented in Tcl, and the second in Python. The `hbs.tcl` file implements all the core features related directly to the interaction with the EDA tools. The `hbs.tcl` provides the following functions:

1. Dumping information about detected cores in JSON format.
2. Listing cores found in `hbs` files.
3. Listing targets for a given core.
4. Running target provided as a command line argument.

The `hbs` is a wrapper for the `hbs.tcl` and serves the following additional functions:

1. Showing documentation for `hbs` Tcl symbols.
2. Generating dependency graph.
3. Listing testbench targets.
4. Running testbench targets.

By default, the user calls the `hbs` program. However, if none of the additional functions are required, the user can call the `hbs.tcl` directly. In such a case, the whole build system is limited to a single file.

3.2 Cores and cores detection

When the user calls `hbs` (or `hbs.tcl`), all directories, starting from the working directory, are recursively scanned to discover all files with the `.hbs` extension (symbolic links are also scanned). Files with the `.hbs` extension are regular Tcl files that are sourced by the `hbs.tcl` script. However, before sourcing `hbs` files, the file list is sorted so that scripts with shorter path depth are sourced as the first ones. For example, let us assume the following three `hbs` files were found:

- `a/b/c/foo.hbs`,
- `d/bar.hbs`,
- `e/f/zaz.hbs`.

Then, they would be sourced in the following order:

1. `d/bar.hbs`,
2. `e/f/zaz.hbs`,
3. `a/b/c/foo.hbs`.

Such an approach allows controlling when custom symbols (Tcl variables and procedures) are ready to use. For example, if the user has a custom procedure used in multiple `hbs` files, then the user can create

separate `utils.hbs` file containing utility procedures, and place it in the the project root directory. This guarantees that `utils.hbs` will be sourced before any `hbs` file in subdirectories. Within `hbs` files, the user usually defines cores and targets, although the user is free to have any valid Tcl code in `hbs` files.

The below snippet presents a very basic flip-flop core definition. The flip-flop core has a single target named `src`. The core consists of a single VHDL file.

```
namespace eval flip-flop {
  proc src {} {
    hbs::AddFile flip-flop.vhd
  }
  hbs::Register
}
```

To register a core, the user must explicitly call `hbs::Register` procedure at the end of the core namespace. Such a mechanism helps to distinguish regular Tcl namespaces from Tcl namespaces representing core definitions. If the user forgets to register a core, the build system gives a potential hint. An example error message is presented below.

```
[user@host tmp] hbs run lib::core::tb
checkTargetExists: core 'lib::core' not found, maybe the core is not:
  1. registered 'hbs doc hbs::Register',
  2. sourced 'hbs doc hbs::IgnoreRegexes'.
```

Each core is identified by its unique path. The core path is equivalent to the namespace path in which `hbs::Register` is called. Using the namespace path as the core path gives the following possibilities:

1. The user can easily stick to the VLNV identifiers if required. This is presented in the below snippet. In this case, the flip-flop core path is `vendor::library::flip-flop::1.0`.

```
namespace eval vendor::library::flip-flop::1.0 {
  proc src {} {
    hbs::AddFile flip-flop.vhd
  }
  hbs::Register
}
```

2. The user can define arbitrary deep core paths (limited by the Tcl shell). This is presented in the below snippet. In this case, the core path consists of seven parts.

```
namespace eval a::b::c::d::e::f::flip-flop {
  proc src {} {
    hbs::AddFile flip-flop.vhd
  }
  hbs::Register
}
```

3. The user can nest namespaces to imitate the structure of libraries and packages. This is presented in following snippet.

```
namespace eval lib {
  namespace eval pkg1 {
    namespace eval d-flip-flop {
      proc src {} {
```



```

        hbs::AddFile d-flip-flop.vhd
    }
    hbs::Register
}
namespace eval t-flip-flop {
    proc src {} {
        hbs::AddFile t-flip-flop.vhd
    }
    hbs::Register
}
}
namespace eval pkg2 {
    namespace eval jk-flip-flop {
        proc src {} {
            hbs::AddFile jk-flip-flop.vhd
        }
        hbs::Register
    }
}
}
}

```

Three flip-flop cores are defined in the snippet. The below snippet presents output for listing flip-flop cores.

```

[user@host tmp]$ hbs list-cores
lib::pkg1::d-flip-flop
lib::pkg1::t-flip-flop
lib::pkg2::jk-flip-flop

```

3.2.1 Excluding hbs files from being sourced

Sometimes a file with the .hbs extension is not a valid hbs file, or maybe you want to temporarily disable valid hbs files from being sourced. HBS provides a built-in mechanism for excluding files with the .hbs extension from being sourced. This is achieved using the `hbs::AddIgnoreRegex` function. You just have to call this function in one of valid hbs files. The function will be executed once the file containing the call is sourced.

Usually the hbs file containing calls to the `hbs::AddIgnoreRegex` proc is placed in the project root directory. This is because hbs files placed in the project root directory are sourced before hbs files placed in subdirectories. Order of hbs files sourcing is described in [Section 3.2](#).

Arguments provided to the `hbs::AddIgnoreRegex` proc are treated as regular expressions. This allows for ignoring multiple paths using a single regex. However, you are free to provide multiple ignore regex, and all of them will be checked while sourcing hbs files.

3.3 Targets and targets detection

3.4 Testbench targets

HBS is capable of automatically detecting testbench targets. Testbench targets are targets which names:

1. start with the `tb-` or `tb_` prefix,
2. end with the `-tb` or `_tb` suffix,
3. equal `tb`.

For example, for the following hbs file:

```

namespace eval my-core {
  proc tb {} {
    puts "Hello from tb"
  }
  proc my-tb {} {
    puts "Hello from my-tb"
  }
  proc tb_my {} {
    puts "Hello from tb_my"
  }
  hbs::Register
}

```

the hbs program detects the following testbench targets:

```

[user@host tmp] hbs list-tb
my-core::my-tb
my-core::tb
my-core::tb_my

```

3.5 Running targets

3.6 Targets parameters

3.7 Target context

3.8 Target dependencies

3.9 EDA tool flow and stages

3.10 EDA tool commands custom arguments

3.11 HBS API extra symbols

The HBS API consists not only of symbols related to the common EDA abstraction layer. For example, there are extra `hbs::Exec` and `hbs::CoreDir` procedures. The first one is a wrapper for the Tcl standard `exec` procedure. Before calling `exec`, the `hbs::Exec` changes the working directory to the directory where the currently evaluated core is defined. When `exec` returns, the `hbs::Exec` restores the working directory. The `hbs::CoreDir` procedure allows the user to get the path of the directory in which the currently evaluated core is defined.

HBS also provides users with the following extra variables:

1. `hbs::ThisCorePath` - the path of the core which target is currently being run,
2. `hbs::ThisTargetPath` - the path of the target which is currently being run,
3. `hbs::ThisTargetName` - the name of the target which is currently being run,
4. `hbs::TopCorePath` - the path of the top core beign run,
5. `hbs::TopTargetPath` - the path of the top target being run,
6. `hbs::TopTarget` - the name of the top target being run,
7. `hbs::TopTargetArgs` - the list with command line arguments passed to the top target.

To get the list of all HBS public symbols you can run `hbs doc` command in the shell.

3.12 Code generation

4 Command line interface commands

4.1 doc - viewing HBS API documentation

The doc command was added to ease viewing documentation for HBS Tcl symbols. The command is executed by the hbs file, so Python is required for the command to work. If no argument is provided for the doc command, then hbs prints a list of all HBS Tcl public symbols. To get more information on the particular symbol, simply provide it as an argument for the doc command. The below snippet presents an example of doc command output.

```
[user@host ~] hbs doc SetStd
# Sets standard revision for HDL files.
#
# To get the value of currently set standard revision simply
# read the value of hbs::Std variable.
#
# Standard revision for a given file must be set before adding a file.
# For example:
#   hbs::SetStd 2008
#   hbs::AddFile entity.vhd
proc SetStd {std}
```

4.2 dump-cores - dumping cores information

4.3 graph - generating dependency graph

4.4 help - displaying help message for commands

The help command serves as a standard help message display command. If no argument is provided, then the help message regards the hbs general use. If argument is provided for the help command, then it must be a valid command name. In such a case, hbs prints help message for the provided command.

4.5 list-cores - listing cores found in hbs files

The list-cores command allows listing all cores discovered by the HBS. You can run `hbs help list-cores` to see help message for the command. The list-cores command is executed by the `hbs.tcl` file, so the command does not require Python to work. The below snippet presents an output for listing all cores in the [VHDL APB library](#).

```
[user@ahost apb] hbs list-cores
vhdl::amba5::apb::bfm
vhdl::amba5::apb::cdc-bridge
vhdl::amba5::apb::checker
vhdl::amba5::apb::crossbar
vhdl::amba5::apb::mock-completer
vhdl::amba5::apb::pkg
vhdl::amba5::apb::serial-bridge
vhdl::amba5::apb::shared-bus
```

The below snippet presents an output for listing various bridge cores in the same APB library.

```
[user@ahost apb] hbs list-cores bridge
vhdl::amba5::apb::cdc-bridge
vhdl::amba5::apb::serial-bridge
```

Please note that you can provide arbitrary strings to the `list-cores` command. The core is listed if its core path contains at least one string provided in arguments. For example, the below snippet presents an output for listing all cores containing the `bri` or `bar` string in the same APB library.

```
[user@host apb] hbs list-cores bri bar
vhdl::amba5::apb::cdc-bridge
vhdl::amba5::apb::crossbar
vhdl::amba5::apb::serial-bridge
```

4.6 list-targets - listing targets for discovered cores

4.7 list-tb - listing testbench targets

The `list-tb` command allows listing all testbench targets discovered by HBS. You can run `hbs help list-tb` to see help message for the command. The `list-tb` command is analogous to the `list-targets` command, but it works solely on testbench targets instead of all targets. The command is executed by the `hbs` file and requires Python to work. The below snippet presents an output for listing testbench targets for bridges in the [VHDL APB library](#).

```
[user@host apb] hbs list-tb bridge
vhdl::amba5::apb::cdc-bridge::tb-to-faster
vhdl::amba5::apb::cdc-bridge::tb-similar-slower
vhdl::amba5::apb::cdc-bridge::tb-similar-faster
vhdl::amba5::apb::cdc-bridge::tb-to-slower
vhdl::amba5::apb::serial-bridge::tb-write
vhdl::amba5::apb::serial-bridge::tb-read
```

If no arguments are provided for the `list-tb` command, then all testbench targets for all discovered cores are listed.

4.8 run - running targets

The `run` command allows running target procedures. You can run `hbs help run` to see help message for the command. Usually, targets are run to carry out the build process or simulation. However, the user is free to carry out any action in the target being run. You can, for example, use targets for software recompilation.

Running targets is described in [Section 3.5](#), [Section 3.6](#), and [Section 3.7](#).

4.9 test - running testbench targets

The `test` command allows running all automatically discovered testbench targets. You can run `hbs help test` to see help message for the command. The `test` command is executed by the `hbs` file and requires Python to work. By default, testbench targets are run in parallel. The default number of workers equals the number of threads on your CPU. If you provide extra arguments to the `test` command, only testbench targets which path contain at least one of the provided strings are run. The below snippet presents an output for running all testbenches of the bus functional model in the [VHDL APB library](#).

```
[user@host ap] hbs test bfm
running 4 targets with 16 workers

vhdl::amba5::apb::bfm::tb-readb    passed  warnings: 1
vhdl::amba5::apb::bfm::tb-read     passed  warnings: 1
vhdl::amba5::apb::bfm::tb-write    passed  warnings: 1
vhdl::amba5::apb::bfm::tb-writeb   passed  warnings: 1

time:      0 h 0 min 0 s
targets:   4
passed:    4
failed:    0
errors:    0
warnings:  4
```

4.10 version - displaying HBS version

The version command displays version of installed HBS. This might be helpful if the same build procedure works on one machine, but does not work on another. Based on the version and changelog, you can quickly discover differences. The below snippet shows an example output for the version command.

```
[user@host ~ 0] hbs version
1.0
```

4.11 whereis - locating cores definition

5 Tcl tips

5.1 Support for arrow keys in tclsh

If you ever tried to use tclsh to REPL (read-eval-print-loop), you probably realized that tclsh by default does not support arrow keys. You can't fix a typo in a line without deleting some line content. There is also no command history support. However, this can be improved. The first solution is install the rlwrap program and call rlwrap tclsh instead of tclsh. To make it shorter to type, you can define an alias for your shell of choice, for example, for bash alias tclsh='rlwrap tclsh'. The second option is to install the Tcl tclreadline package. This package often comes as OS distro package. For example, on Debian/Ubuntu, you can install it with `apt install tcl-tclreadline`. Once installed, create .tclshrc file in your home directory and add the following content:

```
package require tclreadline
tclreadline::Loop
```

Not only you will get support for arrow keys and command history, but also improved prompt.

5.2 Passing variadic arguments to proc

To pass variadic arguments to a proc, the last proc parameter must be called args. You can then easily iterate over the arguments using the foreach loop. The below example is taken directly from the hbs Tcl source code.

```
proc AddIgnoreRegex {args} {
    foreach reg $args {
```

```
hbs::dbg "adding ignore regex $reg"  
lappend hbs::IgnoreRegexes $reg  
}  
}
```