



[Home](#) | [Login](#) | [Logout](#) | [Access Information](#) | [Alerts](#) | [Purchase History](#) | [Cart](#) | [Sitemap](#) | [Help](#)

[Login](#)

[BROWSE](#)

[SEARCH](#)

[IEEE XPLORE GUIDE](#)

[SUPPORT](#)

You are not logged in.

Login

Username

Password



» [Forgot your password?](#)

Please remember to log out when you have finished your session.

You must log in to access:

- Advanced or Author Search
- CrossRef Search
- AbstractPlus Records
- Full Text PDF
- Full Text HTML

Access this document

» [Buy this document now](#)

» Learn more about [subscription options](#)

» Learn more about purchasing [articles](#) and [standards](#)

Article Information

An Innovative Approach for Online Bandwidth Adjustment in IP DiffServ Networks Using Learning Automata

Jahanshahi, Mohsen; Meybodi, Mohammad Reza
Mechatronics and Automation, 2007. ICMA 2007. International Conference on
Volume , Issue , 5-8 Aug. 2007 Page(s):3446 - 3451
Digital Object Identifier 10.1109/ICMA.2007.4304117

Summary: Audio and video conferencing are two examples of the applications that need a network for providing QoS guarantee according to the available bandwidth. A very important factor in QoS is end-to-end delay. The destination node receives the packets after they go through the routers queue. Therefore, if the network guarantees the queuing delay in routers, the network will find the ability to guarantee end-2-end delay. Moreover, the developers too will find the opportunity to sign contracts which are based on Service Level Agreement (SLA). Queuing delay can be solved with using bandwidth provisioning. Typically there are many ways for band provisioning. But just two methods concentrate on the queuing delay in router queue. However due to some shortcomings, these methods are not suitable for our aim. What we have presented in this paper is method which guarantees queuing delay of three service classes of DiffServ networks at the same time. The method that we have suggested uses learning automata, and it will not be necessary to have any knowledge or presumptions of traffic model and network parameter for using it. Thus one can use our adaptive method online on a network which has various features without reconfiguration. On the other hand the computational complexity of our method is very low and this feature enables it to be applied on high-speed networks. We have also evaluated the efficiency of our method in comparison to the previous methods.

» [View citation and abstract](#)

IEEE Members

Log in by entering your IEEE Web Account Username and Password.

IEEE Communications Society members: If you subscribe to the IEEE Electronic Periodicals Package or IEEE Electronic Periodicals Package Plus, you must access your subscription at www.comsoc.org.

Users at Subscribing Institutions

Check with your librarian, information professional, or system manager to determine if you need to log in. Please complete the online [Technical Support Form](#) if you need assistance.

Already Purchased This Article?

Select the [Purchase History](#) link to access the document. You will have 72 hours after purchase to access the

Full Text PDF. Please complete the online [Technical Support Form](#) if you need assistance.

Guests

- Search and access Abstract records free of charge
- [Register](#) for table of contents alerts
- Purchase Full Text PDF documents

» Learn more about [subscription options](#) or how to become an [IEEE Member](#).

[Learn more about IEEE Subscriptions](#)



[Help](#) [Contact Us](#) [Privacy & Security](#) [IEEE.org](#)

© Copyright 2007 IEEE – All Rights Reserved